



DGIWG 109

Portrayal Standard for Multinational Geospatial Co-production Program (MGCP) Data

Document type: Standard

Document date: 29 May 2015

Edition: 2.0.1

Responsible Party: MGCP and DGIWG

Audience: This document is approved for public release and is available to the

public via http://www.dgiwg.org/dgiwg/.

Abstract: This standard defines the portrayal symbols and rulesets used to

generate graphics from data collected in accordance with Multinational Geospatial Co-production Program (MGCP) technical reference

documents.

Note: This document supersedes DGIWG 109 Ed. 1, 17 November 2009

Copyright: (C) Copyright, some rights reserved - (CC) Attribution-

You are free:

- To copy, distribute, display, and perform/execute the work
- To make derivative works
- To make commercial use of the work

Under the following conditions:

- (By:) Attribution. You must give the original authors credit.
- For any reuse or distribution, you must make clear to others the license terms of this work.

Any of these conditions can be waived if you get permission from the copyright holders.

Your fair use and other rights are in no way affected by the above.

This is a human-readable summary of the Legal Code (the full license is available from Creative Commons http://creativecommons.org/licenses/by/2.0/).

Document history

Version	Date	Comments	Authors
2.0.0 (Publication	15 May 2015	Revision of DGIWG Portrayal Standard	MGCP
Draft)		for MGCP Data, v1.0, 17 November, 2009.	
2.0.1	29 May 2015	Final publication version of DGIWG Portrayal Standard for MGCP Data, v2.0.1, 29 May 2015. Corrections and revisions were made to the 15 May v2.0.0 Publication Draft, to include: adjustment of footer in Annex A to correct suppressed label strings; addition/deletion of GC and LP rules on several features; addition of "Rapids" label to Rapids line and point symbol samples; addition of new symbol (PS-04133) for Tower/non- obstruction/control (point); addition of a "List of Figures and Tables".	MGCP
		or a List or rigures and rables .	

Table of Contents

1	١	ntroduction	ļ
2	9	Scope	ļ
3	(Conformance5	5
4	ı	Normative references 5	;
5	ı	Portrayal Standard Report Organization6	ò
6	ı	Feature Symbols Report (Annex A)6	j
	6.1	Feature Information6	ò
	6.2	Generalization Rules	7
	6.3	Symbol Description	3
	6.4	Symbol Component)
	6.5	Symbol Rules	Ĺ
	6.6	Label Rules	}
	6.7	Symbol Samples	ò
	6.8	Color	7
	6.9	Type Fonts	3
	6.1	0 Masking)
Α	nne	ex A – Feature SymbolsA-	i
Α	nne	ex B – Feature Symbol Quick Reference GuideB-	i
Α	nne	ex C – Color	i
Α	nne	ex D - Text Characteristics	i
Α	nne	ex E – Area Components E-	i
Α	nne	ex F – Line Components F-	i
Α	nne	ex G – Point ComponentsG-	i
Α	nne	ex H – Detailed Drawing InstructionsH-	i
Α	nne	ex I – PatternsI-	i
Α	nne	ex J – Generalization and Label Rules	i
Α	nne	ex K – GlossaryK-	i
Α	nne	ex L – Feature Symbol IndexL-	i

List of Figures and Tables

FIGURE 1. FEATURE HEADER AND GENERALIZATION RULES FROM ANNEX A	7
FIGURE 2. SYMBOL DESCRIPTION FROM ANNEX A	8
FIGURE 3. SYMBOL RULE FROM ANNEX A	11
FIGURE 4. SYMBOL RULE FROM ANNEX A WITH ALL CRITERIA	11
FIGURE 5. MULTIPLE SYMBOLS AND RULES FOR ONE FEATURE FROM ANNEX A	12
FIGURE 6. LABEL RULES FROM ANNEX A	
FIGURE 7. SYMBOL SAMPLES FROM ANNEX A	16
FIGURE 8. SAMPLE OF AREA FEATURE WITH LABEL SHOWN OUTSIDE THE AREA	16
FIGURE 9. SAMPLE OF AREA FEATURE WITH LABEL SHOWN OUTSIDE THE AREA	16
FIGURE 10. SAMPLE OF LINE FEATURE LABEL	
FIGURE 11. SAMPLE OF POINT FEATURE LABEL	17
TABLE 1. ATTRIBUTE DIMENSIONS FOR 1:50,000 AND 1:100,000 SCALE TOPOGRAPHIC MAPS	7
TABLE 2. FONT MAPPING	19

1 Introduction

The Multinational Geospatial Co-production Program (MGCP) is a multinational program to collect geospatial data worldwide, concentrating on areas where little data currently exists.

MGCP data is collected in accordance with the standards established in the MGCP Technical Reference Documentation, Version 4 (TRD4) and any related subversions, i.e. v4.1, v4.2, etc. This establishes a MGCP Data Content Specification defined by a Feature Catalogue, an Extraction Guide, a Metadata and a Data Quality Standard. The MGCP Program has a remit for data collection rather than the portrayal of that data or product development.

This standard was developed by the Multinational Geospatial Co-production Program - Technical Group (MGCP-TG) in order for vendors and producers to ultimately portray MGCP data within a TRD4 schema on a hardcopy 1:50,000 or 1:100,000 topographic map.

The standard provides symbol rules that associate geospatial feature/attribute data instances from the MGCP TRD4 Feature Catalogue with agreed symbol specifications.

It also provides supplementary non-MGCP feature content and associated agreed symbol specifications required to develop content requirements to produce a topographic map.

This standard supersedes DGIWG 109, Portrayal Standard for MGCP Data, Edition 1.0, 17 November 2009.

Recommendations for improving this standard should be sent to the Multinational Geospatial Coproduction Program - Technical Group (MGCP-TG) Chair for consideration.

2 Scope

The scope of this standard is to provide portrayal information and graphic symbols for the agreed upon required Real World Objects to be portrayed on a topographic map. It also provides the Symbol Rules encoding for portraying MGCP TRD4 Data.

A Real World Object is a unique item that requires a portrayal. These can constitute a Feature Class (e.g. Railway) or a specific Feature Class/Attribute combination (e.g. a not intact Railway) from a given Feature Catalogue.

Portrayal information consists of symbol rules (which associate data to symbols) and symbol specifications (that define symbols).

Symbol Rules for Real World Objects sourced from MGCP TRD4 Data are encoded in conformance to DGIWG Feature Data Dictionary (DFDD), Baseline 2010-2 and the MGCP TRD4 Feature Catalogue Standard.

Symbol Rules for supplementary Real World Objects not sourced from MGCP Data, i.e. administrative/geopolitical boundaries and elevation data, are encoded in conformance to the DGIWG Feature Data Dictionary (DFDD), Baseline 2013-1.

The Symbol Graphics defined in this specification have been coordinated and agreed upon with DGIWG and constitute the standard symbol for the designated Real World Object in the DGIWG 50K Hardcopy Symbol Library.

The Symbol Specifications in this standard may be implemented independently by vendors in their own systems subject to conformance below. Vendors may need to create their own Symbol Rules as appropriate depending on the Data Dictionary and Feature Catalogue standards used.

3 Conformance

For symbols to conform to this standard they must meet the following criteria.

- Symbols shall be "visually equivalent" to those symbol graphics in the standard. Visually equivalent symbols are those that would be recognized by users as representing the same feature or information.
- Symbols on actual maps shall conform to the delineation of the geospatial feature (area, line, point). Shapes shown in this standard are representative examples only.
- All labels shall be shown in accordance with this standard. Conditional attribute labels will be filled in with the applicable information associated with the feature instance rather than the generic attribute labels shown in the standard.
- Colors on printed maps shall be in accordance with Annex C Color.

4 Normative references

This document references several other documents for additional information:

- a. Multinational Geospatial Co-production Program (MGCP) Technical Reference Documentation (TRD) v4 [MGCP 2014].
- b. DGIWG Feature Data Dictionary (DFDD), Baseline 2010-2 [DGIWG 2010].
- c. DGIWG Feature Data Dictionary (DFDD), Baseline 2013-1 [DGIWG 2013].
- d. DGIWG 50K Hardcopy Symbol Library [DGIWG 2015].
- e. Data Product Specification (DPS), 1:50,000 and 1:100,000 Scale Topographic Map (TM) Portrayal Catalog (TM PC), v1.0 [NGA 2015].
- f. MIL-STD-2410, Mapping, Charting, and Geodesy (MC&G) Reproduction and Printing [DMA 1995].
- g. Pantone Colors Information on Pantone colors is available at http://www.pantone.com
- h. Standard Printing Color Catalog for Mapping, Charting, Geodetic Data and Related Products [US DoD 1987].

i. NGA DBGI Color.doc [NGA 2008].

5 Portrayal Standard Report Organization

The MGCP Portrayal Standard report is organized into the following annexes:

 Annex A – Feature Symbols: provides feature portrayal information, sorted alphabetically by feature name. Subsequent annexes provide additional supporting information and are described therein.

- Annex B Feature Symbol Quick Reference Guide: provides users with an overall view of example symbols for each feature type, as well as serve as an index to assist users in locating the detailed specifications for symbols in Annex A.
- Annex C Color: defines the colors used in the Portrayal Standard in several well-known color specification methodologies.
- Annex D Text Characteristics: defines the characteristics of the text used for labels on feature symbols in Annex A.
- Annex E Area Components: lists each of the area components used in Annex A.
- Annex F Line Components: lists each of the line components used in Annex A.
- Annex G Point Components: lists each of the point components used in Annex A.
- Annex H Detailed Drawing Instructions: provides the detailed specifications for reusable graphic icons used in Annex A.
- Annex I Patterns: provides examples of the area patterns used for feature symbols in Annex
 A.
- Annex J –Generalization and Label Rules: provides the content of the generalization and label rules that are assigned to features and symbols in Annex A.
- Annex K Glossary: provides definitions for many of the terms used in the Portrayal Standard.
- Annex L Feature Symbol Index: provides an index of features in Annex A, sorted by feature/alternate name, and feature code.

6 Feature Symbols Report (Annex A)

6.1 Feature Information

Each feature contained in the MGCP Portrayal Standard is identified by a yellow header that provides the name of the feature and the feature code (Figure 1). There are also some non-features (deemed as "No Code") that are included in the Portrayal Standard. These no code features are included as placeholder symbols for use during product finishing as needed - Leader Line, Point of Change, River Flow Arrow, Road Route Marker, and Vertical Obstruction.

General Building (AL015)

Generalization Rules (see Annex J): GA-9999, GC-9978, GC-9983, GC-9994

Figure 1. Feature header and Generalization Rules from Annex A

6.2 Generalization Rules

Generalization rules are used to adjust or reassign the display space delineation of a map feature for the purpose of achieving the desired cartographic result. The generalization rule category designators are:

GA – Generalization Aggregation rules blend or combine identical contiguous features.

GC – Generalization Change rules indicate when a geometry will be altered or changed from one delineation to another. These rules may also include dimensional conversion guidance to derive symbols for both a 1:50,000 and 1:100,000 scale topographic map (see Table 1).

The Generalization Aggregation (GA) rules should be applied first, before applying the Generalization Change (GC) rules. The generalization rules are listed by their specific rule number (GA-XXXX) or GC-XXXX) directly below the feature header (Figure 1) and are defined in Annex J.

6.2.1 Scale

Table 1 can be used as a quick reference for dimensional attribute (area [ARA], length [LEN], width [WID]) conversions between 1:50,000 and 1:100,000 scales.

Scale	ARA	ARA	ARA	ARA	ARA	ARA	ARA	ARA	ARA
50,000	625	1,600	2,500	5,625	8,125	15,625	62,500	360,000	1,000,000
100,000	2,500	6,400	10,000	22,500	32,500	62,500	250,000	1,400,000	4,000,000

Scale	LEN							
50,000	10	20	25	50	75	100	125	375
100,000	20	40	50	100	150	200	250	750

Scale	WID	WID	WID	WID	WID	WID
50,000	25	40	50	65	75	100
100,000	50	80	100	130	150	200

Table 1. Attribute dimensions for 1:50,000 and 1:100,000 Scale Topographic Maps

6.3 Symbol Description

The Symbol Description section provides detailed information about the symbol graphic specifications and how it is constructed (Figure 2).



Figure 2. Symbol Description from Annex A

6.3.1 Symbol Name

Each symbol in Annex A is identified by a blue header that provides the name of the feature, any attribution information used to further identify the symbol (if applicable), and the geometry of the symbol (area, line or point). Examples of attribution information are "Intact", "Not Intact", "Obstruction" and "Non-obstruction". Note: The term "Not intact" indicates the [FUN] enumerant values of "Abandoned", "Damaged", "Destroyed", "Dismantled" and "Under Construction" (those not deemed "Fully Functional").

6.3.2 Symbol Graphic

Each symbol contains a "Symbol Graphic". The graphic is intended to give a general representation of the symbol's appearance in order to better understand the specifications needed to construct it. Many of the graphics are shown in an enlarged size compared to what would appear on a topographic map. This enlargement was made in order to make the components of the symbol graphic more visible.

6.3.3 Symbol Placement Instructions

The symbol placement instructions provide basic information on how the symbol is to be placed in relation to its geometry.

6.3.4 Symbol Type

A symbol can be classified as either complex, compound or simple. Complex and compound symbols are composed of more than one symbol component, while simple symbols are composed of only one symbol component. Complex symbols are made-up of symbol components with different geometries (e.g. Built-up Area with an area-fill and perimeter line component). Compound symbols are made-up of symbol components with the same geometry (e.g. Wood/evergreen with two area-fill components).

6.3.5 Repeating Point and Interval

This section (if applicable) provides detailed specifications for symbols that have a point component(s) that repeats at certain intervals along a line. Those symbols that contain 2 different repeating point components will be referenced with a "Repeating Point and Interval 2" note.

6.3.6 Note

The Note section (if applicable) provides instruction on how the symbol is to be constructed as a group of components. It may also contain other miscellaneous symbol information as needed.

6.4 Symbol Component

For each symbol component, the following information is provided (see Figure 2):

- Component Reference # A unique identifier for each component in the Portrayal Standard.
- Component Type Identifies whether the component is an area, line, or point. The types may be further detailed as Area-Fill, Line-Styled, Point-Simple, etc. Elements of these component types are provided in subsequent paragraphs.
- Color Token(s) A name describing the color(s) to apply to the symbol component.
- Description A textual description of the component.
- Parameters The specifications for the symbol component. Specific information is dependent on what type of symbol component is involved.

The Parameters section provides the basic specifications needed to construct the component. A "Note" may be included to provide additional instruction and/or how the component is placed in relation to its geometry. The following standard parameters are used to specify the various elements or instructions for the different Component Types.

6.4.1 Point – Simple

The Point – Simple component can be defined by the following parameters:

- Diameter
- Length
- Line Weight
- Note

6.4.2 Point - Shape

The Point – Shape component is defined by parameters listed in Annex H, which also contains detailed drawing instructions.

6.4.3 Line – Simple

The Line – Simple component can be defined by the following parameters:

- Line Weight
- Screen Angle
- Screen Percent
- Note

6.4.4 Line - Styled

The Line – Styled component can be defined by the following parameters:

- Line Weight
- Dash Length
- Dash 2 Length
- Dash 3 Length
- Dash Spacing
- Dash 2 Spacing
- Dash 3 Spacing
- Screen Angle
- Screen Percent
- Note

6.4.5 Area - Fill

The Area - Fill component can be defined by the following parameters:

- Screen Angle
- Screen Percent
- Note

6.4.6 Area - Pattern

The Area - Pattern component can be defined by the following parameters:

- Area Pattern
- Screen Angle
- Screen Percent
- Note

6.4.7 Order of colors and "painters model"

Many symbols are constructed by combining several different symbol components. Where different colored components are overprinted to obtain the desired effect, a "painter's model" may be used to specify the symbol. In the painter's model, the component specified first will be overwritten by components that follow. For example: Road / intact / divided / narrow median (see Figure 2), is specified by a thick black line, overprinted with a less thick dark brown line, followed by another thin black line, which ultimately produces the black "cased" portion of the road symbol. The painter's model in this standard is intended only to describe the symbol. A different implementation may be required for actual map production. In lithographic printing, for example, the thick black line would obscure anything else printed on top of it.

6.5 Symbol Rules

The Symbol Rules section provides the symbol rule information for the preceding symbol description. Symbol rules are rules that indicate the condition in which the symbol is selected. They associate an instance of geospatial data with a particular symbol. Attributes and enumerants included in the Criteria field are based on DGIWG Feature Data Dictionary (DFDD) and appear in both text and code (Figure 3).



Figure 3. Symbol Rule from Annex A

6.5.1 Criteria for symbol portrayal

The Criteria column indicates what specific attribute conditions are required for that particular symbol. A special criterion of "ALL" has been created, which indicates that all instances of the feature/geometry will receive the same symbol (Figure 4).



Figure 4. Symbol Rule from Annex A with ALL Criteria

6.5.2 Features with more than one possible symbol

When a feature has more than one possible symbol (e.g. Wood), more than one symbol rule will exist for that feature. A symbol instance should match one and only one criterion (Figure 5).




Figure 5. Multiple symbols and rules for one feature from Annex A

6.5.3 Symbol rule information

The symbol rule information is presented and defined as follows:

- Reference # Static unique identifier associated with the symbol rule. Used to link the entry to entries in other Annexes.
- Description Textual description of the symbol rule (matches the Symbol Name).
- Criteria Indicates what specific attribute conditions are required for that particular symbol.

6.5.4 Symbol rule syntax

The syntax utilized in the symbol rule criteria is based on the Structured Query Language (SQL) and thereby is easily interpreted by implementation software applications. Attribute names and enumerants are indicated by text and their corresponding codes.

Operators are generally defined as follows:

- = is equal
- <> is not equal
- > greater than
- < less than
- >= greater than or equal
- <= less than or equal

Other syntax operators:

- () used to group like attributes or indicate precedence
- or indicates true if at least one of the conditions is true
- and indicates true if all conditions are true

6.6 Label Rules

Labeling can be used to identify or assist in identification of the meaning of symbols, and also may supply additional information about the feature being portrayed. Labeling requirements for symbols are identified in the Label Rules section for each symbol (Figure 6). If the Label Rules section is not present, then a label is not required for that symbol.




Figure 6. Label Rules from Annex A

6.6.1 Label Placement rules

Label Placement (LP) rules are used to provide the initial baseline type placement for the rendered portrayal of an applicable symbol. LP rules are listed by their specific rule number (LP-XXXX) for each applicable symbol in Annex A and are defined in Annex J.

6.6.2 Label Rule information

The label rule information is presented and defined as follows:

- Reference # Static unique identifier associated with the label rule.
- Description Textual description of the label placement rule.
- Criteria Criteria to further refine the label placement. This is in addition to the symbol rule.
- Label String The content(s) of the label listed in sequence, which can be fixed text, variable label portraying attribute, varying label derived from attribute, or a combination of these.
- Characteristics A type style code for each label in the label string in sequence. This is followed by an explanation of the code. A listing of text characteristic codes is included in Annex D.

6.6.3 Types of labels

Labels can be of the following types:

- Fixed label the symbol has a label, and the content of the label is fixed, for example, the label "Falls" on a Waterfall, or "Rest area" on a Roadside Rest Area.
- Variable label portraying attribute the content of the label changes, depending on attribute information being portrayed. An example would be showing the [Product] label on an Extraction Mine, such as "Coal", "Diamond", "Gold", "Lead", etc. Another example would be to show the [Name] of a feature as a label, for example, "Olympic Stadium", or "Central Park".
- Variable label derived from attribute the content of a label changes based on the attribute information, but the text of the label is not the attribute value. An example would be a Fairgrounds with [Name] = "Unknown" being labeled simply as "Fairgrounds".
- Combination a series of labels of the various types listed above.

6.6.4 Modification of label strings based on attribution

Note that in some cases, the label string may have to be modified depending on whether attribute information is portrayed. For example, if a label string is made up of a variable or attribute based element and a static element, then it wouldn't make sense to have the label "Unknown" or "Other" for the variable portion. In these cases, the variable portion should be omitted rather than place the label containing an attribute based portion such as "Unknown" on the symbol. When concatenating multiple static or dynamic label string elements into a single label string, each static or dynamic label string element by a single space.

6.6.5 Attribute enumerants not intended for labelling

Attribute values that are not intended to be labeled include:

- Unknown [0]
- Multiple [996]
- Not Populated [997]
- Not Applicable [998]

• Other [999]

If an attribute is Unknown [0] or has not been collected, the label is also not shown. Examples of these types of attributes are Height Above Surface Level [HGT], Railway Gauge [GAW], Track or Lane Count [LTN], or Name [NAM].

6.6.6 Text [TXT] attribute

Whenever the Other [999] enumerant for any feature attribute is selected, the Text [TXT] attribute for that feature should be populated. Since the text entered for the [TXT] attribute can refer to the Other [999] enumerant of one or more attributes, no rule can determine if or how the text should be used. However, the text should be considered for potential feature labelling where applicable.

6.6.7 Text Characteristics

The Text Characteristics table in Annex D contains information specific to the text characters. This information contains color, size, case, and style parameters.

6.6.7.1 Text Characteristic parameters

The parameters for text characteristics are specified as follows:

- Text Characteristic # Reference to link the characteristics to the Label Rule information in Annex A.
- Color Token Color Token for the label string.
- Font Style Indication of Condensed, Light Condensed, or Regular.
- Style Indication of Bold or Italics.
- Font Size -- Point (PT) size of the label string.
- Case Indication of capitalization. Valid values are Upper case, Lower case, and Mixed case.

6.6.7.2 Substitution of type size

When space prohibits the use of a prescribed type size, a more appropriate size may be selected by the cartographer.

6.6.7.3 Capitalization of label information

Capitalization of label information on a symbol follows the general structure below:

- The first letter is capitalized, for example, "Falls".
- For multiple words in a descriptive label, the first letter of the first word is capitalized, for example, "Chemical processing facility" or "Water pumping station".
- For proper names, the first letter in each word is capitalized, for example, "Yellowstone National Park".

6.6.7.4 Additional named features

Topographic maps may contain names that are not necessarily extracted and/or symbolized as distinct feature entities. Examples of named "features" included in this category are: dispersed and scattered villages, farmsteads, suburban areas, mountains, mountain ranges, mesas, ridges, valleys, plains, canyons, peaks, hills, capes, points, peninsulas, inlets, etc. Refer to Annex D for the recommended text characteristics of these additional named features (or similar features as appropriate). Label placement rule LP-0050 shall be used to determine the appropriate size of text based on the size of the feature at map scale.

6.7 Symbol Samples

The MGCP Portrayal Standard also provides "Symbol Samples" at the 1:50,000 map scale. The first graphic is a sample of the basic symbol as it would appear on a map. The second and third graphics show possible label examples or relationships to features closely associated with the symbol (Figure 7).



Figure 7. Symbol Samples from Annex A

6.7.1 Baseline Label Placement samples

The symbol samples shown in Annex A also provide an initial baseline label placement (using LP rules) for the rendered portrayal of an applicable symbol (see Figure 8 – Figure 11). Variation from this default placement may be required (via the use of subsequent product finishing rules) in order to resolve overprints and otherwise achieve the desired map readability.




Figure 9. Sample of area feature with label shown outside the area




Figure 11. Sample of point feature label

6.8 Color

A particular symbol may be a single color, or composed of multiple colors. Labels are generally specified in one color.

6.8.1 Methodologies for defining colors

Colors can be specified using several methodologies:

- U.S. Department of Defense Standard Printing Color Catalog for Mapping, Charting, Geodetic Data and Related Products, referred to as "SPC", is a methodology used in the U.S DoD to specify "spot" colors, which are unique mixtures of inks.
- Pantone colors Pantone colors are commonly used in the printing industry and are based on specific mixes of inks. They are sometimes referred to as "spot" colors. Each pantone color has an identifier assigned to it. Information on Pantone colors is available at http://www.pantone.com.
- CMYK Identifies the percentage of Cyan, Magenta, Yellow and Black (key) that is used to generate a specific color in process lithographic printing. Process printing allows a wide variety of colors to be produced from these three primary colors and the black.

6.8.2 Color tokens

The Color Token definitions utilized for this standard are provided in Annex C. This Annex provides a mapping from a specific color token to Pantone color names, to SPC ink colors, and to CMYK values. This mapping allows considerable flexibility in specifying equivalent colors in a variety of methodologies.

Color tokens are used to specify generic names of colors for symbol components. Color tokens can be replaced with different tokens if maps require different viewing conditions. For example, different viewing conditions may be required for red-light readable, or red and blue/green-light readable.

The use of a Color Token methodology provides for the greatest degree of flexibility at implementation to provide for an easy adaptation to various color needs. It further allows for colors to be defined by the software applications as necessary to fulfill product requirements.

Colors in Annex A and Annex D are specified for each symbol component by Color Token. Annex C provides a listing of Pantone colors, SPC ink colors, and CMYK values that are applicable to the MGCP topographic map product. The color token values used in this Standard can be mapped to this table to determine the CMYK values (reference NGA DBGI Color.doc for additional information on color mapping equivalencies).

6.8.3 Specification of colors in digital exchange files

When exchanging digital files of finished map products in Portable Document Format (PDF), it is important to note that specifying colors using the spot color channels in the PDF allows for much greater flexibility in the lithographic printing of the map. If colors are specified only in CMYK, then four-color process printing is the only printing option available and red-light or red and blue/green-light readability cannot be absolutely assured.

6.9 Type Fonts

The TrueType Zurich font has been selected as the most appropriate font to represent the label information for the MGCP 50K product. The following criteria were considered in selecting the font:

- Format should be TrueType
- Must be compatible with the Windows environment
- Must be similar to Swiss742 fonts specified in the MIL-STD-2402 and MIL-STD-2410 (e.g. compatible with the colors, sizes, styles)
- Cost of the purchase of commercial fonts
- All the diacritic marks must be supported
- Extendable (must be possible to add new characters)

6.9.1 Use of commercial type fonts

The analysis concluded that the standard should not be too rigid regarding the use of one or another font. Nevertheless, for avoiding problems with the diacritical marks, the best choice is to use commercial fonts of recognized brand. These have Unicode codification and, in general, support all the current idiomatic characters.

Secondly, the analysis included not only TrueType but also OpenType because to choose one font in particular would lead to extra cost depending on the national mapping work flow. Therefore, the standard should be as flexible as possible.

6.9.2 Use of OpenType font

OpenType will likely become the standard in the near future, given that OpenType has greater capabilities in complex writings (languages), extendable and advanced typography (kerning, and so on). However, some national mapping work flows are not yet fully compatible with the OpenType fonts. An example of this is what happens with the PDF/X standard. The fonts used in the document must be embedded in it, including the metric and the codification's data. Under the 1.6 version, the OpenType fonts are not accepted by the PDF format.

6.9.3 Compatible equivalent type fonts

The Swiss742 font is one of the "sans serif" style types. The first step was to look for any commercial font available similar to the Swiss742 being, at least, TrueType specification. The digital format of the font was not available so the MIL-STD-2410 in PDF version was utilized for comparison. The main brands like Bitstream/Corel, Monotype and Linotype were taken into account. Even though the criterion of the MIL-STD-2410 was to choose a single font, it was determined that the output for paper maps is better if a set of diverse fonts is used. These are TrueType fonts and they produce a good balance of functionality and aesthetics.

Nevertheless, on the basis of these, a set of compatible or equivalent fonts can be established, and the producers may use them at will. Conversion tables must be as flexible and extendable as possible. Table 2, Font Mapping, provides a mapping from the Swiss742 to Zurich and Univers TrueType fonts.

Font	S tyle	To Zurich BT	S tyle	To Univers	S tyle
	Regular (Medium)			Univers® 55	Roman
	Italic		Italic		Roman Oblique
	Bold		Bold	Univers® 65	Bold
Swiss 742	Condensed	Zurich BT	Condensed	Univers® 57	Condensed
	Bold Condensed		Bold Condensed	Univers® 67	Bold Condensed
	Light Condensed		Light Condensed	Univers® 47	Light Condensed
	Light Condensed Italic		Light Condensed Italic	Oliverse 47	Light Condensed Italic

Table 2. Font Mapping

6.10 Masking

In this Portrayal Standard, there are a number of point components or symbols that have "open" or white areas. It is intended that underlying symbology (such as vegetation) would not show through any of these white openings, but rather the component would mask out underlying symbols, not allowing it to fill any of the open or white portions of the symbol. For example, the open or white portion of the Tower symbol would mask the underlying Built-up Area tint, not allowing it to fill any open portion of the Tower symbol.

The following is a complete listing of Component Reference numbers from Annex A containing an open or white area as part of the symbol.

P00009 Non-water well

P00010 Located object

P00012 Building hospital

P00018 Building temple

P00019 Building pagoda

P00022 Cairn

P00028 Vanishing point disappearing

P00030 Tree other

P00031 Building stupa

P00032 Natural pool intermittent

P00040 Qanat/Water well intermittent

P00048 Bridge non-fixed open circle

P00064 Volcano

P00071 Rock formation

P00079 Railway station

P00084 Extraction mine peat

P00089 Helipad at hospital

P00090 Helipad

P00103 Dolphin/Snag/Structural pile

P00108 Fortified building

P00111 Forest/curve

P00131 Crane

P00132 Building checkpoint

P00133 Dish aerial

P00135 Lighthouse

P00136 Memorial monument

P00137 Cooling tower

P00140 Smokestack

P00141 Tower non-communication

P00142 Water tower

P00143 Wind turbine

P00144 Windmill

P00145 Flare pipe

P00148 Water intake tower

P00155 Aerial/Tower communication

P00157 Salt evaporator

P00158 Road route marker motorway non-USA

P00160 Road route marker local/secondary

P00162 Rig inland

P00163 Offshore construction

P00165 Motor vehicle station

P00168 Holding pen

P00175 Dragons teeth

P00179 Survey point geodetic

P00184 Building minaret

P00186 Building diplomatic

P00198 Mooring mast

P00202 Bridge not fixed

P00206 Wreck

P00238 Railway turntable

P00257 Water aerodrome

P00267 Road route marker international

P00268 Road route marker national non-USA

P00271 Cemetery/Tomb other

P00275 Motor vehicle station symbol

P00283 Surface bunker

P00284 Hut

P00285 Building diplomatic flag

P00287 Cable/Communication line

P00292 Vertical obstruction pylon

P00294 Radio aid

P00295 Aircraft revetment

P00296 Building hospital symbol

Annex A – Feature Symbols

This annex presents generalization rules, symbol graphics, symbol descriptions, symbol rules and label rules for MGCP feature portrayal. This information is sorted alphabetically by Feature Name.

A cross reference to DFDD-like Code and specific page locations are provided in the Feature Symbol Index (Annex L).

Administrative Boundary (FA000)

Generalization Rules (see Annex J): GA-9999

Administrative Boundary / international (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound



Symbol Graphic

Note: Component L00123 is centered on Component L00122.

Component Ref #: L00122 Component Type: Line - Styled Color Token: Black

Description: Black 0.5mm Dashed Line (0.5mm wt, 7.0mm dash, 2-2.0mm dashes, 1.0mm gaps)

Parameters:

Line Weight: 0.5mm Dash Length: 7.0mm Dash Spacing: 1.0mm

Dash 2 Length:2.0mmDash 2 Spacing:1.0mmDash 3 Length:2.0mmDash 3 Spacing:1.0mm

Note: The line style is a 7.0mm dash, 1.0mm gap, 2.0mm dash, 1.0mm gap, then the pattern repeats.

Component Ref #: L00123 Component Type: Line - Simple Color Token: Dk-Brown1815-54

Description: Dk-Brown1815-54 2.0mm Screened Line

Parameters:

Line Weight: 2.0mm

Screen Angle: 60 degrees

Screen Percent: 54%

Symbol Rules

Reference #: Description: Criteria:

PS-04002 Administrative Boundary / Geopolitical Line Type [LSP] = Generic International Boundary [17]

international (line)

AND Boundary Status [BST] = (Definite [1], Indefinite [2], In Dispute [3], Other [999], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-9995, LP-9999

Reference #: Description: Criteria:

PL-04002_1 Administrative Boundary / international / definite (line) Boundary Status [BST] = (Definite [1], Other [999], Unknown [0])

Label String: [Name (first side)]

[Name (second side)]

Characteristics: 48

18

48 (Black, Condensed, Bold, 10 pt, Upper case)

PL-04002_2 Administrative Boundary / international / indefinite, in
Boundary Status [BST] = (Indefinite [2], In Dispute [3])

dispute (line)

Label String: [Name1 (first side)] "("[Boundary Status]")"

[Name2 (second side)]

Characteristics: 48, 48, 48, 48

48

48 (Black, Condensed, Bold, 10 pt, Upper case)

Symbol Samples

CANADA
UNITED STATES OF AMERICA

PAKISTAN (INDEFINITE)

INDIA

Administrative Boundary / other separation (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound



Symbol Graphic

Note: Component L00126 is centered on Component L00253.

Component Ref #: L00253 Component Type: Line - Styled Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.5mm Dashed Line (0.5mm wt, 2-2.0mm dashes, 7.0mm dash, 1.0mm gaps)

Parameters:

Line Weight: 0.5mm Dash Length: 2.0mm Dash Spacing: 1.0mm

Dash 2 Length:2.0mmDash 2 Spacing:1.0mmDash 3 Length:7.0mmDash 3 Spacing:1.0mm

Note: The line style is a 2.0mm dash, 1.0mm gap, 2.0mm dash, 1.0mm gap, 7.0mm dash, 1.0mm gap, then the pattern repeats.

Component Ref #: L00126 Component Type: Line - Simple Color Token: Dk-Brown1815-42

Description: Dk-Brown1815-42 2.0mm Screened Line

Parameters:

Reference #:

DK-Brown1815-42 2.0mm Screened Line

Line Weight: 2.0mm

Screen Angle: 60 degrees

Screen Percent: 42%

Symbol Rules

Reference #: Description: Criteria:

PS-04001 Administrative Boundary / other separation (line)

Geopolitical Line Type [LSP] = (Armistice Line [3], Cease Fire Line [7], Claim Line [9], Convention Line [8],
Demarcation Line [5], Generic Administrative Boundary [1], Intercolonial Line [10], Interentity Line [11],
Line of Adjacency [12], Line of Control [4], Line of Convenience [6], Line of Withdrawal [13], Military
Disengagement Line [14], Other [999], Provisional Administrative Line [2], Treaty Line [15], UNCLOS
Claim Boundary [16], Unknown [0])

Claim Boardary [10], Onknown [0])

Criteria:

AND Boundary Status [BST] = (Definite [1], Indefinite [2], In Dispute [3], Other [999], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-9995, LP-9999

PL-04001_1 Administrative Boundary / other separation / known /

definite (line)

Description:

Geopolitical Line Type [LSP] = (Armistice Line [3], Cease Fire Line [7], Claim Line [9], Convention Line [8], Demarcation Line [5], Intercolonial Line [10], Interentity Line [11], Line of Adjacency [12], Line of Control [4], Line of Convenience [6], Line of Withdrawal [13], Military Disengagement Line [14], Provisional Administrative

Line [2], Treaty Line [15], UNCLOS Claim Boundary [16])

AND Boundary Status [BST] = (Definite [1], Other [999], Unknown [0])

Label String: [Name1 (first side)] [Geopolitical Line Type]

[Name2 (second side)]

Characteristics: 48, 48

48

48 (Black, Condensed, Bold, 10 pt, Upper case)

PL-04001_2 Administrative Boundary / other separation / known / indefinite, in dispute (line)

Geopolitical Line Type [LSP] = (Armistice Line [3], Cease Fire Line [7], Claim Line [9], Convention Line [8], Demarcation Line [5], Intercolonial Line [10], Interentity Line [11], Line of Adjacency [12], Line of Control [4], Line of Convenience [6], Line of Withdrawal [13], Military Disengagement Line [14], Provisional Administrative

Line [2], Treaty Line [15], UNCLOS Claim Boundary [16])

AND Boundary Status [BST] = (Indefinite [2], In Dispute [3])

Label String: [Name1 (first side)] [Geopolitical Line Type] "("[Boundary Status]")"

[Name2 (second side)]

Characteristics: 48, 48, 48, 48, 48

48

48 (Black, Condensed, Bold, 10 pt, Upper case)

PL-04001_3 Administrative Boundary / other separation / unknown / definite (line)

Geopolitical Line Type [LSP] = (Generic Administrative Boundary [1], Other [999],

Unknown [0])

AND Boundary Status [BST] = (Definite [1], Other [999], Unknown [0])

Label String: [Name1 (first side)] "Administrative Boundary"

[Name2 (second side)]

Characteristics: 48, 48

48

48 (Black, Condensed, Bold, 10 pt, Upper case)

PL-04001_4 Administrative Boundary / other separation / unknown /

indefinite, in dispute (line)

Geopolitical Line Type [LSP] = (Generic Administrative Boundary [1], Other [999],

Unknown [0])

AND Boundary Status [BST] = (Indefinite [2], In Dispute [3])

Label String: [Name1 (first side)] "Administrative Boundary" "("[Boundary Status]")"

[Name2 (second side)]

Characteristics: 48, 48, 48, 48, 48

48

48 (Black, Condensed, Bold, 10 pt, Upper case)

Symbol Samples

LEBANON DEMARCATION LINE

LEBANON (IN DISPUTE)

ISRAEL

ISRAEL

Administrative Boundary / no defined boundary (line)

Symbol Placement Instructions: Text label only. No graphic parameters

Symbol Type: Simple

NO DEFINED BOUNDARY

Symbol Graphic

Symbol Rules

Reference #: Description:

ption: Criteria:

PS-04450 Administrative Boundary / no

defined boundary (line)

Boundary Status [BST] = No Defined Boundary [4]

Label Rules

Label Placement Rules (see Annex J): LP-9994, LP-9999

Reference #: Description:

PL-04450_1 Administrative Boundary / no defined boundary (line)

Criteria: N/A

Label String: [Name1 (first side)]

[Name1 (first side)]
"NO DEFINED BOUNDARY"

[Name2 (second side)]

Characteristics: 21

21 21

21 (Black, Condensed, 8 pt, Upper case)

Symbol Samples

PAKISTAN NO DEFINED BOUNDARY INDIA

Administrative Division (FA003)

Generalization Rules (see Annex J): GA-9999

Administrative Division / first-order (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: Repeating pattern is Component L00133 followed by Component P00082 centered within each gap. The space between each element is 1.5 mm. Component L00444 is centered on Component L00133.

Component Ref #: L00133 Component Type: Line - Styled Color Token: Black

Description: Black 0.3mm Dashed Line (0.3mm wt, 7.0mm dash, 3.4mm gap)

Parameters:

Line Weight: 0.3mm Dash Length: 7.0mm Dash Spacing: 3.4mm

Component Ref #: L00444 Component Type: Line - Simple Color Token: Dk-Brown1815-42

Description: Dk-Brown1815-42 1.0mm Screened Line

Parameters:

Line Weight: 1.0mm

Screen Angle: 60 degrees

Screen Percent: 42%

Component Ref #: P00082 Component Type: Point - Simple Color Token: Black

Description: Black 0.4mm diameter filled circle

Parameters:

Diameter: 0.4mm

Note: The component is a circle and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04005 Administrative Division / first-order BGN Administrative Level [BAL] = First-order [1]

(area)

Label Rules

Label Placement Rules (see Annex J): LP-9996, LP-9999

Reference #: Description: Criteria:

PL-04005_1 Administrative Division / first-order (area) N/A

Label String: [Name]
Characteristics: 21

21 (Black, Condensed, 8 pt, Upper case)

Symbol Samples

NORTHERN TERRITORY
SOUTHERN TERRITORY

Administrative Division / second-order (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic Note: Repeating pattern is Component L00448 followed by two Component P00082 centered within each gap. The space between each element is 1.5 mm.

Component Ref #: L00448 Component Type: Line - Styled Color Token: Black

Description: Black 0.3mm Dashed Line (0.3mm wt, 7.0mm dash, 5.3mm gap)

Parameters:

Line Weight: 0.3mm Dash Length: 7.0mm Dash Spacing: 5.3mm

Component Ref #: Component Type: Point - Simple Color Token: P00082 Black

Description: Black 0.4mm diameter filled circle

Parameters:

Diameter: 0.4mm

Note: The component is a circle and is filled with the solid color.

Symbol Rules

Reference #: Description:

PS-04006 Administrative Division / second-BGN Administrative Level [BAL] = Second-order [2]

order (area)

Label Rules

LP-9996, LP-9999 Label Placement Rules (see Annex J):

Reference #: Description: Criteria: PL-04006 1 Administrative Division / second-order (area) N/A

> Label String: [Name] Characteristics:

> > 21 (Black, Condensed, 8 pt, Upper case)

Symbol Samples

COBB **FULTON**

Administrative Division / other (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic Note: Repeating pattern is Component L00449 followed by three Component P00082 centered within each gap. The space between each

element is 1.5 mm.

Line - Styled Component Ref #: 100449 Component Type: Color Token: Black

Description: Black 0.3mm Dashed Line (0.3mm wt, 7.0mm dash, 7.2mm gap)

Parameters:

Line Weight: Dash Length: 7.0mm Dash Spacing: 7.2mm 0.3mm

Component Ref #: P00082 Component Type: Point - Simple Color Token: Black

Black 0.4mm diameter filled circle Description:

Parameters:

Reference #:

Diameter: 0.4mm

Description:

Label Placement Rules (see Annex J):

Note: The component is a circle and is filled with the solid color.

Symbol Rules

PS-04007

Administrative Division / other BGN Administrative Level [BAL] = (Fourth-order [4], Other [999], Third-order [3], Undifferentiated [5], (area)

Unknown [0])

Label Rules

Criteria: Reference #: Description: PL-04007_1 Administrative Division / other (area) N/A

LP-9996, LP-9999

Label String: [Name] 21 Characteristics:

21 (Black, Condensed, 8 pt, Upper case)

Symbol Samples

HARRISON
CONCORD

Aeronautical Obstacle (GB220)

Aeronautical Obstacle / single (point)

Symbol Placement Instructions: Origin: Center of dot

Component Type:

Symbol Type: Simple



Symbol Graphic

Note: If the symbol is moved away from the associated dot element, a Leader Line/aero blue is added connecting the symbol and the dot.

Color Token:

Blue072

P00008 Component Ref #: Description: Vertical obstruction

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04516 Aeronautical Obstacle / single

(point)

Height Above Surface Level [HGT] >= 46

Point - Shape

Label Rules Label Placement Rules (see Annex J): LP-9992

Reference #: Description: Criteria:

PL-04516_1 Aeronautical Obstacle / single / onshore (point) Structures that are located onshore

> Label String: [Feature Name]

> > [Highest Elevation]

"("[Height Above Surface Level]")"

Characteristics:

46 95.95.95

15 (Blue072, Condensed, 6 pt, Mixed case) 46 (Blue072, Condensed, Bold, 6 pt, Lower case) 95 (Blue072, Condensed, 6 pt, Lower case)

PL-04516_2 Aeronautical Obstacle / single / offshore (point) Structures that are located offshore

Label String: [Feature Name]

"("[Height Above Surface Level]")"

Characteristics: 15

95, 95, 95

15 (Blue072, Condensed, 6 pt, Mixed case) 95 (Blue072, Condensed, 6 pt, Lower case)

Symbol Samples







Aeronautical Obstacle / multiple (point)

Symbol Placement Instructions: Origin: Center of dot

Symbol Type: Simple



Symbol Graphic

Note: If the symbol is moved away from the associated dot element, a Leader Line/aero blue is added connecting the symbol and the dot.

Component Ref #: P00101 Component Type: Point - Shape Color Token: Blue072

Description: Vertical obstruction multiple

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

(point)

Label Rules

Label Placement Rules (see Annex J): LP-9992

Reference #: Description: Criteria:

PL-04517_1 Aeronautical Obstacle / multiple / onshore / same (point) Same structures that are located onshore

Label String: [Feature Name]"s"

[Highest Elevation]

"("[Height Above Surface Level]")"

Characteristics: 15, 95

46 95, 95, 95

15 (Blue072, Condensed, 6 pt, Mixed case) 46 (Blue072, Condensed, Bold, 6 pt, Lower case) 95 (Blue072, Condensed, 6 pt, Lower case) 95 (Blue072, Condensed, 6 pt, Lower case)

PL-04517_2 Aeronautical Obstacle / multiple / onshore / different

(point)

Label String: [Highest Elevation]

"("[Height Above Surface Level]")"

Characteristics: 46

95, 95, 95

46 (Blue072, Condensed, Bold, 6 pt, Lower case) 95 (Blue072, Condensed, 6 pt, Lower case)

PL-04517_3 Aeronautical Obstacle / multiple / offshore / same (point)

Structures that are located offshore

Different structures that are located offshore

Different structures that are located onshore

Label String: [Feature Name]

"("[Height Above Surface Level]")"

Characteristics: 15

95, 95, 95

15 (Blue072, Condensed, 6 pt, Mixed case) 95 (Blue072, Condensed, 6 pt, Lower case)

PL-04517_4 Aeronautical Obstacle / multiple / offshore / different

(point)

Label String: "("[Height Above Surface Level]")"

Characteristics: 95, 95, 95

95 (Blue072, Condensed, 6 pt, Lower case)

Symbol Samples





Aeronautical Radio Navigation Service (GA034)

Aeronautical Radio Navigation Service / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00294 Component Type: Point - Shape Color Token: Blue072

Description: Radio aid

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04675 Aeronautical Radio Navigation All

Service / all (point)

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:

PL-04675_1 Aeronautical Radio Navigation Service / all (point) N/A

Label String: "Radio aid"
Characteristics: 15

15 (Blue072, Condensed, 6 pt, Mixed case)

Symbol Samples

⊙ Radio aid

Aircraft Hangar (GB230)

Generalization Rules (see Annex J): GA-9999, GC-9993, GC-9994

Aircraft Hangar / intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: A00006 Component Type: Area - Fill Color Token: Black

Description: Black solid fill

Parameters:

Note: The surface geometry is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04456 Aircraft Hangar / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04456_1 Aircraft Hangar / intact (area) N/A

Label String: "Hangar"
Characteristics: 1

Symbol Samples



Aircraft Hangar / not intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: Component L00007 is applied to the perimeter and is filled with Component A00064.

Component Ref #: A00064 Component Type: Area - Fill Color Token: Black-12

Description: Black-12 area fill

Parameters:

Screen Percent:

Screen Angle: 45 degrees

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black

Description: Black 0.1mm Solid Line

12%

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

PS-04039 Aircraft Hangar / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Symbol Samples

Aircraft Hangar / intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Component Ref #: P00006 Component Type: Point - Simple Color Token: Black

Description: Black filled square with all sides 0.8mm

Parameters:

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04455 Aircraft Hangar / intact (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04455_1 Aircraft Hangar / intact (point) N/A

Label String: "Hangar"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Hangar

Aircraft Hangar / not intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00293 Component Type: Point - Shape Color Token: Black/Black-12

Description: Not intact square 0.6mm

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04040 Aircraft Hangar / not intact (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Symbol Samples

Aircraft Revetment (GB050)

Generalization Rules (see Annex J): GA-9999

Aircraft Revetment / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00174 has an initial offset of 0.75mm; after that 1.5mm.

Symbol Graphic

Note: Component P00174 is attached perpendicular to Component L00240 and point outward.

Component Ref #: L00240 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.15mm Solid Line

Parameters:

Line Weight: 0.15mm

29 May 2015 Component Ref #: P00174 Component Type: Point - Simple Color Token: Dk-Brown1815 Description: Dk-Brown1815 0.5mm length line with 0.15mm lineweight Parameters: Line Weight: 0.15mm Length: 0.5mm Symbol Rules Reference #: Description: Criteria: PS-04008 Aircraft Revetment / all (line) ΑII Symbol Samples Aircraft Revetment / all (point) Symbol Placement Instructions: Origin: Center of symbol Symbol Type: Simple **Symbol Graphic** Component Ref #: P00295 Component Type: Point - Shape Color Token: Dk-Brown1815 Description: Aircraft revetment Parameters: Note: See Annex H for detailed drawing instructions. Symbol Rules Description: Criteria: Reference #: Aircraft Revetment / all (point) PS-04037 ΑII Symbol Samples φ **Amusement Park (AK030)** Generalization Rules (see Annex J): GA-9999, GC-9999 Amusement Park / all (area) Symbol Placement Instructions: The symbol is applied to the geometry of the feature. Symbol Type: Simple **Symbol Graphic** Component Ref #: L00210 Line - Styled Color Token: Black Component Type:

Dash Spacing:

0.5mm

0.1mm

Description:

Line Weight:

Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Dash Length:

1.0mm

Symbol Rules Reference #: Description: Criteria: PS-04009 Amusement Park / all (area) ΑII Label Rules Label Placement Rules (see Annex J): LP-3506, LP-4813, LP-9950, LP-9999 Reference #: Description: Criteria: PL-04009 1 Amusement Park / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) Label String: [Name] "Amusement park" Characteristics: 1, 1 1 (Black, Condensed, 6 pt, Mixed case) PL-04009_2 Amusement Park / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under Construction [1]) Label String: [Name] "Amusement park" "("[Condition of Facility]")" Characteristics: 1. 1. 22. 22. 22 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case) Symbol Samples 7 Amusement park Adventurers Amusement Park Amusement park (construction) Amusement Park / intact (point) Symbol Placement Instructions: Origin: Center of symbol Symbol Type: Simple **Symbol Graphic** Component Ref #: P00006 Component Type: Point - Simple Color Token: Black Black filled square with all sides 0.8mm Description: Parameters: Length: 0.8mm Note: The component is a square and is filled with the solid color. Symbol Rules Reference #: Description: Criteria: PS-04459 Amusement Park / intact (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) Label Rules Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999 Reference #: Description: Criteria: PL-04459_1 Amusement Park / intact (point) N/A Label String: [Name] "Amusement park" Characteristics: 1.1 1 (Black, Condensed, 6 pt, Mixed case) Symbol Samples Amusement park Jolly Roger Amusement Park

Amusement Park / not intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00173 Component Type: Point - Shape Color Token: Black/Black-12

Criteria:

Description: Not intact square 0.8mm

Parameters:

Reference #:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

PS-04883 Amusement Park / not intact (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Description:

Reference #: Description: Criteria:
PL-04883_1 Amusement Park / not intact (point) N/A

Label String: "Amusement park"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Amusement park

Approach Lighting System (GB485)

Approach Lighting System / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00010 Component Type: Point - Shape Color Token: Black

Description: Located object

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules eference #: Description: Criteria:

Reference #: Description: Criteria:
PS-04674 Approach Lighting System / all All

(point)

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:

PL-04674_1 Approach Lighting System / all (point) N/A

Label String: "Approach lighting system"

Characteristics: 1

Symbol Samples

 $_{\odot}$ Approach lighting system

Apron (GB015)

Generalization Rules (see Annex J): GA-9999, GC-9994

Apron / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: Component L00217 is applied to the perimeter and is filled with Component A00125.

Component Ref #: A00125 Component Type: Area - Fill Color Token: Blue072-12

Description: Blue072-12 area fill

Parameters:

Screen Angle: 45 degrees
Screen Percent: 12%

Component Ref #: L00217

L00217 Component Type: Line - Simple Color Token: Blue072

Description: Blue072 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:
PS-04010 Apron / all (area) All

Symbol Samples

Aqueduct (BH010)

Generalization Rules (see Annex J): GA-9999

Aqueduct / intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: Component L00015 is applied to the perimeter and is filled with Component A00007.

Component Ref #: A00007 Component Type: Area - Fill Color Token: Cyan-31

Description: Cyan-31 area fill

Parameters:

Screen Angle: 45 degrees
Screen Percent: 31%

Component Ref #: L00015 Component Type: Line - Simple Color Token: Cyan

Description: Cyan 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Symbol Rules

Reference #: Description: Criteria:

PS-04461 Aqueduct / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Rules

LP-0062, LP-4813, LP-9997, LP-9999 Label Placement Rules (see Annex J):

Reference #: Description:

PL-04461_1 Aqueduct / intact / on ground (area) Vertical Relative Location [LOC] = (On Surface [44], Unknown [0])

Label String: [Name] "AQUEDUCT"

Characteristics: 37, 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

PL-04461_2 Aqueduct / intact / elevated (area) Vertical Relative Location [LOC] = Above Surface [45]

> Label String: [Name] "AQUEDUCT" "(ELEVATED)"

Characteristics: 37, 37, 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

PL-04461 3 Aqueduct / intact / underground (area) Vertical Relative Location [LOC] = Below Ground Surface [40]

> [Name] "AQUEDUCT" "(UNDERGROUND)" Label String:

Characteristics: 37, 37, 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

Symbol Samples

CATSKILL AQUEDUCT **AQUEDUCT** AQUEDUCT (UNDERGROUND)

Aqueduct / not intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00041 Component Type: Line - Styled Color Token: Cyan

Cyan 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap) Description:

Parameters:

Line Weight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: PS-04462 Aqueduct / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Criteria:

Label Placement Rules (see Annex J): LP-0062, LP-4813, LP-9950, LP-9997, LP-9999

Reference #: Description: Criteria:

PL-04462 1 Aqueduct / not intact / on ground (area) Vertical Relative Location [LOC] = (On Surface [44], Unknown [0])

> Label String: [Name] "AQUEDUCT" "("[Condition of Facility]")"

Characteristics: 37, 37, 37, 37, 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

PL-04462_2 Aqueduct / not intact / elevated (area)

Vertical Relative Location [LOC] = Above Surface [45]

Label String: [Name] "AQUEDUCT" "(ELEVATED)" "("[Condition of Facility]")"

Characteristics: 37, 37, 37, 37, 37, 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

PL-04462_3 Aqueduct / not intact / underground (area)

Vertical Relative Location [LOC] = Below Ground Surface [40]

Cyan

Label String: [Name] "AQUEDUCT" "(UNDERGROUND)" "("[Condition of Facility]")"

Characteristics: 37, 37, 37, 37, 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

Symbol Samples

AQUEDUCT (DESTROYED)

TEPULA AQUEDUCT (CONSTRUCTION)

AQUEDUCT (ELEVATED) (DAMAGED)

Aqueduct / on ground (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Component Type:

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00016

T00019

Cyan 0.3mm Solid Line

Description: Parameters:

Line Weight: 0.3mm

Symbol Rules

Reference #: Description: Criteria:

PS-04011 Aqueduct / on ground (line) Vertical Relative Location [LOC] = (On Surface [44], Unknown [0])

Label Rules

Line - Simple

Label Placement Rules (see Annex J): LP-3630, LP-4813, LP-9950, LP-9999

Reference #: Description: Cri

PL-04011_1 Aqueduct / on ground / intact (line) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Name] "Aqueduct"

Characteristics: 16, 16

16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

PL-04011_2 Aqueduct / on ground / not intact (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Color Token:

Label String: [Name] "Aqueduct" "("[Condition of Facility]")"

Characteristics: 16, 16, 23, 23, 23

16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case

Symbol Samples

Aqueduct Los Angeles Aqueduct Aqueduct (construction)

Aqueduct / elevated (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Note: Apex of Component P00208 is fixed at the start and end of Component L00016 with each "V" facing away. The 90 degree angle of the "V" is bisected equally by the line component.

Color Token:

Component Ref #: Cyan 0.3mm Solid Line

Symbol Graphic

Component Type:

Line - Simple

Cyan

Description:

Parameters: Line Weight:

0.3mm

L00016

Component Ref #:

P00208

Component Type: Aqueduct/penstock/water race "V"

Criteria:

Point - Shape

Color Token:

Cyan

Description: Parameters:

Note:

See Annex H for detailed drawing instructions.

Reference #: Description:

Aqueduct / elevated (line) PS-04012

Vertical Relative Location [LOC] = Above Surface [45]

Label Rules

Symbol Rules

LP-3630, LP-4813, LP-9950, LP-9999 Label Placement Rules (see Annex J):

Reference #: Description: Criteria:

PL-04012 1 Aqueduct / elevated / intact (line) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Name] "Aqueduct"

Characteristics: 16, 16

16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

PL-04012_2 Aqueduct / elevated / not intact (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

[Name] "Aqueduct" "("[Condition of Facility]")" Label String:

16, 16, 23, 23, 23 Characteristics:

> 16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case)

> > Symbol Samples

Aqueduct

Chirk Aqueduct

Aqueduct (damaged)

Aqueduct / underground / without ganat shafts (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Line Weight:

Component Ref #: Description:

Component Type: Line - Styled Color Token:

Cyan

Cyan 0.3mm Dashed Line (0.3mm wt, 1.0mm dash, 0.5mm gap) Parameters:

Dash Length:

1.0mm

Dash Spacing:

0.5mm

Symbol Rules

Reference #: Description: Aqueduct / underground / without PS-04013

0.3mm

qanat shafts (line)

Vertical Relative Location [LOC] = Below Ground Surface [40]

AND Not associated with ganat shafts Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-4813, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04013_1 Aqueduct / underground / without qanat shafts / intact Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

(line)

Label String: [Name] "Aqueduct"

Characteristics: 16, 16

16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

PL-04013_2 Aqueduct / underground / without qanat shafts / not intact Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], (line)

Dismantled [4], Under Construction [1])

Label String: [Name] "Aqueduct" "("[Condition of Facility]")"

Characteristics: 16, 16, 23, 23, 23

> 16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case)

> > Symbol Samples

Aqueduct (construction)

Aqueduct / underground / with ganat shafts (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00040 has an initial offset of 3.0mm; after that 6.0mm (center to center).

0---0

Symbol Graphic Note: Component P00040 is centered along Component L00040. If a linear aqueduct is not extracted, the symbol shall be applied to a line connecting the extracted point aqueducts (qanat shafts). Individual qanat shafts associated with this feature are not symbolized.

Line - Styled Component Ref #: L00040 Color Token: Component Type: Cyan

Description: Cyan 0.2mm Dashed Line (0.2mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Component Ref #: P00040 Component Type: Point - Simple Color Token: Cyan

Description: Qanat/Water well intermittent

Parameters:

Diameter: 1.0mm Line Weight: 0.15mm

Note: The component is an open circle.

Symbol Rules

Reference #: Description: Criteria:

PS-04463 Aqueduct / underground / with Vertical Relative Location [LOC] = Below Ground Surface [40]

qanat shafts (line)

AND Associated with ganat shafts

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria: PS-04463 1 Aqueduct / underground / with qanat shafts (line) N/A

> Label String: [Name] Characteristics:

> > 16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Aqueduct / all (point)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Note: Aqueduct / point is the symbol used for an individual qanat or karez shaft. Multiple qanat shafts associated with an linear underground aqueduct are not symbolized.

P00040 Component Ref #: Component Type: Point - Simple Color Token: Cyan

Description:

Qanat/Water well intermittent

Parameters:

Diameter: 1.0mm Line Weight: 0.15mm

Note: The component is an open circle.

Symbol Rules

Reference #: Description: Criteria: PS-04242 Aqueduct / all (point) ΑII

Symbol Samples


Archeological Site (AL012)

Generalization Rules (see Annex J): GA-9999

Archeological Site / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #:

L00210

Component Type:

Line - Styled

Color Token:

Black

Description: Parameters:

Line Weight:

Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Dash Length:

1.0mm

Dash Spacing:

0.5mm

Reference #:

0.1mm

Symbol Rules

Criteria:

PS-04017 Archeological Site / all (area)

Description:

ΑII

Label Rules

LP-3506, LP-4813, LP-9999 Label Placement Rules (see Annex J):

Reference #: Description: Criteria:

Archeological Site / all (area) PL-04017_1

N/A

Label String: [Name] "Archeological site"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Archeological site Shawnee Minisink Archeological Site

Archeological Site / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00010 Component Type: Point - Shape Color Token: Black

Description: Located object

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:
PS-04018 Archeological Site / all (point) All

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04018_1 Archeological Site / all (point) N/A

Label String: [Name] "Archeological site"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

 $_{\odot}$ Archeological site $_{\odot}$ Roundtop Archeological Site

Beach (BA050)

Generalization Rules (see Annex J): GA-9999

Beach / pebble (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #: A00036 Component Type: Area - Pattern Color Token: Dk-Brown1815

Description: Dk-Brown1815 Gravel Fill

Parameters:

Area Pattern: AP-99, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04753 Beach / pebble (area) Surface Material Type [SMC] = Pebbles [73]

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04753_1 Beach / pebble (area) N/A

Label String: [Name]
Characteristics: 5

5 (Black, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Beach / sand (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: A00035 Component Type: Area - Pattern Color Token: Dk-Brown1815

Description: Dk-Brown1815 Sand Fill

Parameters:

Area Pattern: AP-95, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04754 Beach / sand (area) Surface Material Type [SMC] = (Other [999], Sand [88], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04754_1 Beach / sand (area) N/A

Label String: [Name]

Characteristics: 5

5 (Black, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples



Beach / all (point)

Symbol Placement Instructions: Text label only. No graphic parameters

Symbol Type: Simple

[NAM]

Symbol Graphic

Symbol Rules

Reference #: Description: Criteria:
PS-04755 Beach / all (point) All

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04755_1 Beach / all (point) N/A

Label String: [Name]
Characteristics: 5

5 (Black, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Red Beach

Berthing Structure (BB190)

Generalization Rules (see Annex J): GA-9999

Berthing Structure / dry (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Note: This symbol is portrayed in conjunction with the Tidal Water symbol and shall mask out the Tidal Water symbol.

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black

Description:

Black 0.1mm Solid Line

Parameters:

Reference #:

Line Weight: 0.1mm

Symbol Rules

Description: Criteria:

PS-04744 Berthing Structure / dry (area) Water Level Effect [WLE] = Always Dry [2], Floating [8], Not Applicable [998], Other [999], Unknown [0]

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04744_1 Berthing Structure / dry (area) N/A

Label String: [Shoreline Construction Type]

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples



Berthing Structure / not dry (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: The symbol is shown in conjunction with with Tidal Water symbol and shall not mask out the Tidal Water symbol.

Component Ref #: A00048 Component Type: Area - Fill Color Token: Black-12

Description: Black-12 area fill

Parameters:

Screen Angle: 15 degrees Screen Percent: 12%

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04745 Berthing Structure / not dry (area) Water Level Effect [WLE] = (Always Submerged [3], Covers and Uncovers [4], Partly Submerged [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria: PL-04745_1 Berthing Structure / not dry (area) N/A

> Label String: [Shoreline Construction Type]

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Component Type:

Symbol Samples





Berthing Structure / dry (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Line - Simple

Color Token:

Black

Symbol Type: Simple



Component Ref #: L00009

Black 0.2mm Solid Line

Description: Parameters:

Line Weight: 0.2mm Symbol Rules

Reference #: Description: Criteria:

PS-04746 Berthing Structure / dry (line) Water Level Effect [WLE] = Always Dry [2], Floating [8], Not Applicable [998], Other [999], Unknown [0]

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04746_1 Berthing Structure / dry (line) N/A

Label String: [Shoreline Construction Type]

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Pier

Shown with Land Water Boundary and Tidal Water:

Berthing Structure / not dry (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00031 Component Type: Line - Styled Color Token: Black

Description: Black 0.2mm Dashed Line (0.2mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04747 Berthing Structure / not dry (line) Water Level Effect [WLE] = (Always Submerged [3], Covers and Uncovers [4], Partly Submerged [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04747_1 Berthing Structure / not dry (line) N/A

Label String: [Shoreline Construction Type]

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

___ Wharf

Bog (BH015)

Generalization Rules (see Annex J): GA-9999

Bog / all (area)

sh slie sh slie sh

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic Note: Co

Note: Component P00167 is applied to the perimeter with a spacing of 0.8mm, center to center, and is filled with Component A00018.

Component Ref #: A00018 Component Type: Area - Pattern Color Token: Cyan

Description: Cyan Bog, Marsh Fill

Parameters:

Area Pattern: AP-12, see Annex I

Component Ref #: P00167 Component Type: Point - Simple Color Token: Cyan

Description: Cyan 0.25mm diameter filled circle

Parameters:

Diameter: 0.25mm

Note: The component is a circle and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04021 Bog / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-9999

Reference #: Description: Criteria:

PL-04021_1 Bog / all (area) Bog Type [BOC] = (Cranberry Bog [7], Peat Bog [14])

Label String: [Bog Type]

Characteristics: 16

16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples






Breakwater (BB041)

Generalization Rules (see Annex J): GA-9999

Breakwater / dry (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Note: This symbol is portrayed in conjunction with the Tidal Water symbol and shall mask out the Tidal Water symbol.

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black

Description:

Black 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

PS-04756 Breakwater / dry (area) Water Level Effect [WLE] = Always Dry [2], Floating [8], Not Applicable [998], Other [999], Unknown [0]

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:

N/A

Label String: "Breakwater"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Breakwater



Breakwater / not dry (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.



Symbol Graphic

Note: The symbol is shown in conjunction with with Tidal Water symbol and shall not mask out the Tidal Water symbol.

Component Type: Component Ref #: A00048 Area - Fill Color Token: Black-12

Description:

Black-12 area fill

Parameters:

Screen Angle: 15 degrees

Screen Percent: 12%

Component Ref #: L00210 Line - Styled Color Token: Black Component Type:

Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap) Description:

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm **Dash Spacing:** 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04757 Breakwater / not dry (area) Water Level Effect [WLE] = (Always Submerged [3], Covers and Uncovers [4], Partly Submerged [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria: PL-04757_1 Breakwater / not dry (area) N/A


> "Breakwater" **Label String:**

1 Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Breakwater



Breakwater / dry (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Component Ref #: L00009 Component Type: Line - Simple Color Token:

Description: Black 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Symbol Rules

Black

Reference #: Description: Criteria:

PS-04758 Breakwater / dry (line) Water Level Effect [WLE] = Always Dry [2], Floating [8], Not Applicable [998], Other [999], Unknown [0]

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04758_1 Breakwater / dry (line) N/A

Label String: "Breakwater"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Shown with Land Water Boundary and Tidal Water:

Breakwater

Breakwater

Breakwater / not dry (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00031 Component Type: Line - Styled Color Token: Black

Description: Black 0.2mm Dashed Line (0.2mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04759 Breakwater / not dry (line) Water Level Effect [WLE] = (Always Submerged [3], Covers and Uncovers [4], Partly Submerged [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04759_1 Breakwater / not dry (line) N/A

Label String: "Breakwater"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

__Breakwater__

Bridge (AQ040)

Generalization Rules (see Annex J): GA-9999, GC-9979, GC-9997

Bridge / fixed / non-pedestrian (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Four Components P00038 are fixed at the start and end of Component L00019. Ticks are angled 45, 135, 225, and 315 degrees outward depending on which end of the line they are placed. See Component P00188 in Annex H for additional drawing instructions.

Component Ref #: L00019 Component Type: Line - Simple Color Token: Black

Two parallel Black 0.3mm Solid Lines Description:

Parameters:

Line Weight: 0.3mm

Spacing is variable based on the width of the overpassing feature. Note:

Component Ref #: P00038 Component Type: Point - Simple Color Token: Black

Description: Black 0.75mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm Length: 0.75mm

Symbol Rules

Reference #: Description: Criteria:

Bridge / fixed / non-pedestrian (line) PS-04130 Bridge Opening Type [BOT] = (Fixed [17], Not Applicable [998], Unknown [0])

> AND Transportation System Type [TRS] = (Aeronautical [1], Aqueduct [2], Bus [4], Canal [5], Maritime [7], Not

Applicable [998], Other [999], Pipeline [10], Railway [12], Road [13], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9999

Reference #: Description:

PL-04130_1 Bridge / fixed / non-pedestrian / intact (line) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

> Label String: [Name] Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

PL-04130_2 Bridge / fixed / non-pedestrian / not intact (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

[Name] "("[Condition of Facility]")" Label String:

Characteristics: 1, 22, 22, 22

> 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples





Bridge / non-fixed / non-pedestrian (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Note: Four Components P00038 are fixed at the start and end of Component L00019. They are angled 45, 135, 225, and 315 degrees outward depending on which end of the line they are placed. Component P00048 is centered between the lines of Component L00019. See Component P00202 in Annex H for additional drawing instructions.

Line - Simple Component Ref #: Component Type: Color Token: L00019

Component Type:

Description: Two parallel Black 0.3mm Solid Lines

P00038

Parameters:

Line Weight: 0.3mm

Note: Spacing is variable based on the width of the overpassing feature.

Description: Black 0.75mm length line with a 0.15mm lineweight

Parameters:

Component Ref #:

Line Weight: 0.15mm Length: 0.75mm

P00048 Point - Simple Black Component Ref #: Component Type: Color Token:

Description: Bridge non-fixed open circle

Parameters:

Line Weight: 0.2mm

The diameter of the open circle is variable based on the width of the overpassing feature. Note:

Symbol Rules

Reference #: Description: PS-04131 Bridge Opening Type [BOT] = (Bascule [4], Lift-bridge [11], Retractable [12], Swing-bridge [10])

Bridge / non-fixed / non-pedestrian

AND Transportation System Type [TRS] = (Aeronautical [1], Aqueduct [2], Bus [4], Canal [5], Maritime [7], Not

Black

Black

Applicable [998], Other [999], Pipeline [10], Railway [12], Road [13], Unknown [0])

Color Token:

Label Rules

Point - Simple

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9999

Reference #: Description Criteria:

PL-04131_1 Bridge / non-fixed / non-pedestrian / intact (line) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

> Label String: [Name]

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], PL-04131 2 Bridge / non-fixed / non-pedestrian / not intact (line)

Dismantled [4], Under Construction [1])

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

Shown with River and Railway:

Shown with VO, River, and Road



Bridge / pedestrian (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic Note: Apex of Component P00105 is fixed at start and end of Component L00011 with each "V" facing away. The 90 degree angle of the "V" is bisected equally by the line component.

Component Ref #: L00011 Line - Simple Color Token: Component Type: Black

Black 0.3mm Solid Line Description:

Parameters:

Line Weight: 0.3mm Component Ref #: Point - Shape Color Token: P00105 Component Type: Black

Description: Lock/pedestrian bridge/sluice gate "V"

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

Bridge / pedestrian (line) PS-04132 Transportation System Type [TRS] = Pedestrian [9]

Symbol Samples

Shown with River and Trail:

Bridge / fixed / non-pedestrian (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic Note: The symbol shall be aligned along the associated transportation feature.

P00188 Point - Shape Black Component Ref #: Component Type: Color Token:

Description: Bridge fixed

Label Placement Rules (see Annex J):

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04470 Bridge / fixed / non-pedestrian

Bridge Opening Type [BOT] = (Fixed [17], Not Applicable [998], Unknown [0]) (point)

> AND Transportation System Type [TRS] = (Aeronautical [1], Aqueduct [2], Bus [4], Canal [5], Maritime [7], Not

Applicable [998], Other [999], Pipeline [10], Railway [12], Road [13], Unknown [0])

Label Rules

Reference #: Description: Criteria:

LP-3505, LP-9950, LP-9999

PL-04470_1 Bridge / fixed / non-pedestrian / intact (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

> Label String: [Name]

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

PL-04470_2 Bridge / fixed / non-pedestrian / not intact (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

Shown with River and Road:





 \asymp

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Note: The symbol shall be aligned along the associated transportation feature.

Component Ref #: P00202 Component Type: Point - Shape Color Token: Black

Description: Bridge not fixed

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04650 Bridge / non-fixed / non-pedestrian Bridge Opening Type [BOT] = (Bascule [4], Lift-bridge [11], Retractable [12], Swing-bridge [10])

(point)

AND Transportation System Type [TRS] = (Aeronautical [1], Aqueduct [2], Bus [4], Canal [5], Maritime [7], Not

Applicable [998], Other [999], Pipeline [10], Railway [12], Road [13], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04650_1 Bridge / non-fixed / non-pedestrian/ intact (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04650_2 Bridge / non-fixed / non-pedestrian / not intact (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples







Bridge / pedestrian (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic Note: The symbol shall be aligned along the associated transportation feature.

Component Ref #: P00201 Component Type: Point - Shape Color Token: Black

Description: Bridge pedestrian

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04645 Bridge / pedestrian (point) Transportation System Type [TRS] = Pedestrian [9]

Symbol Samples

×

Built Up Area (AL020)

Generalization Rules (see Annex J): GA-9999

Built Up Area / intact / dense (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Note: Component L00007 is applied to the perimeter and is filled with Component A00005.

Component Ref #: A00005 Component Type: Area - Fill Color Token: Dk-Brown1815-42

Description: Dk-Brown1815-42 area fill

Parameters:

Screen Angle: 45 degrees
Screen Percent: 42%

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black

Description: Black 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

PS-04068 Built Up Area / intact / dense (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Built-up Area Density Category [BAC] = Dense [2]

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-9999

Reference #: Description: Criteria:

PL-04068_1 Built Up Area / intact / dense / 1st class (area) Relative Importance [ORD] = First [1]

Label String: [Name]
Characteristics: 47

47 (Black, Condensed, Bold, 14 pt, Upper case)

PL-04068_2 Built Up Area / intact / dense / 2nd class (area) Relative Importance [ORD] = Second [2]

Label String: [Name]
Characteristics: 48

48 (Black, Condensed, Bold, 10 pt, Upper case)

PL-04068_3 Built Up Area / intact / dense / 3rd class (area) Relative Importance [ORD] = Third [3]

Label String: [Name]
Characteristics: 49

49 (Black, Condensed, Bold, 10 pt, Mixed case)

PL-04068_4 Built Up Area / intact / dense / 4th class (area) Relative Importance [ORD] = Fourth [4]

Label String: [Name]
Characteristics: 50

50 (Black, Condensed, 10 pt, Mixed case)

PL-04068 5 Built Up Area / intact / dense / 5th class (area) Relative Importance [ORD] = (Fifth [5], Other [999], Unknown [0])

Dk-Brown1815-21

Label String: [Name] Characteristics:

42 (Black, Condensed, 8 pt, Mixed case)

Symbol Samples

CHICAGO

ROMA (ROME)

Built Up Area / intact / sparse or moderate (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Area - Fill

Symbol Type: Complex

Symbol Graphic Note: Component L00007 is applied to the perimeter and is filled with Component A00121.

Component Type:

Component Ref #: Description: Dk-Brown1815-21 area fill

A00121

Parameters:

Screen Angle: 45 degrees Screen Percent:

Line - Simple L00007 Color Token: Component Ref #: Component Type: Black

Description: Black 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

PS-04069 Built Up Area / intact / sparse or Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

moderate (area)

AND Built-up Area Density Category [BAC] = (Sparse [1], Unknown [0])

Color Token:

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-9999

Reference #: Criteria: Description:

PL-04069_1 Built Up Area / intact / sparse or moderate / 1st class (area) Relative Importance [ORD] = First [1]

> Label String: [Name] Characteristics:

> > 47 (Black, Condensed, Bold, 14 pt, Upper case)

PL-04069 2 Built Up Area / intact / sparse or moderate / 2nd class Relative Importance [ORD] = Second [2]

(area)

Label String: [Name] Characteristics:

48 (Black, Condensed, Bold, 10 pt, Upper case)

PL-04069_3 Built Up Area / intact / sparse or moderate / 3rd class Relative Importance [ORD] = Third [3]

(area)

Label String: [Name] Characteristics:

49 (Black, Condensed, Bold, 10 pt, Mixed case)

PL-04069_4 Built Up Area / intact / sparse or moderate / 4th class (area) Relative Importance [ORD] = Fourth [4]

> Label String: [Name] Characteristics:

> > 50 (Black, Condensed, 10 pt, Mixed case)

PL-04069_5 Built Up Area / intact / sparse or moderate / 5th class (area)

Relative Importance [ORD] = (Fifth [5], Other [999], Unknown [0])

Label String: [Name]
Characteristics: 42

42 (Black, Condensed, 8 pt, Mixed case)

Symbol Samples

Madison

Ho Chi Minh City (Saigon)

Built Up Area / not intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00007 is applied to the perimeter and is filled with Component A00063.

Component Ref #: A00063 Component Type: Area - Pattern Color Token: Dk-Brown1815-54

Description: Dk-Brown1815-54 Not Intact BUA Screened Fill

Parameters:

Area Pattern: LP-6, see Annex I Screen Angle: 45 degrees

Screen Percent: 54%

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black

Description: Black 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

PS-04070 Built Up Area / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-9950, LP-9999

Reference #: Description: Criteria:
PL-04070_1 Built Up Area / not intact (area) N/A

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 42, 22, 22, 22

42 (Black, Condensed, 8 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

(destroyed)

Built Up Area / all (point)

Symbol Placement Instructions: Text label only. No graphic parameters

Symbol Type: Simple

[NAM]

Symbol Graphic

Symbol Rules

Criteria:

Reference #: Description: Criteria:

PS-04072 Built Up Area / all (point)

All

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9999

Reference #: Description:

PL-04072_1 Built Up Area / intact (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Name]
Characteristics: 42

42 (Black, Condensed, 8 pt, Mixed case)

PL-04072_2 Built Up Area /not intact (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 42, 22, 22, 22

42 (Black, Condensed, 8 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

Monroe Apua (destroyed)

Cableway (AT041)

Generalization Rules (see Annex J): GA-9999, GC-9988

Cableway / non-obstruction (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00032 Component Type: Line - Styled Color Token: Black

Description: Black 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04155 Cableway / non-obstruction (line) Height Above Surface Level [HGT] < 46

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:

PL-04155_1 Cableway / non-obstruction / recreational (line) Cableway Type [CAT] = (Aerial Tramway [5], Chair-lift [2], Gondola Lift [6],

Industrial Ropeway [8], Material Tramway [9])

Label String: [Cableway Type]

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04155_2 Cableway / non-obstruction / other (line)

Cableway Type [CAT] = (Not Applicable [998], Other [999], Unknown [0])

Blue072

Label String: "Cableway"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Cableway / obstruction (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #:

L00006

Component Type: Blue072 0.73mm Solid Line

Description: Parameters:

Line Weight: 0.73mm

Symbol Rules

Reference #: Description: Criteria:

PS-04158 Cableway / obstruction (line)

Height Above Surface Level [HGT] >= 46

Label Rules

Line - Simple

Label Placement Rules (see Annex J): LP-9991

Description: Reference #:

Criteria: N/A

Color Token:

PL-04158_1 Cableway / obstruction (line)

> Label String: "Cableway"

> > [Highest Elevation]

"("[Height Above Surface Level]")"

Characteristics: 15

46 95, 95, 95

15 (Blue072, Condensed, 6 pt, Mixed case)

46 (Blue072, Condensed, Bold, 6 pt, Lower case)

Symbol Samples

Cableway

Cairn (AL025)

Cairn / all (point)

Symbol Placement Instructions: Origin: Center of small circle

Symbol Graphic

P00022 Component Ref #: Point - Shape Color Token: Component Type: Black

Description: Cairn

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria: PS-04073 Cairn / all (point)

Αll

Label Rules Label Placement Rules (see Annex J): LP-3505

Symbol Type: Simple

Criteria: Reference #: Description: PL-04073_1 Cairn / all (point) N/A

> Label String: "Cairn" Characteristics: 1

> > 1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

🔬 Cairn


Camp (AI030)

Generalization Rules (see Annex J): GA-9999, GC-9999

Camp / all (area)

The symbol is applied to the geometry of the feature. Symbol Placement Instructions:

Symbol Type: Simple



Color Token: Component Ref #: L00210 Component Type: Line - Styled Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Criteria: Description: PS-04481 Camp / all (area) ΑII

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-4813, LP-9999

Reference #: Description: Criteria: PL-04481_1 Camp / all (area) N/A

> Label String: [Name] "Camp"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples



Camp / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00005 Component Type: Point - Shape Color Token: Black

Description: Camp/campsite

Parameters:

Note: See Annex H for detailed drawing instructions.

Reference #: Description: Criteria:

PS-04480 Camp / all (point) All

Label Rules Label Rules Label Rules Label Rules Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04480_1 Camp / all (point) N/A

Label String: [Name] "Camp"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples




Camp Site (AK060)

Generalization Rules (see Annex J): GA-9999, GC-9999

Camp Site / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #: L00210

L00210 Component Type: Line - Styled Color Token:

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Black

Reference #: Description:
PS-04022 Camp Site / all (area)

Criteria: All

			Label Rules		
Label Placemer	nt Rules (see Annex J):	LP-3506, LP-4813, LP-9999	Label Nules		
Reference #:	Description:		Criteria:		
PL-04022_1	Camp Site / all (area)		N/A		
		Tay 2.00			
	Label String: Characteristics:	[Name] "Campsite" 1, 1			
	Characteristics:	1 (Black, Condensed, 6 pt, Mixe	ed case)		
			Symbol Samples		
	t		i		
	Campsite		Cranenest Campsite		
_					
Camp Site /		Plant and the state of	in Control of the Control		
			in: Center of symbol		
	Symbol	Type: Simple			
٨					
•	-				
Symbol G	raphic				
Component	t Ref #: P00005	Component Type:	Point - Shape Co	olor Token: Black	
Description	: Camp/campsite		. I I I I I I I I I I I I I I I I I I I	DIACK	
Parameters Note:		r detailed drawing instructions.			
		5 3000.01101	Symbol Bules		
Reference #:	Description:	Criter	Symbol Rules ia:		
	Camp Site / all (point)	All			
			Label Rules		
	nt Rules (see Annex J):	LP-3505, LP-4813, LP-9999			
Reference #:	Description:		Criteria:		
PL-04482_1	Camp Site / all (point)		N/A		
	Label String:	[Name] "Campsite"			
	Characteristics:	1, 1 1 (Plack Condensed 6 pt Mixe	ad caso)		
		1 (Black, Condensed, 6 pt, Mixe			
			Symbol Samples		
	∧ Campsite		∧ Whip-0-Will Campsite		
	Variabouto		A		
Canal (BH	IO2O)				
Canal (DI	1020)				

Generalization Rules (see Annex J):

Canal / intact / perennial (area)

GA-9999

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: Component L00015 is applied to the perimeter and is filled with Component A00007.

Component Ref #: A00007 Component Type: Area - Fill Color Token: Description: Cyan-31 area fill

Parameters:

Screen Angle: 45 degrees Screen Percent: 31%

Component Ref #: L00015 Component Type: Line - Simple Color Token: Cyan

Cyan 0.2mm Solid Line Description:

Parameters:

Line Weight: 0.2mm

Symbol Rules

Reference #: Description: Criteria:

PS-04023 Canal / intact / perennial (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

> AND Hydrologic Persistence [HYP] = (Perennial [1], Unknown [0])

Cyan-31

Label Rules

Label Placement Rules (see Annex J): LP-0062, LP-4813, LP-9997, LP-9999

Reference #: Description: Criteria:

PL-04023 1 Canal / intact / perennial / on ground (area) Vertical Relative Location [LOC] = (On Surface [44], Unknown [0])

> Label String: [Name] "CANAL"

37, 37 Characteristics:

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

PL-04023_2 Canal / intact / perennial / elevated (area) Vertical Relative Location [LOC] = Above Surface [45]

> Label String: [Name] "CANAL" "(ELEVATED)"

Characteristics: 37, 37, 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

Vertical Relative Location [LOC] = Below Ground Surface [40] PL-04023_3 Canal / intact / perennial / underground (area)

> [Name] "CANAL" "(UNDERGROUND)" Label String:

Characteristics: 37, 37, 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

Symbol Samples

CANAL OSWEGO CANAL

Canal / intact / intermittent, dry (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic Note: Component L00041 is applied to the perimeter and is filled with Component A00020.

Component Ref #: A00020 Component Type: Area - Pattern Color Token: Cyan

Description: Cyan Dry Drainage Fill

Parameters:

Area Pattern: AP-95, see Annex I

Component Ref #: L00041 Component Type: Line - Styled Color Token: Cyan

Description: Cyan 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04024 Canal / intact / intermittent, dry Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

(area)

AND Hydrologic Persistence [HYP] = (Dry [4], Intermittent [2])

Label Rules

Label Placement Rules (see Annex J): LP-0062, LP-4813, LP-9997, LP-9999

Reference #: Description: Criteria:

PL-04024_1 Canal / intact / intermittent, dry / on ground (area) Vertical Relative Location [LOC] = (On Surface [44], Unknown [0])

Label String: [Name] "CANAL"

Characteristics: 37, 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

PL-04024_2 Canal / intact / intermittent, dry / elevated (area) Vertical Relative Location [LOC] = Above Surface [45]

Label String: [Name] "CANAL" "(ELEVATED)"

Characteristics: 37, 37, 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

PL-04024_3 Canal / intact / intermittent, dry / underground (area) Vertical Relative Location [LOC] = Below Ground Surface [40]

Label String: [Name] "CANAL" "(UNDERGROUND)"

Characteristics: 37, 37, 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

Symbol Samples

CANAL CELIC CANAL

Canal / not intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00041 Component Type: Line - Styled Color Token: Cyan

Description: Cyan 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteri

PS-04025 Canal / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-0062, LP-4813, LP-9950, LP-9997, LP-9999

Reference #: Description: Criteria:

PL-04025_1 Canal / not intact / on ground (area) Vertical Relative Location [LOC] = (On Surface [44], Unknown [0])

Label String: [Name] "Canal" "("[Condition of Facility]")"

Characteristics: 37, 37, 37, 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

PL-04025_2 Canal / not intact / elevated (area)

Vertical Relative Location [LOC] = Above Surface [45]

Label String: [Name] "CANAL" "(ELEVATED)" "("[Condition of Facility]")"

Characteristics: 37, 37, 37, 37, 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

PL-04025_3 Canal / not intact / underground (area)

Vertical Relative Location [LOC] = Below Ground Surface [40]

Label String: [Name] "CANAL" "(UNDERGROUND)" "("[Condition of Facility]")"

Characteristics: 37, 37, 37, 37, 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

Symbol Samples

CANAL (CONSTRUCTION)

L & M CANAL (CONSTRUCTION)

CANAL (DAMAGED)

Canal / intact / perennial (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: L00017 Component Type: Line - Simple Color Token: Cyan

Description: Cyan 0.4mm Solid Line

Parameters:

Line Weight: 0.4mm

Symbol Rules

Reference #: Description: Criteria:

PS-04026 Canal / intact / perennial (line) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Hydrologic Persistence [HYP] = (Perennial [1], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04026_1 Canal / intact / perennial / on ground (line) Vertical Relative Location [LOC] = (On Surface [44], Unknown [0])

Label String: [Name] "Canal"
Characteristics: 16, 16

16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

PL-04026_2 Canal / intact / perennial / elevated (line) Vertical Relative Location [LOC] = Above Surface [45]

Label String: [Name] "Canal" "(elevated)"

Characteristics: 16, 16, 23

16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case)

PL-04026_3 Canal / intact / perennial / underground (line) Vertical Relative Location [LOC] = Below Ground Surface [40]

Label String: [Name] "Canal" "(underground)"

Characteristics: 16, 16, 23

16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case)

Symbol Samples

Augusta Canal Canal

Canal / not intact / intermittent, dry (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Line - Styled Component Ref #: Component Type: Color Token: 100045 Cyan

Description: Cyan 0.4mm Dashed Line (0.4mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Reference #:

Description:

Line Weight: 0.4mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04027 Canal / not intact / intermittent, dry Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under (line)

Construction [1])

OR Hydrologic Persistence [HYP] = (Dry [4], Intermittent [2])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-4813, LP-9950, LP-9999

Canal / not intact / on ground (line) PL-04027 1 Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Vertical Relative Location [LOC] = (On Surface [44], Unknown [0]) AND

Criteria:

Label String: [Name] "Canal" "("[Condition of Facility]")"

Characteristics: 16, 16, 23, 23, 23

16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case)

PL-04027_2 Canal / not intact / elevated (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Vertical Relative Location [LOC] = Above Surface [45] AND

[Name] "Canal" "(elevated)" "("[Condition of Facility]")" Label String:

Characteristics: 16, 16, 23, 23, 23, 23

> 16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case)

PL-04027_3 Canal / not intact / underground (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Vertical Relative Location [LOC] = Below Ground Surface [40]

Label String: [Name] "Canal" "(underground)" "("[Condition of Facility]")"

Characteristics: 16, 16, 23, 23, 23, 23

> 16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, condensed, Italic, 6 pt, Lower case)

PL-04027_4 Canal / intermittent, dry / on surface (line) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

> Vertical Relative Location [LOC] = (On Surface [44], Unknown [0]) AND

[Name] "Canal" Label String: Characteristics:

16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

PL-04027_5 Canal / intermittent, dry / elevated (line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Vertical Relative Location [LOC] = Above Surface [45]

Label String: [Name] "Canal" "(elevated)"

Characteristics: 16, 16, 23

16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case)

PL-04027_6 Canal / intermittent, dry / underground (line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Vertical Relative Location [LOC] = Below Ground Surface [40]

Label String: [Name] "Canal" "(underground)"

Characteristics: 16, 16, 23

16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case)

Symbol Samples

Canal (construction)

Droitwich Canal (construction)

Canal (unmaintained)

Cane (EC010)

Generalization Rules (see Annex J): GA-9999

Cane / all (area)

 $\label{thm:continuity} \textbf{Symbol Placement Instructions:} \qquad \textbf{The symbol is applied to the geometry of the feature.}$

Component Type:

Symbol Type: Simple

Symbol Graphic

Component Ref #: A00050

Description: Green362 Cane Fill

Parameters:

Area Pattern: AP-86, see Annex I

Color Token:

Green362

Symbol Rules = e #: Description: Criteria:

Reference #: Description: Criter
PS-04028 Cane / all (area) All

Symbol Samples

Area - Pattern



Cart Track (AP010)

Generalization Rules (see Annex J): GA-9999

Cart Track / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00035 Component Type: Line - Styled Color Token: Black

Description: Black 0.25mm Dashed Line (0.25mm wt, 3.5mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.25mm Dash Length: 3.5mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04128 Cart Track / all (line) All

Label Rules

Label Placement Rules (see Annex J): LP-3630

Reference #: Description: Criteria:

PL-04128_1 Cart Track / all (line) Road Weather Restriction [WTC] = Winter Only [3]

Label String: "Winter only"

Characteristics: 10

10 (Black, Light Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Winter only

Catalytic Cracker (AC020)

Catalytic Cracker / non-obstruction / intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00006 Component Type: Point - Simple Color Token: Black

Description: Black filled square with all sides 0.8mm

Parameters:

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04029 Catalytic Cracker / non-obstruction Height Above Surface Level [HGT] < 46 / intact (point)

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04029_1 Catalytic Cracker / non-obstruction / intact (point) N/A

Label String: "Catalytic cracker"

Characteristics: 1

Symbol Samples

Catalytic cracker

Catalytic Cracker / non-obstruction / not intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

_

Symbol Graphic

Component Ref #: P00293 Component Type: Point - Shape Color Token: Black/Black-12

Description: Not intact square 0.6mm

Parameters:

PS-04752

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

Catalytic Cracker / non-obstruction

/ not intact (point)

Height Above Surface Level [HGT] < 46

AND Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Symbol Samples

Causeway Structure (AQ063)

Generalization Rules (see Annex J): GA-9999

Causeway Structure / all (line)

Symbol Placement Instructions: Text label only. No graphic parameters

Symbol Type: Simple

CAUSEWAY

Symbol Graphic

Symbol Rules

Reference #: Description: Criteria:
PS-04136 Causeway Structure / all (line) All

Label Rules

Label Placement Rules (see Annex J): LP-3630

Reference #: Description: Criteria:
PL-04136_1 Causeway Structure / all (line) N/A

Label String: "CAUSEWAY"

Characteristics: 27

Symbol Samples

CAUSEWAY

Shown with Road, Land Water Boundary, and Tidal Water:

CAUSEWAY

Cave Mouth (DB029)

Cave Mouth / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Note: The narrow end of the symbol should be orientated towards the higher elevation.

Component Ref #: P00183 Component Type: Point - Shape Color Token: Black

Description: Cave mouth

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04032 Cave Mouth / all (point) All

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04032 1 Cave Mouth / all (point) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

→ Mammoth Cave

Cemetery (AL030)

Generalization Rules (see Annex J): GA-9999, GC-9982

Cemetery / other (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component P00271 is centered within Component L00210.

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Component Ref #: P00271 Component Type: Point - Shape Color Token: Black

Description: Cemetery/tomb other

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04078 Cemetery / other (area) Religious Designation [REL] = (Other [999], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04078_1 Cemetery / other (area) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

[____] Woodlawn Cemetery

Cemetery / buddhism (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

L

Symbol Graphic Note: Component P00272 is centered within Component L00210.

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Component Ref #: P00272 Component Type: Point - Shape Color Token: Black

Description: Cemetery/tomb Buddhism

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

 Reference #:
 Description:
 Criteria:

 PS-04075
 Cemetery / buddhism (area)
 Religious Designation [REL] = Buddhism [1]

Religious Designation [REL] - Budulish

Label Placement Rules (see Annex J): LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04075_1 Cemetery / buddhism (area) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Label Rules

Okunoin Cemetery

Cemetery / christian (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component P00253 is centered within Component L00210.

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Component Ref #: P00253 Component Type: Point - Shape Color Token: Black

Description: Cemetery/tomb Christian

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04076 Cemetery / christian (area) Religious Designation [REL] = Christian [4]

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04076_1 Cemetery / christian (area) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

[____] Holy Sepulchre Cemetery

Cemetery / islam (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component P00254 is centered within Component L00210.

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Component Ref #: P00254 Component Type: Point - Shape Color Token: Black

Description: Cemetery/tomb Islam

Parameters:

	See Annex H fo	or detailed drawing	g ilisti uctions.				
				Symbol Rul	es		
Reference #: PS-04074	Description: Cemetery / islam (area)	١	Criter		l. 141- 14 [2]		
F3-04074	Cemetery / Islam (area)	1	Keligi	ious Designation [REL] Label Rules	j = isiam [2]		
Label Placem	ent Rules (see Annex J):	LP-3506, LP-99	99	Label Rules			
Reference #:	Description:			Cr	iteria:		
PL-04074_1	Cemetery / islam (are	ea)		N,			
	_	[Name]					
		1 1 (Black, Conder	nsed, 6 pt, Mix	ed case)			
				Symbol Samp	les		
	[<u>-</u> Ÿ_]		[Y Makbarat As-Salaam			
emetery /	judaism (area)						
,,		l Placement Instru	ictions: The	symbol is applied to t	he geometry of the feat	cure.	
	Symbol	Type: Complex					
<u></u>	 !						
	<u> </u>						
Symbol (Graphic Note: C	Component P0025	55 is centered v	within Component L00	0210.		
Componer	nt Ref #: L00210	Comp	onent Type:	Line - Styled	Color Token:	Black	
Description		ashed line (0.1mm	ı wt, 1.0mm da	ash, 0.5mm gap)			
<u>Parameter</u> Line Weigh		D. d.					
		Dasn	Length:	1.0mm	Dash Spacing:	0.5mm	
Componer	nt Ref #· P00255						
Componer Description	n: Cemetery/tomb	Comp	Length: conent Type:	1.0mm Point - Shape	Dash Spacing: Color Token:	0.5mm Black	
Description Parameter	n: Cemetery/tomb	Comp o Judaism	oonent Type:	Point - Shape			
Description	n: Cemetery/tomb	Comp	oonent Type:	Point - Shape	Color Token:		
Description Parameter Note:	n: Cemetery/tomb	Comp o Judaism	ponent Type:	Point - Shape Symbol Rul	Color Token:		
Description Parameter	n: Cemetery/tomb	Comp o Judaism or detailed drawin _i	ponent Type: g instructions. Criter	Point - Shape Symbol Rul	Color Token:		
Description Parameter Note: Reference #:	n: Cemetery/tomb	Comp o Judaism or detailed drawin _i	ponent Type: g instructions. Criter	Point - Shape Symbol Rul	Color Token: es J = Judaism [5]		
Description Parameter Note: Reference #: PS-04077	n: Cemetery/tomb	Comp o Judaism or detailed drawin _i	ponent Type: Ig instructions. Criter Religi	Point - Shape Symbol Rul ria: ious Designation [REL]	Color Token: es J = Judaism [5]		
Description Parameter Note: Reference #: PS-04077	See Annex H for Description: Cemetery / judaism (and the second	Compo Judaism or detailed drawing	ponent Type: Ig instructions. Criter Religi	Point - Shape Symbol Rul ria: ious Designation [REL] Label Rules	Color Token: es J = Judaism [5]		
Description Parameter Note: Reference #: PS-04077 Label Placeme	See Annex H for Description: Cemetery / judaism (are the Rules (see Annex J):	Compo Judaism or detailed drawing rea) LP-3506, LP-99	ponent Type: Ig instructions. Criter Religi	Point - Shape Symbol Rul ria: ious Designation [REL] Label Rules	Color Token: es J = Judaism [5] iteria:		
Description Parameter Note: Reference #: PS-04077 Label Placeme Reference #:	See Annex H for Description: Cemetery / judaism (are the Rules (see Annex J): Description: Cemetery / judaism (are the Rules (see Annex J): Description: Cemetery / judaism (are the Rules (see Annex J):	Compo Judaism or detailed drawing rea) LP-3506, LP-99	ponent Type: Ig instructions. Criter Religi	Point - Shape Symbol Rul ria: ious Designation [REL] Label Rules Cr	Color Token: es J = Judaism [5] iteria:		
Description Parameter Note: Reference #: PS-04077 Label Placeme Reference #:	See Annex H for Description: Cemetery / judaism (arent Rules (see Annex J): Description:	Compo Judaism or detailed drawing rea) LP-3506, LP-99	ponent Type: Ig instructions. Criter Religi	Point - Shape Symbol Rul ria: ious Designation [REL] Label Rules Cr	Color Token: es J = Judaism [5] iteria:		
Description Parameter Note: Reference #: PS-04077 Label Placeme Reference #:	See Annex H for Description: Cemetery / judaism (and ent Rules (see Annex J): Description: Cemetery / judaism (and Label String:	Compo Judaism or detailed drawing ea) LP-3506, LP-99 area) [Name]	ponent Type: In grinstructions. Criter Religions	Point - Shape Symbol Rul ria: ious Designation [REL] Label Rules Cr N,	Color Token: es J = Judaism [5] iteria:		
Description Parameter Note: Reference #: PS-04077 Label Placeme Reference #:	See Annex H for Description: Cemetery / judaism (and ent Rules (see Annex J): Description: Cemetery / judaism (and Label String:	Compo Judaism or detailed drawing rea) LP-3506, LP-99 area) [Name] 1	ponent Type: In grinstructions. Criter Religions	Point - Shape Symbol Rul ria: ious Designation [REL] Label Rules Cr N,	Color Token: es J = Judaism [5] iteria: //A		
Description Parameter Note: Reference #: PS-04077 Label Placeme Reference #:	See Annex H for Description: Cemetery / judaism (and ent Rules (see Annex J): Description: Cemetery / judaism (and Label String:	Compo Judaism or detailed drawing rea) LP-3506, LP-99 area) [Name] 1	ponent Type: In grinstructions. Criter Religions	Point - Shape Symbol Rul ria: ious Designation [REL] Label Rules Cr N,	Color Token: es J = Judaism [5] iteria: //A		
Description Parameter Note: Reference #: PS-04077 Label Placeme Reference #:	See Annex H for Description: Cemetery / judaism (and ent Rules (see Annex J): Description: Cemetery / judaism (and Label String:	Compo Judaism or detailed drawing rea) LP-3506, LP-99 area) [Name] 1	ponent Type: In grinstructions. Criter Religions	Point - Shape Symbol Rul ria: ious Designation [REL] Label Rules Cr N,	Color Token: es J = Judaism [5] iteria: //A		

Cemetery / other (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

 \mathbf{T}

Symbol Graphic

Component Ref #: P00271 Component Type: Point - Shape Color Token: Black

Description: Cemetery/tomb other

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04083 Cemetery / other (point) Religious Designation [REL] = (Other [999], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04083_1 Cemetery / other (point) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

__New York Marble Cemetery

Cemetery / buddhism (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00272 Component Type: Point - Shape Color Token: Black

Description: Cemetery/tomb Buddhism

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04080 Cemetery / buddhism (point) Religious Designation [REL] = Buddhism [1]

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04080_1 Cemetery / buddhism (point) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

்டChimes Memorial Garden

Cemetery / christian (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

t

Symbol Graphic

Component Ref #: P00253 Component Type: Point - Shape Color Token: Black

Description: Cemetery/tomb Christian

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04079 Cemetery / christian (point) Religious Designation [REL] = Christian [4]

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04079_1 Cemetery / christian (point) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

+Holy Cross Cemetery

Cemetery / islam (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Y

Symbol Graphic

Component Ref #: P00254 Component Type: Point - Shape Color Token: Black

Description: Cemetery/tomb Islam

†

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04081 Cemetery / islam (point) Religious Designation [REL] = Islam [2]

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04081_1 Cemetery / islam (point) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Y Dar-us-Salaam

Cemetery / judaism (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

T

Symbol Graphic

Component Ref #: P00255 Component Type: Point - Shape Color Token: Black

Description: Cemetery/tomb Judaism

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04082 Cemetery / judaism (point) Religious Designation [REL] = Judaism [5]

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04082_1 Cemetery / judaism (point) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

T Siver Lake Cemetery

Checkpoint (AH070)

T

Checkpoint / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00132 Component Type: Point - Shape Color Token: Black

Description: Building checkpoint

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Description: PS-04033 Checkpoint / all (point)

Criteria: ΑII

Reference #:

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria: PL-04033_1 Checkpoint / all (point) N/A

> Label String: [Name] Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

 Θ

⊜ Eagle Pass



Circular Irrigation System (AJ010)

Generalization Rules (see Annex J): GA-9999

Circular Irrigation System / all (area)

Symbol Placement Instructions: Text label only. No graphic parameters

Symbol Type: Simple

Circular irrigation system

Symbol Graphic

Reference #:

Symbol Rules

Reference #: Description: PS-04303

Criteria: ΑII

Circular Irrigation System / all (area)

Label Rules

Label Placement Rules (see Annex J): LP-3506

Description:

Criteria:

PL-04303_1 Circular Irrigation System / all (area) N/A

Label String:

"Circular irrigation system"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Circular irrigation system

Cistern (BI010)

Cistern / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00007 Component Type: Point - Simple Color Token: Cyan

Description: Cyan filled square with all sides 0.8mm

Parameters:

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:
PS-04052 Cistern / all (point) All

Symbol Samples

•

Cleared Way (EC040)

Generalization Rules (see Annex J): GA-9999

Cleared Way / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

{NO SYMBOL}

Symbol Graphic Note: The symbol is a mask of the Thicket (EB020) and Wood (EC030) feature symbols.

Symbol Rules

Reference #: Description: Criteria:
PS-04853 Cleared Way / all (area) All

Symbol Samples

{NO SYMBOL}



Communication Line (AT060)

Generalization Rules (see Annex J): GA-9999, GC-9988

Communication Line / non-obstruction (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00287 has an initial offset of 3.5mm; after that 7.0mm.

Symbol Graphic

Note: Component P00287 is centered along Component L00445.

Component Ref #:

Component Type:

Line - Simple

Color Token:

Blue072

Description: Parameters: Line Weight:

0.25mm

L00445

P00287

Component Ref #:

Component Type:

Point - Simple

Color Token:

Blue072

Blue072 0.8mm diameter open circle

Blue072 0.25mm Solid Line

Description:

Parameters: Diameter:

0.8mm

Line Weight: 0.25mm

Note:

The component is an open circle.

Symbol Rules

Reference #: Description: Criteria:


PS-04729 Communication Line / non-

obstruction (line)

Height Above Surface Level [HGT] < 46

Symbol Samples





Communication Line / obstruction (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.



Symbol Graphic

Symbol Type: Complex

Component Ref #: Component Type: Line - Simple Color Token: L00006 Blue072

Description: Blue072 0.73mm Solid Line

Parameters:

Line Weight: 0.73mm

Symbol Rules

Reference #: Description: Criteria:

PS-04730 Communication Line / obstruction

(line)

Height Above Surface Level [HGT] >= 46

Label Rules

Label Placement Rules (see Annex J): LP-9991

Criteria: Reference #: Description: PL-04730_1 Communication Line / obstruction (line) N/A

> Label String: "Communication line" [Highest Elevation]

> > "("[Height Above Surface Level]")"

Characteristics: 15 95, 95, 95 15 (Blue072, Condensed, 6 pt, Mixed case) 46 (Blue072, Condensed, Bold, 6 pt, Lower case) 95 (Blue072, Condensed, 6 pt, Lower case)

Symbol Samples

Communication line	
242	
(72)	


Communication Station (AT050)

Generalization Rules (see Annex J): GA-9999, GC-9983, GC-9999

Communication Station / non-obstruction (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04726 Communication Station / non-Height Above Surface Level [HGT] < 46

obstruction (area)

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04726_1 Communication Station / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: "Communication station"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04726_2 Communication Station / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: "Communication station" "("[Condition of Facility]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

_____ Communication station ______ Communication station (destroyed)

Communication Station / non-obstruction / intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00006 Component Type: Point - Simple Color Token: Black

Description: Black filled square with all sides 0.8mm

Parameters:

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04727 Communication Station / non- Height Above Surface Level [HGT] < 46

obstruction / intact (point)

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04727_1 Communication Station / intact (point) N/A

Label String: "Communication station"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

_Communication station

Communication Station / non-obstruction / not intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00173 Component Type: Point - Shape Color Token: Black/Black-12

Description: Not intact square 0.8mm

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria

PS-04728 Communication Station / non-Height Above Surface Level [HGT] < 46

obstruction / not intact (point)

AND Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Symbol Samples

Communication station

Conveyor (AF020)

Generalization Rules (see Annex J): GA-9999

Conveyor / non-obstruction (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00032 Component Type: Line - Styled Color Token: Black

Description: Black 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04034 Conveyor / non-obstruction (line) Height Above Surface Level [HGT] < 46

Label Rules

Label Placement Rules (see Annex J): LP-3630

Reference #: Description: Criteria:

PL-04034_1 Conveyor / non-obstruction (line) N/A

Label String: "Conveyor"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

_Conveyor

Conveyor / obstruction (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00006 Component Type: Line - Simple Color Token: Blue072

Description: Blue072 0.73mm Solid Line

Parameters:

Line Weight: 0.73mm

Symbol Rules

Reference #: Description: Crite

PS-04886 Conveyor / obstruction (line) Height Above Surface Level [HGT] >= 46

Label Rules

Label Placement Rules (see Annex J): LP-9991

Reference #: Description: Criteria: PL-04886_1 Conveyor / obstruction (line)

> Label String: "Conveyor"

[Highest Elevation]

"("[Height Above Surface Level]")"

Characteristics:

95, 95, 95

15 (Blue072, Condensed, 6 pt, Mixed case) 46 (Blue072, Condensed, Bold, 6 pt, Lower case)

Symbol Samples

N/A

Conveyor / non-obstruction (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Point - Shape Component Ref #: P00010 Color Token: Black Component Type:

Description: Located object

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04887 Conveyor / non-obstruction (point) Height Above Surface Level [HGT] < 46

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria: PL-04887_1 Conveyor / non-obstruction (point) N/A

> Label String: "Conveyor"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Label Rules

⊙ Conveyor

Conveyor / obstruction (point)

Symbol Placement Instructions: Origin: Center of open circle

Symbol Type: Simple



Component Ref #: P00113 Component Type: Point - Shape Color Token: Blue072

Description: Vertical obstruction linear

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04888 Conveyor / obstruction (point) Height Above Surface Level [HGT] >= 46

Label Rules

Label Placement Rules (see Annex J): LP-9992

Reference #: Description: Criteria:

PL-04888_1 Conveyor / obstruction (point) N/A

Label String: "Conveyor"

[Highest Elevation]

"("[Height Above Surface Level]")"

Characteristics: 15

46 95, 95, 95

15 (Blue072, Condensed, 6 pt, Mixed case) 46 (Blue072, Condensed, Bold, 6 pt, Lower case)

Symbol Samples



Crane (AF040)

Crane / non-obstruction (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00131 Component Type: Point - Shape Color Token: Black

Description: Crane

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04038 Crane / non-obstruction (point) Height Above Surface Level [HGT] < 46

Symbol Samples

Shown with Tidal Water:

Θ

Э

Crevasse (BJ031)

Generalization Rules (see Annex J): GA-9999

Crevasse / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: Component L00016 is applied to the perimeter and is filled with Component A00062.

Component Ref #: A00062 Component Type: Area - Pattern Color Token: Cyan Description: Cyan Diagonal Line Fill

Parameters:

Area Pattern: LP-3, see Annex I

Component Ref #: L00016 Component Type: Line - Simple Color Token: Cyan

Description: Cyan 0.3mm Solid Line

Parameters:

Line Weight: 0.3mm

Symbol Rules

Reference #: Description: Criteria:
PS-04496 Crevasse / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3505

Reference #: Description: Criteria:

PL-04496_1 Crevasse / all (area) N/A

Label String: "Crevasse"
Characteristics: 32

32 (Cyan, Condensed, Italic, 6-9 pt, Mixed case)

Symbol Samples



Crevasse / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #: L00248 Component Type: Line - Simple Color Token: Cyan

Description: Cyan 0.25mm Solid Line

<u>Parameters:</u>

Line Weight: 0.25mm

Symbol Rules

Reference #: Description: Criteria:
PS-04497 Crevasse / all (line) All

Label Rules

Label Placement Rules (see Annex J): LP-3630

Reference #: Description: Criteria:
PL-04497_1 Crevasse / all (line) N/A

Label String: "Crevasse"
Characteristics: 16

Symbol Samples

Crevasse

Crevice (DB061)

Generalization Rules (see Annex J): GA-9999

Crevice / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00105 is applied to the perimeter and is filled with Component A00061.

Component Ref #: A00061 Component Type: Area - Pattern Color Token: Dk-Brown1815

Description: Dk-Brown1815 Diagonal Line Fill

Parameters:

Area Pattern: LP-3, see Annex I

Component Ref #: L00105 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.3mm Solid Line

Parameters:

Line Weight: 0.3mm

Symbol Rules

Reference #: Description: Criteria:

PS-04498 Crevice / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3505

Reference #: Description: Criteria:


PL-04498_1 Crevice / all (area) N/A

Label String: "Crevice"

Characteristics: 6

6 (Black, Condensed, Italic, 6-9 pt, Mixed case)

Symbol Samples



Crevice / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Type: Line - Simple Component Ref #: Color Token: Dk-Brown1815 L00024

Description: Dk-Brown1815 0.25mm Solid Line

Parameters:

Line Weight: 0.25mm

Symbol Rules

Criteria: Reference #: Description: PS-04499 Crevice / all (line) ΑII

Label Rules

Label Placement Rules (see Annex J): LP-3630

Criteria: Reference #: Description: PL-04499_1 Crevice / all (line) N/A

> Label String: "Crevice" Characteristics:

> > 5 (Black, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Crevice

Crop Land (EA010)

Generalization Rules (see Annex J): GA-9999

Crop Land / dry crops (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound



Symbol Graphic

Note: Components A00060 and A00118 are combined into one symbol. Display level from bottom to top: Component A00060; Component A00118. The entire pattern is rotated to 30 degrees.

A00060 Area - Fill Color Token: Dk-Brown1815-07 Component Ref #: Component Type:

Description: Dk-Brown1815-07 area fill

Parameters:

Screen Angle: 45 degrees Screen Percent: 7%

Area - Pattern Component Ref #: A00118 Component Type: Color Token: Green362

Green362 Cropland dot fill Description:

Parameters:

Area Pattern: No existing MIL_STD_2410 area pattern. See Annex I for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04304 Crop Land / dry crops (area) Farming Method [FMM] = (Fallow [1], Other [999], Permanent [3], Slash and Burn [4], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3506

Reference #: Description:

PL-04304_1 Crop Land / dry crops (area) Farming Pattern [FFP] = Terraced [3]

> "Terraces" **Label String:**

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples



Crop Land / irrigated crops (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound



Symbol Graphic

Note: Components A00127 and A00118 are combined into one symbol. Display level from bottom to top: Component A00127; Component A00118. The entire pattern is rotated to 30 degrees.

Component Ref #: A00127 Component Type: Area - Fill Color Token: Green362-07

Description: Green362-07 area fill

Parameters:

Screen Angle: 45 degrees

Screen Percent: 7%

Component Ref #: A00118 Component Type: Area - Pattern Color Token: Green362

Description: Green362 Cropland dot fill

Parameters:

Area Pattern: No existing MIL_STD_2410 area pattern. See Annex I for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria

PS-04019 Crop Land / irrigated crops (area) Farming Method [FMM] = Permanent Irrigation [5]

Label Rules

Label Placement Rules (see Annex J): LP-3506

Reference #: Description: Criteria:

PL-04019_1 Crop Land / irrigated crops (area) Farming Pattern [FFP] = Terraced [3]

Label String: "Terraces"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples



Terraces

Culvert (AQ065)

Culvert / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Note: The apex of the "V"s are aligned to each side of the corresponding transportation feature.

Component Ref #: P00106 Component Type: Point - Shape Color Token: Black

Description: Culvert double "V"

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:
PS-04705 Culvert / all (point) All

Symbol Samples

><

Shown with River and Cart Track:

Cut (DB070)

Generalization Rules (see Annex J): GA-9999

Cut / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00174 has an initial offset of 0.75mm; after that 1.5mm.

Symbol Graphic

Note: Component P00174 is perpendicular to and on the inward side of Component L00241.

Component Ref #: L00241 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Two parallel Dk-Brown1815 0.15mm Solid Lines

Parameters:

Line Weight: 0.15mm

Note: Spacing is variable based on the width of the overpassing feature. The minimum space between each line and the linear portion of the over

passing feature shall be 0.2 mm.

Component Ref #: P00174 Component Type: Point - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.5mm length line with 0.15mm lineweight

Parameters:

Line Weight: 0.15mm
Length: 0.5mm

Symbol Rules

Reference #: Description: Criteria:
PS-04243 Cut / all (line) All

Symbol Samples

Cut Line (DB071)

Generalization Rules (see Annex J): GA-9999

Cut Line / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00174 has an initial offset of 0.75mm; after that 1.5mm.

Symbol Graphic Note: Component P00174 is perpendicular to and on the downhill side of Component L00240.

Component Ref #: L00240 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.15mm Solid Line

Parameters:

Line Weight: 0.15mm

Component Ref #: P00174 Component Type: Point - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.5mm length line with 0.15mm lineweight

Parameters:

Line Weight: 0.15mm
Length: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04244 Cut Line / all (line) All

Symbol Samples

Dam (BI020)

Generalization Rules (see Annex J): GA-9999, GC-9995, GC-9997

Dam / hard (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00013 Component Type: Line - Simple Color Token: Black

Description: Black 0.4mm Solid Line

Parameters:

Line Weight: 0.4mm

Symbol Rules

Reference #: Description: Criteria:

PS-04214 Dam / hard (area) Structural Material Type [MCC] = (Asphalt [5], Brick [9], Concrete [21], Masonry [62], Metal [64],

Prestressed Concrete [77], Reinforced Concrete [83])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04214_1 Dam / hard / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Name] "Dam"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04214_2 Dam / hard / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: [Name] "Dam" "("[Condition of Facility]")"

Characteristics: 1, 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

Dam	Hoover Dam	Shown with River and VO: Dam 310 (53)	
2			
Dam / loose (area)			
Symbo	I Placement Instructions: The symbol is applied to the geometry of the fe I Type: Simple	ature.	
Symbol Graphic			
Component Ref #: L00195 Description: Dk-Brown1815 Parameters: Line Weight: 0.4mm	Component Type: Line - Simple Color Token: 0.4mm Solid Line	Dk-Brown1815	
	Symbol Rules		
Reference #: Description: PS-04215 Dam / loose (area)	Criteria: Structural Material Type [MCC] = (Clay [16], Com Macadam [57], Other [999], Part Metal [72], Pet Stone [108], Unknown [0], Wood [117])	nposition [20], Conglomerate [22], Gravel [46], obles [73], Rock [84], Rubble [86], Sand [88], Soil [104],	
	Label Rules		
Label Placement Rules (see Annex J):	LP-3505, LP-4813, LP-9950, LP-9999		
Reference #: Description:	Criteria:		
PL-04215_1 Dam / loose / intact	(area) Condition of Facility [FU	N] = (Fully Functional [6], Unknown [0])	
Label String:	[Name] "Dam"		
Characteristics:	1, 1 1 (Black, Condensed, 6 pt, Mixed case)		
PL-04215_2 Dam / loose / not in		N] = (Abandoned [2], Damaged [13], Destroyed [3],	
Label String:	[Name] "Dam" "("[Condition of Facility]")"	,	
Characteristics:	1, 1, 22, 22, 22 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)		
	Symbol Samples		
Dam	Castaic Dam	Shown with River:	
Dam / hard / transportation	(line)		

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

L00019 Line - Simple Component Ref #: Color Token: Component Type: Black

Description: Two parallel Black 0.3mm Solid Lines

Parameters:

Line Weight: 0.3mm Note: Spacing is variable based on the width of the overpassing feature.

Symbol Rules

Reference #: Description: Criteria:

PS-04217 Dam / hard / transportation (line) Structural Material Type [MCC] = (Asphalt [5], Brick [9], Concrete [21], Masonry [62], Metal [64],

Prestressed Concrete [77], Reinforced Concrete [83])

AND Transportation System Type [TRS] = (Aeronautical [1], Aqueduct [2], Bus [4], Canal [5], Maritime [7],

Pipeline [10], Railway [12], Road [13])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04217_1 Dam / hard / transportation / intact (line) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Name] "Dam"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04217_2 Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: [Name] "Dam" "("[Condition of Facility]")"

Characteristics: 1, 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

Bagnell Dam

Shown with Road and River:

Dam / loose / transportation (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: L00247 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Two parallel Dk-Brown1815 0.3mm Solid Lines

Parameters:

Line Weight: 0.3mm

Note: Spacing is variable based on the width of the overpassing feature.

Symbol Rules

Reference #: Description: Criteria:

PS-04502 Dam / loose / transportation (line) Structural Material Type [MCC] = (Clay [16], Composition [20], Conglomerate [22], Gravel [46],

Macadam [57], Other [999], Part Metal [72], Pebbles [73], Rock [84], Rubble [86], Sand [88], Soil [104],

Stone [108], Unknown [0], Wood [117])

Transportation System Type [TRS] = (Aeronautical [1], Aqueduct [2], Bus [4], Canal [5], Maritime [7],

Pipeline [10], Railway [12], Road [13])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04502_1 Dam / loose / transportation / intact (line) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Name] "Dam"

Characteristics: 1,

1 (Black, Condensed, 6 pt, Mixed case)

AND

PL-04502_2 Dam / loose / transportation / not intact (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under Construction [1])

Label String: [Name] "Dam" "("[Condition of Facility]")"

Characteristics: 1, 1, 22, 22, 22

> 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

> > Symbol Samples

Smith Dam

Shown with VO: 288

Dam / hard / no transportation (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #: L00013 Component Type: Line - Simple Color Token: Black

Description: Black 0.4mm Solid Line

Parameters:

Line Weight: 0.4mm

Symbol Rules

Reference #: Description: Criteria:

PS-04216 Dam / hard / no transportation Structural Material Type [MCC] = (Asphalt [5], Brick [9], Concrete [21], Masonry [62], Metal [64], (line)

Prestressed Concrete [77], Reinforced Concrete [83])

Transportation System Type [TRS] = (Not Applicable [998], Other [999], Pedestrian [9], Unknown [0]) AND

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria: PL-04216_1 Dam / hard / no transportation (line) N/A

> Label String: [Name] Characteristics: 1

> > 1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Yorkville Dam

Shown with VO:
Dam
286

Dam / loose / no transportation (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: Component Type: Line - Simple Color Token: L00195 Dk-Brown1815

Criteria:

Description: Dk-Brown1815 0.4mm Solid Line

Parameters:

Line Weight: 0.4mm

Symbol Rules

Reference #: Description: PS-04429

Dam / loose / no transportation

(line)

Structural Material Type [MCC] = (Clay [16], Composition [20], Conglomerate [22], Gravel [46], Macadam [57], Other [999], Part Metal [72], Pebbles [73], Rock [84], Rubble [86], Sand [88], Soil [104],

Stone [108], Unknown [0], Wood [117])

AND Transportation System Type [TRS] = (Not Applicable [998], Other [999], Pedestrian [9], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria: PL-04429_1 Dam / loose / no transportation (line) N/A

> Label String: [Name] Characteristics: 1

> > 1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Harbaqa Dam

Shown with River:

Dam / hard (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Note: The symbol shall be aligned perpendicular to the associated hydrographic feature.

Component Ref #: P00269 Point - Simple Color Token: Black Component Type:

PS-04218

Description: Black 1.5mm length line with a 0.4mm lineweight

Parameters:

Line Weight: 0.4mm 1.5mm Length:

Symbol Rules

Reference #: Description:

Dam / hard (point)

Structural Material Type [MCC] = (Asphalt [5], Brick [9], Concrete [21], Masonry [62], Metal [64],

Prestressed Concrete [77], Reinforced Concrete [83])

Symbol Samples

Shown with River:

Shown with VO Symbol:

Dam / loose (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Note: The symbol shall be aligned perpendicular to the associated hydrographic feature.

Component Ref #: P00270 Component Type: Point - Simple Color Token: Dk-Brown1815

Description: Parameters:

Line Weight: 0.4mm
Length: 1.5mm

Symbol Rules

Dk-Brown1815 1.5mm length line with a 0.4mm lineweight

Reference #: Description: Criteria:

PS-04430 Dam / loose (point) Structural Material Type [MCC] = (Clay [16], Composition [20], Conglomerate [22], Gravel [46],

Macadam [57], Other [999], Part Metal [72], Pebbles [73], Rock [84], Rubble [86], Sand [88], Soil [104],

Stone [108], Unknown [0], Wood [117])

Symbol Samples

Shown with River:

Shown with VO Symbol:

L 201 (46)

Dish Aerial (AT010)

Dish Aerial / non-obstruction (point)

Symbol Placement Instructions: Origin: Center of open circle

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00133 Component Type: Point - Shape Color Token: Black

Description: Dish aerial

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04152 Dish Aerial / non-obstruction (point) Height Above Surface Level [HGT] < 46

Symbol Samples

8

Disposal Site (AB000)

Generalization Rules (see Annex J): GA-9999, GC-9983

Disposal Site / non-obstruction (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Line - Styled Component Ref #: L00210 Component Type:

Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Reference #:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Criteria:

Symbol Rules

PS-04278

Disposal Site / non-obstruction Height Above Surface Level [HGT] < 46

(area)

Description:

Label Rules Label Placement Rules (see Annex J): LP-3506, LP-4813, LP-9999

Reference #: Description: Criteria: PL-04278_1 Disposal Site / non-obstruction (area) N/A

> [Name] [By-product] "Disposal site" Label String:

Characteristics: 1, 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Disposal site

Refuse disposal site

Ditch (BH030)

Generalization Rules (see Annex J): GA-9999

Ditch / perennial (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: Component L00015 is applied to the perimeter and is filled with Component A00007.

Component Ref #: A00007 Component Type: Area - Fill Color Token: Cyan-31

Description:

Cyan-31 area fill

Parameters:

Screen Angle: 45 degrees Screen Percent: 31%

L00015 Component Ref #: Cyan 0.2mm Solid Line

Description: Parameters:

Line Weight: 0.2mm

Symbol Rules

Color Token:

Cyan

Reference #: Description:

PS-04179 Ditch / perennial (area) Hydrologic Persistence [HYP] = (Perennial [1], Unknown [0])

Component Type:

Label Rules

Line - Simple

Label Placement Rules (see Annex J): LP-0062, LP-9997, LP-9999

Reference #: Description: Criteria: PL-04179_1 Ditch / perennial (area)

N/A

Label String: [Name]
Characteristics: 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

Symbol Samples

GARDEN CITY DITCH

Ditch / intermittent, dry (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic Note: Component L00041 is applied to the perimeter and is filled with Component A00020.

Component Ref #: A00020 Component Type: Area - Pattern Color Token: Cyan

Description: Cyan Dry Drainage Fill

Parameters:

Area Pattern: AP-95, see Annex I

Component Ref #: L00041 Component Type: Line - Styled Color Token: Cyan

Description: Cyan 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04180 Ditch / intermittent, dry (area) Hydrologic Persistence [HYP] = (Dry [4], Intermittent [2])

Label Rules

Label Placement Rules (see Annex J): LP-0062, LP-9997, LP-9999

Reference #: Description: Criteria:
PL-04180_1 Ditch / intermittent, dry (area) N/A

Label String: [Name]
Characteristics: 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

Symbol Samples

DAVIDSON DITCH

Ditch / perennial (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Type: Line - Simple Component Ref #: L00108 Color Token: Cyan 0.1mm Solid Line

Description:

PS-04181

Parameters: Line Weight: 0.1mm

Symbol Rules

Reference #: Description:

Ditch / perennial (line)

Hydrologic Persistence [HYP] = (Perennial [1], Unknown [0])

Cyan

Symbol Samples

Ditch / intermittent, dry (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Criteria:

Symbol Type: Simple

Symbol Graphic

Component Type: Line - Styled Component Ref #: L00246 Color Token: Cyan

Description: Cyan 0.1mm Dashed Line (0.1mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Line Weight: Dash Length: Dash Spacing: 0.5mm 0.1mm 2.0mm

Symbol Rules

Reference #: Description: Criteria:

PS-04182 Ditch / intermittent, dry (line) Hydrologic Persistence [HYP] = (Dry [4], Intermittent [2])

Symbol Samples

Dragon's Teeth (AL060)

Generalization Rules (see Annex J): GA-9999

Dragon's Teeth / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00175 is centered in the 1.0mm gap of component L00243 (every 4.0mm).

Symbol Graphic

Note: Component P00175 is centered on and perpendicular to Component L00243.

Component Ref #: L00243 Component Type: Line - Styled Color Token: Black

Black 0.3mm Dashed Line (0.3mm wt, 4.0mm dash, 1.0mm gap) Description:

Parameters:

Line Weight: 0.3mm Dash Length: 4.0mm Dash Spacing: 1.0mm Component Ref #: P00175

Description: Dragons teeth

Parameters:

0.3mm Line Weight: Length: 1.0mm

Note: The component is an open square.

Symbol Rules

Reference #: Description: Criteria: Dragon's Teeth / all (area) PS-04503 ΑII

Label Rules

Point - Simple

Color Token:

Black

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria: PL-04503_1 Dragon's Teeth / all (area) N/A

> Label String: "Dragon's teeth"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Component Type:

Symbol Samples



Dragon's Teeth / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00175 is centered in the 1.0mm gap of component L00243 (every 4.0mm).



Note: Component P00175 is centered on and perpendicular to Component L00243.

Component Ref #: L00243 Component Type: Line - Styled Color Token: Black

Description: Parameters: Line Weight:

0.3mm Dash Length:

1.0mm

Black

Black 0.3mm Dashed Line (0.3mm wt, 4.0mm dash, 1.0mm gap)

4.0mm

Dash Spacing:

Color Token:

P00175 Point - Simple Component Ref #: Component Type:

Description:

Dragons teeth

Parameters:

Line Weight: 0.3 mmLength: 1.0mm

Note: The component is an open square.

Symbol Rules

Criteria: Reference #: Description: PS-04504 Dragon's Teeth / all (line) ΑII

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria: PL-04504 1 Dragon's Teeth / all (line) N/A

> Label String: "Dragon's teeth"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples


_____ Dragon's teeth

Dry Dock (BB090) Generalization Rules (see Annex J): GA-9999, GC-9981 Dry Dock / all (area) Symbol Placement Instructions: The symbol is applied to the geometry of the feature. Symbol Type: Simple **Symbol Graphic** Component Ref #: L00009 Component Type: Line - Simple Color Token: Black Black 0.2mm Solid Line Description: Parameters: Line Weight: 0.2mm Symbol Rules Reference #: Description: Criteria: PS-04168 Dry Dock / all (area) ΑII Label Rules Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9999 Reference #: Criteria: Description: PL-04168_1 Dry Dock / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) Label String: "Dry dock" Characteristics: 1 (Black, Condensed, 6 pt, Mixed case) PL-04168_2 Dry Dock / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under Construction [1]) Label String: "Dry Dock" "("[Condition of Facility]")" Characteristics: 1, 22, 22, 22 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case) Symbol Samples Shown with Land Water Boundary and Tidal Water: Dry dock Dry dock (construction)

Electric Power Station (AD010)

Generalization Rules (see Annex J): GA-9999

Electric Power Station / all (area)



Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Component Ref #: L00210 Line - Styled Color Token: Component Type: Black Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap) Parameters: Dash Length: 1.0mm Line Weight: 0.1mm Dash Spacing: 0.5mm Symbol Rules Reference #: Description: Criteria: Electric Power Station / all (area) PS-04293 Αll Label Rules LP-3506, LP-4813, LP-9950, LP-9999 Label Placement Rules (see Annex J): Reference #: Description: Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) PL-04293_1 Electric Power Station / intact (area) Label String: [Name] [Power Station Type] "Power plant" Characteristics: 1.1.1 1 (Black, Condensed, 6 pt, Mixed case) PL-04293_2 Electric Power Station / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under Construction [1]) [Name] [Power Station Type] "Power plant "("[Condition of Facility]")" Label String: Characteristics: 1. 1. 1. 22. 22. 22 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case) Symbol Samples Sequoyah Nuclear Plant 7 Power plant Nuclear power plant (destroyed) **Electric Power Station / intact (point) Symbol Placement Instructions:** Origin: Center of symbol Symbol Type: Simple **Symbol Graphic** Component Ref #: P00006 Component Type: Point - Simple Color Token: Black Black filled square with all sides 0.8mm Description: Parameters: 0.8mm Length: The component is a square and is filled with the solid color. Note: Symbol Rules Reference #: Description: Criteria: PS-04294 **Electric Power Station / intact** Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) Label Rules Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999 Reference #: Description: Criteria: PL-04294_1 Electric Power Station / intact (point) N/A Label String: [Name] [Power Station Type] "Power plant" Characteristics: 1.1.1

Symbol Samples

1 (Black, Condensed, 6 pt, Mixed case)

Power plant Oyster Creek Nuclear Power Plant Nuclear power plant

Electric Power Station / not intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00173 Component Type: Point - Shape Color Token: Black/Black-12

Description: Not intact square 0.8mm

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04896 Electric Power Station / not intact Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

(point) Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04896_1 Electric Power Station / not intact (point) N/A

Label String: "Power plant"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Power plant


Elevation Contour (CA010)

Generalization Rules (see Annex J): GA-9999

Elevation Contour / land / index (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #: L00023 Comp Description: Dk-Brown1815 0.2mm Solid Line

Component Type:

Line - Simple

Criteria:

Color Token:

Dk-Brown1815

Description: Parameters:

PS-04342

Line Weight: 0.2mm

Symbol Rules

Reference #: Description:

Elevation Contour / land / index (line)

Elevation Surface Category [ESC] = (Land [1], Unknown [0])

MGCP Portrayal Standard, Annex A (v2.0.1)

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04342_1 Elevation Contour / land / index / greater than zero (line) Highest Elevation [ZVH] > 0

Label String: [Highest Elevation]

Characteristics: 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case)

PL-04342_2 Elevation Contour / land / index / zero (line) Highest Elevation [ZVH] = 0

Label String: "ZERO"
Characteristics: 92

92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

PL-04342 3 Elevation Contour / land / index / minus (line) Highest Elevation [ZVH] < 0

Label String: "MINUS" [Highest Elevation]

Characteristics: 92, 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case) 92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

Symbol Samples

---300 -

Elevation Contour / land / index / approximate (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00176 Component Type: Line - Styled Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.2mm Dashed Line (0.2mm wt, 5.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 5.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04343 Elevation Contour / land / index / Elevation Surface Category [ESC] = (Land [1], Unknown [0])

approximate (line)

AND Hypsography Portrayal Type [HQC] = Approximate Index Contour [7]

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04343_1 Elevation Contour / land / index / approximate / greater Highest Elevation [ZVH] > 0

than zero (line)

Label String: [Highest Elevation]

Characteristics: 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case)

PL-04343_2 Elevation Contour / land / index / approximate / zero (line)

Highest Elevation [ZVH] = 0

Label String: "ZERO"
Characteristics: 92

92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

PL-04343_3 Elevation Contour / land / index / approximate / minus

Highest Elevation [ZVH] < 0

(line)

Label String: "MINUS" [Highest Elevation]

Characteristics: 92, 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case) 92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

Symbol Samples

Elevation Contour / land / intermediate (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Note: Elevation contour values shall not be labeled for intermediate elevation contours except when percent of slope is < 5 in an area >= 150

mm x 150 mm.

Component Ref #: L00107 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

PS-04346 Elevation Contour / land /

intermediate (line)

Elevation Surface Category [ESC] = (Land [1], Unknown [0])

AND Hypsography Portrayal Type [HQC] = (Intermediate Carrying Contour [19], Intermediate Contour [2])

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04346_1 Elevation Contour / land / intermediate / greater than zero Highest Elevation [ZVH] > 0

(line)

Label String: [Highest Elevation]

Characteristics: 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case)

PL-04346_2 Elevation Contour / land / intermediate / zero (line) Highest Elevation [ZVH] = 0

Label String: "ZERO"
Characteristics: 92

92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

PL-04346_3 Elevation Contour / land / intermediate / minus (line) Highest Elevation [ZVH] < 0

Label String: "MINUS" [Highest Elevation]

Characteristics: 92, 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case) 92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

Symbol Samples

Elevation Contour / land / intermediate / approximate (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Note: Elevation contour values shall not be labeled for intermediate elevation contours except when percent of slope is < 5 in an area >= 150 mm x 150 mm.

Component Ref #: L00177 Component Type: Line - Styled Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.1mm Dashed Line (0.1mm wt, 5.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 5.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria

PS-04347 Elevation Contour / land / Elevation Surface Category [ESC] = (Land [1], Unknown [0])

intermediate / approximate (line)

AND Hypsography Portrayal Type [HQC] = Approximate Intermediate Contour [12]

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04347_1 Elevation Contour / land / intermediate / approximate / Highest Elevation [ZVH] > 0

greater than zero (line)

Label String: [Highest Elevation]

Characteristics: 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case)

PL-04347_2 Elevation Contour / land / intermediate / approximate / Highest Elevation [ZVH] = 0

zero (line)

Label String: "ZERO"
Characteristics: 92

92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

PL-04347_3 Elevation Contour / land / intermediate / approximate / Highest Elevation [ZVH] < 0

minus (ine)

Label String: "MINUS" [Highest Elevation]

Characteristics: 92, 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case) 92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

Symbol Samples

-220 --

Elevation Contour / land / half auxiliary (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Line - Styled Component Ref #: L00109 Component Type: Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.1mm Dashed Line (0.1mm wt, 3.0mm dash, 0.5mm gap)

Parameters:

Line Weight: Dash Length: 3.0mm Dash Spacing: 0.5mm 0.1mm

Symbol Rules

Reference #: Description: Criteria:

PS-04350 Elevation Contour / land / half Elevation Surface Category [ESC] = (Land [1], Unknown [0])

auxiliary (line)

AND Hypsography Portrayal Type [HQC] = (Auxiliary Carrying Contour [20], Half Auxiliary Contour [3])

Highest Elevation [ZVH] > 0

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04350 1 Elevation Contour / land / half auxiliary / greater than zero

(line)

Label String: [Highest Elevation]

Characteristics:

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case)

PL-04350_2 Elevation Contour / land / half auxiliary / zero (line) Highest Elevation [ZVH] = 0

> "ZERO" Label String: Characteristics:

> > 92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

PL-04350 3 Elevation Contour / land / half auxiliary / minus (line) Highest Elevation [ZVH] < 0

> Label String: "MINUS" [Highest Elevation]

Characteristics: 92, 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case) 92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

Symbol Samples

Elevation Contour / land / quarter auxiliary (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Line - Styled Component Ref #: 100117 Component Type: Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.1mm Dashed Line (0.1mm wt, 1.5mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.5mm Dash Spacing: 0.5mm

Symbol Rules

Criteria: Reference #: Description:

PS-04360 Elevation Contour / land / quarter

auxiliary (line)

Elevation Surface Category [ESC] = (Land [1], Unknown [0])

AND Hypsography Portrayal Type [HQC] = Quarter Auxiliary Contour [14]

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04360_1 Elevation Contour / land / quarter auxiliary / greater than Highest Elevation [ZVH] > 0

zero (line)

Label String: [Highest Elevation]

Characteristics: 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case)

PL-04360_2 Elevation Contour / land / quarter auxiliary/ zero (line) Highest Elevation [ZVH] = 0

Label String: "ZERO"
Characteristics: 92

92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

PL-04360_3 Elevation Contour / land / quarter auxiliary / minus (line) Highest Elevation [ZVH] < 0

Label String: "MINUS" [Highest Elevation]

Characteristics: 92, 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case) 92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

Symbol Samples

-----15------

Elevation Contour / land / mound / index (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: The same as the corresponding depression elevation contour.

/—\

Symbol Graphic Note: Component P00065 is perpendicular to and on the downhill side of Component L00023.

Component Ref #: L00023 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Component Ref #: P00065 Component Type: Point - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.5mm length line with a 0.1mm lineweight

Parameters:

Line Weight: 0.1mm
Length: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04358 Elevation Contour / land / mound / Elevation Surface Category [ESC] = (Land [1], Unknown [0])

index (line)

AND Hypsography Portrayal Type [HQC] = Mound Index Contour [8]

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04358_1 Elevation Contour / land / mound / index / greater than Highest Elevation [ZVH] > 0

zero (line)

Label String: [Highest Elevation]

Characteristics: 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case)

PL-04358_2 Elevation Contour / land / mound / index / zero (line) Highest Elevation [ZVH] = 0

Label String: "ZERO"
Characteristics: 92

92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

PL-04358_3 Elevation Contour / land / mound / index / minus (line) Highest Elevation [ZVH] < 0

Label String: "MINUS" [Highest Elevation]

Characteristics: 92, 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case) 92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

Symbol Samples



Elevation Contour / land / mound / intermediate (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: The same as the corresponding depression elevation contour.

Symbol Graphic

Note: Component P00065 is perpendicular to and on the downhill side of Component L00107.

Component Ref #: L00107 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Component Ref #: P00065 Component Type: Point - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.5mm length line with a 0.1mm lineweight

Parameters:

Line Weight: 0.1mm
Length: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04359 Elevation Contour / land / mound / Elevation Surface Category [ESC] = (Land [1], Unknown [0])

intermediate (line)

AND Hypsography Portrayal Type [HQC] = Mound Intermediate Contour [9]

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04359_1 Elevation Contour / land / mound / intermediate / greater Highest Elevation [ZVH] > 0

than zero (line)

Label String: [Highest Elevation]

Characteristics: 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case)

PL-04359 2 Elevation Contour / land / mound / intermediate / zero Highest Elevation [ZVH] = 0

(line)

Label String: "ZERO"
Characteristics: 92

92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

PL-04359_3 Elevation Contour / land / mound / intermediate / minus

(line)

Label String: "MINUS" [Highest Elevation]

Characteristics: 92, 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case) 92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

Symbol Samples



Elevation Contour / land / depression / index (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Each depression elevation contour shall have equally spaced ticks extending from the contour towards the

Highest Elevation [ZVH] < 0

lower elevation. The bottom most depression elevation contour shall have a tick interval of 0.5 mm. The first ascending depression contour shall have a tick interval of 1.0 mm, the second shall have a tick interval of 2.0

mm, and all subsequent shall have a tick interval of 3.0.

Symbol Graphic Note: Component P00065 is perpendicular to and on the downhill side of Component L00023.

Component Ref #: L00023 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Component Ref #: P00065 Component Type: Point - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.5mm length line with a 0.1mm lineweight

Parameters:

Line Weight: 0.1mm
Length: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04354 Elevation Contour / land / Elevation Surface Category [ESC] = (Land [1], Unknown [0])

depression / index (line)

AND Hypsography Portrayal Type [HQC] = Depression Index Contour [5]

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04354_1 Elevation Contour / land / depression / index / greater Highest Elevation [ZVH] > 0

than zero (line)

Label String: [Highest Elevation]

Characteristics: 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case)

PL-04354_2 Elevation Contour / land / depression / index / zero (line) Highest Elevation [ZVH] = 0

Label String: "ZERO"
Characteristics: 92

92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)


PL-04354_3 Elevation Contour / land / depression / index / minus (line) Highest Elevation [ZVH] < 0

Label String: "MINUS" [Highest Elevation]

Characteristics: 92, 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case) 92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)





Elevation Contour / land / depression / intermediate (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Each depression elevation contour shall have equally spaced ticks extending from the contour towards the

lower elevation. The bottom most depression elevation contour shall have a tick interval of 0.5 mm. The first ascending depression contour shall have a tick interval of 1.0 mm, the second shall have a tick interval of 2.0

mm, and all subsequent shall have a tick interval of 3.0.

Symbol Graphic

Note: Component P00065 is perpendicular to and on the downhill side of Component L00107. Elevation contour values shall not be labeled for intermediate elevation contours except when percent of slope is < 5 in an area >= 150 mm x 150 mm.

Component Ref #: L00107 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Component Ref #: P00065 Component Type: Point - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.5mm length line with a 0.1mm lineweight

Parameters:

Line Weight: 0.1mm
Length: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04356 Elevation Contour / land / depression / intermediate (line)

evation Contour / land / Elevation Surface Category [ESC] = (Land [1], Unknown [0])

AND Hypsography Portrayal Type [HQC] = Depression Intermediate Contour [6]

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04356_1 Elevation Contour / land / depression / intermediate / Highest Elevation [ZVH] > 0

greater than zero (line)

Label String: [Highest Elevation]

Characteristics: 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case)

PL-04356_2 Elevation Contour / land / depression / intermediate / zero Highest Elevation [ZVH] = 0

(line)

Label String: "ZERO"
Characteristics: 92

92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

PL-04356_3 Elevation Contour / land / depression / intermediate / Highest Elevation [ZVH] < 0

minus (line)

Label String: "MINUS" [Highest Elevation]


Characteristics: 92, 20

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case) 92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

Symbol Samples

Depression contours with variable tick spacing:





Elevation Contour / land / depression / auxiliary (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00065 is centered on every dash of Component L00109.



Note: Component P00065 is perpendicular to and on the downhill side of Component L00109.

Line - Styled Component Ref #: L00109 Component Type: Color Token: Dk-Brown1815

Description:

Parameters:

Line Weight: 0.1mm Dash Length: 3.0mm Dash Spacing: 0.5mm

Dk-Brown1815 0.1mm Dashed Line (0.1mm wt, 3.0mm dash, 0.5mm gap)

Component Ref #: Point - Simple P00065 Color Token: Dk-Brown1815

Component Type: Dk-Brown1815 0.5mm length line with a 0.1mm lineweight Description:

Parameters:

Line Weight: 0.1mm Length: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04362 Elevation Contour / land / Elevation Surface Category [ESC] = (Land [1], Unknown [0])

depression / auxiliary (line)

AND Hypsography Portrayal Type [HQC] = Depression Auxiliary Contour [22]

Label Rules

Label Placement Rules (see Annex J): LP-3987

Description: Reference #:

PL-04362_1 Elevation Contour / land / depression / auxiliary / greater Highest Elevation [ZVH] > 0

than zero (line)

Label String: [Highest Elevation]

Characteristics:

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case)

PL-04362_2 Elevation Contour / land / depression / auxiliary / zero Highest Elevation [ZVH] = 0

(line)

Label String: "ZERO" Characteristics:

92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

PL-04362 3 Elevation Contour / land / depression / auxiliary / minus Highest Elevation [ZVH] < 0

Label String: "MINUS" [Highest Elevation]

Characteristics:

20 (Dk-Brown1815, Condensed, Italic, 7 pt, Lower case) 92 (Dk-Brown1815, Condensed, Italic, 7 pt, Upper case)

Symbol Samples



Elevation Contour / snow, ice / index (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #: L00015 Component Type:

Description: Cyan 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Symbol Rules

Line - Simple

Reference #: Description: Criteria:

PS-04344 Elevation Contour / snow, ice /

index (line)

Elevation Surface Category [ESC] = Snow Field and/or Ice-field [2]

AND Hypsography Portrayal Type [HQC] = (Index Carrying Contour [21], Index Contour [1])

Color Token:

Cyan

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04344_1 Elevation Contour / snow, ice / index / greater than zero Highest Elevation [ZVH] > 0

(line)

Label String: [Highest Elevation]

Characteristics: 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case)

PL-04344_2 Elevation Contour / snow, ice / index / zero (line) Highest Elevation [ZVH] = 0

Label String: "ZERO"
Characteristics: 90

90 (Cyan, Condensed, Italic, 7 pt, Upper case)

PL-04344_3 Elevation Contour / snow, ice / index / minus (line) Highest Elevation [ZVH] < 0

Label String: "MINUS" [Highest Elevation]

Characteristics: 90, 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case) 90 (Cyan, Condensed, Italic, 7 pt, Upper case)

Symbol Samples

----- 300

Elevation Contour / snow, ice / index / approximate (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00042 Component Type: Line - Styled Color Token: Cyan

Description: Cyan 0.2mm Dashed Line (0.2mm wt, 5.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 5.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04345 Elevation Contour / snow, ice / Elevation Surface Category [ESC] = Snow Field and/or Ice-field [2]

index / approximate (line)

AND Hypsography Portrayal Type [HQC] = Approximate Index Contour [7]

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04345_1 Elevation Contour / snow, ice / index / approximate / Highest Elevation [ZVH] > 0

greater than zero (line)

Label String: [Highest Elevation]

Characteristics: 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case)

PL-04345_2 Elevation Contour / snow, ice / index / approximate/ zero

(line)

Label String: "ZERO"
Characteristics: 90

90 (Cyan, Condensed, Italic, 7 pt, Upper case)

PL-04345_3 Elevation Contour / snow, ice / index / approximate / Highest Elevation [ZVH] < 0

minus (line)

Label String: "MINUS" [Highest Elevation]

Characteristics: 90, 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case) 90 (Cyan, Condensed, Italic, 7 pt, Upper case)

Symbol Samples

Elevation Contour / snow, ice / intermediate (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Note: Elevation contour values shall not be labeled for intermediate elevation contours except when percent of slope is < 5 in an area >= 150

Highest Elevation [ZVH] = 0

mm x 150 mm.

Component Ref #: L00108 Component Type: Line - Simple Color Token: Cyan

Description: Cyan 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

PS-04348 Elevation Contour / snow, ice / Elevation Surface Category [ESC] = Snow Field and/or Ice-field [2]

intermediate (line)

AND Hypsography Portrayal Type [HQC] = (Intermediate Carrying Contour [19], Intermediate Contour [2])

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04348_1 Elevation Contour / snow, ice / intermediate / greater than Highest Elevation [ZVH] > 0

zero (line)

Label String: [Highest Elevation]

Characteristics: 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case)

PL-04348_2 Elevation Contour / snow, ice / intermediate / zero (line) Highest Elevation [ZVH] = 0

Label String: "ZERO"
Characteristics: 90

90 (Cyan, Condensed, Italic, 7 pt, Upper case)

PL-04348 3 Elevation Contour / snow, ice / intermediate / minus (line) Highest Elevation [ZVH] < 0

Label String: "MINUS" [Highest Elevation]

Characteristics:

19 (Cyan, Condensed, Italic, 7 pt, Lower case) 90 (Cyan, Condensed, Italic, 7 pt, Upper case)

Symbol Samples

220

Elevation Contour / snow, ice / intermediate / approximate (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Note: Elevation contour values shall not be labeled for intermediate elevation contours except when percent of slope is < 5 in an area >= 150

mm x 150 mm

Component Ref #: L00178 Component Type: Line - Styled Color Token: Cyan

Cyan 0.1mm Dashed Line (0.1mm wt, 5.0mm dash, 0.5mm gap) Description:

Parameters:

Line Weight: 0.1mm Dash Length: 5.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04349 Elevation Contour / snow, ice / Elevation Surface Category [ESC] = Snow Field and/or Ice-field [2]

intermediate / approximate (line)

AND Hypsography Portrayal Type [HQC] = Approximate Intermediate Contour [12]

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04349_1 Elevation Contour / snow, ice / intermediate / approximate Highest Elevation [ZVH] > 0

/ greater than zero (line)

Label String: [Highest Elevation]

Characteristics:

19 (Cyan, Condensed, Italic, 7 pt, Lower case)

PL-04349_2 Elevation Contour / snow, ice / intermediate / approximate Highest Elevation [ZVH] = 0

/ zero (line)

Label String: "ZERO" Characteristics:

90 (Cyan, Condensed, Italic, 7 pt, Upper case)

PL-04349_3 Elevation Contour / snow, ice / intermediate / approximate Highest Elevation [ZVH] < 0

/ minus (line)

Label String: "MINUS" [Highest Elevation]

Characteristics: 90.19

19 (Cyan, Condensed, Italic, 7 pt, Lower case)

90 (Cyan, Condensed, Italic, 7 pt, Upper case)


Symbol Samples

220

Elevation Contour / snow, ice / half auxiliary (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #: L00110 Component Type: Line - Styled Color Token: Cyan

Description: Cyan 0.1mm Dashed Line (0.1mm wt, 3.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 3.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04351 Elevation Contour / snow, ice / half Elevation Surface Category [ESC] = Snow Field and/or Ice-field [2]

auxiliary (line)

AND Hypsography Portrayal Type [HQC] = (Auxiliary Carrying Contour [20], Half Auxiliary Contour [3])

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04351_1 Elevation Contour / snow, ice / half auxiliary / greater than Highest Elevation [ZVH] > 0

zero (line)

Label String: [Highest Elevation]

Characteristics: 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case)

PL-04351_2 Elevation Contour / snow, ice / half auxiliary / zero (line) Highest Elevation [ZVH] = 0

Label String: "ZERO"
Characteristics: 90

90 (Cyan, Condensed, Italic, 7 pt, Upper case)

PL-04351_3 Elevation Contour / snow, ice / half auxiliary / minus (line) Highest Elevation [ZVH] < 0

Label String: "MINUS" [Highest Elevation]

Characteristics: 90, 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case) 90 (Cyan, Condensed, Italic, 7 pt, Upper case)

Symbol Samples

Elevation Contour / snow, ice / quarter auxiliary (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00118 Component Type: Line - Styled Color Token: Cyan

Description: Cyan 0.1mm Dashed Line (0.1mm wt, 1.5mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.5mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criter

PS-04361 Elevation Contour / snow, ice /

quarter auxiliary (line)

Elevation Surface Category [ESC] = Snow Field and/or Ice-field [2]

AND Hypsography Portrayal Type [HQC] = Quarter Auxiliary Contour [14]

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04361_1 Elevation Contour / snow, ice / quarter auxiliary / greater Highest Elevation [ZVH] > 0

than zero (line)

Label String: [Highest Elevation]

Characteristics: 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case)

PL-04361_2 Elevation Contour / snow, ice / quarter auxiliary / zero Highest Elevation [ZVH] = 0

(line)

Label String: "ZERO"
Characteristics: 90

90 (Cyan, Condensed, Italic, 7 pt, Upper case)

PL-04361_3 Elevation Contour / snow, ice / quarter auxiliary / minus Highest Elevation [ZVH] < 0

(line)

Label String: "MINUS" [Highest Elevation]

Characteristics: 90, 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case) 90 (Cyan, Condensed, Italic, 7 pt, Upper case)

Symbol Samples

-----15------

Elevation Contour / snow, ice / mound / index (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: The same as the corresponding depression elevation contour.

Symbol Graphic

Note: Component P00055 is perpendicular to and on the downhill side of Component L00015.

Component Ref #: L00015 Component Type: Line - Simple Color Token: Cyan

Description:

Cyan 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Component Ref #: P00055 Component Type: Point - Simple Color Token: Cyan

Description: Cyan 0.5mm length line with a 0.1mm lineweight

Parameters:

Line Weight: 0.1mm
Length: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04738 Elevation Contour / snow, ice / Elevation Surface Category [ESC] = Snow Field and/or Ice-field [2] mound / index (line)

AND Hypsography Portrayal Type [HQC] = Mound Index Contour [8]

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04738_1 Elevation Contour / snow, ice / mound / index / greater

than zero (line)

Label String: [Highest Elevation]

Characteristics: 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case)

PL-04738_2 Elevation Contour / snow, ice / mound / index / zero (line)

Highest Elevation [ZVH] = 0

Highest Elevation [ZVH] < 0

Highest Elevation [ZVH] > 0

Label String: "ZERO"
Characteristics: 90

90 (Cyan, Condensed, Italic, 7 pt, Upper case)

PL-04738_3 Elevation Contour / snow, ice / mound / index / minus

(line)

Label String: "MINUS" [Highest Elevation]

Characteristics: 90, 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case) 90 (Cyan, Condensed, Italic, 7 pt, Upper case)

Symbol Samples



Elevation Contour / snow, ice / mound / intermediate (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: The same as the corresponding depression elevation contour.

Symbol Graphic

Note: Component P00055 is perpendicular to and on the downhill side of Component L00108.

Component Ref #: L00108 Component Type: Line - Simple Color Token: Cyan

Description: Cyan 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Component Ref #: P00055 Component Type: Point - Simple Color Token: Cyan

Description: Cyan 0.5mm length line with a 0.1mm lineweight

Parameters:

Line Weight: 0.1mm
Length: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04739 Elevation Contour / snow, ice / Elevation Surface Category [ESC] = Snow Field and/or Ice-field [2] mound / intermediate (line)

AND Hypsography Portrayal Type [HQC] = Mound Intermediate Contour [9]

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04739_1 Elevation Contour / snow, ice / mound / intermediate / Highest Elevation [ZVH] > 0

greater than zero (line)

Label String: [Highest Elevation]

Characteristics: 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case)

PL-04739_2 Elevation Contour / snow, ice / mound / intermediate/

zero (line)

Label String: "ZERO"
Characteristics: 90

90 (Cyan, Condensed, Italic, 7 pt, Upper case)

PL-04739_3 Elevation Contour / snow, ice / mound / intermediate/

minus (line)

Label String: "MINUS" [Highest Elevation]

Characteristics: 90, 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case) 90 (Cyan, Condensed, Italic, 7 pt, Upper case)

Symbol Samples



Elevation Contour / snow, ice / depression / index (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Each depression elevation contour shall have equally spaced ticks extending from the contour towards the

Highest Elevation [ZVH] = 0

Highest Elevation [ZVH] < 0

lower elevation. The bottom most depression elevation contour shall have a tick interval of $0.5\,$ mm. The first ascending depression contour shall have a tick interval of $1.0\,$ mm, the second shall have a tick interval of $2.0\,$

mm, and all subsequent shall have a tick interval of 3.0.

Symbol Graphic Note: Component P00055 is perpendicular to and on the downhill side of Component L00015.

Component Ref #: L00015 Component Type: Line - Simple Color Token: Cyan

Description: Parameters:

Line Weight: 0.2mm

Component Ref #: P00055 Component Type: Point - Simple Color Token: Cyan

Description: Cyan 0.5mm length line with a 0.1mm lineweight

Cyan 0.2mm Solid Line

Parameters:

Line Weight: 0.1mm
Length: 0.5mm

Symbol Rules

Reference #: Description: Criteria

PS-04355 Elevation Contour / snow, ice / Elevation Surface Category [ESC] = Snow Field and/or Ice-field [2] depression / index (line)

AND Hypsography Portrayal Type [HQC] = Depression Index Contour [5]

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04355 1 Elevation Contour / snow, ice / depression / index / greater Highest Elevation [ZVH] > 0

than zero (line)

Label String: [Highest Elevation]

Characteristics: 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case)

PL-04355_2 Elevation Contour / snow, ice / depression / index / zero Highest Elevation [ZVH] = 0

(line)

Label String: "ZERO"
Characteristics: 90

90 (Cyan, Condensed, Italic, 7 pt, Upper case)

PL-04355_3 Elevation Contour / snow, ice / depression / index / minus

(line)


Label String: "MINUS" [Highest Elevation]

Characteristics: 90, 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case) 90 (Cyan, Condensed, Italic, 7 pt, Upper case)

Symbol Samples





Elevation Contour / snow, ice / depression / intermediate (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Each depression elevation contour shall have equally spaced ticks extending from the contour towards the

Color Token:

Highest Elevation [ZVH] < 0

lower elevation. The bottom most depression elevation contour shall have a tick interval of 0.5 mm. The first ascending depression contour shall have a tick interval of 1.0 mm, the second shall have a tick interval of 2.0

Cyan

mm, and all subsequent shall have a tick interval of 3.0.

Symbol Graphic Note: Component P00055 is perpendicular to and on the downhill side of Component L00108. Elevation contour values shall not be labeled

for intermediate elevation contours except when percent of slope is < 5 in an area >= 150 mm x 150 mm.

Component Ref #: L00108 Component Type: Line - Simple Description: Cyan 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Component Ref #: P00055 Component Type: Point - Simple Color Token: Cyan

Description: Cyan 0.5mm length line with a 0.1mm lineweight

Parameters:

Line Weight: 0.1mm
Length: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04357 Elevation Contour / snow, ice / Elevation Surface Category [ESC] = Snow Field and/or Ice-field [2]

depression / intermediate (line)

AND Hypsography Portrayal Type [HQC] = Depression Intermediate Contour [6]

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04357_1 Elevation Contour / snow, ice / depression / intermediate / Highest Elevation [ZVH] > 0

greater than zero (line)

Label String: [Highest Elevation]

Characteristics: 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case)

PL-04357_2 Elevation Contour / snow, ice / depression / intermediate / Highest Elevation [ZVH] = 0

zero (line)

Label String: "ZERO"
Characteristics: 90

90 (Cyan, Condensed, Italic, 7 pt, Upper case)

PL-04357 3 Elevation Contour / snow, ice / depression / intermediate / Highest Elevation [ZVH] < 0

minus (line)


Label String: "MINUS" [Highest Elevation]

Characteristics: 90, 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case) 90 (Cyan, Condensed, Italic, 7 pt, Upper case)

Symbol Samples





Elevation Contour / snow, ice / depression / auxiliary (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00055 is centered on every dash of Component L00110.



Symbol Graphic

Note: Component P00055 is perpendicular to and on the downhill side of Component L00110.

Component Ref #: L00110 Component Type: Line - Styled Color Token: Cyan

Description: Cyan 0.1mm Dashed Line (0.1mm wt, 3.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 3.0mm Dash Spacing: 0.5mm

Component Ref #: P00055 Component Type: Point - Simple Color Token: Cyan

Description: Cyan 0.5mm length line with a 0.1mm lineweight

Parameters:

Line Weight: 0.1mm
Length: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04363 Elevation Contour / snow, ice / Elevation Surface Category [ESC] = Snow Field and/or Ice-field [2]

depression / auxiliary (line)

AND Hypsography Portrayal Type [HQC] = Depression Auxiliary Contour [22]

Label Rules

Label Placement Rules (see Annex J): LP-3987

Reference #: Description: Criteria:

PL-04363_1 Elevation Contour / snow, ice / depression / auxiliary / Highest Elevation [ZVH] > 0

greater than zero (line)

Label String: [Highest Elevation]

Characteristics: 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case)

PL-04363_2 Elevation Contour / snow, ice / depression / auxiliary / zero Highest Elevation [ZVH] = 0

(line)

Label String: "ZERO"
Characteristics: 90

90 (Cyan, Condensed, Italic, 7 pt, Upper case)

PL-04363_3 Elevation Contour / snow, ice / depression / auxiliary / Highest Elevation [ZVH] < 0

minus (line)

Label String: "MINUS" [Highest Elevation]

Characteristics: 90, 19

19 (Cyan, Condensed, Italic, 7 pt, Lower case) 90 (Cyan, Condensed, Italic, 7 pt, Upper case)



Embankment (DB090)

Generalization Rules (see Annex J): GA-9999

Embankment / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00174; 1.5mm

Symbol Graphic Note: Component P00174 is attached perpendicular to and on the downhill side of Component L00240.

Component Ref #: L00240 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.15mm Solid Line

Parameters:

Line Weight: 0.15mm

Component Ref #: P00174 Component Type: Point - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.5mm length line with 0.15mm lineweight

Parameters:

Length: 0.15mm

Length: 0.5mm

Symbol Rules

Reference #: Description: Criteria:
PS-04246 Embankment / all (area) All

Symbol Samples

Embankment / fill (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00174 has an initial offset of 0.75mm; after that 1.5mm.

Symbol Graphic

Note: Component P00174 is perpendicular to and on the downhill side of Component L00240.

Component Ref #: L00240 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.15mm Solid Line

Parameters:

Line Weight: 0.15mm

Component Ref #: P00174 Component Type: Point - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.5mm length line with 0.15mm lineweight

Parameters:

Line Weight: 0.15mm
Length: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04248 Embankment / fill (line) Embankment Type [FIC] = Fill [2]

AND Transportation System Type [TRS] = (Not Applicable [998], Other [999], Pedestrian [9], Unknown [0])

Embankment / with transportation (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00174 has an initial offset of 0.75mm; after that 1.5mm.

Symbol Graphic

Note: Component P00174 is perpendicular to and on the downhill side of each Component L00241.

Component Ref #: L00241 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Two parallel Dk-Brown1815 0.15mm Solid Lines

Parameters:

Line Weight: 0.15mm

Note: Spacing is variable based on the width of the overpassing feature. The minimum space between each line and the linear portion of the over

passing feature shall be 0.2 mm.

Component Ref #: P00174 Component Type: Point - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.5mm length line with 0.15mm lineweight

Parameters:

Length: 0.15mm

Length: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04250 Embankment / with transportation Embankment Type [FIC] = (Dyke [3], Fill [2], Mound [1], Unknown [0])

AND

(line)

Transportation System Type [TRS] = (Aeronautical [1], Aqueduct [2], Bus [4], Canal [5], Maritime [7],

Pipeline [10], Railway [12], Road [13])

Symbol Samples

Shown with road:

Shown with railway:

Embankment / without transportation (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00067 has an initial offset of 0.75mm; after that 1.5mm.

Symbol Graphic Note: Component P00067 is perpendicular to and on the downhill side of Component L00240.

Component Ref #: L00240 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.15mm Solid Line

Parameters:

4444

Line Weight: 0.15mm

Component Ref #: P00067 Component Type: Point - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.8mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm

Length: 0.8mm

Symbol Rules

Reference #: Description: Criteria:

PS-04251 Embankment / without Embankment Type [FIC] = (Dyke [3], Mound [1], Unknown [0])

AND

transportation (line)

Symbol Samples

ransportation System Type [TRS] = (Not Applicable [998], Other [999], Pedestrian [9], Unknown [0])

Engineered Earthwork (AH025)

Generalization Rules (see Annex J): GA-9999

Engineered Earthwork / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Line - Simple

Color Token:

Black

Symbol Type: Simple



Component Ref #: L00011

Description: Black 0.3mm Solid Line

Parameters:

Line Weight: 0.3mm

Symbol Rules

Component Type:

Reference #: Description: Criteria:

PS-04508 Engineered Earthwork / all (line) All

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:

PL-04508_1 Engineered Earthwork / other (line) Engineered Earthwork Type [EET] = (Battery [1], Rampart [4], Redoubt [5])

Label Rules

Label String: [Engineered Earthwork Type]

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04508_2 Engineered Earthwork / parapet (line) Engineered Earthwork Type [EET] = Military Parapet [2]

Label String: "Parapet"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04508_3 Engineered Earthwork / trench (line) Engineered Earthwork Type [EET] = (Military Trench [3], Other [999], Unknown

[0])

Label String: "Trench"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Trench Battery

Entrance and/or Exit (AQ090)

Entrance and/or Exit / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Note: The baseline of the symbol is centered perpendicular to the end of the associated transportation feature, with the angled element facing towards the transportation feature.

Component Ref #: P00073 Component Type: Point - Shape Color Token: Black

Description: Tunnel entrance not water

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:
PS-04725 Entrance and/or Exit / all (point) All

Symbol Samples

Shown with Road:

Esker (DB100)

Generalization Rules (see Annex J): GA-9999

)

Esker / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00023 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Symbol Rules

Label Rules

Reference #: Description: Criteria:

PS-04509 Esker / all (line) All

Label Placement Rules (see Annex J): LP-3630

Reference #: Description: Criteria:

PL-04509_1 Esker / all (line) N/A

Label String: "Esker"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Esker

Extraction Mine (AA010)

Generalization Rules (see Annex J): GA-9999, GC-9982

Extraction Mine / intact / not peat (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00210 is applied to the perimeter and Component P00001 is placed in the center.

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Component Ref #: P00001 Component Type: Point - Shape Color Token: Black

Description: Extraction mine intact not peat

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04266 Extraction Mine / intact / not peat Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

(area)

AND Extraction Mine Type [MZN] = (Area Strip-mine [6], Below Surface [9], Opencast [3], Placer [4], Prospect

[5], Unknown[0])

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04266_1 Extraction Mine / intact / not peat / named / type known /

product known (area)

AND Extraction Mine Type [MZN] = (Opencast [3], Placer [4], Prospect [5], Area Strip-

mine [6], Below Surface [9])

Name [NAM] <> Unknown

AND Product [PPO] = (Bauxite [9], Coal [18], Copper [26], Diamond [33], Gold [48],

Iron [58], Lead [59], Manganese [65], Quartz [89], Salt [95], Silver [105], Uranium

[120], Zinc [126])

Label String: [Name] "("[Extraction Mine Type]")" "("[Product]")"

Characteristics: 1, 22, 22, 22, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04266 2 Extraction Mine / intact / not peat / named / type known /

product unknown (area)

Name [NAM] <> Unknown

AND Extraction Mine Type [MZN] = (Opencast [3], Placer [4], Prospect [5], Area Strip-

mine [6], Below Surface [9])

AND Product [PPO] = (Other [999], Unknown [0])

Label String: [Name] "("[Extraction Mine Type]")"

Characteristics: 1, 22, 22, 22

> 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04266_3 Extraction Mine / intact / not peat / named / type

unknown / product known (area)

Name [NAM] <> Unknown

Extraction Mine Type [MZN] = Unknown [0] AND

Product [PPO] = (Bauxite [9], Coal [18], Copper [26], Diamond [33], Gold [48], AND

Iron [58], Lead [59], Manganese [65], Quartz [89], Salt [95], Silver [105], Uranium

[120], Zinc [126])

Label String: [Name] "("[Product]")"

Characteristics: 1, 22, 22, 22

> 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04266_4 Extraction Mine / intact / not peat / named / type unknown / product unknown (area)

Name [NAM] <> Unknown

AND Extraction Mine Type [MZN] = Unknown [0]

AND Product [PPO] = (Other [999], Unknown [0])

Label String: [Name] Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04266_5 Extraction Mine / intact / not peat / unnamed / type

Name [NAM] = Unknown

known / product known (area)

AND Extraction Mine Type [MZN] = (Opencast [3], Placer [4], Prospect [5], Area Strip-

mine [6], Below Surface [9])

AND Product [PPO] = (Bauxite [9], Coal [18], Copper [26], Diamond [33], Gold [48],

Iron [58], Lead [59], Manganese [65], Quartz [89], Salt [95], Silver [105], Uranium

[120], Zinc [126])

Label String: [Extraction Mine Type] "("[Product]")"

Characteristics: 1, 22, 22, 22

> 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04266_6 Extraction Mine / intact / not peat / unnamed / type known / product unknown (area)

Name [NAM] = Unknown

AND Extraction Mine Type [MZN] = (Opencast [3], Placer [4], Prospect [5], Area Strip-

mine [6], Below Surface [9])

AND Product [PPO] = (Other [999], Unknown [0])

Label String: [Extraction Mine Type]

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Extraction Mine / intact / not peat / unnamed / type PL-04266 7

unknown / product known (area)

Name [NAM] = Unknown

AND Extraction Mine Type [MZN] = Unknown [0]

AND Product [PPO] = (Bauxite [9], Coal [18], Copper [26], Diamond [33], Gold [48],

Iron [58], Lead [59], Manganese [65], Quartz [89], Salt [95], Silver [105], Uranium

[120], Zinc [126])

Label String: [Product]

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Area strip-mine

Extraction Mine / not intact / not peat (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00210 is applied to the perimeter and Component P00002 is placed in the center.

Component Ref #: Component Type: Line - Styled Color Token: L00210 Black

Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap) Description:

Parameters:

Line Weight: 0.1mm Dash Length: Dash Spacing: 0.5mm 1.0mm

Component Ref #: P00002 Component Type: Point - Shape Color Token: Black

Extraction mine not intact not peat Description:

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description:

Extraction Mine / not intact / not PS-04267 Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under peat (area)

Construction [1])

AND Extraction Mine Type [MZN] = (Area Strip-mine [6], Below Surface [9], Opencast [3], Placer [4], Prospect

[5], Unknown[0])

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04267 1 Extraction Mine / not intact / not peat / named / type

known / product known (area)

Extraction Mine Type [MZN] = (Opencast [3], Placer [4], Prospect [5], Area Strip-AND

mine [6], Below Surface [9])

Name [NAM] <> Unknown

AND Product [PPO] = (Bauxite [9], Coal [18], Copper [26], Diamond [33], Gold [48],

Iron [58], Lead [59], Manganese [65], Quartz [89], Salt [95], Silver [105], Uranium

[120], Zinc [126])

Label String: [Name] "("[Extraction Mine Type]")" "("[Product]")"

Characteristics: 1, 22, 22, 22, 22, 22, 22

> 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04267_2 Extraction Mine / not intact / not peat / named / type

known / product unknown (area)

Name [NAM] <> Unknown

AND Extraction Mine Type [MZN] = (Opencast [3], Placer [4], Prospect [5], Area Strip-

mine [6], Below Surface [9])

AND Product [PPO] = (Other [999], Unknown [0])

Label String: [Name] "("[Extraction Mine Type]")"

Characteristics: 1, 22, 22, 22

> 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04267_3 Extraction Mine / not intact / not peat / named / type

unknown / product known (area)

Name [NAM] <> Unknown

AND Extraction Mine Type [MZN] = Unknown [0]

AND Product [PPO] = (Bauxite [9], Coal [18], Copper [26], Diamond [33], Gold [48], Iron [58], Lead [59], Manganese [65], Quartz [89], Salt [95], Silver [105], Uranium [120], Zinc [126]) Label String: [Name] "("[Product]")" Characteristics: 1, 22, 22, 22 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case) PL-04267_4 Extraction Mine / not intact / not peat / named / type Name [NAM] <> Unknown unknown / product unknown (area) AND Extraction Mine Type [MZN] = Unknown [0] Product [PPO] = (Other [999], Unknown [0]) AND Label String: [Name] Characteristics: 1 (Black, Condensed, 6 pt, Mixed case) PL-04267_5 Extraction Mine / not intact / not peat / unnamed / type Name [NAM] = Unknown known / product known (area) AND Extraction Mine Type [MZN] = (Opencast [3], Placer [4], Prospect [5], Area Stripmine [6], Below Surface [9]) Product [PPO] = (Bauxite [9], Coal [18], Copper [26], Diamond [33], Gold [48], AND Iron [58], Lead [59], Manganese [65], Quartz [89], Salt [95], Silver [105], Uranium [120], Zinc [126]) Label String: [Extraction Mine Type] "("[Product]")" Characteristics: 1, 22, 22, 22 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case) PL-04267 6 Extraction Mine / not intact / not peat / unnamed / type Name [NAM] = Unknown known / product unknown (area) AND Extraction Mine Type [MZN] = (Opencast [3], Placer [4], Prospect [5], Area Stripmine [6], Below Surface [9]) AND Product [PPO] = (Other [999], Unknown [0]) Label String: [Extraction Mine Type] Characteristics: 1 1 (Black, Condensed, 6 pt, Mixed case) PL-04267_7 Extraction Mine / not intact / not peat / unnamed / type Name [NAM] = Unknown unknown / product known (area) AND Extraction Mine Type [MZN] = Unknown [0] Product [PPO] = (Bauxite [9], Coal [18], Copper [26], Diamond [33], Gold [48], AND Iron [58], Lead [59], Manganese [65], Quartz [89], Salt [95], Silver [105], Uranium [120], Zinc [126]) Label String: [Product] Characteristics: 1 (Black, Condensed, 6 pt, Mixed case) Symbol Samples Opencast × ×

Extraction Mine / peat (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: A00001 Component Type: Area - Pattern Color Token: Black

Description: Black Peat Fill

Parameters:

Area Pattern: AP-129, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04268 Extraction Mine / peat (area) Extraction Mine Type [MZN] = Peatery [8]

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04268_1 Extraction Mine / peat (area) N/A

Label String: "Peat cuttings"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples



Extraction Mine / intact / not peat (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00001 Component Type: Point - Shape Color Token: Black

Description: Extraction mine intact not peat

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04269 Extraction Mine / intact / not peat

(point)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Extraction Mine Type [MZN] = (Area Strip-mine [6], Below Surface [9], Opencast [3], Placer [4], Prospect

[5], Unknown[0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04269_1 Extraction Mine / intact / not peat / named / type known / Name [NAM] <> Unknown

AND

product known (point)

AND Extraction Mine Type [MZN] = (Opencast [3], Placer [4], Prospect [5], Area Strip-

mine [6], Below Surface [9])

AND Product [PPO] = (Bauxite [9], Coal [18], Copper [26], Diamond [33], Gold [48],

Iron [58], Lead [59], Manganese [65], Quartz [89], Salt [95], Silver [105], Uranium

[120], Zinc [126])

Label String: [Name] "("[Extraction Mine Type]")" "("[Product]")"

Characteristics: 1, 22, 22, 22, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04269_2 Extraction Mine / intact / not peat / named / type known / product unknown (point)

Name [NAM] <> Unknown

AND Extraction Mine Type [MZN] = (Opencast [3], Placer [4], Prospect [5], Area Strip-

mine [6], Below Surface [9])

AND Product [PPO] = (Other [999], Unknown [0])

Label String: [Name] "("[Extraction Mine Type]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04269_3 Extraction Mine / intact / not peat / named / type unknown / product known (point)

Name [NAM] <> Unknown

AND Extraction Mine Type [MZN] = Unknown [0]

AND Product [PPO] = (Bauxite [9], Coal [18], Copper [26], Diamond [33], Gold [48],

Iron [58], Lead [59], Manganese [65], Quartz [89], Salt [95], Silver [105], Uranium

[120], Zinc [126])

Label String: [Name] "("[Product]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04269_4 Extraction Mine / intact / not peat / named / type unknown / product unknown (point)

Name [NAM] <> Unknown

AND Extraction Mine Type [MZN] = Unknown [0]

AND Product [PPO] = (Other [999], Unknown [0])

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04269_5 Extraction Mine / intact / not peat / unnamed / type known / product known (point)

Name [NAM] = Unknown

AND Extraction Mine Type [MZN] = (Opencast [3], Placer [4], Prospect [5], Area Strip-

mine [6], Below Surface [9])

AND Product [PPO] = (Bauxite [9], Coal [18], Copper [26], Diamond [33], Gold [48],

Iron [58], Lead [59], Manganese [65], Quartz [89], Salt [95], Silver [105], Uranium

[120], Zinc [126])

Label String: [Extraction Mine Type] "("[Product]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04269_6 Extraction Mine / intact / not peat / unnamed / type known / product unknown (point)

Name [NAM] = Unknown

AND Extraction Mine Type [MZN] = (Opencast [3], Placer [4], Prospect [5], Area Strip-

mine [6], Below Surface [9])

AND Product [PPO] = (Other [999], Unknown [0])

Label String: [Extraction Mine Type]

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

PL-04269_7 Extraction Mine / intact / not peat / unnamed / type unknown / product known (point)

Name [NAM] = Unknown

AND Extraction Mine Type [MZN] = Unknown [0]

AND Product [PPO] = (Bauxite [9], Coal [18], Copper [26], Diamond [33], Gold [48],

Iron~[58], Lead~[59], Manganese~[65], Quartz~[89], Salt~[95], Silver~[105], Uranium~[65], Vertical Control of the control of

[120], Zinc [126])

Label String: [Product]

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

★ Prospect
★ Coal

Extraction Mine / not intact / not peat (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00002 Component Type: Point - Shape Color Token: Black

Description: Extraction mine not intact not peat

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04270 Extraction Mine / not intact / not Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

peat (point) Construction [

AND Extraction Mine Type [MZN] = (Area Strip-mine [6], Below Surface [9], Opencast [3], Placer [4], Prospect

[5], Unknown[0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04270_1 Extraction Mine / not intact / not peat / named / type Name [NAM] <> Unknown

known / product known (point)

AND Extraction Mine Type [MZN] = (Opencast [3], Placer [4], Prospect [5], Area Strip-

mine [6], Below Surface [9])

AND Product [PPO] = (Bauxite [9], Coal [18], Copper [26], Diamond [33], Gold [48],

Iron [58], Lead [59], Manganese [65], Quartz [89], Salt [95], Silver [105], Uranium

[120], Zinc [126])

Label String: [Name] "("[Extraction Mine Type]")" "("[Product]")"

Characteristics: 1, 22, 22, 22, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04270_2 Extraction Mine / not intact / not peat / named / type Nam

known / product unknown (point)

Name [NAM] <> Unknown

AND Extraction Mine Type [MZN] = (Opencast [3], Placer [4], Prospect [5], Area Strip-

mine [6], Below Surface [9])

AND Product [PPO] = (Other [999], Unknown [0])

Label String: [Name] "("[Extraction Mine Type]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04270_3 Extraction Mine / not intact / not peat / named / type unknown / product known (point)

ot peat / named / type Name [NAM] <> Unknown

AND Extraction Mine Type [MZN] = Unknown [0]

AND Product [PPO] = (Bauxite [9], Coal [18], Copper [26], Diamond [33], Gold [48],

Iron [58], Lead [59], Manganese [65], Quartz [89], Salt [95], Silver [105], Uranium

[120], Zinc [126])

Label String: [Name] "("[Product]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04270_4 Extraction Mine / not intact / not peat / named / type

unknown / product unknown (point)

Name [NAM] <> Unknown

AND Extraction Mine Type [MZN] = Unknown [0]

AND Product [PPO] = (Other [999], Unknown [0])

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04270_5 Extraction Mine / not intact / not peat / unnamed / type

known / product known (point)

Name [NAM] = Unknown

AND Extraction Mine Type [MZN] = (Opencast [3], Placer [4], Prospect [5], Area Strip-

mine [6], Below Surface [9])

AND Product [PPO] = (Bauxite [9], Coal [18], Copper [26], Diamond [33], Gold [48],

Iron [58], Lead [59], Manganese [65], Quartz [89], Salt [95], Silver [105], Uranium

[120], Zinc [126])

Label String: [Extraction Mine Type] "("[Product]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04270_6 Extraction Mine / not intact / not peat / unnamed / type known / product unknown (point)

Name [NAM] = Unknown

AND Extraction Mine Type [MZN] = (Opencast [3], Placer [4], Prospect [5], Area Strip-

mine [6], Below Surface [9])

AND Product [PPO] = (Other [999], Unknown [0])

Label String: [Extraction Mine Type]

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

PL-04270_7 Extraction Mine / not intact / not peat / unnamed / type

unknown / product known (point)

Name [NAM] = Unknown

AND Extraction Mine Type [MZN] = Unknown [0]

AND Product [PPO] = (Bauxite [9], Coal [18], Copper [26], Diamond [33], Gold [48],

Iron [58], Lead [59], Manganese [65], Quartz [89], Salt [95], Silver [105], Uranium

[120], Zinc [126])

Label String: [Product]

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

× × Placer × Iron

Extraction Mine / peat (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00084 Component Type: Point - Shape Color Token: Black

Description: Extraction mine peat

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04271 Extraction Mine / peat (point) Extraction Mine Type [MZN] = Peatery [8]

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04271_1 Extraction Mine / peat (point) N/A

Label String: "Peat cuttings"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Peat cuttings


Facility (AL010)

Generalization Rules (see Annex J): GA-9999, GC-9999

Facility / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:
PS-04280 Facility / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-4813, LP-9950, LP-9999

Criteria: Reference #: Description: PL-04280_1 Facility / intact / important (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) AND Feature Function [FFN] = (Botanical and/or Zoological Reserve Activities [907], Diplomacy [825], Education [850], Government [811], Human Health Activities [860], Manufacturing [99], Religious Activities [930], Telecommunications [610], Transport [480], Utilities [350]) Label String: [Name] [Feature Function] Characteristics: 1 (Black, Condensed, 6 pt, Mixed case) PL-04280_2 Facility / intact / military (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) AND Feature Function [FFN] = Defence Activities [835] Label String: [Name] "Military" Characteristics: 1. 1 1 (Black, Condensed, 6 pt, Mixed case) PL-04280_3 Facility / intact / prison (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) AND Feature Function [FFN] = Imprisonment [843] Label String: [Name] "Prison" Characteristics: 1 (Black, Condensed, 6 pt, Mixed case) PL-04280 4 Facility / intact / other (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) AND Feature Function [FFN] = (Accommodation [550], Administration [810], Agriculture [2], Commerce [440], Other [999], Residence [563], Sports Centre [912], Unknown [0]) Label String: [Name] Characteristics: 1 (Black, Condensed, 6 pt, Mixed case) PL-04280_5 Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Facility / not intact / important (area) Dismantled [4], Under Construction [1]) AND Feature Function [FFN] = (Botanical and/or Zoological Reserve Activities [907], Diplomacy [825], Education [850], Government [811], Human Health Activities [860], Manufacturing [99], Religious Activities [930], Telecommunications [610], Transport [480], Utilities [350]) Label String: [Name] [Feature Function] "("[Condition of Facility]")"

> Characteristics: 1, 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04280 6 Facility / not intact / military (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

AND Feature Function [FFN] = Defence Activities [835]

[Name] "Military" "("[Condition of Facility]")" Label String:

Characteristics: 1, 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04280 7 Facility / not intact / prison (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

AND Feature Function [FFN] = Imprisonment [843]

Label String: [Name] "Prison" "("[Condition of Facility]")"

Characteristics: 1, 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04280_8 Facility / not intact / other (area)

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

AND

Feature Function [FFN] = (Accommodation [550], Administration [810], Agriculture [2], Commerce [440], Other [999], Residence [563], Sports Centre

[912], Unknown [0])

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

____ Military ____ York Manufacturing ____ Alcatraz Prison (abandoned)

Facility / intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00006 Component Type: Point - Simple Color Token: Black

Description: Black filled square with all sides 0.8mm

Parameters:

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04286 Facility / intact (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04286_1 Facility / intact / important (point) Feature Function [FFN] = (Botanical and/or Zoological Reserve Activities [907], Diplomacy [825], Education [850], Government [811], Human Health Activities

[860], Manufacturing [99], Religious Activities [930], Telecommunications [610],

Transport [480], Utilities [350])

Label String: [Name] [Feature Function]

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04286_2 Facility / intact / military (point) Feature Function [FFN] = Defence Activities [835]

Label String: [Name] "Military"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04286_3 Facility / intact / prison (point) Feature Function [FFN] = Imprisonment [843]

Label String: [Name] "Prison"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04286 4 Facility / intact / other (point) Feature Function [FFN] = (Accommodation [550], Administration [810], Agriculture [2], Commerce [440], Other [999], Residence [563], Sports Centre

[912], Unknown [0])

Label String: [Name]

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Government

_ San Quentin State Prison

Facility / not intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Reference #: Description:

Component Ref #: P00173 Component Type: Point - Shape Color Token: Black/Black-12

Criteria:

Not intact square 0.8mm Description:

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

PS-04291 Facility / not intact (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04291_1 Facility / not intact / important (point) Feature Function [FFN] = (Botanical and/or Zoological Reserve Activities [907], Diplomacy [825], Education [850], Government [811], Human Health Activities

[860], Manufacturing [99], Religious Activities [930], Telecommunications [610],

Transport [480], Utilities [350])

[Name] [Feature Function] Label String:

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

PL-04291_2 Facility / not intact / military (point) Feature Function [FFN] = Defence Activities [835]

> Label String: [Name] "Military"

Characteristics: 1.1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04291_3 Facility / not intact / prison (point) Feature Function [FFN] = Imprisonment [843]

> Label String: [Name] "Prison"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Facility / not intact / other (point) PL-04291_4 Feature Function [FFN] = (Accommodation [550], Administration [810],

Agriculture [2], Commerce [440], Other [999], Residence [563], Sports Centre

[912], Unknown [0])

Label String: [Name] Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Transport

Fairground (AK090) Generalization Rules (see Annex J): GA-9999, GC-9999 Fairground / all (area) Symbol Placement Instructions: The symbol is applied to the geometry of the feature. Symbol Type: Simple **Symbol Graphic** Line - Styled Component Ref #: L00210 Component Type: Color Token: Black Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap) Description: Parameters: Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm Symbol Rules Reference #: Description: Criteria: PS-04057 Fairground / all (area) ΑII Label Rules Label Placement Rules (see Annex J): LP-3506, LP-4813, LP-9999 Reference #: Criteria: Description: PL-04057_1 Fairground / intact (area) N/A Label String: [Name] "Fairgrounds" Characteristics: 1 (Black, Condensed, 6 pt, Mixed case) Symbol Samples Fairgrounds Indiana State Fairgrounds Fairground / all (point) **Symbol Placement Instructions:** Origin: Center of symbol Symbol Type: Simple **Symbol Graphic** Component Type: Component Ref #: Point - Simple Color Token: Black Description: Black filled square with all sides 0.8mm Parameters: Length: 0.8mm The component is a square and is filled with the solid color. Note: Symbol Rules Criteria: Reference #: Description: PS-04510 Fairground / all (point) ΑII

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:
PL-04510_1 Fairground / intact (point) N/A

Label String: [Name] "Fairgrounds"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Fairgrounds

Lenoir County Fairgrounds

Fence (AL070)

Generalization Rules (see Annex J): GA-9999

Fence / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic Note: Repeating pattern is Component L00442 followed by Component P00286 centered within each gap.

Component Ref #: L00442 Component Type: Line - Styled Color Token: Black

Description: Black 0.15mm Dashed Line (0.15mm wt, 3.0mm dash, 1.0mm gap)

Description: Parameters:

Line Weight: 0.15mm Dash Length: 3.0mm Dash Spacing: 1.0mm

Component Ref #: P00286 Component Type: Point - Shape Color Token: Black

Description: Fence "X"

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04084 Fence / all (line) All

Symbol Samples


Ferry Crossing (AQ070)

Generalization Rules (see Annex J): GA-9999, GC-9991

Ferry Crossing / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #: L00031 Component Type: Line - Styled Color Token: Black

Description: Black 0.2mm Dashed Line (0.2mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04137 Ferry Crossing / all (line) All

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-4813, LP-9999

Reference #: Description: Criteria:
PL-04137_1 Ferry Crossing / all (line) N/A

Label String: [Name] [Transportation System Type] "Ferry"

Characteristics: 1, 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Ferry Staten Island Pedestrian Ferry Pedestrian ferry

Ferry Crossing / all (point)

Symbol Placement Instructions: Text label only. No graphic parameters

Symbol Type: Simple

Ferry

Symbol Graphic

Symbol Rules

Reference #: Description: Criteria:
PS-04531 Ferry Crossing / all (point) All

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:
PL-04531_1 Ferry Crossing / all (point) N/A

Label String: [Name] [Transportation System Type] "Ferry"

Characteristics: 1, 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Ferry Elwell Road Ferry Road ferry

Firing Range (FA015)

Generalization Rules (see Annex J): GA-9999, GC-9999

Firing Range / all (area)

			The symbol is applied	to the geometry of the feat	ture.
$_{\Gamma}$ — —	Symbol	Type: Simple			
İ	1				
Symbol	Graphic				
Componer Descriptio <u>Parameter</u>	n: Black 0.1mm Da	Component Typ ashed line (0.1mm wt, 1.0mi		Color Token:	Black
Line Weigl		Dash Length:	1.0mm	Dash Spacing:	0.5mm
- 6 "			Symbol	Rules	
Reference #: PS-04532	Description: Firing Range / all (area)		riteria: .II		
	0 - 0-7 - (,	,	Label Rule	es .	
Label Placemo	ent Rules (see Annex J):	LP-3506, LP-4813, LP-995			
Reference #:	Description:			Criteria:	
PL-04532_1	Firing Range / intact (area)		Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])
	Label String:	[Name] "Firing range"			
	Characteristics:	1, 1 1 (Black, Condensed, 6 pt,	Miyod caso)		
PL-04532_2	Firing Range / not int		iviixed case)	Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],
				Dismantled [4], Under Co	
	Label String:	[Name] "Firing range" "("[Condition of Facility]")"	
	Characteristics:	1, 1, 22, 22, 22 1 (Black, Condensed, 6 pt,	Mixed case)		
		22 (Black, Condensed, 6 pt	, Lower case)		
			Symbol Sa	mples	
	F = = 1 Eiring range		Creekside	Firing Range	
	Firing range		l orostolao	Timig hango	
iring Rang	e / all (point)				
		Placement Instructions:	Origin: Center of sym	bol	
	Symbol	Type: Simple			
C.)				
Complete I	Conchin				
Symbol	Grapnic				
Componer Descriptio		Component Typ	e: Point - Shape	Color Token:	Black
<u>Parameter</u>	rs:				
Note:	See Annex H fo	or detailed drawing instruction	ons.		
Defense "	Description .	_	Symbol	Rules	
Reference #: PS-04838	Description: Firing Range / all (point		riteria: .II		
	0 - 0-7 -	,	Label Rule	25	
Label Placemo	ent Rules (see Annex J):	LP-3505, LP-4813, LP-999			
Reference #:	Description:			Criteria:	
PL-04838_1	Firing Range / all (poi	nt)		N/A	
	Label String:	[Name] "Firing range"			

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

⊙ Firing range ⊝ Blackhawk Firing Range

Fish Farm Facility (BH051)

Generalization Rules (see Annex J): GA-9999, GC-9999

Fish Farm Facility / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature. Symbol Type: Simple

Symbol Graphic

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04184 Fish Farm Facility / all (area) All

Label Placement Rules (see Annex J): LP-3506, LP-4813, LP-9950, LP-9999

2 5550, 2 5550, 2 5555

Reference #: Description: Criteria:

PL-04184_1 Fish Farm Facility / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Name] "Fish farm"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04184_2 Fish Farm Facility / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: [Name] "Fish farm" "("[Condition of Facility]")"

Characteristics: 1, 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

-----Fish farm ----Fish farm (construction)

Fish Farm Facility / intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00006 Component Type: Point - Simple Color Token: Black

Description: Black filled square with all sides 0.8mm

Parameters:

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

Reference #: Description: Criteria:

PS-04530 Fish Farm Facility / intact (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:
PL-04530_1 Fish Farm Facility / intact (point) N/A

Label String: [Name] "Fish farm"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Fish farm Coolwater Fish Farm

Fish Farm Facility / not intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00173 Component Type: Point - Shape Color Token: Black/Black-12

Description: Not intact square 0.8mm

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04673 Fish Farm Facility / not intact (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04673_1 Fish Farm Facility / not intact (point) N/A

Label String: "Fish farm"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Fish farm

Flare Pipe (AF070)

Flare Pipe / non-obstruction (point)

Symbol Placement Instructions: Origin: Center of open circle

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00145 Component Type: Point - Shape Color Token: Black

Description: Flare pipe

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04041 Flare Pipe / non-obstruction (point) Height Above Surface Level [HGT] < 46

Symbol Samples

ĺ

Flume (BH060)

Generalization Rules (see Annex J): GA-9999

Flume / on surface (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #: L00016
Description: Cyan 0.3mm Solid Line

Component Type:

Line - Simple

Color Token:

Cyan

Parameters:

Reference #:

Line Weight: 0.3mm

Symbol Rules

Description: Criteria:

PS-04773 Flume / on surface (line) Vertical Relative Location [LOC] = (On Surface [44], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630

Reference #: Description: Criteria:
PL-04773_1 Flume / on surface (line) N/A

Label String: "Flume"
Characteristics: 16

16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

Flume

Flume / below surface (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00235 Component Type: Line - Styled Color Token: Cyan

Description: Cyan 0.3mm Dashed Line (0.3mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.3mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04774 Flume / below surface (line) Vertical Relative Location [LOC] = Below Ground Surface [40]

Label Rules

Label Placement Rules (see Annex J): LP-3630

Reference #: Description: Criteria:

PL-04774_1 Flume / below surface (line) N/A

Label String: "Flume"
Characteristics: 16

16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Flume

Ford (BH070)

Generalization Rules (see Annex J): GA-9999, GC-9986

Ford / all (point)

Symbol Placement Instructions: Text label only. No graphic parameters

Symbol Type: Simple

Ford

Symbol Graphic

Symbol Rules

Reference #: Description: Criteria:
PS-04186 Ford / all (point) All

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04186_1 Ford / all (point) N/A

Label String: "Ford"
Characteristics: 5

5 (Black, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Ford

Shown with road and river:

Forest Clearing (EC060)

Generalization Rules (see Annex J): GA-9999

Forest Clearing / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

{NO SYMBOL}

Symbol Graphic Note: The symbol is a mask of the Thicket (EB020) and Wood (EC030) feature symbols.

Symbol Rules

Reference #: Description: Criter
PS-04852 Forest Clearing / all (area) All

Symbol Samples

{NO SYMBOL}

Shown with Wood:


Fortification (AH050)

Generalization Rules (see Annex J): GA-9999, GC-9982, GC-9983

Fortification / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00009 is applied to the perimeter and Component P00108 is placed in the center.

Component Ref #: L00009 Component Type: Line - Simple Color Token: Black

Description: Black 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Component Ref #: P00108 Component Type: Point - Shape Color Token: Black

Description: Fortified building

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Crite

PS-04046 Fortification / all (area) Height Above Surface Level [HGT] < 46

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04046_1 Fortification / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

> Label String: [Name] Characteristics:

1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04046_2 Fortification / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 1, 22, 22, 22

> 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

> > Symbol Samples

Д

Fort Delaware Д

(abandoned) Д

Fortification / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00108 Point - Shape Color Token: Component Type: Black

Description: Fortified building

Parameters:

See Annex H for detailed drawing instructions. Note:

Symbol Rules

Reference #: Description: Criteria:

PS-04047 Fortification / all (point) Height Above Surface Level [HGT] < 46

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04047_1 Fortification / intact (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

> Label String: [Name]

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

PL-04047_2 Fortification / not intact (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: [Name] "("[Condition of Facility]")"

1, 22, 22, 22 Characteristics:

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

⊭ (destroyed) Д

General Building (AL015)

Generalization Rules (see Annex J): GA-9999, GC-9978, GC-9983, GC-9994

General Building / non-obstruction / intact / generic or important (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: A00006 Description:

Black solid fill

Parameters:

Note:

The surface geometry is filled with the solid color.

Symbol Rules

Area - Fill

Reference #: Description:

PS-04680

General Building / non-obstruction / intact / generic or important (area) Height Above Surface Level [HGT] < 46

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Color Token:

AND

Component Type:

Feature Function [FFN] = (Accommodation [550], Administration [810], Agriculture [2], Aircraft Repair [341], Animal Boarding [919], Auditorium [892], Commerce [440], Community Centre [893], Cooling [355], Defence Activities [835], Firefighting [845], General Repair [330], Government [811], Grain Milling [107], Guard [781], Harbour Control [513], Imprisonment [843], Institution [859], Law Enforcement [841], Library [902], Manufacturing [99], Maritime Pilotage [511], Market [475], Motor Vehicle Manufacture [290], Motor Vehicle Parking [535], Motor Vehicle Repair [343], Museum [905], Observation Station [721], Oil-mill [105], Opera House [894], Other [999], Palace [815], Paper-mill [171], Petroleum Refining [192], Postal Activities [540], Power Generation [351], Print Publishing [582], Pumping [501], Radio Broadcasting [601], Residence [563], Restaurant [572], Retail Banking [643], Satellite Ground Control [626], Sawmilling [161], Scientific Research and Development [720], Signalling [486], Social Work [887], Sports Centre [912], Steel Mill [241], Telecommunications [610], Television Broadcasting [604], Terminal [481], Theatre [891], Transport [480], Unknown [0], Utilities [350], Warehousing and Storage [530], Water Treatment [362], Weather Station [722], Wind Tunnel [730], Yacht-club [955])

Black

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description:

PL-04680 1

General Building / non-obstruction / intact / generic or important / other (area)

Criteria:

Feature Function [FFN] = (Auditorium [892], Firefighting [845], Government [811], Grain Milling [107], Library [902], Motor Vehicle Manufacture [290], Museum [905], Observation Station [721], Oil-mill [105], Opera House [894], Palace [815], Paper-mill [171], Petroleum Refining [192], Sawmilling [161], Sports Centre [912], Steel Mill [241], Terminal [481], Theatre [891], Weather Station

[722], Wind Tunnel [730], Yacht-club [955])

Label String: [Name] [Feature Function]

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

PL-04680 2 General Building / non-obstruction / intact / generic or

important / military (area)

[Name] "Military" Label String:

Characteristics: 1. 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04680 3 General Building / non-obstruction / intact / generic or

important / police (area)

Label String: [Name] "Police"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

PL-04680 4 General Building / non-obstruction / intact / generic or

important / prison (area)

Label String: [Name] "Prison"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Feature Function [FFN] = Defence Activities [835]

Feature Function [FFN] = Law Enforcement [841]

Feature Function [FFN] = Imprisonment [843]

Symbol Samples

Metropolitan Museum of Art

Prison

General Building / non-obstruction / intact / christian (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: The base of Component P00013 is placed perpendicular to and centered along the northernmost edge of Component A00006.

Component Ref #: A00006 Component Type: Area - Fill Color Token: Black

Description: Black solid fill

Parameters:

Note: The surface geometry is filled with the solid color.

Component Ref #: P00013 Component Type: Point - Shape Color Token: Black

Description: Building Christian cross

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04681 General Building / non-obstruction Height Above Surface Level [H

6-04681 General Building / non-obstruction Height Above Surface Level [HGT] < 46 / intact / christian (area)

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Feature Function [FFN] = (Place of Worship [931], Religious Activities [930])

AND House of Worship Type [HWT] = (Cathedral [2], Chapel [3], Church [4], Tabernacle [15])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04681_1 General Building / non-obstruction / intact / christian (area) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples





General Building / non-obstruction / intact / islam (area)

Symbol Type: Complex

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Graphic

Note: The base of Component P00014 is placed perpendicular to and centered along the northernmost edge of Component A00006.

Component Ref #: A00006 Component Type: Area - Fill Color Token: Black

Description: Black solid fill

Parameters:

Note: The surface geometry is filled with the solid color.

Component Ref #: P00014 Component Type: Point - Shape Color Token: Black

Description: Building Islamic crescent

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04682 General Building / non-obstruction Height Above Surface Level [HGT] < 46 / intact / islam (area)

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Feature Function [FFN] = (Place of Worship [931], Religious Activities [930])

AND House of Worship Type [HWT] = (Marabout [5], Minaret [6], Mosque [9])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04682 1 General Building / non-obstruction / intact / islam (area) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

≚ Istiqlal

General Building / non-obstruction / intact / pagoda (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: The base of Component P00019 is placed perpendicular to and centered along the northernmost edge of Component A00006.

Component Ref #: A00006 Component Type: Area - Fill Color Token: Black

Description: Black solid fill

Parameters:

Note: The surface geometry is filled with the solid color.

Component Ref #: P00019 Component Type: Point - Shape Color Token: Black

Description: Building pagoda

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04683 General Building / non-obstruction Height Above Surface Level [HGT] < 46 / intact / pagoda (area)

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Feature Function [FFN] = (Place of Worship [931], Religious Activities [930])

AND House of Worship Type [HWT] = Pagoda [11]

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04683_1 General Building / non-obstruction / intact / pagoda (area) N/A

> Label String: [Name] Characteristics: 1

> > 1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

General Building / non-obstruction / intact / stupa (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: The base of Component P00031 is placed perpendicular to and centered along the northernmost edge of Component A00006.

Component Ref #: A00006 Component Type: Area - Fill Color Token: Black

Black solid fill Description:

Parameters:

The surface geometry is filled with the solid color. Note:

Component Ref #: Point - Shape P00031 Component Type: Color Token: Black

Description: **Building stupa**

Parameters:

PL-04684_1

Note: See Annex H for detailed drawing instructions.

Symbol Rules Reference #: Description: Criteria:

PS-04684 General Building / non-obstruction Height Above Surface Level [HGT] < 46

/ intact / stupa (area) AND

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) Feature Function [FFN] = (Place of Worship [931], Religious Activities [930]) AND

N/A

House of Worship Type [HWT] = Stupa [21] AND

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Criteria: Reference #: Description:

General Building / non-obstruction / intact / stupa (area)

Label String: [Name]

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples



Enlightenment

General Building / non-obstruction / intact / judaism (area)

I

Symbol Graphic

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Note: The base of Component P00017 is placed perpendicular to and centered along the northernmost edge of Component A00006.

Component Ref #: A00006 Component Type: Area - Fill Color Token: Black
Description: Black solid fill

Parameters:

Note: The surface geometry is filled with the solid color.

Component Ref #: P00017 Component Type: Point - Shape Color Token: Black

Description: Building Judaism "T"

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04685 General Building / non-obstruction Height Above Surface Level [HGT] < 46 / intact / judaism (area)

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Feature Function [FFN] = (Place of Worship [931], Religious Activities [930])

AND House of Worship Type [HWT] = Synagogue [20]

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04685_1 General Building / non-obstruction / intact / judaism (area) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

I

I Kittab Attia

General Building / non-obstruction / intact / temple (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: The base of Component P00018 is placed perpendicular to and centered along the northernmost edge of Component A00006.

Component Ref #: A00006 Component Type: Area - Fill Color Token: Black

Description: Black solid fill

Parameters:

Note: The surface geometry is filled with the solid color.

Component Ref #: P00018 Component Type: Point - Shape Color Token: Black

Description: Building temple

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04686 General Building / non-obstruction

/ intact / temple (area)

Height Above Surface Level [HGT] < 46

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Feature Function [FFN] = (Place of Worship [931], Religious Activities [930])

AND House of Worship Type [HWT] = Temple [16]

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04686_1 General Building / non-obstruction / intact / temple (area) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Ħ

→ Dhakeshwari

General Building / non-obstruction / intact / house of worship (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: A00006 Component Type: Area - Fill Color Token: Black

Description: Black solid fill

Parameters:

PL-04687_1

Note: The surface geometry is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04687 General Building / non-obstruction / intact / house of worship (area)

General Building / non-obstruction Height Above Surface Level [HGT] < 46

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Feature Function [FFN] = (Place of Worship [931], Religious Activities [930])

AND House of Worship Type [HWT] = (Not Applicable [998], Other [999], Religious Community [7], Shrine

[14], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:

General Building / non-obstruction / intact / house of worship / known (area)

Label String: [Name] [House of Worship Type]

Characteristics: 1. 1

stics: 1, 1 1 (Black, Condensed, 6 pt, Mixed case)

PL-04687_2 General Building / non-obstruction / intact / house of

worship / other (area)

House of Worship Type [HWT] = (Not Applicable [998], Other [999], Unknown[0])

House of Worship Type [HWT] = (Religious Community [7], Shrine [14])

AND Name [NAM] <> Unknown

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04687_3 General Building / non-obstruction / intact / house of worship / unknown (area)

House of Worship Type [HWT] = (Not Applicable [998], Other [999], Unknown[0])

AND Name [NAM] = Unknown

Label String: "House of worship"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Religious community

House of worship

Shrine

General Building / non-obstruction / intact / school (area)

Symbol Graphic

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Note: The base of Component P00016 is placed perpendicular to and centered along the northernmost edge of Component A00006.

Component Ref #: A00006

Component Type:

Area - Fill

Color Token:

Black

Description: Parameters: Black solid fill

Note:

The surface geometry is filled with the solid color.

Component Ref #: Description:

P00016 **Building school flag** Component Type:

Point - Shape

Color Token:

Black

Parameters:

PS-04688

Note: See Annex H for detailed drawing instructions.

Reference #: Description:

General Building / non-obstruction

/ intact / school (area)

Criteria:

Height Above Surface Level [HGT] < 46

Symbol Rules

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) AND Feature Function [FFN] = (Education [850], Higher Education [855])

Criteria:

N/A

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: PL-04688 1 General Building / non-obstruction / intact / school (area)

Label String: [Name] Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Horizon

General Building / non-obstruction / intact / hospital (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

 \oplus

Symbol Graphic

Note: Component P00012 is placed in the center of Component A00006.

Component Ref #: A00006 Component Type: Area - Fill Color Token: Black

Description: Black solid fill

Parameters:

Note: The surface geometry is filled with the solid color.

Component Ref #: P00296 Component Type: Point - Shape Color Token: Black

Description: Building hospital symbol

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04689 General Building / non-obstruction / intact / hospital (area)

tion Height Above Surface Level [HGT] < 46

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Feature Function [FFN] = (Human Health Activities [860], In-patient Care [861])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04689_1 General Building / non-obstruction / intact / hospital (area) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

 \oplus



①

General Building / non-obstruction / intact / diplomatic (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: The base of Component P00285 is placed perpendicular to and centered along the northernmost edge of Component A00006.

Component Ref #: A00006 Component Type: Area - Fill Color Token: Black

Description: Black solid fill

Parameters:

Note: The surface geometry is filled with the solid color.

Component Ref #: P00285 Component Type: Point - Shape Color Token: Black

Description: Building diplomatic flag

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04691 General Building / non-obstruction Height Above Surface Level [HGT] < 46

/ intact / diplomatic (area)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) AND AND Feature Function [FFN] = (Diplomacy [825], Embassy [827])

N/A

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

General Building / non-obstruction / intact / diplomatic

(area)

PL-04691_1

Label String: [Name] Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

□ U.S. Embassy

General Building / non-obstruction / intact / petrol sale (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: The base of Component P00275 is placed perpendicular to and centered along the northernmost edge of Component A00006.

Component Ref #: Area - Fill Color Token: A00006 Component Type: Black

Description: Black solid fill

Description:

Parameters:

Note: The surface geometry is filled with the solid color.

Point - Shape Component Ref #: P00275 Color Token: Black Component Type:

Criteria:

Description: Motor vehicle station symbol

Parameters:

Reference #:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

PS-04708 General Building / non-obstruction

Height Above Surface Level [HGT] < 46 / intact / petrol sale (area)

> AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Feature Function [FFN] = Petrol Sale [470] AND

Symbol Samples



General Building / non-obstruction / not intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00007 is applied to the perimeter and is filled with Component A00064.

Component Ref #: Description:

A00064 Black-12 area fill Component Type:

Area - Fill

Color Token: Black-12

Parameters:

Screen Angle:

45 degrees

Screen Percent: 12%

Component Ref #:

L00007

Black 0.1mm Solid Line

Component Type: Line - Simple Color Token:

Black

Description:

Parameters:

PS-04692

Line Weight: 0.1mm

Symbol Rules

Reference #: Description:

Criteria: General Building / non-obstruction

/ not intact (area)

Height Above Surface Level [HGT] < 46

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04692_1 General Building / non-obstruction / not intact (area) Feature Function [FFN] = (Auditorium [892], Diplomacy [825], Education [850], Embassy [827], Firefighting [845], Government [811], Grain Milling [107], Higher Education [855], Human Health Activities [860], In-patient Care [861], Library [902], Motor Vehicle Manufacture [290], Museum [905], Observation Station [721], Oil-mill [105], Opera House [894], Palace [815], Paper-mill [171], Petroleum Refining [192], Place of Worship [931], Religious Activities [930], Sawmilling [161], Sports Centre [912], Steel Mill [241], Terminal [481], Theatre [891], Weather Station [722], Wind Tunnel [730], Yacht-club [955])

Label String: [Name] Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

AND

Symbol Samples

St. Thomas Moore Catholic Church

General Building / non-obstruction / intact / generic (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00050 Component Type:

Criteria:

Point - Simple Color Token:

Black

Description:

PS-04693

Black filled square with all sides 0.5mm Parameters:

0.5mm Length:

Note: The component is a square and is filled with the solid color.

Symbol Rules

Reference #: Description:

General Building / non-obstruction

/ intact / generic (point)

Height Above Surface Level [HGT] < 46

AND

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND

Feature Function [FFN] = (Accommodation [550], Administration [810], Agriculture [2], Aircraft Repair [341], Animal Boarding [919], Commerce [440], Community Centre [893], Cooling [355], General Repair [330], Guard [781], Harbour Control [513], Institution [859], Manufacturing [99], Maritime Pilotage [511], Market [475], Motor Vehicle Parking [535], Motor Vehicle Repair [343], Other [999], Postal Activities [540], Power Generation [351], Print Publishing [582], Pumping [501], Radio Broadcasting [601], Residence [563], Restaurant [572], Retail Banking [643], Satellite Ground Control [626], Scientific Research and Development [720], Signalling [486], Social Work [887], Telecommunications [610], Television Broadcasting [604], Transport [480], Unknown [0], Utilities [350], Warehousing and Storage [530], Water Treatment [362])

Symbol Samples

General Building / non-obstruction / intact / important (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Point - Simple Component Ref #: P00006 Component Type: Color Token: Black

Black filled square with all sides 0.8mm Description:

Parameters:

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

General Building / non-obstruction PS-04694 Height Above Surface Level [HGT] < 46

/ intact / important (point)

AND

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

> Feature Function [FFN] = (Auditorium [892], Defence Activities [835], Firefighting [845], Government [811], Grain Milling [107], Imprisonment [843], Law Enforcement [841], Library [902], Motor Vehicle Manufacture [290], Museum [905], Observation Station [721], Oil-mill [105], Opera House [894], Palace [815], Paper-mill [171], Petroleum Refining [192], Sawmilling [161], Sports Centre [912], Steel Mill [241],

Terminal [481], Theatre [891], Weather Station [722], Wind Tunnel [730], Yacht-club [955])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description:

PL-04694_1

General Building / non-obstruction / intact / important /

other (point)

Label String: Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

[Name] [Feature Function]

PL-04694 2 General Building / non-obstruction / intact / important /

military (point)

Label String: [Name] "Military"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Criteria:

Feature Function [FFN] = (Auditorium [892], Firefighting [845], Government [811], Grain Milling [107], Library [902], Motor Vehicle Manufacture [290], Museum [905], Observation Station [721], Oil-mill [105], Opera House [894], Palace [815], Paper-mill [171], Petroleum Refining [192], Sawmilling [161], Sports Centre [912], Steel Mill [241], Terminal [481], Theatre [891], Weather Station [722], Wind Tunnel [730], Yacht-club [955])

Feature Function [FFN] = Defence Activities [835]

PL-04694_3 General Building / non-obstruction / intact / important /

police (point)

Label String: [Name] "Police"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

PL-04694_4 General Building / non-obstruction / intact / important /

prison (point)

Label String: [Name] "Prison"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Police

_ Buckingham Palace

General Building / non-obstruction / intact / christian (point)

Symbol Placement Instructions:

Origin: Center of filled square

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00075 Description:

Building Christian

Component Type:

Point - Shape

Color Token:

Black

Feature Function [FFN] = Law Enforcement [841]

Feature Function [FFN] = Imprisonment [843]

Parameters:

PS-04695

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description:

General Building / non-obstruction

/ intact / christian (point)

Height Above Surface Level [HGT] < 46

AND

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

N/A

AND

Feature Function [FFN] = (Place of Worship [931], Religious Activities [930])

AND

House of Worship Type [HWT] = (Cathedral [2], Chapel [3], Church [4], Tabernacle [15])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

Criteria:

PL-04695_1 General Building / non-obstruction / intact / christian

(point) Label String: [Name]

Characteristics:

İ

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

‡ First Baptist

General Building / non-obstruction / intact / minaret (point)

Symbol Placement Instructions: Origin: Center of dot

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00184 Component Type: Point - Shape Color Token: Black

Description: Building minaret

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04696 General Building / non-obstruction Height Above Surface Level [HGT] < 46 / intact / minaret (point)

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Feature Function [FFN] = (Place of Worship [931], Religious Activities [930])

AND House of Worship Type [HWT] = Minaret [6]

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04696_1 General Building / non-obstruction / intact / minaret (point) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

₹ %White

General Building / non-obstruction / intact / islam (point)

Symbol Placement Instructions: Origin: Center of filled square

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00076 Component Type: Point - Shape Color Token: Black

Description: Building Islamic

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04697 General Building / non-obstruction Height Above Surface Level [HGT] < 46 / intact / islam (point)

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Feature Function [FFN] = (Place of Worship [931], Religious Activities [930])

AND House of Worship Type [HWT] = (Marabout [5], Mosque [9])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04697_1 General Building / non-obstruction / intact / islam (point)

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

N/A

Y Al-Azhar

General Building / non-obstruction / intact / pagoda (point)

Symbol Placement Instructions: Origin: Center of open square

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00019 Component Type: Point - Shape Color Token: Black

Description: Building pagoda

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04698 General Building / non-obstruction

/ intact / pagoda (point)

ion Height Above Surface Level [HGT] < 46

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Feature Function [FFN] = (Place of Worship [931], Religious Activities [930])

AND House of Worship Type [HWT] = Pagoda [11]

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04698_1 General Building / non-obstruction / intact / pagoda (point) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Feiying

General Building / non-obstruction / intact / stupa (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Point - Shape Color Token: Component Ref #: Component Type: Black P00031

Description: **Building stupa**

Parameters:

See Annex H for detailed drawing instructions. Note:

Symbol Rules

Reference #: Description: Criteria:

PS-04699 General Building / non-obstruction / intact / stupa (point)

Height Above Surface Level [HGT] < 46

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Feature Function [FFN] = (Place of Worship [931], Religious Activities [930]) AND

House of Worship Type [HWT] = Stupa [21] AND

Label Rules

LP-3505, LP-9999 Label Placement Rules (see Annex J):

Reference #: Description: Criteria:

PL-04699_1 General Building / non-obstruction / intact / stupa (point) N/A

> [Name] Label String: Characteristics: 1

> > 1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

▲Nirvana ▲

General Building / non-obstruction / intact / judaism (point)

Symbol Placement Instructions: Origin: Center of filled square

Symbol Type: Simple

Symbol Graphic

P00077 Point - Shape Color Token: Black Component Ref #: Component Type:

Criteria:

Description: **Building Judaism**

Description:

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules Reference #:

PS-04700 General Building / non-obstruction

Height Above Surface Level [HGT] < 46 / intact / judaism (point)

> Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) AND

AND Feature Function [FFN] = (Place of Worship [931], Religious Activities [930])

AND House of Worship Type [HWT] = Synagogue [20]

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Criteria: Reference #: Description:

PL-04700 1 General Building / non-obstruction / intact / judaism (point) N/A

> Label String: [Name] Characteristics: 1

> > 1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

I Amuna

General Building / non-obstruction / intact / temple (point)

Symbol Placement Instructions: Origin: Center of open rectangle

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00018 Component Type: Point - Shape Color Token: Black

Description: Building temple

Parameters:

Note: See Annex H for detailed drawing instructions.

Reference #: Description: Criteria:

PS-04701 General Building / non-obstruction Height Above Surface Level [HGT] < 46

/intact / temple (point)

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Feature Function [FFN] = (Place of Worship [931], Religious Activities [930])

AND House of Worship Type [HWT] = Temple [16]

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04701_1 General Building / non-obstruction / intact / temple (point) N/A

Label String: [Name]

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

r Wat Buddha Lela

General Building / non-obstruction / intact / house of worship (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00006 Component Type: Point - Simple Color Token: Black

Description: Black filled square with all sides 0.8mm

Parameters:

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

Symbol Rules

Reference #: Description:

PS-04704 General Building / non-obstruction

/ intact / house of worship (point)

Height Above Surface Level [HGT] < 46

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Feature Function [FFN] = (Place of Worship [931], Religious Activities [930])

House of Worship Type [HWT] = (Not Applicable [998], Other [999], Religious Community [7], Shrine AND

[14], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:

House of Worship Type [HWT] = (Religious Community [7], Shrine [14]) PL-04704 1 General Building / non-obstruction / intact / house of

worship / known(point)

Label String: [Name] [House of Worship Type]

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

PL-04704_2 General Building / non-obstruction / intact / house of House of Worship Type [HWT] = (Not Applicable [998], Other [999], Unknown[0])

worship / other (point)

Name [NAM] <> Unknown AND

Label String: [Name] Characteristics:

> 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04704_3 General Building / non-obstruction / intact / house of House of Worship Type [HWT] = (Not Applicable [998], Other [999], Unknown[0])

worship / unknown (point)

AND Name [NAM] = Unknown

Label String: "House of worship"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

House of worship

Shrine

General Building / non-obstruction / intact / school (point)

Symbol Placement Instructions: Origin: Center of filled square

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00118 Component Type: Point - Shape Color Token: Black

Building school Description:

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04706 General Building / non-obstruction Height Above Surface Level [HGT] < 46

/ intact / school (point)

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) AND Feature Function [FFN] = (Education [850], Higher Education [855]) Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04706_1 General Building / non-obstruction / intact / school (point) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Roosevelt

General Building / non-obstruction / intact / hospital (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00012 Component Type: Point - Shape Color Token: Black

Description: Building hospital

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04707 General Building / non-obstruction Height Above Surface Level [HGT] < 46

/ intact / hospital (point)

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Feature Function [FFN] = (Human Health Activities [860], In-patient Care [861])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04707_1 General Building / non-obstruction / intact / hospital (point) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

• Barnes-Jewish

General Building / non-obstruction / intact / diplomatic (point)

Symbol Placement Instructions: Origin: Center of filled square

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00186 Component Type: Point - Shape Color Token: Black

Description: Building diplomatic

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04476 General Building / non-obstruction Height Above Surface Level [HGT] < 46

/ intact / diplomatic (point)

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Feature Function [FFN] = (Diplomacy [825], Embassy [827])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04476_1 General Building / non-obstruction / intact / diplomatic N/A

(point)

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

P U. S. Embassy

General Building / non-obstruction / intact / petrol sale (point)

Symbol Placement Instructions: Origin: Center of filled square

Symbol Type: Simple

Y

Symbol Graphic

Component Ref #: P00165 Component Type: Point - Shape Color Token: Black

Description: Motor vehicle station

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04709 General Building / non-obstruction Height Above Surface Level [HGT] < 46 / intact / petrol sale (point)

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Feature Function [FFN] = Petrol Sale [470]

Symbol Samples

<u>Y</u>

General Building / non-obstruction / not intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00293 Component Type: Point - Shape Color Token: Black/Black-12

Description: Not intact square 0.6mm

Parameters:

Note: See Annex H for detailed drawing instructions.

Reference #: Description: Criteria:

PS-04714 General Building / non-obstruction

/ not intact (point)

Height Above Surface Level [HGT] < 46

AND Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Symbol Samples

Geologic Fault (DB110)

Generalization Rules (see Annex J): GA-9999

Geologic Fault / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00023 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Symbol Rules

Reference #: Description: Criteria:

PS-04252 Geologic Fault / all (line) All

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-4813, LP-9999

Reference #: Description: Criteria:
PL-04252_1 Geologic Fault / all (line) N/A

Label String: [Name] "Fault"

Characteristics: 5, 5

5 (Black, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Fault

San Andreas Fault

Geophysical Prospecting Grid (FA090)

Generalization Rules (see Annex J): GA-999

Geophysical Prospecting Grid / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00452 Component Type: Line - Styled Color Token: Black-54

Description: Black-54 0.2mm Screened Dashed Line (0.2mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Screen Angle: 45 degrees
Screen Percent: 54%

Symbol Rules

Criteria:

ΑII

Reference #: Description:
PS-04899 Geophysical Prospecting Grid / all

(line)

Symbol Samples


Geopolitical Entity (FA002)

Generalization Rules (see Annex J): GA-9999

Geopolitical Entity / other (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Grapilic

Component Ref #: L00237 Component Type: Line - Styled Color Token:

Description: Black 0.25mm Dashed Line (0.25mm wt, 5.0mm dash, 1.0mm gap)

Parameters:

Line Weight: 0.25mm Dash Length: 5.0mm Dash Spacing: 1.0mm

Symbol Rules

Black

Reference #: Description:

Criteria:

PS-04537 Geopolitical Entity / other (area)

Geopolitical Entity Type [GEC] = (Area of No Sovereignty [5], Demilitarized Zone (DMZ) [7], Dependent Political Entity [11], Economic Region [15], Freely Associated State [12], Independent Political Entity [13], Leased Area [9], Other [999], Political Entity [10], Semi-independent Political Entity [14], Territory [16], Unknown [0], Zone of Occupation [8])

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04537_1 Geopolitical Entity / demilitarized zone (DMZ) (area) Geopolitical Entity Type [GEC] = Demilitarized Zone (DMZ) [7]

Label String: "DEMILITARIZED ZONE"

Characteristics: 48

48 (Black, Condensed, Bold, 10 pt, Upper case)

PL-04537_2 Geopolitical Entity / zone of occupation (area) Geopolitical Entity Type [GEC] = Zone of Occupation [8]

Label String: [Name] "OCCUPIED"

Characteristics: 48, 48

48 (Black, Condensed, Bold, 10 pt, Upper case)

PL-04537_3 Geopolitical Entity / other (area) Geopolitical Entity Type [GEC] = (Area of No Sovereignty [5], Buffer Zone [17],

Dependent Political Entity [11], Economic Region [15], Freely Associated State [12], Independent Political Entity [13], Leased Area [9], Other [999], Political Entity [10], Semi-independent Political Entity [14], Territory [16], Unknown [0])

Label String: [Name]
Characteristics: 48

48 (Black, Condensed, Bold, 10 pt, Upper case)

Symbol Samples

DEMILITARIZED ZONE

SOUTH OSSETIA OCCUPIED

Geopolitical Entity / buffer zone (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00044 is centered on the first dash of Component L00398, then every fourth dash after that.

Symbol Graphic

Note: Component L00398 is applied to the perimeter and Components L00123 and P00044 are placed on the inside of the surface. Component P00044 is attached on the inside of surface and perpendicular to Component L00398.

Component Ref #: L00398 Component Type: Line - Styled Color Token: Black

Description: Black 0.4mm Dashed Line (0.4mm wt, 3.0mm dash, 1.0mm gap)

Parameters:

Line Weight: 0.4mm Dash Length: 3.0mm Dash Spacing: 1.0mm

Component Ref #: L00123 Component Type: Line - Simple Color Token: Dk-Brown1815-54

Description: Dk-Brown1815-54 2.0mm Screened Line

Parameters:

Line Weight: 2.0mm

Screen Angle: 60 degrees

Screen Percent: 54%

Component Ref #: P00044 Component Type: Point - Simple Color Token: Black

Description: Black 1.5mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm
Length: 1.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04876 Geopolitical Entity / buffer zone

(area)

Geopolitical Entity Type [GEC] = Buffer Zone [17]

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04876_1 Geopolitical Entity / buffer zone (area) N/A

Label String: [Name]
Characteristics: 48

48 (Black, Condensed, Bold, 10 pt, Upper case)

Symbol Samples

GIBRALTAR-SPAIN NEUTRAL ZONE

Geothermal Outlet (DB115)

Generalization Rules (see Annex J): GA-9999

Geothermal Outlet / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: L00105 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.3mm Solid Line

Parameters:

Line Weight: 0.3mm

Symbol Rules

Reference #: Description: Criteria:

PS-04253 Geothermal Outlet / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04253_1 Geothermal Outlet / all (area) N/A

Label String: [Name] "Geothermal outlet"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples



Geothermal Outlet / all (point)

Symbol Placement Instructions: Origin: Center of solid circle

Symbol Type: Simple



Symbol Graphic

Note: Tail of symbol is oriented downstream.

Component Ref #: Point - Shape Color Token: P00027 Component Type: Dk-Brown1815

Description: Geothermal outlet

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria: PS-04254

Geothermal Outlet / all (point) Αll

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Criteria: Reference #: Description: PL-04254_1 Geothermal Outlet / all (point) N/A

> Label String: [Name] "Geothermal outlet"

1. 1 Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Geothermal outlet Beehive Geyser

Glacier (BJ030)

Generalization Rules (see Annex J): GA-9999

Glacier / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00041 is applied to the perimeter and is filled with Component A00017.

A00017 Component Type: Area - Pattern Color Token: Component Ref #: Cyan

Description: Cyan Glacier Fill

Parameters:

Area Pattern: AP-104, see Annex I

Component Ref #: Line - Styled Component Type: Color Token: Cyan

Cyan 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap) Description:

Parameters:

Line Weight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria: PS-04228 Glacier / all (area) ΑII

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Criteria: Reference #: Description: PL-04228_1 Glacier / all (area) N/A

Label String: [Name] Characteristics:

38 (Cyan, Condensed, Italic, 6-16 pt, Mixed case)

Symbol Samples





Golf Course (AK100)

Generalization Rules (see Annex J): GA-9999

Golf Course / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00368 is applied to the perimeter and is filled with Component A00101.

Component Ref #: A00101 Component Type: Area - Fill Color Token: Green362-12

Description:

Green362-12 area fill

Parameters:

Screen Angle: 45 degrees Screen Percent: 12%

Component Ref #:

Description:

Component Type: Line - Styled

Color Token:

Green362

Green362 0.15mm Dashed Line (0.15mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.15mm Dash Length: 1.0mm

Dash Spacing:

0.5mm

Symbol Rules

Reference #: Description: Criteria: PS-04058 Golf Course / all (area) ΑII

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-4813, LP-9999

Reference #: Description: Criteria: PL-04058_1 Golf Course / all (area) N/A

> Label String: [Name] "Golf course"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Rancho Park Golf Course

- Golf course

Grain Elevator (AM030)

Generalization Rules (see Annex J): GA-9999, GC-9983, GC-9993, GC-9994

Grain Elevator / non-obstruction / intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: A00006 Component Type: Area - Fill Color Token: Black

Description: Black solid fill

Parameters:

Note: The surface geometry is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04106 Grain Elevator / non-obstruction / Height Above Surface Level [HGT] < 46

intact (area)

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:

PL-04106 1 Grain Elevator / non-obstruction / intact (area) N/A

Label String: "Grain elevator"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Grain elevator

Grain Elevator / non-obstruction / not intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: Component L00007 is applied to the perimeter and is filled with Component A00064.

Component Ref #: A00064 Component Type: Area - Fill Color Token: Black-12

Description: Black-12 area fill

<u>Parameters:</u>

Screen Angle: 45 degrees
Screen Percent: 12%

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black

Description: Black 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

PS-04781 Grain Elevator / non-obstruction / Height Above Surface Level [HGT] < 46

not intact (area)

AND Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:

PL-04781_1 Grain Elevator / non-obstruction / not intact (area)

N/A

Label String: "Grain elevator"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Grain elevator

Grain Elevator / non-obstruction (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00010 Component Type: Point - Shape Color Token: Black

Criteria:

Description: Located object

Description:

Parameters:

Reference #:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

PS-04105 Grain Elevator / non-obstruction Height Above Surface Level [HGT] < 46

(point)

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04105_1 Grain Elevator / non-obstruction (point) N/A

Label String: "Grain elevator"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

 $_{\odot}$ Grain elevator

Grain Storage Structure (AM020)

Generalization Rules (see Annex J): GA-9999, GC-9983, GC-9993, GC-9994

Grain Storage Structure / non-obstruction / intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: A00006 Area - Fill Color Token: Component Type: Black

Description: Black solid fill

Parameters:

The surface geometry is filled with the solid color. Note:

Symbol Rules

Reference #: Description: Criteria:

PS-04101 Grain Storage Structure / non-Height Above Surface Level [HGT] < 46

obstruction / intact (area)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) AND

Label Rules

Label Placement Rules (see Annex J): LP-3505

Criteria: Reference #: Description:

PL-04101_1 Grain Storage Structure / non-obstruction / intact (area) N/A

> Label String: "Silo" Characteristics:

> > 1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Silo

Grain Storage Structure / non-obstruction / not intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic Note: Component L00007 is applied to the perimeter and is filled with Component A00064.

Component Ref #: A00064 Area - Fill Black-12 Component Type: Color Token:

Description: Black-12 area fill

Parameters:

Screen Angle: 45 degrees Screen Percent: 12%

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black

Description: Black 0.1mm Solid Line

Parameters:

Reference #:

Line Weight: 0.1mm

Symbol Rules

Description: Criteria: PS-04784

Grain Storage Structure / non-Height Above Surface Level [HGT] < 46 obstruction / not intact (area)

> Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under AND

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:

PL-04784 1 Grain Storage Structure / non-obstruction / not intact (area) N/A

> Label String: "Silo" Characteristics: 1

> > 1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Silo

Grain Storage Structure / non-obstruction (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00010 Component Type: Point - Shape Color Token: Black

Description: Located object

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04102 Grain Storage Structure / non-Height Above Surface Level [HGT] < 46

obstruction (point)

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:

PL-04102_1 Grain Storage Structure / non-obstruction (point) N/A

Label String: "Silo"
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

⊙ Silo

Grassland (EB010)

Generalization Rules (see Annex J): GA-9999

Grassland / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: A00126 Component Type: Area - Pattern Color Token: Green362

Description: Green362 Grassland Fill

Parameters:

Area Pattern: No existing MIL_STD_2410 area pattern. See Annex I for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:
PS-04030 Grassland / all (area) All

Symbol Samples

Greenhouse (AJ110)

Generalization Rules (see Annex J): GA-9999, GC-9994, GC-9996

Greenhouse / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00007 is applied to the perimeter and is filled with Components A00059 and A00124. Display level from bottom to top: Component A00059; Component A00124.

Area - Fill Component Ref #: A00059 Color Token: Green362-42 Component Type:

Description: Green362-42 area fill

Parameters:

Screen Angle: 45 degrees

Screen Percent: 42%

Area - Pattern A00124 Component Type: Color Token: Green362 Component Ref #:

Description: Green362 Greenhouse Fill

Parameters:

Area Pattern: LP-6, see Annex I

L00007 Line - Simple Component Ref #: Component Type: Color Token: Black Black 0.1mm Solid Line

Description:

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria: PS-04396 Greenhouse / all (area) ΑII

Symbol Samples



Greenhouse / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: Component Type: Point - Shape Color Token: Black/Green362-42

Description: Greenhouse

Parameters:

Note: See Annex H for detailed drawing instructions.

			Symbol Rule	S		
	Description:		Criteria:			
PS-04397	Greenhouse / all (point)	All			
			Symbol Sampl	es		
Groin (BB	8043)					
	Rules (see Annex J)	: GA-9999				
Groin / dry	(area)					
	Sy	ymbol Placement Instructions:	The symbol is applied to the	e geometry of the featu	ire.	
	Sy	ymbol Type: Simple				
Symbol G	Graphic N	ote: This symbol is portrayed in	conjunction with the Tidal \	Vater symbol and shall r	nask out the Tidal Water symbol.	
Componen	t Ref #: L00007	Component Ty	vpe: Line - Simple	Color Token:	Black	
Description	n: Black 0.1n	nm Solid Line	, poi	Color Tokem	5.00.0	
Parameters Line Weigh						
			Symbol Rule			
Reference #:	Description:		Criteria:	3		
PS-04760	Groin / dry (area)		Water Level Effect [WLE] =	Always Dry [2], Floating	[8], Not Applicable [998], Other [999],	Unknown [0])
			Label Rules			
Label Placeme	ent Rules (see Anne	x J): LP-3505				
Reference #: Description:			Cri	teria:		
PL-04760_1 Groin / dry (area)			N/	4		
	Label Str	ing: "Groin"				
	Characteris	tics: 1 1 (Black, Condensed, 6 pt	: Mixed case)			
		1 (Black, Colldelised, 0 p	Symbol Sampl	25		
			Symbol Sampi	25		
		CI	nown with Land Water Boundary	nd Tidal Water		
	Groin	31	Groin	itu Tidai vvater.		
Groin / not	dry (area)					
		ymbol Placement Instructions:	The symbol is applied to the	e geometry of the featu	ire.	
	Sy	mbol Type: Complex				
L — —						
Symbol G	Graphic N	ote: The symbol is shown in con	junction with with Tidal Wa	er symbol and shall not	mask out the Tidal Water symbol.	

Component Ref #: A00048 Component Type: Area - Fill

Description: Black-12 area fill

Parameters:

Screen Angle: 15 degrees
Screen Percent: 12%

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Color Token:

Black-12

Reference #: Description: Criteria:

PS-04761 Groin / not dry (area) Water Level Effect [WLE] = (Always Submerged [3], Covers and Uncovers [4], Partly Submerged [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04761_1 Groin / not dry (area) N/A

Label String: "Groin"
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Groin



Groin / dry (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.



Symbol Graphic

Component Ref #: L00009 Component Type: Line - Simple Color Token: Black

Description: Black 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Symbol Rules

Reference #: Description: Criteria:

PS-04762 Groin / dry (line) Water Level Effect [WLE] = (Always Dry [2], Floating [8], Not Applicable [998], Other [999], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04762_1 Groin / dry (line) N/A

Label String: "Groin"
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Groin

Shown with Land Water Boundary and Tidal Water:

Groin

Groin / not dry (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00031 Component Type: Line - Styled Color Token: Black

Description: Black 0.2mm Dashed Line (0.2mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04763 Groin / not dry (line) Water Level Effect [WLE] = (Always Submerged [3], Covers and Uncovers [4], Partly Submerged [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04763_1 Groin / not dry (line) N/A

Label String: "Groin"
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Groin

Gully (DB200)

Generalization Rules (see Annex J): GA-9999

Gully / all (area)

Symbol Placement Instructions: Text label only. No graphic parameters

Symbol Type: Simple

[NAM]

Symbol Graphic

Symbol Rules

Reference #: Description: Criteria:
PS-04566 Gully / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04566_1 Gully / all (area) N/A

Label String: [Name]
Characteristics: 5

5 (Black, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Coley Gully

Gully / all (line)

Symbol Placement Instructions: Text label only. No graphic parameters

Symbol Type: Simple

[NAM]

Symbol Graphic

Symbol Rules

Reference #: Description: Criteria:

PS-04567 Gully / all (line) All

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:
PL-04567_1 Gully / all (line) N/A

Label String: [Name]
Characteristics: 5

5 (Black, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Water Mill Gully

Harbour (BB005)

Generalization Rules (see Annex J): GA-9999

Harbour / all (area)

Symbol Placement Instructions: Text label only. No graphic parameters

Symbol Type: Simple

[NAM]

Symbol Graphic

Symbol Rules

Reference #: Description: Criteria:
PS-04602 Harbour / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:

PL-04602_1 Harbour / all (area) N/A

Label String: [Name]
Characteristics: 8

8 (Black, Condensed, Italic, 6-16 pt, Mixed case)

Symbol Samples

Pearl Harbor

Hazardous Rock (BD130)

Hazardous Rock / exposed (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

 \times

Symbol Graphic

Note: No symbol is portrayed if the Water Level Effect (WLE) = Always Submerged [3].

Component Ref #: P00095 Component Type: Point - Shape Color Token: Black

Description: Hazardous rock/reef

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04658 Hazardous Rock / exposed (point) Water Level Effect [WLE] = (Always Dry [2], Covers and Uncovers [4], Floating [8], Not Applicable [998],

Other [999], Partly Submerged [1], Unknown [0]

Symbol Samples

*

Heating Facility (AD050)

Generalization Rules (see Annex J): GA-9999

Heating Facility / all (area)

Symbol Placement Instructions:

The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:
PS-04299 Heating Facility / all (area) All

Label Rules

): LP-3506, LP-4813, LP-9950, LP-9999

Reference #: Description: Criteria: PL-04299_1 Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) Heating Facility / intact (area) Label String: [Name] "Heating facility" Characteristics: 1, 1 1 (Black, Condensed, 6 pt, Mixed case) PL-04299_2 Heating Facility / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under Construction [1]) [Name] "Heating facility" "("[Condition of Facility]")" Label String: Characteristics: 1, 1, 22, 22, 22 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case) Symbol Samples Walnut Street Heating Plant ? Heating facility Heating Facility / intact (point) Symbol Placement Instructions: Origin: Center of symbol Symbol Type: Simple **Symbol Graphic** P00006 Component Ref #: Component Type: Point - Simple Color Token: Black Description: Black filled square with all sides 0.8mm Parameters: Length: 0.8mm The component is a square and is filled with the solid color. Note: Symbol Rules Reference #: Description: Criteria: Heating Facility / intact (point) PS-04300 Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) Label Rules LP-3505, LP-4813, LP-9999 Label Placement Rules (see Annex J): Reference #: Description: Criteria: PL-04300_1 Heating Facility / intact (point) N/A Label String: [Name] "Heating facility" Characteristics: 1. 1 1 (Black, Condensed, 6 pt, Mixed case) Symbol Samples

■ Charter Street Heating Plant

Heating Facility / not intact (point)

■ Heating facility

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00173 Component Type: Point - Shape Color Token: Black/Black-12

Description: Not intact square 0.8mm

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04907 Heating Facility / not intact (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04907_1 Heating Facility / not intact (point) N/A

Label String: "Heating facility"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

☐ Heating facility

Hedgerow (EA020)

Generalization Rules (see Annex J): GA-9999

Hedgerow / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00235 has an initial offset of 1.0mm; after that 2.0mm.

Symbol Graphic

Note: Component P00235 is centered perpendicular to Component L00361.

Component Ref #: L00361 Component Type: Line - Simple Color Token: Green362

Description: Green362 0.15mm Solid Line

Parameters:

Line Weight: 0.15mm

Component Ref #: P00235 Component Type: Point - Simple Color Token: Green362

Description: Green362 0.35mm length line with a 0.45mm lineweight

Parameters:

Line Weight: 0.45mm
Length: 0.35mm

Symbol Rules |

Reference #: Description: Criteria:
PS-04307 Hedgerow / all (line) All

Symbol Samples

Helipad (GB030)

Helipad / non-hospital (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Point - Shape Blue072 Component Ref #: P00090 Color Token: Component Type:

Description: Helipad

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules |

Description: Reference #: Criteria:

PS-04326 Helipad / non-hospital (point) Helipad Associated Facility [HAF] = (Heliport [1], Land Aerodrome [2], Non-hospital Building [4], Offshore

Construction [9], Other [999], Rig [6], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9998, LP-9999

Reference #: Description: Criteria:

PL-04326_1 Helipad / non-hospital (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: "("[Condition of Facility]")"

Characteristics: 26, 26, 26

26 (Blue072, Condensed, 7 pt, Lower case)

Symbol Samples





Helipad / hospital (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00089 Component Type: Point - Shape Color Token: Blue072

Description: Helipad at hospital

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: PS-04327

Helipad / hospital (point) Helipad Associated Facility [HAF] = Hospital [3]

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9998, LP-9999 Reference #: Description: Criteria:

PL-04327_1 Helipad / hospital (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: "("[Condition of Facility]")"

Characteristics: 26, 26, 26

26 (Blue072, Condensed, 7 pt, Lower case)

Symbol Samples

Н

H (construction)

Heliport (GB035)

Generalization Rules (see Annex J): GA-9999

Heliport / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap) Description:

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria: PS-04328 Heliport / all (area)

ΑII

Label Rules LP-3506, LP-9950, LP-9999 Label Placement Rules (see Annex J):

Reference #: Description: Criteria:

PL-04328_1 Heliport / intact (area)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Name] [ICAO Location Indicator]

[Aerodrome Elevation]

Characteristics: 24, 29

24 (Blue072, Condensed, 7 pt, Mixed case) 26 (Blue072, Condensed, 7 pt, Lower case) 29 (Blue072, Condensed, 7 pt, Upper case)

PL-04328_2 Heliport / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

[Name] [ICAO Location Indicator] Label String:

"("[Condition of Facility]")" [Aerodrome Elevation]

Characteristics: 24, 29

26, 26, 26

24 (Blue072, Condensed, 7 pt, Mixed case) 26 (Blue072, Condensed, 7 pt, Lower case)

29 (Blue072, Condensed, 7 pt, Upper case)

Symbol Samples

Palmetto Heliport 290

Shown with Helipad:
Hanchey Army Heliport KHEY
97

Hill Airforce Heliport KHIF (construction)
1460

Holding Pen (AJ030) Generalization Rules (see Annex J): GA-9999 Holding Pen / all (area) **Symbol Placement Instructions:** The symbol is applied to the geometry of the feature. Symbol Type: Simple **Symbol Graphic** Line - Simple Component Ref #: L00240 Component Type: Color Token: Dk-Brown1815 Dk-Brown1815 0.15mm Solid Line Description: Parameters: Line Weight: 0.15mm Symbol Rules Reference #: Description: Criteria: PS-04048 Holding Pen / all (area) ΑII Label Rules Label Placement Rules (see Annex J): LP-3505 Reference #: Criteria: Description: PL-04048_1 Holding Pen / all (area) N/A Label String: "Holding Pen" Characteristics: 1 (Black, Condensed, 6 pt, Mixed case) Symbol Samples Holding pen Holding Pen / all (point) **Symbol Placement Instructions:** Origin: Center of symbol Symbol Type: Simple **Symbol Graphic** Component Ref #: P00168 Component Type: Point - Simple Color Token: Dk-Brown1815 Description: Holding pen Parameters: Line Weight: 0.15mm Length: 0.8mm Note: The component is an open square.

Symbol Rules

Criteria:

Reference #: Description:

Symbol Samples

Hop Field (EA055)

Generalization Rules (see Annex J): GA-9999

Hop Field / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: A00029 Component Type: Area - Pattern Color Token: Green362

Description: Green362 Vineyard / Hops Fill

Parameters:

Area Pattern: AP-77, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04316 Hop Field / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-3506

Reference #: Description: Criteria:

PL-04316_1 Hop Field / all (area) N/A

Label String: "Hops"
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Hops.

Hut (AL099)

Hut / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00284 Component Type: Point - Simple Color Token: Black

Description: Hut

Parameters:

Line Weight:	0.1mm					29 May 2015
Length:	0.6mm					
Note:	The component is an open s	nuare				
Trotte:	The component is an open s	quai c.				
Reference #: D	escription:	Crite	Symbol Ru	es ————————————————————————————————————		
	ut / all (point)	All				
			Symbol Samp	les		
			,			
Hydrocarb	ons Field (AA052)					
Generalization Rul	les (see Annex J): GA-9999					
Hydrocarbons	s Field / all (area)					
	Symbol Placement In	structions: The	symbol is applied to	the geometry of the feat	ure.	
	Symbol Type: Simple	9				
1	l					
'						
Symbol Gra	phic					
Component R Description: Parameters:	Ref #: L00210 C Black 0.1mm Dashed line (0.1	omponent Type: Imm wt, 1.0mm d	Line - Styled ash, 0.5mm gap)	Color Token:	Black	
Line Weight:	0.1mm D	ash Length:	1.0mm	Dash Spacing:	0.5mm	
			Symbol Ru	es		
	escription:	Crite	ria:			
PS-04548 Hy	ydrocarbons Field / all (area)	All				
Label Placement	Rules (see Annex J): LP-3506, LI	P-4813, LP-9999	Label Rules			
	Description:	·	C	riteria:		
	Hydrocarbons Field / all (area)			/A		
		drocarbons field"				
	Characteristics: 1, 1 1 (Black, Co	ndensed, 6 pt, Mix	red case)			
			Symbol Samp	les		
	Hydrocarbons field		Highlander Hydrocar	oons Field		
ce Cliff (B)	1040)					

ice citti (bjo40)

Generalization Rules (see Annex J): GA-9999

Ice Cliff / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00055 has an initial offset of 0.0mm; after that 0.5mm.

minimi

Symbol Graphic

Note: Component P00055 is perpendicular to and on the downhill side of Component L00015.

Component Ref #: L00015 Component Type: Line - Simple Color Token: Cyan
Description: Cyan 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Component Ref #: P00055 Component Type: Point - Simple Color Token: Cyan

Description: Cyan 0.5mm length line with a 0.1mm lineweight

Parameters:

Line Weight: 0.1mm
Length: 0.5mm

Symbol Rules

Reference #: Description: Criteria:
PS-04229 | Ice Cliff / all (line) | All

Symbol Samples

Shown with Tidal Water and Ice Shelf:

Ice Peak (BJ060)

Ice Peak / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00066 Component Type: Point - Shape Color Token: Dk-Brown1815

Description: Ice peak not frozen water

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:
PS-04230 | Ice Peak / all (point) | All

Symbol Samples

Shown with spot elevation:

Ice Route (AQ075)

Generalization Rules (see Annex J): GA-9999

Ice Route / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00032 Component Type: Line - Styled Color Token: Black

Description: Black 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04138 | Ice Route / all (line) | All

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-4813, LP-9999

Label String: [Name] "ICE ROUTE"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

ICE ROUTE MADELINE ISLAND ICE ROUTE

Island (BA030)

Generalization Rules (see Annex J): GA-9999

Island / all (area)

Symbol Placement Instructions: Text label only. No graphic parameters

Symbol Type: Simple

[NAM]

Symbol Graphic

Symbol Rules

Reference #: Description: Criteria:

PS-04164 Island / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04164_1 Island / all (area) N/A

Label String: [Name]
Characteristics: 12

12 (Black, Condensed, Italic, 6-16 pt, Upper case)

Symbol Samples

KODIAK ISLAND



Lake (BH080)

Generalization Rules (see Annex J): GA-9999

MAUI

Lake / perennial (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00015 is applied to the perimeter and is filled with Component A00007.

Component Ref #: A00007 Component Type: Area - Fill Color Token: Cyan-31

Description: Cyan-31 area fill

Parameters:

Screen Angle: 45 degrees

Screen Percent: 31%

Component Ref #: L00015 Component Type: Line - Simple Color Token: Cyan

Description: Cyan 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Symbol Rules

Reference #: Description: Criteria:

PS-04764 Lake / perennial (area) Hydrologic Persistence [HYP] = (Perennial [1], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria

PL-04764_1 Lake / perennial / fresh (area) Water Type [SCC] = (Fresh [11], Unknown [0])

Label String: [Name]
Characteristics: 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

PL-04764_2 Lake / perennial / salt (area) Water Type [SCC] = (Brackish [12], Salty [10])

Label String: [Name] "(salt)"

Characteristics: 37, 33

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case) 33 (Cyan, Condensed, Italic, 7-16 pt, Lower case)

Symbol Samples







Lake / intermittent, dry (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00041 is applied to the perimeter and is filled with Component A00020.

Area - Pattern Component Ref #: A00020 Component Type: Color Token: Cyan Description: Cyan Dry Drainage Fill Parameters:

Area Pattern: AP-95, see Annex I

L00041 Component Ref #: Component Type: Line - Styled Color Token: Cyan

Description: Cyan 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Dash Length: Line Weight: 0.2mm 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04765 Lake / intermittent, dry (area) Hydrologic Persistence [HYP] = (Dry [4], Intermittent [2])

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:

PL-04765_1 Lake / intermittent, dry / fresh (area) Water Type [SCC] = (Fresh [11], Unknown [0])

> Label String: [Name] Characteristics:

> > 37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

PL-04765_2 Lake / intermittent, dry / salt (area) Water Type [SCC] = (Brackish [12], Salty [10])

> Label String: [Name] "(salt)" Characteristics: 37.33

> > 37 (Cyan, Condensed, Italic, 7-16 pt, Upper case) 33 (Cyan, Condensed, Italic, 7-16 pt, Lower case)

> > > Symbol Samples








Land Aerodrome (GB005)

Generalization Rules (see Annex J): GA-9999

Land Aerodrome / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Note: The label string for the associated Runway is included as part of the label string for Land Aerodrome.

Component Ref #: Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

1.0mm Line Weight: Dash Length: Dash Spacing: 0.5mm 0.1mm

Symbol Rules

Reference #: Description: Criteria: ΑII

Label Rules

Label Placement Rules (see Annex J): LP-9950, LP-9990, LP-9999

Reference #: Description:

Land Aerodrome / intact (area) PL-04317_1

Criteria:

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String:

[Name] [ICAO Location Indicator] {label string of associated Runway} [Aerodrome Elevation]

Characteristics: 24, 29

24 26

> 24 (Blue072, Condensed, 7 pt, Mixed case) 26 (Blue072, Condensed, 7 pt, Lower case) 29 (Blue072, Condensed, 7 pt, Upper case)

PL-04317_2 Land Aerodrome / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under Construction [1])

Label String: [Name] [ICAO Location Indicator]

{label string of associated Runway} "("[Condition of Facility]")" [Aerodrome Elevation]

Characteristics: 24, 29

> 24 26

24 (Blue072, Condensed, 7 pt, Mixed case) 26 (Blue072, Condensed, 7 pt, Lower case) 29 (Blue072, Condensed, 7 pt, Upper case)

Symbol Samples

Washington Dulles Intl KIAD Hard surface

San Diego Intl KSAN Hard surface (construction)



Land Subject To Inundation (BH090)

Generalization Rules (see Annex J): GA-9999

Land Subject To Inundation / not controlled (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Area - Pattern Component Ref #: A00015 Component Type:

Description: Cyan Land Subject to Inundation Fill

Parameters:

Area Pattern: AP-10, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04192 Land Subject To Inundation / not

controlled (area)

Controlled [CNS] = (Uncontrolled [1000], Unknown [0])

Color Token:

Cyan

Symbol Samples

Land Subject To Inundation / controlled (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: Component L00041 is applied to the perimeter and is filled with Component A00015.

Component Ref #: Component Type: Area - Pattern Color Token: Cyan

Cyan Land Subject to Inundation Fill Description:

Parameters:

Area Pattern: AP-10, see Annex I

Component Ref #: L00041 Component Type: Line - Styled Color Token: Cyan

Cyan 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap) Description:

Parameters:

Line Weight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Criteria:

Symbol Rules

Reference #: Description: PS-04193

Land Subject To Inundation /

controlled (area)

Controlled [CNS] = Controlled [1001]

Symbol Samples

Land Water Boundary (BA010)

Generalization Rules (see Annex J):

Land Water Boundary / other (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #:

L00015

Component Type:

Line - Simple

Color Token:

Cyan

Description:

Cyan 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Symbol Rules

Reference #: Description: Criteria:

PS-04162 Land Water Boundary / other (line) Shoreline Type [SLT] = (Building Rubble [11], Other [999], Sandy [13], Shingly [14], Stony [10], Unknown

Symbol Samples

Shown with Tidal Water:

Land Water Boundary / mangrove, marsh (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #: L00041 Component Type: Line - Styled Color Token: Cyan

Description: Cyan 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04163 Land Water Boundary / mangrove, Shoreline Type [SLT] = (Mangrove [6], Marshy [8])

marsh (line)

Symbol Samples

Shown with Marsh and Tidal Water:



Launch Pad (GB040)

Launch Pad / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00010 Component Type: Point - Shape Color Token: Black

Description: Located object

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:
PS-04315 Launch Pad / all (point) All

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9950

Reference #: Description: Criter

PL-04315_1 Launch Pad / intact (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: "Launch pad"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04315_2 Launch Pad / not intact (point)

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under Construction [1])

Label String: "Launch pad" "("[Condition of Facility]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

 $_{\odot}$ Launch pad

Leader Line (No Code)

Leader Line / black (curve)

Symbol Placement Instructions: The symbol is manually positioned to point from a label to a feature symbol.

Symbol Type: Simple

Symbol Graphic

Note: The color of the leader matches the color of the feature symbol it is pointing to.

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black

Description:

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

Black 0.1mm Solid Line

PS-04948 Leader Line / black (curve) Portray as needed

Symbol Samples

Shown with Launch pad: Launch pad

Leader Line / cyan (curve)

Symbol Placement Instructions: The symbol is manually positioned to point from a label to a feature symbol.

Symbol Type: Simple

Symbol Graphic

Note: The color of the leader matches the color of the feature symbol it is pointing to.

Component Ref #: L00108 Component Type: Line - Simple Color Token: Cyan

Description: Cyan 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

PS-04949 Leader Line / cyan (curve) Portray as needed

Symbol Samples

Shown with Rapids:

Snake Rapids

Leader Line / aero blue (curve)

Symbol Placement Instructions: The symbol is manually positioned to point from a label to a feature symbol.

Symbol Type: Simple

Symbol Graphic

Note: The color of the leader matches the color of the feature symbol it is pointing to.

Component Ref #: L00217 Component Type: Line - Simple Color Token: Blue072

Description: Blue072 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

PS-04950 Leader Line / aero blue (curve) Portray as needed

Symbol Samples



Lock (BI030)

Generalization Rules (see Annex J): GA-9999, GC-9990, GC-9991

Lock / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound



Symbol Graphic

Note: Component L00010 is applied to the longest edges of the surface geometry. Component L00451 is connected at each end of component L00010 with apex of each "V" pointing upstream.

Component Ref #: L00451 Component Type: Line - Simple Color Token: Black

Description: Black surface lock "V" (0.15mm wt)

Parameters:

Line Weight: 0.15mm

Note: Each leg is equal and based on width of the surface geometry, and is connected to form a "V" at a 90 degree angle.

Component Ref #: L00010 Component Type: Line - Simple Color Token: Black

Description: Black 0.25mm Solid Line

Parameters:

Line Weight: 0.25mm

Symbol Rules

Reference #: Description: Criteria:
PS-04221 Lock / all (area) All

Label Rules

0050 ID-0000

Reference #: Description: Criteria:

PL-04221_1 Lock / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Name] "Lock"

Characteristics: 1, 1

Lock / not intact (area)

1 (Black, Condensed, 6 pt, Mixed case)


Label String: [Name] "Lock" "("[Condition of Facility]")"

Characteristics: 1, 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

Lock Gatum Locks



Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Lock / all (line)

PL-04221_2

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex





Symbol Graphic

Note: Apex of Component P00105 is fixed at the start and end of Component L00145 and each "V" points upstream. The 90 degree angle of the "V" is bisected equally by the line component.

Component Ref #: L00145 Component Type: Line - Simple Color Token: N/.

Description: 0mm Line weight line. This is a place holder for lines that do not have any line component only a point element at each end of the line.

Parameters:

Line Weight: 0.0mm

Component Ref #: P00105 Component Type: Point - Shape Color Token: Black

Description: Lock/pedestrian bridge/sluice gate "V"

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04222 Lock / all (line) All



Shown with Canal:

Lock / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Note: Component P00035 is centered on the associated drainage symbol with apex pointing upstream.

Component Ref #: P00035 Component Type: Point - Shape Color Token: Black

Description: Basin gate/lock

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04223 Lock / all (point) All

Symbol Samples

Shown with Canal:

Mangrove Swamp (ED030)

<<

Generalization Rules (see Annex J): GA-9999

Mangrove Swamp (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Area - Fill

Symbol Type: Complex



Symbol Graphic

Note: Component L00041 is applied to the perimeter and is filled with Components A00007 and A00025. Display level from bottom to top:

Color Token:

Cyan-31

Component A00007; Component A00025.

Component Type:

Component Ref #: A00007
Description: Cyan-31 area fill

Parameters:

Screen Angle: 45 degrees

Screen Percent: 31%

Component Ref #: A00025 Component Type: Area - Pattern Color Token: Green362

Description: Green362 Mangrove Fill

Parameters:

Area Pattern: AP-8, see Annex I

Label Placement Rules (see Annex J):

Component Ref #: L00041 Component Type: Line - Styled Color Token: Cyan

Description: Cyan 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04302 Mangrove Swamp (area) All

Label Rules

LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:

PL-04302_1 Mangrove Swamp (area) N/A

Label String: [Name]
Characteristics: 39

39 (Black, Condensed, Italic, 7-16 pt, Upper case)

Symbol Samples





Mariculture Site (BH050)

Generalization	Rules (see Annex J):	GA-9999, GC-9999							
Mariculture Site / all (area)									
Symbol	Syml	The symbol is applied to the geometry of the feature. Sol Type: Simple							
Compone Descriptio Paramete	on: Black 0.1mm	Component Type: Line - Styled Color Token: Black Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)							
Line Weig		Dash Length: 1.0mm Dash Spacing: 0.5mm							
	Symbol Rules								
Reference #: PS-04767	Description: Mariculture Site / all	Criteria: (area) All							
		Label Rules							
Label Placem	ent Rules (see Annex J)	: LP-3506, LP-4813, LP-9950, LP-9999							
Reference #: Description: Criteria:									
PL-04767_1 Mariculture Site / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown									
	Label String	: [Name] "Mariculture site"							
	Characteristics	1, 1 1 (Black, Condensed, 6 pt, Mixed case)							
PL-04767_2	Mariculture Site / ı	condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under Construction [1])							
	Label String	[Name] "Mariculture site" "("[Condition of Facility]")"] "Mariculture site" "("[Condition of Facility]")"						
	Characteristics: 1, 1, 22, 22, 22 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)								
		Symbol Samples							
	Mariculture site	Crescent Mariculture Site (destroyed)							

Mariculture Site / intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00006 Component Type: Point - Simple Color Token: Black

Description: Black filled square with all sides 0.8mm

Parameters:

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04779 Mariculture Site / intact (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:
PL-04779_1 Mariculture Site / intact (point) N/A

Label String: [Name] "Mariculture site"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Mariculture site Wadell Mariculture Center

Mariculture Site / not intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00173 Component Type: Point - Shape Color Token: Black/Black-12

Description: Not intact square 0.8mm

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04780 Mariculture Site / not intact (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04780_1 Mariculture Site / not intact (point) N/A

Label String: "Mariculture site"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

_Mariculture site

Maritime Signal Station (BB155)

Maritime Signal Station / intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00006 Component Type: Point - Simple Color Token: Black

Description: Black filled square with all sides 0.8mm

Parameters:

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04599 Maritime Signal Station / intact

(point)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04599_1 Maritime Signal Station / intact / known (point) Maritime Station Type [STA] = (Bridge Signal Station [29], Coast Guard Station

Label Rules

[1], Fireboat Station [2], Ice Signal Station [4], International Port Signals Station [32], Lock Signal Station [30], Military Practice Signal Station [33], Pilot Lookout Station [37], Pilot Station [11], Port Control Station [6], Radar Surveillance Station [36], Rescue Station [5], Signal Station [13], Storm Signal Station [15], Tidal Stream Station [27], Tide Station [17], Time Signal Station [19], Traffic Signal Station [28], Warning Signal Station [35], Water-police Station [3], Weather

Signal Station [21])

Label String: [Name] [Maritime Station Type]

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04599_2 Maritime Signal Station / intact / unknown (point) Maritime Station Type [STA] = (Other [999], Unknown [0])

Label String: [Name] "Signal station"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Signal station

Fairfax Rescue Station

Maritime Signal Station / not intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00293 Component Type: Point - Shape Color Token: Black/Black-12

Description: Not intact square 0.6mm

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04103 Maritime Signal Station / not intact (point)

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description:

PL-04103_1 Maritime Signal Station / not intact / known (point)

Criteria:

Maritime Station Type [STA] = (Bridge Signal Station [29], Coast Guard Station [1], Fireboat Station [2], Ice Signal Station [4], International Port Signals Station [32], Lock Signal Station [30], Military Practice Signal Station [33], Pilot Lookout Station [37], Pilot Station [11], Port Control Station [6], Radar Surveillance Station [36], Rescue Station [5], Signal Station [13], Storm Signal Station [15], Tidal Stream Station [27], Tide Station [17], Time Signal Station [19], Traffic Signal Station [28], Warning Signal Station [35], Water-police Station [3], Weather Signal Station [21])

Label String: [Name] [Maritime Station Type]

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04103_2 Maritime Signal Station / not intact / unknown (point)

Maritime Station Type [STA] = (Other [999], Unknown [0])

Label String: [Name] "Signal station"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Signal station Kitty Hawk Coast Guard Station

Marsh (ED010)

Generalization Rules (see Annex J): GA-9999

Marsh / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component P00167 is applied to the perimeter with a spacing of 0.8mm, center to center, and is filled with Component A00018.

Component Ref #: A00018 Component Type: Area - Pattern Color Token: Cyan

Description:

Cyan Bog, Marsh Fill

Parameters:

Area Pattern: AP-12, see Annex I

Component Ref #: P00167 Component Type: Point - Simple Color Token: Cyan

Description: Cyan 0.25mm diameter filled circle

Parameters:

Diameter: 0.25mm

Note: The component is a circle and is filled with the solid color.

Symbol Rules

Reference #: Description:
PS-04312 Marsh / all (area)

All

Criteria:

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04312_1 Marsh / all (area) N/A

Label String: [Name]

Characteristics: 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

Symbol Samples





Memorial Monument (AL130)

Memorial Monument / non-obstruction (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00136 Component Type: Point - Shape Color Token: Black

Description: Memorial monument

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria

PS-04087 Memorial Monument / non- Height Above Surface Level [HGT] < 46

obstruction (point)

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04087_1 Memorial Monument / non-obstruction (point) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

District of Columbia War Memorial

Military Installation (SU001)

Generalization Rules (see Annex J): GA-9999

Military Installation / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic Note: Repeating pattern is Component L00450 followed by Component P00047 centered within each gap. Component L00455 is centered on Component L00450.

Component Ref #: L00450 Component Type: Line - Styled Color Token: Black

Description: Black 0.15mm Dashed line (0.15mm wt, 3.0mm dash, 2.0mm gap)

Parameters:

Line Weight: 0.15mm Dash Length: 3.0mm Dash Spacing: 2.0mm Component Ref #: Component Type: Line - Simple Color Token: Black-42 L00455 Description: Black-42 1.0mm Screened Line Parameters: Line Weight: 1.0mm Screen Angle: 60 degrees Screen Percent: 42% Component Ref #: P00047 Component Type: Point - Simple Color Token: Black Description: Black 0.25mm diameter filled circle Parameters: Diameter: 0.25mm Note: The component is a circle and is filled with the solid color. Symbol Rules Reference #: Description: Criteria: PS-04324 Military Installation / all (area) ΑII Label Rules LP-0050, LP-3506, LP-4813, LP-9950, LP-9999 Label Placement Rules (see Annex J): Reference #: Description: PL-04324 1 Military Installation / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) [Name] "Military Installation" Label String: Characteristics: 1 (Black, Condensed, 6 pt, Mixed case) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], PL-04324_2 Military Installation / not intact (area) Dismantled [4], Under Construction [1]) [Name] "Military Installation" "("[Condition of Facility]")" Label String: Characteristics: 1, 1, 22, 22, 22 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case) Symbol Samples MILITARY INSTALLATION MILITARY INSTALLATION (destroyed) FORT BRAGG Military Installation / intact (point) Symbol Placement Instructions: Origin: Center of symbol Symbol Type: Simple **Symbol Graphic** Component Ref #: P00006 Component Type: Point - Simple Color Token: Black Black filled square with all sides 0.8mm Description: Parameters: Length: 0.8mm Note: The component is a square and is filled with the solid color. Symbol Rules Reference #: Description: Criteria: PS-04325 Military Installation / intact (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) Label Rules Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999 Reference #: Description: Criteria:

PL-04325_1	Military Installation / intact (point)		N/A			
	Label String:	[Name] "Military installa	tion"			
	Characteristics:	1, 1 1 (Black, Condensed, 6 p	t, Mixed case)			
			Symbol Samples			
	Military installation		Fort Johnston Military Installatio	n		
Military Ins	tallation / not int	tact (point)				
	Symbo	l Placement Instructions:	Origin: Center of symbol			
	Symbo	l Type: Simple				
]					
Symbol	Graphic					
Componer		Component Ty	/pe: Point - Shape	Color Token:	Black/Black-12	
Descriptio <u>Parameter</u>	· ·	ire u.8mm				
Note:	See Annex H f	or detailed drawing instruc	tions.			
Reference #:	Description		Symbol Rules			
PS-04913	Description: Military Installation / r	not intact	Criteria: Condition of Facility [FUN] = (A	Abandoned [2], Dam	aged [13], Destroyed [3], D	Dismantled [4], Under
	(point)		Construction [1])			
Label Placeme	ent Rules (see Annex J):	LP-3505, LP-4813, LP-99	Label Rules			
Reference #:	Description:		Criter	ia:		
PL-04913_1	Military Installation	/ not intact (point)	N/A			
	Label String:	[Name] "Military installa	tion"			
	Characteristics:	1, 1 1 (Black, Condensed, 6 p	t Mixed case)			
		T (Black, Colldelised, 6 p	Symbol Samples			
			Symbol Samples			
	Military installation					
	D:1					
	Pile (AM040)	CA 0000 CC 0003				
	Rules (see Annex J): e / non-obstruction	GA-9999, GC-9983				
ivilliciai Pili		I Placement Instructions:	The symbol is applied to the	geometry of the feat	ure.	
		Type: Simple	,	,,		
L — —	i					
I	l					

Symbol Graphic

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04109 Mineral Pile / non-obstruction (area) Height Above Surface Level [HGT] < 46

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-9999

Reference #: Description: Criteria:

PL-04109_1 Mineral Pile / non-obstruction / known (area) Product [PPO] = (Coal [18], Coke [21], Gravel [53], Metal [69], Salt [95], Sand

[96], Stone [110])

Label String: [Product] "pile"

Characteristics: 1, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04109_2 Mineral Pile / non-obstruction / unknown (area) Product [PPO] = (Multiple [996], Other [999], Unkown [0])

Label String: "Mineral pile"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Mineral pile [___] Gravel pile

Mineral Pile / non-obstruction (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00010 Component Type: Point - Shape Color Token: Black

Description: Located object

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Crite

PS-04110 Mineral Pile / non-obstruction

(point)

Height Above Surface Level [HGT] < 46

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04110_1 Mineral Pile / non-obstruction / known (point) Product [PPO] = (Coal [18], Coke [21], Gravel [53], Metal [69], Salt [95], Sand

[96], Stone [110])

Label String: [Product] "pile"

Characteristics: 1, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Mineral Pile / non-obstruction / unknown (point) PL-04110_2

Product [PPO] = (Multiple [996], Other [999], Unkown [0])

Label String: "Mineral pile"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

 $_{\odot}$ Mineral pile $_{\odot}$ Coal pile

Mooring Mast (AQ110)

Mooring Mast / non-obstruction (point)

Symbol Placement Instructions: Origin: Center of open circle

Symbol Type: Simple



Symbol Graphic

Component Ref #: Point - Shape Color Token: Black P00198 Component Type:

Description: Mooring mast

Parameters:

See Annex H for detailed drawing instructions. Note:

Symbol Rules

Reference #: Description: Criteria:

PS-04139 Mooring Mast / non-obstruction

(point)

Height Above Surface Level [HGT] < 46

Symbol Samples

Moraine (BJ020)

Generalization Rules (see Annex J): GA-9999

Moraine / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #: A00036 Area - Pattern Color Token: Dk-Brown1815 Component Type:

Description: Dk-Brown1815 Gravel Fill

Reference #: Description:

Area Pattern: AP-99, see Annex I

Symbol Rules

PS-04227 Moraine / all (area) Criteria: ΑII

Symbol Samples



Mountain Pass (DB150)

Mountain Pass / all (point)

Symbol Placement Instructions:

Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Note: The symbol shall be aligned along the associated transportation feature, if present. Otherwise, the symbol shall be aligned so that the "open" ends are towards the lower elevations.

Component Ref #:

P00029 Mountain pass

Component Type:

Point - Shape

Color Token:

Black

Description: Parameters:

See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: PS-04255

Note:

Description: Mountain Pass / all (point) Criteria:

ΑII

Label Rules

Label Placement Rules (see Annex J):

LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04255_1 Mountain Pass / all (point) N/A

Label String: [Name]

[Highest Elevation]

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

) (1362

) (Stevens Pass 1238

Named Location (ZD040)

Named Location / all (point)

Symbol Placement Instructions:

Symbol Type: Simple

Text label only. No graphic parameters

[NAM]

Symbol Graphic

Symbol Rules

Reference #: Description:

Criteria:

PS-04323 Named Location / all (point)

ΑII

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04323_1 Named Location / other (point) Apply to all named locations except for populated places.

Label String: [Name]
Characteristics: 45

45 (Black, Light Condensed, 6-16 pt, Upper case)

PL-04323_2 Named Location / populated place (point) Apply to populated place named locations.

Label String: [Name]
Characteristics: 42

42 (Black, Condensed, 8 pt, Mixed case)

Symbol Samples

BADLANDS Georgetown

Natural Pool (BH170)

Natural Pool / perennial (point)

Symbol Placement Instructions: Origin: Center of solid circle

Symbol Type: Simple



Symbol Graphic

Note: Tail of symbol is oriented downstream.

Component Ref #: P00026 Component Type: Point - Shape Color Token: Cyan

Description: Natural pool perennial

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria

PS-04210 Natural Pool / perennial (point) Hydrologic Persistence [HYP] = Perennial [1]

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04210_1 Natural Pool / perennial (point) N/A

Label String: [Name]
Characteristics: 16

16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Greer Spring

Natural Pool / intermittent, dry (point)

Symbol Placement Instructions: Origin: Center of open circle

Symbol Type: Simple



Symbol Graphic

Note: Tail of symbol is oriented downstream.

Component Ref #: P00032 Component Type: Point - Shape Color Token: Cyan

Description: Natural pool intermittent

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04211 Natural Pool / intermittent, dry Hydrologic Persistence [HYP] = (Dry [4], Intermittent [2], Unknown [0])

(point)

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04211_1 Natural Pool / intermittent, dry (point) N/A

Label String: [Name]
Characteristics: 16

16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Periodic Sprii

Oasis (EC020)

Generalization Rules (see Annex J): GA-9999, GC-9999

8

Oasis / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: L00021 Component Type: Line - Simple Color Token: Green362

Description: Green362 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Symbol Rules

Reference #: Description: Criteria:
PS-04310 Oasis / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04310_1 Oasis / all (area) N/A

Label String: [Name] "Oasis"

Characteristics: 3, 3

3 (Black, Condensed, 6-16 pt, Mixed case)

Oasis Symbol Samples Huacachina Oasis

Oasis / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00260 Component Type: Point - Shape Color Token: Green362

Description: Oasis

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04654 Oasis / all (point) All

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04654_1 Oasis / all (point) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

X

🔭 Quara Oasis

Offshore Platform (BD110)

Offshore Platform / non-obstruction (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

•

Symbol Graphic

Component Ref #: P00163 Component Type: Point - Shape Color Token: Black

Description: Offshore construction point

Parameters:

Note: See Annex H for detailed drawing instructions.

Reference #: Description: Criteria:

Reference #: Description: Criteria:

PS-04201 Offshore Platform / non-obstruction Height Above Surface Level [HGT] < 46

(point)

Label Rules Label Placement Rules (see Annex J): LP-3505 Reference #: Description: Criteria: PL-04201_1 Offshore Platform / non-obstruction (point) N/A Label String: "Platform" Characteristics: 1 1 (Black, Condensed, 6 pt, Mixed case) **Symbol Samples** Shown with tidal water: Platform Platform

Orchard (EA040)

Generalization Rules (see Annex J): GA-9999

Orchard / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #:

A00028 Component Type: Area - Pattern Color Token: Green362

Description: Green362 Orchard / Plantation Fill

Parameters:

Area Pattern: AP-74, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04305 Orchard / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04305_1 Orchard / crop known (area) Crop Species [CSP] = (Banana [41], Fruit Tree [15], Nut [113], Palm [157], Rubber

[29])

Label String: [Name] [Crop Species]

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04305_2 Orchard / crop unknown (area) Crop Species [CSP] = (Other [999], Unknown [0])

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Morris Orchard Banana

Park (AK120)

Generalization Rules (see Annex J): GA-9999, GC-9999

Park / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic Note: Component L00368 is applied to the perimeter and is filled with Component A00101.

Component Ref #: A00101 Component Type: Area - Fill Color Token: Green362-12

Description: Green362-12 area fill

Parameters:

Screen Angle: 45 degrees

Screen Percent: 12%

Component Ref #: L00368 Component Type: Line - Styled Color Token: Green362

Description: Green362 0.15mm Dashed Line (0.15mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.15mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04059 Park / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04059_1 Park / all (area) N/A

Label String: [Name] "Park"

Characteristics: 3, 3

3 (Black, Condensed, 6-16 pt, Mixed case)

Symbol Samples





Park / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00146 Component Type: Point - Simple Color Token: Green362

Description: Green362 filled square with all sides 0.8mm

Parameters:

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:
PS-04594 Park / all (point) All

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04594_1 Park / all (point)

N/A

Label String: [Name] "Park"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Park Greenacre Park


Particle Accelerator (AL140)

Generalization Rules (see Annex J): GA-9999, GC-9989

Particle Accelerator / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04090 Particle Accelerator / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04090_1 Particle Accelerator / all (area) N/A

Label String: [Name] "Particle accelerator"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

_ _ _ Particle accelerator

_____Large Hadron Collider Particle Accelerator

Particle Accelerator / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00014 Component Type: Line - Simple Color Token: Black

Description: Black 0.5mm Solid Line

Parameters:

Line Weight: 0.5mm

Reference #: Description: Criteria:

PS-04597 Particle Accelerator / all (line) All

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-4813, LP-9999

Reference #: Description: Criteria:
PL-04597_1 Particle Accelerator / all (line) N/A

Label String: [Name] "Particle accelerator"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Particle accelerator Stanford Linear Collider Particle Accelerator

Penstock (BH110)

Generalization Rules (see Annex J): GA-9999

Penstock / on surface (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00016 Component Type: Line - Simple Color Token: Cyan

Description: Cyan 0.3mm Solid Line

Parameters:

Line Weight: 0.3mm

Symbol Rules

Reference #: Description: Criteria:

PS-04194 Penstock / on surface (line) Vertical Relative Location [LOC] = (On Surface [44], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630

Reference #: Description: Criteria:
PL-04194_1 Penstock / on surface (line) N/A

Label String: "Penstock"
Characteristics: 16

16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Penstock

Penstock / below surface (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: Line - Styled Color Token: L00235 Component Type: Cyan

Description: Cyan 0.3mm Dashed Line (0.3mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.3mm Dash Length: 1.0mm **Dash Spacing:** 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04195 Penstock / below surface (line) Vertical Relative Location [LOC] = Below Ground Surface [40]

Label Rules

Label Placement Rules (see Annex J): LP-3630

Reference #: Description: Criteria: PL-04195_1 Penstock / below surface (line) N/A

> "Penstock" Label String: Characteristics: 16

> > 16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Note: Apex of Component P00208 is fixed at the start and end of Component L00016 with each "V" facing away. The 90 degree angle of the

Color Token:


Cyan

Penstock

Penstock / above surface (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



"V" is bisected equally by Component L00016. Line - Simple

Component Type:

L00016 Component Ref #: Cyan 0.3mm Solid Line Description:

Parameters:

Line Weight: 0.3mm

Component Ref #: P00208 Point - Shape Color Token: Cyan Component Type:

Aqueduct/penstock/water race "V" Description:

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04196 Penstock / above surface (line) Vertical Relative Location [LOC] = Above Surface [45]

Label Rules

Label Placement Rules (see Annex J): LP-3630

Reference #: Description: Criteria: PL-04196_1 Penstock / above surface (line) N/A

> Label String: "Penstock" Characteristics: 16

Symbol Samples



Pipeline (AQ113)

Generalization Rules (see Annex J): GA-9999

Pipeline / on surface / not water (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00193 has an initial offset of 5.0mm; after that 10.0mm.

Symbol Graphic

Note: Component P00193 is centered along Component L00009.

Component Ref #: L00009 Component Type: Line - Simple Color Token: Black

Description: Black 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Component Ref #: P00193 Component Type: Point - Simple Color Token: Black

Description: Black 0.7mm diameter filled circle

Parameters:

Diameter: 0.7mm

Note: The component is a circle and is filled with the solid color.

Reference #: Description: Criteria:

PS-04329 Pipeline / on surface / not water Vertical Relative Location [LOC] = (On Surface [44], Unknown [0])

(line)

AND Product [PPO] = (Chemical [16], Gas [45], Petrol [46], Oil [75], Other [999], Sewage [101], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04329_1 Pipeline / on surface / not water / intact (line) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Product]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04329_2 Pipeline / on surface / not water / not intact (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],


Dismantled [4], Under Construction [1])

Label String: [Product] "("[Condition of Facility]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples



Pipeline / on surface / water (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00125 has an initial offset of 5.0mm; after that 10.0mm.

Line - Simple

Symbol Graphic Note: Component P00125 is centered along Component L00015.

Component Ref #: L00015
Description: Cyan 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Component Ref #: P00125 Component Type: Point - Simple Color Token: Cyan

Component Type:

Description: Cyan 0.7mm diameter filled circle

Parameters:

Diameter: 0.7mm

Note: The component is a circle and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04330 Pipeline / on surface / water (line) Vertical Relative Location [LOC] = (On Surface [44], Unknown [0])

AND Product [PPO] = Water [122]

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999

Reference #: Description:

PL-04330_1 Pipeline / on surface / water / not intact (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Criteria:

Dismantled [4], Under Construction [1])

Color Token:

Cyan

Label String: "("[Condition of Facility]")"

Characteristics: 93, 93, 93

93 (Cyan, Condensed, 6 pt, Lower case)

Symbol Samples

(construction)

Pipeline / below surface / not water (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00193 is centered on the first dash then every other dash of Component L00404.

Symbol Graphic

Note: Component P00193 is centered along Component L00404.

Component Ref #: L00404 Component Type: Line - Styled Color Token: Black

Description: Black 0.2mm Dashed Line (0.2mm wt, 4.0mm dash, 1.0mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 4.0mm Dash Spacing: 1.0mm

Component Ref #: P00193 Component Type: Point - Simple Color Token: Black

Description: Black 0.7mm diameter filled circle

Parameters:

Diameter: 0.7mm

Note: The component is a circle and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04331 Pipeline / below surface / not water

(line)

Vertical Relative Location [LOC] = (Above Waterbody Bottom [46], Below Waterbody Bottom [23], Below

Ground Surface [40], On Waterbody Bottom [17])

AND Product [PPO] = (Chemical [16], Gas [45], Petrol [46], Oil [75], Other [999], Sewage [101], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04331_1 Pipeline / below surface / not water / intact (line) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Product] Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

PL-04331 2 Pipeline / below surface / not water / not intact (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

[Product] "("[Condition of Facility]")" Label String:

Characteristics: 1, 22, 22, 22

> 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

> > **Symbol Samples**



Pipeline / below surface / water (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00125 is centered on the first dash then every other dash of Component L00405.

Symbol Graphic

Note: Component P00125 is centered along Component L00405.

Component Ref #: 100405 Line - Styled Component Type: Color Token: Cyan

Cyan 0.2mm Dashed Line (0.2mm wt, 4.0mm dash, 1.0mm gap) Description:

Parameters:

Line Weight: 0.2mm Dash Length: 4.0mm Dash Spacing: 1.0mm

Point - Simple Component Ref #: P00125 Component Type: Color Token: Cyan

Description: Cyan 0.7mm diameter filled circle

Parameters:

0.7mm Diameter:

Note: The component is a circle and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

Pipeline / below surface / water PS-04332 Vertical Relative Location [LOC] = (Above Waterbody Bottom [46], Below Waterbody Bottom [23], Below (line)

Ground Surface [40], On Waterbody Bottom [17])

AND Product [PPO] = Water [122]

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04332_1 Pipeline / below surface / water / not intact (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: "("[Condition of Facility]")"

Characteristics: 93, 93, 93

93 (Cyan, Condensed, 6 pt, Lower case)

Symbol Samples

(construction)

Pipeline / above surface / not water (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00193 has an initial offset of 5.0mm; after that 10.0mm.

Symbol Graphic

Note: Apex of Component P00045 is fixed at the start and end of Component L00009 with each "V" facing away. The 90 degree angle of the "V" is bisected equally by Component L00009. Component P00193 is centered along Component L00009.

Component Ref #: L00009 Component Type: Line - Simple Color Token: Black

Description:

Black 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

P00193 Point - Simple Black Component Ref #: Component Type: Color Token:

Description: Black 0.7mm diameter filled circle

Parameters:

Diameter: 0.7mm

The component is a circle and is filled with the solid color. Note:

Component Ref #: P00045 Point - Shape Color Token: Black Component Type:

Description: Pipeline elevated "V"

Parameters:

See Annex H for detailed drawing instructions. Note:

Symbol Rules

Reference #: Description: Criteria:

PS-04333 Pipeline / above surface / not water Vertical Relative Location [LOC] = Above Surface [45]

Product [PPO] = (Chemical [16], Gas [45], Petrol [46], Oil [75], Other [999], Sewage [101], Unknown [0]) AND

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999

Reference #: Description:

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) PL-04333_1 Pipeline / above surface / not water / intact (line)

> Label String: [Product]

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04333_2 Pipeline / above surface / not water / not intact (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

[Product] "("[Condition of Facility]")" Label String:

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

Sewage

Pipeline / above surface / water (line)

-

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00125 has an initial offset of 5.0mm; after that 10.0mm.

Symbol Graphic

Note: Apex of Component P00058 is fixed at the start and end of Component L00015 with each "V" facing away. The 90 degree angle of the "V" is bisected equally by Component L00015. Component P00125 is centered along Component L00015.

Component Ref #: L00015 Component Type: Line - Simple Color Token: Cyan

Description:

Cyan 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Component Ref #: P00125 Component Type: Point - Simple Color Token: Cyan

Description: Cyan 0.7mm diameter filled circle

Parameters:

Diameter: 0.7mm

Note: The component is a circle and is filled with the solid color.

Component Ref #: P00058 Component Type: Point - Shape Color Token: Cyan

Description: Pipeline water elevated "V"

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

LP-3630, LP-9950, LP-9999

Reference #: Description: Criteria:

PS-04334 Pipeline / above surface / water Vertical Relative Location [LOC] = Above Surface [45]

(line)

Label Placement Rules (see Annex J):

AND Product [PPO] = Water [122]

Label Rules

Reference #: Description: Criteria:

PL-04334_1 Pipeline / above surface / water / not intact (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: "("[Condition of Facility]")"

Characteristics: 93, 93, 93

93 (Cyan, Condensed, 6 pt, Lower case)

Symbol Samples

—

(destroyed)

Point of Change (No Code)

Point of Change / all (point)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Note: The symbol is placed perpendicular to and on the upper side (north) of the associated feature symbol. It is used only where necessary to denote a non-symbolized change in information or classification.

Component Ref #: P00153 Component Type: Point - Simple Color Token: Black

Description: Black 2.0mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm
Length: 2.0mm

Reference #: Description: Criteria:
PS-04857 Point of Change / all (point)

Symbol Rules

Symbol Rules

Symbol Samples

Symbol Samples

Shown with Road:
8 LANES | 6 LANES

Power Line (AT030)

Generalization Rules (see Annex J): GA-9999, GC-9988

Power Line / non-obstruction (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00020 has an initial offset of 10.0mm; after that 20.0mm.

Symbol Graphic

Note: Component P00020 is centered along Component L00005. Default orientation for top of component P00020 should point in a northerly direction.

Component Ref #: L00005 Component Type: Line - Simple Color Token: Blue072

Description: Blue072 0.4mm Solid Line

Parameters:

Line Weight: 0.4mm

Component Ref #: P00020 Component Type: Point - Shape Color Token: Blue072

Description: Pylon

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04433 Power Line / non-obstruction (line) Height Above Surface Level [HGT] < 46

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04433_1 Power Line / non-obstruction / not intact (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: "("[Condition of Facility]")"

Characteristics: 15

15 (Blue072, Condensed, 6 pt, Mixed case)

Symbol Samples



Power Line / obstruction (line)

Symbol Graphic

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Component Ref #: L00006 Component Type: Line - Simple Color Token: Blue072

Description: Blue072 0.73mm Solid Line

Parameters:

Line Weight: 0.73mm

Symbol Rules

Reference #: Description: Criteria:

PS-04474 Power Line / obstruction (line) Height Above Surface Level [HGT] >= 46

Label Rules

Label Placement Rules (see Annex J): LP-9991

Reference #: Description: Criteria:

PL-04474_1 Power Line / obstruction (line) N/A

Label String: "Powerline"

[Highest Elevation]
"("[Height Above Surface Level]")"

"("[Height Above Surface Level]")

Characteristics: 15

46 95, 95, 95

15 (Blue072, Condensed, 6 pt, Mixed case) 46 (Blue072, Condensed, Bold, 6 pt, Lower case)

Symbol Samples

Powerline 242 (72)

Power Substation (AD030)

Generalization Rules (see Annex J): GA-9999, GC-9982

Power Substation / all (area)

Symbol Placement Instructions:

Symbol Type: Complex

The symbol is applied to the geometry of the feature.

Symbol Graphic

Note: Component L00210 is applied to the perimeter and Component P00138 is placed in the center.

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Component Ref #: P00138 Component Type: Point - Shape Color Token: Black/Blue072-42

Description: Power substation

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:
PS-04297 Power Substation / all (area) All

Label Rules

Label Placement Rules (see Annex J):

LP-3506, LP-9950, LP-9999

Reference #:

Description:

Criteria:

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under Construction [1])

Label String:

("[Condition of Facility]")"

Characteristics:

22, 22, 22

22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

Power Substation / all (point)

Symbol Placement Instructions: Origin: Center of open square

4

Symbol Graphic

Component Ref #: P00138 Component Type: Point - Shape Color Token: Black/Blue072-42

Description: Power substation

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04298 Power Substation / all (point) All

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9999

Symbol Type: Simple

Reference #: Description: Criteria:

PL-04298_1 Power Substation /not intact (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: "("[Condition of Facility]")"

Characteristics: 22, 22, 22

22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples


2 (construction

Processing Facility (AC000)

Generalization Rules (see Annex J): GA-9999

Processing Facility / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.



Symbol Type: Simple

Component Description Parameters	: Black 0.1mm Da	Component Type: Line ashed line (0.1mm wt, 1.0mm dash, 0.5	e - Styled imm gap)	Color Token:	Black
Line Weigh		Dash Length: 1.0	mm	Dash Spacing:	0.5mm
			Symbol I	Rules	
Reference #:	Description:	Criteria:			
PS-04410	Processing Facility / all				
Lahel Placeme	nt Rules (see Annex J):	LP-3506, LP-4813, LP-9950, LP-9999	abel Rule	S	
	,	El 3300, El 4013, El 3330, El 3333		Cuitania	
Reference #:	Description: Processing Facility / i	nto et / known (over)		Criteria:	- (Fully Functional [6] Halmanna [0])
PL-04410_1	Processing Facility / II	ntact / known (area)		Condition of Facility [FON]	= (Fully Functional [6], Unknown [0])
			AND	Cement [15], Chemical [16] Explosive [38], Fish [39], Fo [58], Lead [59], Lumber [63 [137], Petrol [46], Plastic [8 [101], Silver [105], Snow [1	n [2], Asphalt [4], Biochemical [136], Brick [13], l, Coal [18], Coke [21], Concrete [23], Copper [26], lood [41], Gas [45], Glass [47], Gold [48], Ice [57], Iron lood, Metal [69], Oil [75], Paper [80], Petrochemical lood, Radioactive Material [90], Rubber [94], Sewage lood, Steel [109], Sugar [111], Textile [114], Tobacco lood testation Product [121], Water [122], Zinc [126])
	Label String:	[Name] [Product] "processing facility"			
	Characteristics:	1, 1, 22 1 (Black, Condensed, 6 pt, Mixed case 22 (Black, Condensed, 6 pt, Lower cas			
PL-04410_2	Processing Facility / i	ntact / unknown (area)		Condition of Facility [FUN]	= (Fully Functional [6], Unknown [0])
			AND	Product [PPO] = (Other [999	9], Unknown [0])
	Label String:	[Name] "Processing facility"			
	Characteristics:	1, 1 1 (Black, Condensed, 6 pt, Mixed case	<u>e)</u>		
PL-04410_3	Processing Facility / r	not intact / known (area)		Condition of Facility [FUN] = Dismantled [4], Under Cons	= (Abandoned [2], Damaged [13], Destroyed [3], struction [1])
			AND	Cement [15], Chemical [16] Explosive [38], Fish [39], Fo [58], Lead [59], Lumber [63 [137], Petrol [46], Plastic [8 [101], Silver [105], Snow [1	n [2], Asphalt [4], Biochemical [136], Brick [13], l, Coal [18], Coke [21], Concrete [23], Copper [26], nod [41], Gas [45], Glass [47], Gold [48], Ice [57], Iron n], Metal [69], Oil [75], Paper [80], Petrochemical number [44], Radioactive Material [90], Rubber [94], Sewage number [106], Sugar [111], Textile [114], Tobacco number [126], Water [122], Zinc [126])
	Label String:	[Name] [Product] "processing facility"	" "("[Condit	tion of Facility]")"	
	Characteristics:	1, 1, 22, 22, 22, 22 1 (Black, Condensed, 6 pt, Mixed case 22 (Black, Condensed, 6 pt, Lower cas			
PL-04410_4	Processing Facility / r	oot intact / unknown (area)		Condition of Facility [FUN] = Dismantled [4], Under Cons	= (Abandoned [2], Damaged [13], Destroyed [3], struction [1])
			AND	Product [PPO] = (Other [99	9], Unknown [0])
	Label String:	[Name] "Processing facility" "("[Cond	ition of Fac	ility]")"	
	Characteristics:	1, 1, 22, 22, 22 1 (Black, Condensed, 6 pt, Mixed case 22 (Black, Condensed, 6 pt, Lower cas	•		
		Sy	mbol Saı	mples	
	Processing facility		Oil processing	facility	, York Processing Facility (damaged)

Processing Facility / intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Point - Simple Component Ref #: P00006 Component Type: Color Token: Black

Description: Black filled square with all sides 0.8mm

Parameters:

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04411 Processing Facility / intact (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04411_1 Product [PPO] = (Aluminum [2], Asphalt [4], Biochemical [136], Brick [13], Processing Facility / intact / known (point)

Cement [15], Chemical [16], Coal [18], Coke [21], Concrete [23], Copper [26], Explosive [38], Fish [39], Food [41], Gas [45], Glass [47], Gold [48], Ice [57], Iron [58], Lead [59], Lumber [63], Metal [69], Oil [75], Paper [80], Petrochemical [137], Petrol [46], Plastic [84], Radioactive Material [90], Rubber [94], Sewage [101], Silver [105], Snow [106], Steel [109], Sugar [111], Textile [114], Tobacco [117], Uranium [120], Vegetation Product [121], Water [122], Zinc [126])

Label String: [Name] [Product] "processing facility"

Characteristics: 1. 1. 22

> 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04411 2 Processing Facility / intact / unknown (point) Product [PPO] = (Other [999], Unknown [0])

> Label String: [Name] "Processing facility"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Processing facility Hyperion Sewage Treatment Plant Fish processing facility

Processing Facility / not intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00173 Component Type: Point - Shape Color Token: Black/Black-12

Description: Not intact square 0.8mm

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Criteria: Description:

PS-04412 Processing Facility / not intact Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under (point)

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description:

Criteria:

PL-04412_1 Processing Facility / not intact / known (point)

Product [PPO] = (Aluminum [2], Asphalt [4], Biochemical [136], Brick [13], Cement [15], Chemical [16], Coal [18], Coke [21], Concrete [23], Copper [26], Explosive [38], Fish [39], Food [41], Gas [45], Glass [47], Gold [48], Ice [57], Iron [58], Lead [59], Lumber [63], Metal [69], Oil [75], Paper [80], Petrochemical [137], Petrol [46], Plastic [84], Radioactive Material [90], Rubber [94], Sewage [101], Silver [105], Snow [106], Steel [109], Sugar [111], Textile [114], Tobacco [117], Uranium [120], Vegetation Product [121], Water [122], Zinc [126])

Label String: [Name] [Product] "processing facility"

Characteristics: 1, 1, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04412_2 Processing Facility / not intact / unknown (point)

Product [PPO] = (Other [999], Unknown [0])

Label String: [Name] "Processing facility"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Processing facility

Protection Shed (AL210)

Generalization Rules (see Annex J): GA-9999, GC-9997

Protection Shed / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Component Ref #: L00200 Component Type: Line - Simple Color Token: Black

Description: Black 1.5mm Solid Line

Parameters:

Line Weight: 1.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04558 Protection Shed / all (line) All

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04558 1 Protection Shed / all (line) N/A

Label String: "Protection shed"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Protection shed

Shown with Road: Protection shed

Protection Shed / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Note: The symbol is aligned with the associated transportation feature.

Component Ref #: P00152 Component Type: Point - Simple Color Token: Black

Black 2.5mm length line with a 1.5mm lineweight Description:

Parameters:

Line Weight: 1.5mm Length: 2.5mm

Symbol Rules

Reference #: Description: Criteria:

Protection Shed / all (point) PS-04563 ΑII

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria: PL-04563_1 Protection Shed / all (point) N/A

> Label String: "Protection shed"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Protection shed

Public Square (AL170)

Generalization Rules (see Annex J): GA-9999

Public Square / all (area)

Symbol Placement Instructions: Text label only. No graphic parameters

Symbol Type: Simple

[NAM]

Symbol Graphic

Symbol Rules

Criteria: Reference #: Description: PS-04091 Public Square / all (area) ΑII

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04091_1 Public Square / all (area) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Union Square

	•	~ • • •		446
1311100	$n \cdot n \cdot \alpha$	Station (116
Pulli	UIIIP	STATION	AU	110
	C		,,,	

Generalization Rules (see Annex J): GA-9999

deneralization it	dies (see Alliex 1).	UA-3333				
Pumping Sta	tion / all (area)				
Symbol Gr	Symb	ool Placement Instructions: T	he symbol is applied	to the geometry of the feat	ure.	
Component Description: Parameters:	Black 0.1mm	Component Type Dashed line (0.1mm wt, 1.0mm	n dash, 0.5mm gap)	Color Token:	Black	
Line Weight:	: 0.1mm	Dash Length:	1.0mm	Dash Spacing:	0.5mm	
			Symbol I	Rules		
	Description:		iteria:			
PS-04142 P	Pumping Station / all	l (area) Al				
			Label Rule	S		
Label Placemen	nt Rules (see Annex J)	: LP-3506, LP-9950, LP-9999)			
Reference #:	Description:			Criteria:		
PL-04142_1	Pumping Station /	intact (area)		Condition of Facility [FUN]	= (Fully Functional [6], Unknown [0])	
	Label String	: [Product] "Pumping station	"			
	Characteristics	s: 1, 1 1 (Black, Condensed, 6 pt, N	Mixed case)			
PL-04142_2	Pumping Station /	not intact (area)		Condition of Facility [FUN] Dismantled [4], Under Cor	= (Abandoned [2], Damaged [13], Destroyenstruction [1])	ed [3],
	Label String	: [Product] "Pumping station	" "("[Condition of Fa	cility]")"		
	Characteristics	5: 1, 1, 22, 22, 22 1 (Black, Condensed, 6 pt, N 22 (Black, Condensed, 6 pt,	,			
			Symbol Sar	mples		
	Pumping s	tation	[] Water	pumping station		

Pumping Station / intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00006 Component Type: Point - Simple Color Token: Black

Description: Black filled square with all sides 0.8mm

Parameters:

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04143 Pumping Station / intact (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04143_1 Pumping Station / intact (point) N/A

Label String: [Product] "Pumping station"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Pumping station Sewage pumping station

Pumping Station / not intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

ш

Symbol Graphic

Component Ref #: P00173 Component Type: Point - Shape Color Token: Black/Black-12

Description: Not intact square 0.8mm

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria

PS-04917 Pumping Station / not intact (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04917_1 Pumping Station / not intact (point) N/A

Label String: "Pumping station"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

_Pumping station

Pylon (AT042)

Pylon / non-obstruction (point)

Symbol Placement Instructions: Origin: Center of dot

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00010 Component Type: Point - Shape Color Token: Black

Description: Located object

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04866 Pylon / non-obstruction (point) Height Above Surface Level [HGT] < 46

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04866_1 Pylon / non-obstruction (point) N/A

Label String: "Pylon"
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

⊙ Pylon

Pylon / obstruction (point)

Symbol Placement Instructions: Origin: Center of open circle

Symbol Type: Simple



Symbol Graphic

Note: The vertical axis of the symbol is orientated perpendicular to the line element of the coincident Cableway, Communication Line or Power Line feature, with the top of the symbol pointing in a northerly direction.

Component Ref #: P00292 Component Type: Point - Shape Color Token: Blue072

Description: Vertical obstruction pylon

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04947 Pylon / obstruction (point) Height Above Surface Level [HGT] >= 46

Label Rules

Label Placement Rules (see Annex J): LP-9992

Reference #: Description:

Criteria: N/A

PL-04947_1 Pylon / obstruction (point)

"Pylon"

[Highest Elevation]

"("[Height Above Surface Level]")"

Characteristics: 15

Label String:

46 95, 95, 95

15 (Blue072, Condensed, 6 pt, Mixed case)

46 (Blue072, Condensed, Bold, 6 pt, Lower case)

Symbol Samples





Quarry (AA012)

Generalization Rules (see Annex J): GA-9999, GC-9982

Quarry / intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00210 is applied to the perimeter and Component P00001 is placed in the center.

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Component Ref #: P00001 Component Type: Point - Shape Color Token: Black

Description: Extraction mine intact not peat

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04669 Quarry / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04669_1 Quarry / intact / named / product known (area) Name [NAM] <> "Unknown"

AND Product [PPO] = (Clay [17], Dolomite [35], Granite [50], Gravel [53], Marble [66],

Rock [93], Sand [96], Stone [110], Madrepore [129])

Label String: [Name] "Quarry" "("[Product]")"

Characteristics: 1, 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04669_2 Quarry / intact / named / product unknown (area) Name [NAM] <> "Unknown"

AND Product [PPO] = (Multiple [996], Other [999], Unknown [0])

Label String: [Name] "Quarry"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04669_3 Quarry / intact / unnamed / product known (area) Name [NAM] = "Unknown"

AND Product [PPO] = (Clay [17], Dolomite [35], Granite [50], Gravel [53], Marble [66],

Rock [93], Sand [96], Stone [110], Madrepore [129])

Label String: "Quarry" "("[Product]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04669_4 Quarry / intact / unnamed / product unknown (area) Name [NAM] = "Unknown"

AND Product [PPO] = (Multiple [996], Other [999], Unknown [0])

Label String: "Quarry"
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

 ★
 Quarry

 Danby Quarry (marble)

Quarry (marble)

Quarry / not intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.



Symbol Graphic

Note: Component L00210 is applied to the perimeter and Component P00002 is placed in the center.

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Symbol Type: Complex

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Component Ref #: P00002 Component Type: Point - Shape Color Token: Black

Description: Extraction mine not intact not peat

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04670 Quarry / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04670_1 Quarry / not intact / named / product known (area) Name [NAM] <> "Unknown"

AND Product [PPO] = (Clay [17], Dolomite [35], Granite [50], Gravel [53], Marble [66],

Rock [93], Sand [96], Stone [110], Madrepore [129])

Label String: [Name] "Quarry" "("[Product]")"

Characteristics: 1, 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04670_2 Quarry / not intact / named / product unknown (area)

Name [NAM] <> "Unknown"

Name [NAM] = "Unknown"

AND Product [PPO] = (Multiple [996], Other [999], Unknown [0])

Label String: [Name] "Quarry"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04670_3 Quarry / not intact / unnamed / product known (area)

Product [PPO] = (Clay [17], Dolomite [35], Granite [50], Gravel [53], Marble [66],

Rock [93], Sand [96], Stone [110], Madrepore [129])

Label String: "Quarry" "("[Product]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04670_4 Quarry / not intact / unnamed / product unknown (area) Name [NAM] = "Unknown"

AND Product [PPO] = (Multiple [996], Other [999], Unknown [0])

Label String: "Quarry"


Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

AND







Quarry / intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00001 Component Type: Point - Shape Color Token: Black

Description: Extraction mine intact not peat

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria

PS-04671 Quarry / intact (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04671_1 Quarry / intact / named / product known (point) Name [NAM] <> "Unknown"

AND Product [PPO] = (Clay [17], Dolomite [35], Granite [50], Gravel [53], Marble [66],

Rock [93], Sand [96], Stone [110], Madrepore [129])

Label String: [Name] "Quarry" "("[Product]")"

Characteristics: 1, 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04671_2 Quarry / intact / named / product unknown (point) Name [NAM] <> "Unknown"

AND Product [PPO] = (Multiple [996], Other [999], Unknown [0])

Label String: [Name] "Quarry"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04671_3 Quarry / intact / unnamed / product known (point) Name [NAM] = "Unknown"

Quarry / intact / unnamed / product known point)

AND Product [PPO] = (Clay [17], Dolomite [35], Gravite [50], Gravel [53], Marble [66],

Rock [93], Sand [96], Stone [110], Madrepore [129])

Label String: "Quarry" "("[Product]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04671_4 Quarry / intact / unnamed / product unknown (point) Name [NAM] = "Unknown"

AND Product [PPO] = (Multiple [996], Other [999], Unknown [0])

Label String: "Quarry"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

★ Quarry (gravel)
★ Three Oaks Quarry (gravel)

Quarry / not intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00002 Component Type: Point - Shape Color Token: Black

Description: Extraction mine not intact not peat

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04672 Quarry / not intact (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04672_1 Quarry / not intact / named / product known (point) Name [NAM] <> "Unknown"

AND Product [PPO] = (Clay [17], Dolomite [35], Granite [50], Gravel [53], Marble [66],

Rock [93], Sand [96], Stone [110], Madrepore [129])

Label String: [Name] "Quarry" "("[Product]")"

Characteristics: 1, 1, 22, 22, 22

> 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04672_2 Quarry / not intact / named / product unknown (point) Name [NAM] <> "Unknown"

Name [NAM] = "Unknown"

Product [PPO] = (Multiple [996], Other [999], Unknown [0]) AND

Label String: [Name] "Quarry"

Characteristics: 1.1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04672_3 Quarry / not intact / unnamed / product known (point)

Product [PPO] = (Clay [17], Dolomite [35], Granite [50], Gravel [53], Marble [66],

Rock [93], Sand [96], Stone [110], Madrepore [129])

Label String: "Quarry" "("[Product]")"

Characteristics: 1, 22, 22, 22

> 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04672 4 Quarry / not intact / unnamed / product unknown (point) Name [NAM] = "Unknown"

Product [PPO] = (Multiple [996], Other [999], Unknown [0]) AND

"Quarry" Label String:

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

AND

★ Todd Quarry (rock) Quarry (rock)

Racetrack (AK130)

Generalization Rules (see Annex J): GA-9999, GC-9988

Racetrack / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: L00013

Component Type:

Line - Simple

Color Token:

Black

Description:

Black 0.4mm Solid Line

Line Weight:

Reference #:

Parameters:

0.4mm

Symbol Rules

Reference #: Description: PS-04060 Racetrack / all (line)

Criteria:

Label Rules

Label Placement Rules (see Annex J): Description:

LP-3505, LP-4813, LP-9999

Criteria:

PL-04060_1 Racetrack / all (line) N/A

							29 May 2015
	Labe	String: [Name]] "Racetrack"				
	Charac	teristics: 1, 1					
		1 (Black	k, Condensed, 6 pt				
				Symbol Sa	mples		
		Racetrack		Talade	ga Superspeedway		
		,					
Radar St	ation (AT	·0/15)					
Radar Stati	on / intact		ant Instructions	Origina Contar of sum	hal		
		Symbol Type: S		Origin: Center of sym	DOI		
	_	Symbol Type: S	шре				
Symbol	Graphic						
Componei Descriptio		0006 filled square with a	Component Ty all sides 0.8mm	rpe: Point - Simple	Color Token:	Black	
Paramete	rs:						
Length:	0.8m						
Note:	The o	component is a squ	are and is filled w	ith the solid color.			
				Symbol	Rules		
Reference #:	Description:			Criteria:			
PS-04159	Radar Station	/ intact (point)			UN] = (Fully Functional [6],	, Unknown [0])	
Label Blacom	ent Rules (see A	innov I): ID 250	05, LP-4813, LP-99	Label Rule	es		
			J5, LP-4615, LP-95	999			
Reference #:					Criteria:		
PL-04159_1	Radar Statio	on / intact (point)			N/A		
	Labe	String: [Name]] "Radar station"				
	Charac	teristics: 1, 1					
		1 (Black	k, Condensed, 6 pt				
				Symbol Sa	mples		
Radar station				Gettysburg A	ir Force Radar Station		
Radar Stati	on / not in	tact (point)					
		Symbol Placeme	ent Instructions:	Origin: Center of sym	bol		
		Symbol Type: S	imple				
	1						
	_						

Point - Shape Black/Black-12 Component Ref #: P00173 Component Type: Color Token:

Description: Not intact square 0.8mm

Parameters:

Symbol Graphic

See Annex H for detailed drawing instructions. Note:

Symbol Rules

Reference #: Description: Criteria:

PS-04918 Radar Station / not intact (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Criteria: Reference #: Description: PL-04918_1 Radar Station / not intact (point) N/A

> Label String: "Radar station"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Radar station

Railway (AN010)

Generalization Rules (see Annex J): GA-9999

Railway / intact / broad, standard / electrified / >= 2 tracks (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00282 has an initial offset of 3.2mm; after that 12.8mm.

Repeating Point and Interval 2: Component P00278 has an initial offset of 9.6mm; after that 12.8mm.

Line - Simple

Symbol Graphic Note: Components P00282 and P00278 are centered perpendicular to Component L00011 with the 0.7mm length line of P00282 on the

northernmost side. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Color Token:

Black

Component Ref #: L00011 Component Type: Black 0.3mm Solid Line

Description:

Parameters: Line Weight: 0.3mm

Component Ref #: P00282 Component Type: Point - Shape Color Token: Black

Railway tick broad electrified double Description:

Parameters:

See Annex H for detailed drawing instructions. Note:

Component Ref #: Point - Shape Color Token: P00278 Component Type: Black

Description: Railway tick broad double

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: PS-04383

Railway / intact / broad, standard / electrified / >= 2 tracks (line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Railway Gauge Classification [RGC] = (Broad [1], Standard [3], Unknown [0])

Railway Power Method [RRA] = (Electrified Track [1], Overhead Electrified [3]) AND

AND Track or Lane Count [LTN] >= 2

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], Unknown [0])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

Railway Use [RRC] = (Logging [8], Long-haul [33], Other [999], Unknown [0]) AND

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Criteria: Reference #: Description:

PL-04383_1 Railway / intact / broad / electrified / > 2 tracks (line)

Railway Gauge Classification [RGC] = Broad [1]

AND Track or Lane Count [LTN] > 2

Label String: [Name] [Track or Lane Count] "TRACKS" [Railway Gauge] "m"

Characteristics: 27, 28, 27, 28, 28,

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04383_2 Railway / intact / broad / electrified / 2 tracks (line)

Railway Gauge Classification [RGC] = Broad [1]

AND Track or Lane Count [LTN] = 2

Label String: [Name] [Railway Gauge] "m"

Characteristics: 27, 28, 28

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04383_3 Railway / intact / standard / electrified / > 2 tracks (line)

Railway Gauge Classification [RGC] = (Standard [3], Unknown [0])

AND Track or Lane Count [LTN] > 2

Label String: [Name] [Track or Lane Count] "TRACKS"

Characteristics: 27, 28, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04383_4 Railway / intact / standard / electrified / 2 tracks (line)

Railway Gauge Classification [RGC] = (Standard [3], Unknown [0])


AND Track or Lane Count [LTN] = 2

Label String: [Name]
Characteristics: 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples





Railway / intact / broad, standard / electrified / 1 track (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00280 has an initial offset of 3.2mm; after that 12.8mm.

Repeating Point and Interval 2: Component P00044 has an initial offset of 9.6mm; after that 12.8mm.

Symbol Graphic

Note: Components P00280 and P00044 are centered perpendicular to Component L00011 with the 0.7mm length line of P00280 on the northernmost side. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00011 Component Type: Line - Simple Color Token: Black

Description: Parameters:

Line Mainhte

Line Weight: 0.3mm

Component Ref #: P00280 Component Type: Point - Shape Color Token: Black

Description: Railway tick broad electrified

Parameters:

Note: See Annex H for detailed drawing instructions.

Black 0.3mm Solid Line

Component Ref #: P00044 Component Type: Point - Simple Color Token: Black

Description: Black 1.5mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm Length: 1.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04382

Railway / intact / broad, standard / electrified / 1 track (line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Railway Gauge Classification [RGC] = (Broad [1], Standard [3], Unknown [0]) Railway Power Method [RRA] = (Electrified Track [1], Overhead Electrified [3]) AND

AND Track or Lane Count [LTN] <= 1

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], Unknown [0])

Railway in Road [RIR] = (Separated from Road [1000], Unknown [0]) AND

AND Railway Use [RRC] = (Logging [8], Long-haul [33], Other [999], Unknown [0])

Label Rules

Label Placement Rules (see Annex J):

LP-3630, LP-9999

Description: Reference #:

Criteria:

PL-04382 1 Railway / intact / broad / electrified / 1 track (line) Railway Gauge Classification [RGC] = Broad [1]

Label String: [Name] [Railway Gauge] "m"

27, 28, 28 Characteristics:

> 27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

Railway / intact / standard / electrified / 1 track (line) PL-04382_2

Railway Gauge Classification [RGC] = (Standard [3], Unknown [0])

Black

Label String: [Name] Characteristics:

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples



L & T RAILROAD

Railway / intact / narrow / electrified / >= 2 tracks (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Component P00281 has an initial offset of 3.2mm; after that 12.8mm on the northernmost side of Repeating Point and Interval:

Component L00011.

Component P00277 has an initial offset of 9.6mm; after that 12.8mm on the southernmost side of Repeating Point and Interval 2:

Note: Components P00281 and P00277 are perpendicular to and on alternating sides of Component L00011. No symbol is portrayed if the

Color Token:

Component L00011.

Line - Simple

Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #:

Symbol Graphic

L00011 Black 0.3mm Solid Line Description:

Parameters:

Line Weight: 0.3mm

Component Ref #: P00281 Component Type: Point - Shape Color Token: Black

Component Type:

Description: Railway tick narrow electrified double

Parameters:

See Annex H for detailed drawing instructions. Note:

P00277 Point - Shape Black Component Ref #: Component Type: Color Token:

Description: Railway tick narrow double

Parameters:

Note: See Annex H for detailed drawing instructions.

			Symbo	Rules		
eference #:	Description:		Criteria:	Triules —		
5-04385	Railway / intact / narro electrified / >= 2 tracks			FUN] = (Fully Functional [6], Unknown [0])		
	-	AND	Railway Gauge Classi	fication [RGC] = (Monorail [6], Narrow [2])		
		AND	Railway Power Meth	od [RRA] = (Electrified Track [1], Overhead Electrified [3])		
		AND	Track or Lane Count	LTN] >= 2		
		AND	Vertical Relative Loca	tion [LOC] = (Above Surface [45], On Surface [44], Unknown [0])		
		AND	Railway in Road [RIR]	= (Separated from Road [1000], Unknown [0])		
		AND	Railway Use [RRC] = (Logging [8], Long-haul [33], Other [999], Unknown [0])		
			Label Ru	es		
abel Placem	ent Rules (see Annex J):	LP-3630, LP-9999				
eference #:	Description:			Criteria:		
L-04385_1	Railway / intact / nai	rrow / electrified / > 2 to	racks (line)	Railway Gauge Classification [RGC] = Narrow [2]		
			AND	Track or Lane Count [LTN] > 2		
	Label String:	[Name] [Track or Lane	Count] "TRACKS" [Track	Information : Railway Gauge] "m"		
	Characteristics:		nsed, Italic, 6 pt, Upper nsed, Italic, 6 pt, Lower			
L-04385_2	Railway / intact / nai	row / electrified / 2 tra	cks (line)	Railway Gauge Classification [RGC] = Narrow [2]		
			AND	Track or Lane Count [LTN] = 2		
	Label String:	[Name] [Track Informa	ation : Railway Gauge] "r	n"		
	Characteristics:		nsed, Italic, 6 pt, Upper nsed, Italic, 6 pt, Lower			
L-04385_3	Railway / intact / mo	norail / electrified / > 2	•	Railway Gauge Classification [RGC] = Monorail [6]		
			AND	Track or Lane Count [LTN] > 2		
	Label String: [Name] [Railway Gauge Classification] [Track or Lane Count] "TRACKS"					
	Characteristics:	27, 27, 28, 27 27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)				
PL-04385_4	Railway / intact / mo	norail / electrified / 2 t	racks (line)	Railway Gauge Classification [RGC] = Monorail [6]		
			AND	Track or Lane Count [LTN] = 2		
	Label String:	[Name] [Railway Gaug	ge Classification]			
	Characteristics:	27, 27 27 (Black, Light Conde	nsed, Italic, 6 pt, Upper	case)		
			Symbol S			

SHORTLINE RAILROAD 4 TRACKS

Railway / intact / narrow / electrified / 1 track (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00279 has an initial offset of 3.2mm; after that 12.8mm on the northernmost side of

Component L00011.

Repeating Point and Interval 2: Component P00038 has an initial offset of 9.6mm; after that 12.8mm on the southernmost side of

Color Token:

Black

Component L00011.

Line - Simple

Symbol Graphic Note: Components P00279 and P00038 are perpendicular to and on alternating sides of Component L00011. No symbol is portrayed if the

Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: Description:

L00011 Black 0.3mm Solid Line

Parameters:

Line Weight: 0.3mm

Component Ref #: P00279 Component Type: Point - Shape Color Token: Black

Component Type:

Description: Railway tick narrow electrified

Parameters:

Note: See Annex H for detailed drawing instructions.

Component Ref #: P00038 Component Type: Point - Simple Color Token: Black

Description: Black 0.75mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm
Length: 0.75mm

Symbol Rules

Reference #: Description:
PS-04384 Railway / intact / narrow /

electrified / 1 track (line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Railway Gauge Classification [RGC] = (Monorail [6], Narrow [2])

AND Railway Power Method [RRA] = (Electrified Track [1], Overhead Electrified [3])

AND Track or Lane Count [LTN] <= 1

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], Unknown [0])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

AND Railway Use [RRC] = (Logging [8], Long-haul [33], Other [999], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description:

Criteria:

PL-04384_1 Railway / intact / narrow / electrified / 1 track (line) Railway Gauge Classification [RGC] = Narrow [2]

Criteria:

Label String: [Name] [Track Information : Railway Gauge] "m"

Characteristics: 27, 28, 28

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04384_2 Railway / intact / monorail / electrified / 1 track (line)

Railway Gauge Classification [RGC] = Monorail [6]

Label String: [Name] [Railway Gauge Classification]

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

C & J RAILROAD

Railway / intact / broad, standard / non-electrified / >= 2 tracks (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00278 has an initial offset of 3.2mm; after that 6.4mm.

#

Symbol Graphic

Note: Component P00278 is centered perpendicular to Component L00011. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00011 Component Type: Line - Simple Color Token: Black

Description: Black 0.3mm Solid Line

Description:

Parameters:

Line Weight: 0.3mm

Component Ref #: P00278 Component Type: Point - Shape Color Token: Black

Description: Railway tick broad double

Parameters:

Reference #:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

PS-04378 Railway / intact / broad, standard / Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

non-electrified / >= 2 tracks (line)

Criteria:

AND Railway Gauge Classification [RGC] = (Broad [1], Standard [3], Unknown [0])

AND Railway Power Method [RRA] = (Non-electrified [4], Unknown [0])

AND Track or Lane Count [LTN] >= 2

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], Unknown [0])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

AND Railway Use [RRC] = (Logging [8], Long-haul [33], Other [999], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:

PL-04378_1 Railway / intact / broad / non-electrified / > 2 tracks (line) Railway Gauge Classification [RGC] = Broad [1]

AND Track or Lane Count [LTN] > 2

Label String: [Name] [Track or Lane Count] "TRACKS" [Railway Gauge] "m"

Characteristics: 27, 28, 27, 28, 28,

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04378_2 Railway / intact / broad / non-electrified / 2 tracks (line) Railway Gauge Classification [RGC] = Broad [1]

AND Track or Lane Count [LTN] = 2

Label String: [Name] [Railway Gauge] "m"

Characteristics: 27, 28, 28

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04378_3 Railway / intact / standard / non-electrified / > 2 tracks Railway Gauge Classification [RGC] = (Standard [3], Unknown [0]) (line)

AND Track or Lane Count [LTN] > 2

Label String: [Name][Track or Lane Count] "TRACKS"

Characteristics: 27, 28, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04378_4 Railway / intact / standard / non-electrified / 2 tracks (line) Railway Gauge Classification [RGC] = (Standard [3], Unknown [0])

Label String: [Name] Characteristics:

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples






Railway / intact / broad, standard / non-electrified / 1 track (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00044 has an initial offset of 3.2mm; after that 6.4mm.



Symbol Graphic

Note: Component P00044 is centered perpendicular to Component L00011. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00011 Component Type: Line - Simple Color Token: Black

Black 0.3mm Solid Line Description:

Parameters:

Line Weight: 0.3mm

P00044 Component Type: Point - Simple Color Token: Black Component Ref #:

Description: Black 1.5mm length line with a 0.15mm lineweight

Parameters:

Reference #:

Line Weight: 0.15mm Length: 1.5mm

Description:

Symbol Rules

PS-04377 Railway / intact / broad, standard / Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

non-electrified / 1 track (line)

AND Railway Gauge Classification [RGC] = (Broad [1], Standard [3], Unknown [0])

Railway Power Method [RRA] = (Non-electrified [4], Unknown [0]) AND

AND Track or Lane Count [LTN] <= 1

Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], Unknown [0]) AND

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

AND Railway Use [RRC] = (Logging [8], Long-haul [33], Other [999], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description:

PL-04377 1 Railway / intact / broad / non-electrified / 1 track (line) Railway Gauge Classification [RGC] = Broad [1]

> Label String: [Name] [Railway Gauge] "m"

Characteristics: 27, 28, 28


27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

Railway / intact / standard / non-electrified / 1 track (line) PL-04377_2 Railway Gauge Classification [RGC] = (Standard [3], Unknown [0])

> Label String: [Name] Characteristics:

> > 27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples



Railway / intact / narrow / non-electrified / >= 2 tracks (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00277 has an initial offset of 3.2mm; after that 6.4mm.

Symbol Graphic

Note: Component P00277 is perpendicular to and on alternating sides of Component L00011. No symbol is portrayed if the Vertical Relative

Location [LOC] = Below Ground Surface [40].

Component Ref #: L00011 Component Type: Line - Simple Color Token: Black

Description: Black 0.3mm Solid Line

Parameters:

Line Weight: 0.3mm

Component Ref #: P00277 Component Type: Point - Shape Color Token: Black

Description: Railway tick narrow double

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04395 Railway / intact / narrow / nonelectrified / >= 2 tracks (line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Railway Gauge Classification [RGC] = (Monorail [6], Narrow [2])

AND Railway Power Method [RRA] = (Non-electrified [4], Unknown [0])

AND Track or Lane Count [LTN] >= 2

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], Unknown [0])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

AND Railway Use [RRC] = (Logging [8], Long-haul [33], Other [999], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:

PL-04395_1 Railway / intact / narrow / non-electrified / > 2 tracks (line) Railway Gauge Classification [RGC] = Narrow [2]

AND Track or Lane Count [LTN] > 2

Label String: [Name] [Track or Lane Count] "TRACKS" [Track Information : Railway Gauge] "m"

Characteristics: 27, 28, 27, 28, 28

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04395_2 Railway / intact / narrow / non-electrified / 2 tracks (line) Railway Gauge Classification [RGC] = Narrow [2]

AND Track or Lane Count [LTN] = 2

Label String: [Name] [Track Information : Railway Gauge] "m"

Characteristics: 27, 28, 28

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04395_3 Railway / intact / monorail / non-electrified / > 2 tracks Railway Gauge Classification [RGC] = Monorail [6] (line)

AND Track or Lane Count [LTN] > 2

Label String: [Name] [Railway Gauge Classification] [Track or Lane Count] "TRACKS"

Characteristics: 27, 27, 28, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04395_4 Railway / intact / monorail / non-electrified / 2 tracks (line) Railway Gauge Classification [RGC] = Monorail [6]

AND Track or Lane Count [LTN] = 2

Label String: [Name] [Railway Gauge Classification]

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

Railway / intact / narrow / non-electrified / 1 track (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00038 has an initial offset of 3.2mm; after that 6.4mm.

Symbol Graphic

Note: Components P00038 is perpendicular to and on alternating sides of Component L00011. No symbol is portrayed if the Vertical

Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00011 Component Type: Line - Simple Color Token: Black

Description: Black 0.3mm Solid Line

Parameters:

Line Weight: 0.3mm

Component Ref #: P00038 Component Type: Point - Simple Color Token: Black

Description: Black 0.75mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm
Length: 0.75mm

Symbol Rules

Reference #: Description: Criteria:

PS-04394 Railway / intact / narrow / nonelectrified / 1 track (line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Railway Gauge Classification [RGC] = (Monorail [6], Narrow [2])

AND Railway Power Method [RRA] = (Non-electrified [4], Unknown [0])

AND Track or Lane Count [LTN] <= 1

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], Unknown [0])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

AND Railway Use [RRC] = (Logging [8], Long-haul [33], Other [999], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:

PL-04394_1 Railway / intact / narrow / non-electrified / 1 track (line) Railway Gauge Classification [RGC] = Narrow [2]

Label String: [Name] [Track Information : Railway Gauge] "m"

Characteristics: 27, 28, 28

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04394 2 Railway / intact / monorail / non-electrified / 1 track (line) Railway Gauge Classification [RGC] = Monorail [6]

Label String: [Name] [Railway Gauge Classification]

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

CJK RAILROAD

Railway / not intact / broad, standard / electrified / >= 2 tracks (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00282 is centered on the first dash then every other dash of Component L00039.

Repeating Point and Interval 2: Component P00278 is centered on the second dash then every other dash of Component L00039.

Symbol Graphic Note: Components P00282 and P00278 are centered perpendicular to Component L00039 with the 0.7mm length line of P00282 on the northernmost side. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00039 Line - Styled Component Type: Color Token: Black Description: Black 0.3mm Dashed Line (0.3mm wt, 5.9mm dash, 0.5mm gap) Parameters: Line Weight: 0.3mm Dash Length: 5.9mm Dash Spacing: 0.5mm Point - Shape Component Ref #: P00282 Component Type: Color Token: Black Description: Railway tick broad electrified double

Parameters:

Note: See Annex H for detailed drawing instructions.

Component Ref #: P00278 Component Type: Point - Shape Color Token: Black

Description: Railway tick broad double

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04391 Railway / not intact / broad, Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Under Construction [1])

standard / electrified / >= 2 tracks

(line)

AND Railway Gauge Classification [RGC] = (Broad [1], Standard [3], Unknown [0])

AND Railway Power Method [RRA] = (Electrified Track [1], Overhead Electrified [3])

AND Track or Lane Count [LTN] >= 2

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], Unknown [0])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

Railway Use [RRC] = (Logging [8], Long-haul [33], Other [999], Unknown [0]) AND

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04391_1 Railway / not intact / broad / electrified / > 2 tracks (line) Railway Gauge Classification [RGC] = Broad [1]

> AND Track or Lane Count [LTN] > 2

[Name] [Track or Lane Count] "TRACKS" [Railway Gauge] "m" "("[Condition of Facility]")" Label String:

Characteristics: 27, 28, 27, 28, 28, 27, 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case) PL-04391 2 Railway / not intact / standard / electrified / > 2 tracks Railway Gauge Classification [RGC] = (Standard [3], Unknown [0])

AND Track or Lane Count [LTN] > 2

[Name] [Track or Lane Count] "TRACKS" "("[Condition of Facility]")" Label String:

27, 28, 27, 27, 27, 27 Characteristics:

> 27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04391_3 Railway / not intact / broad / electrified / 2 tracks (line) Railway Gauge Classification [RGC] = Broad [1]

Track or Lane Count [LTN] = 2 AND

[Name] [Railway Gauge] "m" "("[Condition of Facility]")" **Label String:**

Characteristics: 27, 28, 28, 27, 27, 27

> 27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04391_4 Railway / not intact / standard / electrified / 2 tracks (line) Railway Gauge Classification [RGC] = (Standard [3], Unknown [0])

Track or Lane Count [LTN] = 2 AND


Label String: [Name] "("[Condition of Facility]")"

Characteristics: 27, 27, 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples







Railway / not intact / broad, standard / electrified / 1 track (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00280 is centered on the first dash then every other dash of Component L00039.

Repeating Point and Interval 2: Component P00044 is centered on the second dash and then every other dash of Component L00039.

Symbol Graphic

Component Ref #:

Note: Components P00280 and P00044 are centered perpendicular to Component L00039 with the 0.7mm length line of P00280 on the northernmost side. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Type: Line - Styled Color Token: L00039 Black

Description: Parameters: Black 0.3mm Dashed Line (0.3mm wt, 5.9mm dash, 0.5mm gap)

Line Weight: 0.3mm Dash Length: 5.9mm Dash Spacing: 0.5mm

Component Ref #: P00280 Component Type: Point - Shape Color Token: Black

Description: Railway tick broad electrified

Parameters:

See Annex H for detailed drawing instructions. Note:

Component Ref #: Component Type: Point - Simple Color Token: Black

Description: Black 1.5mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm Length: 1.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04390 Railway / not intact / broad,

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Under Construction [1]) standard / electrified / 1 track (line)

> AND Railway Gauge Classification [RGC] = (Broad [1], Standard [3], Unknown [0])

AND Railway Power Method [RRA] = (Electrified Track [1], Overhead Electrified [3])

AND Track or Lane Count [LTN] <= 1

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], Unknown [0])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

Railway Use [RRC] = (Logging [8], Long-haul [33], Other [999], Unknown [0]) AND

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04390 1 Railway / not intact / broad / electrified / 1 track (line) Railway Gauge Classification [RGC] = Broad [1]

> [Name] [Railway Gauge] "m" "("[Condition of Facility]")" Label String:

27, 28, 28, 27, 27, 27 Characteristics:

> 27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04390_2 Railway / not intact / standard / electrified / 1 track (line) Railway Gauge Classification [RGC] = (Standard [3], Unknown [0])


> Label String: [Name] "("[Condition of Facility]")"


Characteristics: 27, 27, 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples







Railway / not intact / narrow / electrified / >= 2 tracks (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00281 is centered on the first dash then every other dash, on the northernmost side of

Component L00039.

Component P00277 is centered on the second dash then every other dash, on the southernmost side of Repeating Point and Interval 2:

Color Token:

Black

Component L00039.

Symbol Graphic Note: Components P00281 and P00277 are perpendicular to and on alternating sides of Component L00039. No symbol is portrayed if the

Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: 100039

Line - Styled Component Type:

Black 0.3mm Dashed Line (0.3mm wt, 5.9mm dash, 0.5mm gap) Description:

Parameters:

Line Weight: 0.3mm Dash Length: 5.9mm Dash Spacing: 0.5mm

Component Ref #: P00281 Point - Shape Color Token: Black Component Type:

Description: Railway tick narrow electrified double

Parameters:

See Annex H for detailed drawing instructions. Note:

Component Ref #: Point - Shape Color Token: P00277 Black Component Type:

Description: Railway tick narrow double

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04393 Railway / not intact / narrow / Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Under Construction [1]) electrified / >= 2 tracks (line)

> AND Railway Gauge Classification [RGC] = (Monorail [6], Narrow [2])

> > Railway Power Method [RRA] = (Electrified Track [1], Overhead Electrified [3]) AND

AND Track or Lane Count [LTN] >= 2

Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], Unknown [0]) AND

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0]) Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04393_1 Railway / not intact / narrow / electrified / > 2 tracks (line) Railway Gauge Classification [RGC] = Narrow [2]

AND Track or Lane Count [LTN] > 2

Label String: [Name] [Track or Lane Count] "TRACKS" "("[Condition of Facility]")" [Track Information : Railway Gauge] "m"

Characteristics: 27, 28, 27, 27, 27, 27, 28, 28

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04393_2 Railway / not intact / narrow / electrified / 2 tracks (line) Railway Gauge Classification [RGC] = Narrow [2]

AND Track or Lane Count [LTN] = 2

Label String: [Name] "("[Condition of Facility]")" [Track Information : Railway Gauge] "m"

Characteristics: 27, 27, 27, 28, 28

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04393_3 Railway / not intact / monorail / electrified / > 2 tracks Railway Gauge Classification [RGC] = Monorail[6]

(line)

AND Track or Lane Count [LTN] > 2

Label String: [Name] [Railway Gauge Classification] [Track or Lane Count] "TRACKS" "("[Condition of Facility]")"

Characteristics: 27, 27, 28, 27, 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04393_4 Railway / not intact / monorail / electrified / 2 tracks (line) Railway Gauge Classification [RGC] = Monorail[6]

AND Track or Lane Count [LTN] = 2

Label String: [Name] [Railway Gauge Classification] "("[Condition of Facility]")"

Characteristics: 27, 27, 27, 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

(CONSTRUCTION)

VIRGINIA RAILROAD (CONSTRUCTION)

(DAMAGED)

Railway / not intact / narrow / electrified / 1 track (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00279 is centered on the first dash then every other dash, on the northernmostside of

Component L00039.

Repeating Point and Interval 2: Component P00038 is centered on the second dash then every other dash, on the southernmost side of

Component L00039.

Note: Components P00279 and P00038 are perpendicular to and on alternating sides of Component L00039. No symbol is portrayed if the

Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00039 Component Type: Line - Styled Color Token: Black

Description: Black 0.3mm Dashed Line (0.3mm wt, 5.9mm dash, 0.5mm gap)

Parameters:

Symbol Graphic

Line Weight: 0.3mm Dash Length: 5.9mm Dash Spacing: 0.5mm

Component Ref #: P00279 Component Type: Point - Shape Color Token: Black

Description: Railway tick narrow electrified

Parameters:

Note: See Annex H for detailed drawing instructions.

Component Ref #: P00038 Component Type: Point - Simple Color Token: Black

Criteria:

Description: Black 0.75mm length line with a 0.15mm lineweight

Parameters:

Reference #:

Line Weight: 0.15mm
Length: 0.75mm

Symbol Rules

PS-04392 Railway / not intact / narrow /

Description:

electrified / 1 track (line)

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Under Construction [1])

AND Railway Gauge Classification [RGC] = (Monorail [6], Narrow [2])

AND Railway Power Method [RRA] = (Electrified Track [1], Overhead Electrified [3])

AND Track or Lane Count [LTN] <= 1

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], Unknown [0])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

AND Railway Use [RRC] = (Logging [8], Long-haul [33], Other [999], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04392_1 Railway / not intact / narrow / electrified / 1 track (line) Railway Gauge Classification [RGC] = Narrow [2]

Label String: [Name] "("[Condition of Facility]")" [Track Information : Railway Gauge] "m"

Characteristics: 27, 27, 27, 27, 28, 28

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04392_2 Railway / not intact / monorail / electrified / 1 track (line) Railway Gauge Classification [RGC] = Monorail [6]

Label String: [Name] [Railway Gauge Classification] "("[Condition of Facility]")"

Characteristics: 27, 27, 27, 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

(DAMAGED) _____CNS RAILROAD (CONSTRUCTION) _____ (CONSTRUCTION)

Railway / not intact / broad, standard / non-electrified / >= 2 tracks (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00278 is centered on every dash of Component L00039.

Symbol Graphic

Note: Component P00278 is centered perpendicular to Component L00039. No symbol is portrayed if the Vertical Relative Location [LOC] =

Below Ground Surface [40].

Component Ref #: L00039 Component Type: Line - Styled Color Token: Black

Description: Black 0.3mm Dashed Line (0.3mm wt, 5.9mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.3mm Dash Length: 5.9mm Dash Spacing: 0.5mm

Component Ref #: P00278 Component Type: Point - Shape Color Token: Black

Description: Railway tick broad double

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules Reference #: Description: Criteria: PS-04387 Railway / not intact / broad, Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Under Construction [1]) standard / non-electrified / >= 2 tracks (line) AND Railway Gauge Classification [RGC] = (Broad [1], Standard [3], Unknown [0]) AND Railway Power Method [RRA] = (Non-electrified [4], Unknown [0]) AND Track or Lane Count [LTN] >= 2 AND Vertical Relative Location [LOC] = (On Surface [44], Unknown [0]) Railway in Road [RIR] = (Separated from Road [1000], Unknown [0]) AND Railway Use [RRC] = (Logging [8], Long-haul [33], Other [999], Unknown [0]) AND Label Rules Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999 Reference #: Description: Criteria: PL-04387 1 Railway / not intact / broad / non-electrified / > 2 tracks Railway Gauge Classification [RGC] = Broad [1] (line) AND Track or Lane Count [LTN] > 2 [Name] [Track or Lane Count] "TRACKS" [Railway Gauge] "m" "("[Condition of Facility]")" Label String: 27, 28, 27, 28, 28, 27, 27, 27 Characteristics: 27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case) PL-04387_2 Railway / not intact / standard / non-electrified / > 2 tracks Railway Gauge Classification [RGC] = (Standard [3], Unknown [0]) (line) AND Track or Lane Count [LTN] > 2 Label String: [Name] [Track or Lane Count] "TRACKS" "("[Condition of Facility]")" Characteristics: 27, 28, 27, 27, 27, 27 27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case) Railway Gauge Classification [RGC] = Broad [1] PL-04387_3 Railway / not intact / broad / non-electrified / 2 tracks (line) AND Track or Lane Count [LTN] = 2 Label String: [Name] [Railway Gauge] "m" "("[Condition of Facility]")" 27, 28, 28, 27, 27, 27 Characteristics: 27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case) PL-04387_4 Railway / not intact / standard / non-electrified / 2 tracks Railway Gauge Classification [RGC] = (Standard [3], Unknown [0]) (line) AND Track or Lane Count [LTN] = 2 [Name] "("[Condition of Facility]")" **Label String:** 27, 27, 27, 27 Characteristics: 27 (Black, Light Condensed, Italic, 6 pt, Upper case) Symbol Samples (CONSTRUCTION) (DAMAGED) JACKSON RAII ROAD (CONSTRUCTION)

Railway / not intact / broad, standard / non-electrified / 1 track (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00044 is centered on every dash of Component L00039.

Symbol Graphic

Note: Component P00044 is centered perpendicular to Component L00039. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

L00039 Line - Styled Component Type: Color Token: Component Ref #: Black

Description: Black 0.3mm Dashed Line (0.3mm wt, 5.9mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.3mm Dash Length: 5.9mm Dash Spacing: 0.5mm

Point - Simple Component Ref #: P00044 Component Type: Color Token: Black

Description:

Black 1.5mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm Length: 1.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04386 Railway / not intact / broad,

standard / non-electrified / 1 track

(line)

AND Railway Gauge Classification [RGC] = (Broad [1], Standard [3], Unknown [0])

AND Railway Power Method [RRA] = (Non-electrified [4], Unknown [0])

AND Track or Lane Count [LTN] <= 1

Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], Unknown [0]) AND

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Under Construction [1])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

AND Railway Use [RRC] = (Logging [8], Long-haul [33], Other [999], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04386 1 Railway / not intact / broad / non-electrified / 1 track (line) Railway Gauge Classification [RGC] = Broad [1]

> Label String: [Name] [Railway Gauge] "m" "("[Condition of Facility]")"

Characteristics: 27, 28, 28, 27, 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04386_2 Railway / not intact / standard / non-electrified / 1 track

(line)

Label String: [Name] "("[Condition of Facility]")"

27, 27, 27, 27 Characteristics:

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

(CONSTRUCTION)

S & W RAILROAD (CONSTRUCTION)

(ABANDONED)

Railway Gauge Classification [RGC] = (Standard [3], Unknown [0])

Railway / not intact / narrow / non-electrified / >= 2 tracks (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00277 is centered on every dash of Component L00039.

Symbol Graphic

Note: Component P00277 is perpendicular to and on alternating sides of Component L00039. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00039 Component Type: Line - Styled Color Token: Black

Description: Black 0.3mm Dashed Line (0.3mm wt, 5.9mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.3mm Dash Length: 5.9mm Dash Spacing: 0.5mm

Component Ref #: P00277 Component Type: Point - Shape Color Token: Black

Description: Railway tick narrow double

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol	Rules
- /	

Reference #: Description: Criteria:

PS-04389 Railway / not intact / narrow / nonelectrified / >= 2 tracks (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Under Construction [1])

AND Railway Gauge Classification [RGC] = (Monorail [6], Narrow [2])

AND Railway Power Method [RRA] = (Non-electrified [4], Unknown [0])

AND Track or Lane Count [LTN] >= 2

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], Unknown [0])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

AND Railway Use [RRC] = (Logging [8], Long-haul [33], Other [999], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04389_1 Railway / not intact / narrow / non-electrified / > 2 tracks

(line)

AND Track or Lane Count [LTN] > 2

Railway Gauge Classification [RGC] = Narrow [2]

Label String: [Name] [Track or Lane Count] "TRACKS" "("[Condition of Facility]")" [Track Information : Railway Gauge] "m"

Characteristics: 27, 28, 27, 27, 27, 27, 28, 28

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04389_2 Railway / not intact / narrow / non-electrified / 2 tracks Railway Gauge Classification [RGC] = Narrow [2]

AND Track or Lane Count [LTN] = 2

Label String: [Name] "("[Condition of Facility]")" [Track Information : Railway Gauge] "m"

Characteristics: 27, 27, 27, 28, 28

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04389_3 Railway / non-intact / monorail / non-electrified / > 2 Railway Gauge Classification [RGC] = Monorail[6] tracks (line)

AND Track or Lane Count [LTN] > 2

Label String: [Name] [Railway Gauge Classification] [Track or Lane Count] "TRACKS" "("[Condition of Facility]")"

Characteristics: 27, 27, 28, 27, 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04389_4 Railway / non-intact / monorail / non-electrified / 2 tracks Railway Gauge Classification [RGC] = Monorail[6] (line)

AND Track or Lane Count [LTN] = 2

Label String: [Name] [Railway Gauge Classification] "("[Condition of Facility]")"

Characteristics: 27, 27, 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

(CONSTRUCTION)

SALEM RAILROAD (DAMAGED)

(DAMAGED)

Railway / not intact / narrow / non-electrified / 1 track (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00038 is centered on every dash of Component L00039.

Symbol Graphic

Location [LOC] = Below Ground Surface [40].

Component Ref #: L00039 Component Type: Line - Styled Description: Black 0.3mm Dashed Line (0.3mm wt, 5.9mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.3mm Dash Length: 5.9mm Dash Spacing: 0.5mm

Component Ref #: P00038 Component Type: Point - Simple Color Token: Black

Description: Black 0.75mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm
Length: 0.75mm

Symbol Rules

Reference #: Description: Criteria:

PS-04388 Railway / not intact / narrow / nonelectrified / 1 track (line)

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Under Construction [1])

AND Railway Gauge Classification [RGC] = (Monorail [6], Narrow [2])

AND Railway Power Method [RRA] = (Non-electrified [4], Unknown [0])

AND Track or Lane Count [LTN] <= 1

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], Unknown [0])

Note: Component P00038 is perpendicular to and on alternating sides of Component L00039. No symbol is portrayed if the Vertical Relative

Color Token:

Black

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

AND Railway Use [RRC] = (Logging [8], Long-haul [33], Other [999], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04388_1 Railway / not intact / narrow / non-electrified / 1 track Railway Gauge Classification [RGC] = Narrow [2]

(line)

Label String: [Name] "("[Condition of Facility]")" [Track Information : Railway Gauge] "m"

Characteristics: 27, 27, 27, 27, 28, 28

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04388_2 Railway / not intact / monorail / non-electrified / 1 track Railway Gauge Classification [RGC] = Monorail [6]

(line)

Label String: [Name] [Railway Gauge Classification] "("[Condition of Facility]")"

Characteristics: 27, 27, 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

(CONSTRUCTION)

READING RAILROAD (CONSTRUCTION)

(ABANDONED)

Railway / intact / railway in road (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00038 has an initial offset of 3.2mm; after that 6.4mm.

Symbol Graphic

Note: The symbol is a combination of two lines and one point. Display Level from bottom to top: Component L00232, Component L00231, and Component P00038. Component P00038 is centered on and perpendicular to Component L00232. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00232 Component Type: Line - Simple Color Token: Black

Black 0.75mm Solid Line Description:

Parameters:

Line Weight: 0.75mm

Component Ref #: Component Type: Line - Simple Color Token: PaperWhite L00231

Description: PaperWhite 0.45mm Solid Line

Parameters:

Line Weight: 0.45mm

Component Ref #: P00038 Component Type: Point - Simple Color Token: Black

Black 0.75mm length line with a 0.15mm lineweight Description:

Parameters:

Line Weight: 0.15mm Length: 0.75mm

Symbol Rules Reference #: Description: Criteria:

PS-04379 Railway / intact / railway in road Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

(line)

Vertical Relative Location [LOC] = (On Surface [44], Unknown [0]) AND

AND Railway in Road [RIR] = (In Road [1001])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria: N/A

PL-04379 1 Railway / intact / railway in road (line)

> Label String: [Name] Characteristics: 27

> > 27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

B & O RAILROAD

Railway / not intact / railway in road (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00038 is centered on every dash of Component L00230.

Symbol Graphic

Note: The complex line is a combination of two lines and one point. Display Level from bottom to top: Component L00230, Component L00231, and Component P00038. Component P00038 is perpendicular to Component L00230. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00230 Component Type: Line - Styled Color Token: Black

Description: Black 0.75mm Dashed Line (0.75mm wt, 5.9mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.75mm Dash Length: 5.9mm Dash Spacing: 0.5mm

Component Ref #: L00231 Component Type: Line - Simple Color Token: PaperWhite

Description: PaperWhite 0.45mm Solid Line

Parameters:

Line Weight: 0.45mm

Component Ref #: P00038 Component Type: Point - Simple Color Token: Black

Description: Black 0.75mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm
Length: 0.75mm

Symbol Rules

Reference #: Description: Criteria:

PS-04439 Railway / not intact / railway in Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Under Construction [1])

road (line)

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], Unknown [0])

AND Railway in Road [RIR] = In Road [1001]

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04439_1 Railway / not intact / railway in road (line) N/A

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 27, 27, 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

(DAMAGED) SOUTHERN RAILROAD (CONSTRUCTION)

(CONSTRUCTION)

Railway / intact / carline (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00044 has an initial offset of 1.9mm; after that 3.8mm.

Symbol Graphic

Note: Component P00044 is centered perpendicular to Component L00008. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00008 Component Type: Line - Simple Color Token: Black

Description: Black 0.15mm Solid Line

Parameters:

Line Weight: 0.15mm

Component Ref #: P00044 Component Type: Point - Simple Color Token: Black

Description: Black 1.5mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm Length: 1.5mm

Symbol Rules

Reference #: Description: Criteria:

Railway / intact / carline (line) PS-04380 Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

> AND Vertical Relative Location [LOC] = (On Surface [44], Unknown [0]) AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

AND Railway Use [RRC] = (Automated Transit System [32], Carline [2], Funicular [15], Tramway [14],

Underground Railway [6])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria: PL-04380 1 Railway / intact / carline (line) N/A

> Label String: [Name] [Railway Use]

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples



METRO RAIL AUTOMATED TRANSIT SYSTEM

Railway / not intact / carline (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00044 is centered on every dash of Component L00198.



+++

Note: Component P00044 is centered perpendicular to Component L00198. No symbol is portrayed if the Vertical Relative Location [LOC] =

Below Ground Surface [40].

Component Ref #: L00198 Component Type: Line - Styled Color Token: Black

Black 0.15mm Dashed Line (0.15mm wt, 3.3mm dash, 0.5mm gap) Description:

Parameters:

Line Weight: Dash Length: 0.5mm 0.15mm 3.3mm Dash Spacing:

Component Ref #: P00044 Component Type: Point - Simple Color Token: Black

Description: Black 1.5mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm Length: 1.5mm

Symbol Rules

Reference #: Criteria: Description:

PS-04438 Railway / not intact / carline (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Under Construction [1])

> AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], Unknown [0])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

Criteria:

AND Railway Use [RRC] = (Automated Transit System [32], Carline [2], Funicular [15], Tramway [14],

Underground Railway [6])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999

Reference #: Description:

PL-04438_1 Railway / not intact / carline (line)

N/A

Label String: [Name] [Railway Use] "("[Condition of Facility]")"

Characteristics: 27, 27, 27, 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

(CONSTRUCTION)

DUBAI METRO ELEVATED AUTOMATED TRANSIT SYSTEM (CONSTRUCTION)

(DAMAGED)

Railway / dismantled, destroyed (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00036 Component Type: Line - Styled Color Token: Black

Description: Black 0.3mm Dashed Line (0.3mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.3mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04381 Railway / dismantled, destroyed Condition of Facility [FUN] = (Destroyed [6], Dismantled [5])

(line)

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:
PL-04381_1 Railway / dismantled, destroyed (line) N/A

Label String: [Condition of Facility] "railway"

Characteristics: 10, 28

10 (Black, Light Condensed, Italic, 6 pt, Mixed case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

Symbol Samples

Dismantled railway

Destroyed railway

Railway Sidetrack (AN050)

Generalization Rules (see Annex J): GA-9999

Railway Sidetrack / intact / broad, standard / electrified (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00280 has an initial offset of 3.2mm; after that 12.8mm.

Repeating Point and Interval 2: Component P00044 has an initial offset of 9.6mm; after that 12.8mm.

Note: Components P00280 and P00044 are centered perpendicular to Component L00008 with the 0.7mm length line of P00280 on the northernmost side. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].



Symbol Graphic

Component Ref #: L00008 Component Type: Line - Simple Color Token: Black

Description:

Parameters:

Line Weight: 0.15mm

Component Ref #: P00280 Component Type: Point - Shape Color Token: Black

Description: Railway tick broad electrified

Parameters:

Note: See Annex H for detailed drawing instructions.

Black 0.15mm Solid Line

Component Ref #: P00044 Component Type: Point - Simple Color Token: Black

Description: Black 1.5mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm
Length: 1.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04124 Railway Sidetrack / intact / broad, Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) standard / electrified (line)

AND Railway Gauge Classification [RGC] = (Broad [1], Standard [3], Unknown [0])

AND Railway Power Method [RRA] = (Electrified Track [1], Overhead Electrified [3])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

Symbol Samples



Railway Sidetrack / intact / narrow / electrified (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00279 has an initial offset of 3.2mm; after that 12.8mm on the northernmost side of

Component L00008.

Repeating Point and Interval 2: Component P00038 has an initial offset of 9.6mm; after that 12.8mm on the southernmost side of

Component L00008.

Symbol Graphic Note: Components P00279 and P00038 are perpendicular to and on alternating sides of Component L00008. No symbol is portrayed if the

Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00008 Component Type: Line - Simple Color Token: Black

Description: Black 0.15mm Solid Line

Parameters:

Line Weight: 0.15mm

Component Ref #: P00279 Component Type: Point - Shape Color Token: Black

Description: Railway tick narrow electrified

Parameters:

Note: See Annex H for detailed drawing instructions.

Component Ref #: P00038 Component Type: Point - Simple Color Token: Black

Description: Black 0.75mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm
Length: 0.75mm

Symbol Rules

Reference #: Description: Criteria:

PS-04125 Railway Sidetrack / intact / narrow Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

/ electrified (line)

AND Railway Gauge Classification [RGC] = (Monorail [6], Narrow [2])

AND Railway Power Method [RRA] = (Electrified Track [1], Overhead Electrified [3])

Symbol Samples



Railway Sidetrack / intact / broad, standard / non-electrified (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00044 has an initial offset of 3.2mm; after that 6.4mm.



Note: Component P00044 is centered perpendicular to Component L00008. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00008 Component Type: Line - Simple Color Token: Black

Description: Black 0.15mm Solid Line

Parameters:

Line Weight: 0.15mm

Component Ref #: P00044 Component Type: Point - Simple Color Token: Black

Description: Black 1.5mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm
Length: 1.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04122 Railway Sidetrack / intact / broad, Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) standard / non-electrified (line)

AND Railway Gauge Classification [RGC] = (Broad [1], Standard [3], Unknown [0])

AND Railway Power Method [RRA] = (Non-electrified [4], Unknown [0])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

Symbol Samples



Railway Sidetrack / intact / narrow / non-electrified (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00038 has an initial offset of 3.2mm; after that 6.4mm.

Symbol Graphic

Note: Component P00038 is perpendicular to and on alternating sides of Component L00008. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00008 Component Type: Line - Simple Color Token: Black

Description: Black 0.15mm Solid Line

Parameters:

Line Weight: 0.15mm

Component Ref #: P00038 Component Type: Point - Simple Color Token: Black

Description: Black 0.75mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm
Length: 0.75mm

Symbol Rules

Reference #: Description: Criteria:

PS-04123 Railway Sidetrack / intact / narrow

/ non-electrified (line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Railway Gauge Classification [RGC] = (Monorail [6], Narrow [2])

AND Railway Power Method [RRA] = (Non-electrified [4], Unknown [0])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

Symbol Samples

Railway Sidetrack / not intact / broad, standard / electrified (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00280 is centered on the first dash then every other dash of Component L00205.

Repeating Point and Interval 2: Component P00044 is centered on the second dash then every other dash of Component L00205.

Symbol Graphic

Note: Components P00280 and P00044 are centered perpendicular to Component L00205 with the 0.7mm length line of P00280 on the northernmost side. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Color Token:

Black

Component Ref #: L00205 Component Type: Line - Styled

Description: Black 0.15mm Dashed Line (0.15mm wt, 5.4mm dash, 1.0mm gap)

Parameters:

Line Weight: 0.15mm Dash Length: 5.4mm Dash Spacing: 1.0mm

Component Ref #: P00280 Component Type: Point - Shape Color Token: Black

Description: Railway tick broad electrified

Parameters:

Note: See Annex H for detailed drawing instructions.

Component Ref #: P00044 Component Type: Point - Simple Color Token: Black

Description: Black 1.5mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm
Length: 1.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04442 Railway Sidetrack / not intact / Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Under Construction [1])

broad, standard / electrified (line)

AND Railway Gauge Classification [RGC] = (Broad [1], Standard [3], Unknown [0])

AND Railway Power Method [RRA] = (Electrified Track [1], Overhead Electrified [3])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

Symbol Samples

Railway Sidetrack / not intact / narrow / electrified (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00279 is centered on the first dash then every other dash, on the northernmost side of

Component L00205.

Repeating Point and Interval 2: Component P00038 is centered on the second dash then every other dash, on the southernmost side of

Component L00205.

Symbol Graphic Note: Components P00279 and P00038 are perpendicular to and on alternating sides of Component L00205. No symbol is portrayed if the

Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00205 Component Type: Line - Styled Color Token: Black

Description: Black 0.15mm Dashed Line (0.15mm wt, 5.4mm dash, 1.0mm gap)

Parameters:

Line Weight: 0.15mm Dash Length: 5.4mm Dash Spacing: 1.0mm

Component Ref #: P00279 Component Type: Point - Shape Color Token: Black

Description: Railway tick narrow electrified

narrow / electrified (line)

Parameters:

Note: See Annex H for detailed drawing instructions.

Component Ref #: P00038 Component Type: Point - Simple Color Token: Black

Description: Black 0.75mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm
Length: 0.75mm

Symbol Rules

Reference #: Description: Criteria:

PS-04443 Railway Sidetrack / not intact / Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Under Construction [1])

AND Railway Gauge Classification [RGC] = (Monorail [6], Narrow [2])

AND Railway Power Method [RRA] = (Electrified Track [1], Overhead Electrified [3])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

Symbol Samples

Railway Sidetrack / not intact / broad, standard / non-electrified (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00044 is centered on every dash of Component L00205.

Symbol Graphic

Note: Component P00044 is centered perpendicular to Component L00205. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00205 Component Type: Line - Styled Color Token: Black

Description: Black 0.15mm Dashed Line (0.15mm wt, 5.4mm dash, 1.0mm gap)

Parameters:

Line Weight: 0.15mm Dash Length: 5.4mm Dash Spacing: 1.0mm

Component Ref #: P00044 Component Type: Point - Simple Color Token: Black

Description: Black 1.5mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm
Length: 1.5mm

Symbol Rules

Reference #: Description:
PS-04440 Railway Sidetrack / not intact /

Railway Sidetrack / not intact / broad, standard / non-electrified

(line)

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Under Construction [1])

AND Railway Gauge Classification [RGC] = (Broad [1], Standard [3], Unknown [0])

AND Railway Power Method [RRA] = (Non-electrified [4], Unknown [0])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

Symbol Samples

Railway Sidetrack / not intact / narrow / non-electrified (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00038 is centered on every dash of Component L00205.

Symbol Graphic

Note: Component P00038 is perpendicular to and on alternating sides of Component L00205. No symbol is portrayed if the Vertical Relative

Location [LOC] = Below Ground Surface [40].

Component Ref #: L00205 Component Type: Line - Styled Color Token: Black

Description: Black 0.15mm Dashed Line (0.15mm wt, 5.4mm dash, 1.0mm gap)

Parameters:

Line Weight: 0.15mm Dash Length: 5.4mm Dash Spacing: 1.0mm

Component Ref #: P00038 Component Type: Point - Simple Color Token: Black

Description: Black 0.75mm length line with a 0.15mm lineweight

Parameters:

Line Weight: 0.15mm
Length: 0.75mm

Symbol Rules

Reference #: Description: Criteria:

PS-04441 Railway Sidetrack / not intact / Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Under Construction [1])

narrow / non-electrified (line)

AND Railway Gauge Classification [RGC] = (Monorail [6], Narrow [2])

AND Railway Power Method [RRA] = (Non-electrified [4], Unknown [0])

AND Railway in Road [RIR] = (Separated from Road [1000], Unknown [0])

Symbol Samples

Symbol Type: Complex

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Repeating Point and Interval: Component P00038 has an initial offset of 3.2mm; after that 6.4mm.

Symbol Graphic

Note: The symbol is a combination of two lines and one point. Display Level from bottom to top: Component L00232, Component L00231, and Component P00038. Component P00038 is centered on and perpendicular to Component L00232. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00232 Line - Simple Color Token: Black Component Type:

Black 0.75mm Solid Line Description:

Parameters:

Line Weight: 0.75mm

Component Ref #: 100231 Component Type: Line - Simple Color Token: PaperWhite

PaperWhite 0.45mm Solid Line Description:

Parameters:

Line Weight: 0.45mm

Point - Simple Component Ref #: P00038 Component Type: Color Token: Black

Black 0.75mm length line with a 0.15mm lineweight Description:

Parameters:

Line Weight: 0.15mm Length: 0.75mm

Symbol Rules

Reference #: Description: Criteria:

PS-04953 Railway Sidetrack / intact / railway

in road (line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Railway in Road [RIR] = In Road [1001]

Symbol Samples

Railway Sidetrack / not intact / railway in road (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00038 is centered on every dash of Component L00230.

Symbol Graphic

Note: The symbol is a combination of two lines and one point. Display Level from bottom to top: Component L00230, Component L00231, and Component P00038. Component P00038 is perpendicular to Component L00230. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Line - Styled Component Ref #: L00230 Color Token: Component Type: Black Black 0.75mm Dashed Line (0.75mm wt, 5.9mm dash, 0.5mm gap) Description: Parameters: Line Weight: 0.75mm Dash Length: 5.9mm Dash Spacing: 0.5mm Line - Simple Component Ref #: L00231 Component Type: Color Token: **PaperWhite**

PaperWhite 0.45mm Solid Line Description:

Parameters:

Line Weight: 0.45mm

Component Ref #: Component Type: Point - Simple Color Token: Black

Black 0.75mm length line with a 0.15mm lineweight Description:

Parameters:

Line Weight: 0.15mm Length: 0.75mm

Symbol Rules

Reference #: Description: Criteria:

PS-04954 Railway Sidetrack / not intact / Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Under Construction [1]) railway in road (line)

AND Railway in Road [RIR] = In Road [1001]

Symbol Samples

Railway Sidetrack / dismantled, destroyed (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00447 Component Type: Line - Styled Color Token: Black

Description: Black 0.15mm Dashed Line (0.15mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.15mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04919 Railway Sidetrack / dismantled, Condition of Facility [FUN] = (Destroyed [6], Dismantled [5])

destroyed (line)

Symbol Samples

Railway Turntable (AN075)

Railway Turntable / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00238 Component Type: Point - Shape Color Token: Black

Description: Railway turntable

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04127 Railway Turntable / all (point)

ΑII

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9999

Reference #: Description:

Criteria:

PL-04127_1 Railway Turntable / not intact (point)

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])


Label String: "("[Condition of Facility]")"

Characteristics: 28, 28, 28

28 (Black, Light Condensed, Italic, 6 pt, Lower case)

Symbol Samples

0



⟨damaged⟩

Railway Yard (AN060)

Generalization Rules (see Annex J): GA-9999

Railway Yard / all (area)

Symbol Placement Instructions: Text label only. No graphic parameters

Symbol Type: Simple

[NAM]

Symbol Graphic

Symbol Rules

Reference #: Description: Criteria:

PS-04126 Railway Yard / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9999

Reference #: Description: Criteria

PL-04126_1 Railway Yard / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Name]
Characteristics: 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04126_2 Railway Yard / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 27, 28, 28, 28

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

Symbol Samples

POTOMAC RAILWAY YARD

Shown with Railway and Sidetrack symbols:

POTOMAC RAILWAY YARD

Rapids (BH120)

Generalization Rules (see Annex J): GA-9999, GC-9989, GC-9991

Rapids / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #: A00065 Component Type: Area - Pattern Color Token: Cyan

Description: Cyan Rapids Pattern

Parameters:

Area Pattern: AP-105, see Annex I

Symbol Rules

Reference #: Description: Criteria:
PS-04197 Rapids / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-4813, LP-9999

Reference #: Description: Criteria:
PL-04197_1 Rapids / all (area) N/A

Label String: [Name] "Rapids"

Characteristics: 16, 16

16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples







Rapids / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound

Symbol Graphic

Note: The symbol is a combination of two lines. Display Level from bottom to top: Component L00389, Component L00186.

Component Ref #: L00389 Component Type: Line - Simple Color Token: Cyan

Description:

Cyan 0.9mm Solid Line

Parameters:

Line Weight: 0.9mm

Component Ref #: L00186 Component Type: Line - Simple Color Token: PaperWhite

Description: PaperWhite 0.5mm Solid Line

Parameters:

Line Weight: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04198 Rapids / all (line) All

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:
PL-04198_1 Rapids / all (line) N/A

Label String: [Name] "Rapids"

Characteristics: 16, 16

16 (Cyan, Condensed, Italic, 6 pt, Mixed case) Symbol Samples = Rapids = Rock Creek Rapids Shown with River: Rapids / all (point)

Symbol Placement Instructions: Origin: Center of symbol Symbol Type: Simple Note: The symbol is aligned perpendicular to the associated drainage feature. **Symbol Graphic** P00195 Point - Shape Component Ref #: Component Type: Color Token: Cyan Description: Rapids Parameters: Note: See Annex H for detailed drawing instructions. Symbol Rules Criteria: Reference #: Description: PS-04199 Rapids / all (point) ΑII Label Rules LP-3505, LP-4813, LP-9999 Label Placement Rules (see Annex J): Reference #: Description: Criteria: PL-04199_1 Rapids / all (point) N/A Label String: [Name] "Rapids" Characteristics: 16, 16 16 (Cyan, Condensed, Italic, 6 pt, Mixed case) Symbol Samples Shown with River: = Rapids = Hakatai Rapids Rapids

Recreational Pier (AK190)

Generalization Rules (see Annex J): GA-9999

Recreational Pier / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Note: This symbol is portrayed in conjunction with the Tidal Water symbol and shall mask out the Tidal Water symbol.

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black
Description: Black 0.1mm Solid Line

Description: Parameters:

Line Weight: 0.1mm

Symbol Rules Reference #: Description: Criteria: PS-04063 Recreational Pier / all (area) ΑII Label Rules Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999 Reference #: Description: Criteria: PL-04063_1 Recreational Pier / all (area) N/A Label String: [Name] "Pier" Characteristics: 1, 1 1 (Black, Condensed, 6 pt, Mixed case) Symbol Samples Shown with Land Water Boundary and Tidal Water: Pier Navy Pier Recreational Pier / all (line) Symbol Placement Instructions: The symbol is applied to the geometry of the feature. Symbol Type: Simple **Symbol Graphic** Line - Simple L00009 Component Ref #: Component Type: Color Token: Black Black 0.2mm Solid Line Description: Parameters: Line Weight: 0.2mm Symbol Rules Reference #: Description: Criteria: PS-04064 Recreational Pier / all (line) ΑII Label Rules LP-3505, LP-4813, LP-9999 Label Placement Rules (see Annex J): Reference #: Description: Criteria: PL-04064_1 Recreational Pier / all (line) N/A Label String: [Name] "Pier" Characteristics: 1 (Black, Condensed, 6 pt, Mixed case) Symbol Samples Shown with Land Water Boundary and Tidal Water: Pier Pacifica Pier

Recycling Site (AB010)

Generalization Rules (see Annex J): GA-9999

Recycling Site / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:
PS-04279 Recycling Site / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-4813, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04279_1 Recycling Site / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Name] "Recycling site"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04279_2 Recycling Site / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: [Name] "Recycling site" "("[Condition of Facility]")"

Characteristics: 1, 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

[Recycling site

Reef (BD120)

Generalization Rules (see Annex J): GA-9999, GC-9997, GC-9999

Reef / exposed (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component P00207 is applied to the perimeter with a spacing of 0.75mm between origins, and the area is filled with Component A00048. The vertical axis of Component P00207 is perpendicular to the surface delineation and the open end of the symbol faces towards the inside of the Reef area. This symbol is portrayed in conjunction with the Tidal Water symbol and should NOT mask out the Tidal Water symbol. No symbol is portrayed if the Water Level Effect (WLE) = Always Submerged [3].

Component Ref #: A00048 Component Type: Area - Fill Color Token: Black-12

Description: Black-12 area fill

<u>Parameters:</u>

Screen Angle: 15 degrees

Screen Percent: 12%

Component Ref #: P00207 Component Type: Point - Shape Color Token: Black-54

Description: Reef arc

Parameters:

Note: See Annex H for detailed drawing instructions.

Reference #: Description: Criteria:

PS-04663 Reef / exposed (area) Water Level Effect [WLE] = (Always Dry [2], Covers and Uncovers [4], Floating [8], Not Applicable [998],

Other [999], Partly Submerged [1], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:

PL-04663_1 Reef / exposed (area) N/A

Label String: [Name]
Characteristics: 12

12 (Black, Condensed, Italic 6-16 pt, Upper case)

Symbol Samples



Reef / exposed (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Note: Component P00207 is applied with a spacing of 0.75mm between the origins. The vertical axis of Component P00207 is perpendicular to the curve delineation with the open end of the symbol facing landward. No symbol is portrayed if the Water Level Effect (WLE) = Always Submerged [3].

Component Ref #: P00207 Component Type: Point - Shape Color Token: Black-54

Description: Reef arc

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04662 Reef / exposed (line) Water Level Effect [WLE] = (Always Dry [2], Covers and Uncovers [4], Floating [8], Not Applicable [998],

Other [999], Partly Submerged [1], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-0051, LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04662_1 Reef / exposed (line) N/A

Label String: [Name]
Characteristics: 6

6 (Black, Condensed, Italic 6-9 pt, Mixed case)

Symbol Samples

Shown with tidal water:

Lighthouse Reef

Reef / exposed (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Note: No symbol is portrayed if the Water Level Effect (WLE) = Always Submerged [3].

Component Ref #: Point - Shape Color Token: P00095 Component Type: Black

Description: Hazardous rock/reef

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

Reef / exposed (point) PS-04661 Water Level Effect [WLE] = (Always Dry [2], Covers and Uncovers [4], Floating [8], Not Applicable [998],

Other [999], Partly Submerged [1], Unknown [0])

Symbol Samples

Reservoir (BH130)

Generalization Rules (see Annex J): GA-9999

Reservoir / intact / perennial (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: Component L00007 is applied to the perimeter and is filled with Component A00007.

Component Ref #: A00007 Component Type: Area - Fill Color Token: Cyan-31

Description:

Cyan-31 area fill

Parameters:

Screen Angle: 45 degrees Screen Percent: 31%

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black

Black 0.1mm Solid Line Description:

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

Reservoir / intact / perennial (area) PS-04785 Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

> AND Hydrologic Persistence [HYP] = (Perennial [1], Unknown [0])

> > Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Criteria: Reference #: Description: PL-04785_1 Reservoir / intact / perennial (area) N/A

> Label String: [Name] Characteristics: 5

> > 5 (Black, Condensed, Italic, 6 pt, Mixed case)


Symbol Samples

Taum Sauk Reservoir

Reservoir / intact / intermittent, dry (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00007 is applied to the perimeter and is filled with Component A00020.

Component Ref #: A00020 Component Type: Area - Pattern Color Token: Cyan

Description: Cyan Dry Drainage Fill

Parameters:

Area Pattern: AP-95, see Annex I

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black

Description: Black 0.1mm Solid Line

Parameters:

Reference #:

Line Weight: 0.1mm

Symbol Rules

PS-04786 Reservoir / intact / intermittent, dry Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Criteria:

(area)

Description:

AND Hydrologic Persistence [HYP] = (Dry [4], Intermittent [2])

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:

PL-04786_1 Reservoir / intact / intermittent, dry (area) N/A

Label String: [Name]
Characteristics: 5

5 (Black, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Koje-ji Reservoir

Reservoir / not intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00029 is applied to the perimeter and is filled with Component A00020.

Component Ref #: A00020 Component Type: Area - Pattern Color Token: Cyan

Description:
Parameters:

Area Pattern: AP-95, see Annex I

Cyan Dry Drainage Fill

Component Ref #: L00029 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed Line (0.1mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04787 Reservoir / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04787_1 Reservoir / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 5, 35, 35, 35

5 (Black, Condensed, Italic, 6 pt, Mixed case) 35 (Black, Condensed, Italic, 6 pt, Lower case)

Symbol Samples

Rueter-Hess Reservoir (construction)

Rice Field (BH135)

Generalization Rules (see Annex J): GA-9999

Rice Field / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: A00019 Component Type: Area - Pattern Color Token: Cyan

Description: Cyan Rice Fill

<u>Parameters:</u>

Area Pattern: AP-4, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04200 Rice Field / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-3506

Reference #: Description: Criteria:

PL-04200_1 Rice Field / all (area) Farming Pattern [FFP] = Terraced [3]

Label String: "Terraces"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples





Rig (AA040)

Rig / non-obstruction (point)

Symbol Placement Instructions: Origin: Center of dot

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00162 Component Type: Point - Shape Color Token: Black

Description: Rig inland

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04272 Rig / non-obstruction (point) Height Above Surface Level [HGT] < 46

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04272_1 Rig / non-obstruction (point) N/A

Label String: [Product]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Oil 1

River (BH140)

Generalization Rules (see Annex J): GA-9999

River / perennial (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: Component L00015 is applied to the perimeter and is filled with Component A00007.

Component Ref #: A00007 Component Type: Area - Fill Color Token: Cyan-31 Description: Cyan-31 area fill

Parameters:

Screen Angle: 45 degrees
Screen Percent: 31%

Component Ref #: L00015 Component Type: Line - Simple Color Token: Cyan

Description: Cyan 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Symbol Rules

Reference #: Description: Criteria:

PS-04202 River / perennial (area) Hydrologic Persistence [HYP] = (Perennial [1], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-0062, LP-9997, LP-9999

Reference #: Description: Criteria:
PL-04202_1 River / perennial (area) N/A

Label String: [Name]
Characteristics: 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

Symbol Samples

COLORADO RIVER

River / intermittent, dry (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic Note: Component L00041 is applied to the perimeter and is filled with Component A00020.

Component Ref #: A00020 Component Type: Area - Pattern Color Token: Cyan

Description: Cyan Dry Drainage Fill

Parameters:

Area Pattern: AP-95, see Annex I

Component Ref #: L00041 Component Type: Line - Styled Color Token: Cyan

Description: Cyan 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria

PS-04203 River / intermittent, dry (area) Hydrologic Persistence [HYP] = (Dry [4], Intermittent [2])

Label Rules

Label Placement Rules (see Annex J): LP-0062, LP-9997, LP-9999

Reference #: Description: Criteria:

PL-04203_1 River / intermittent, dry (area) N/A

Label String: [Name]
Characteristics: 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

Symbol Samples

River / perennial (line)

WHITE RIVER

	Symbol Type:	Simple					
Symbol Graphic							
	00015 n 0.2mm Solid Line	Component Ty	pe: Line - Simple	Color Token:	Cyan		
Line Weight: 0.2	mm						
2.5			Symbol Rul	es —————			
Reference #: Description PS-04204 River / pere			Criteria: Hydrologic Persistence [HY	Dl – (Derennial [1]	nown [0])		
, реге			Label Rules	r j = (i ereililai [1], Olik	alowii [0])		
Label Placement Rules (see	e Annex J): LP-00)51, LP-3630, LP-99					
Reference #: Descriptio	n:		Cr	iteria:			
PL-04204_1 River / pe	rennial (line)		N,	N/A			
	bel String: [Name	e]					
Cnar	acteristics: 58 58 (Cy	an, Condensed, Ital	lic, 7-9 pt, Mixed case)				
			Symbol Samp	les			
			, ,				
		_	Eagle River				
iver / intermittent	dry (line)						
ver / intermittent,	-	ont Instructions:	The symbol is applied to t	he geometry of the feet	turo		
iver / intermittent,	Symbol Placem	ent Instructions:	The symbol is applied to t	he geometry of the feat	ture.		
iver / intermittent,	-		The symbol is applied to t	he geometry of the feat	ture.		
iver / intermittent,	Symbol Placem		The symbol is applied to t	he geometry of the feat	ture.		
iver / intermittent,	Symbol Placem		The symbol is applied to t	he geometry of the feat	ture.		
	Symbol Placem		The symbol is applied to t	he geometry of the feat	ture.		
Symbol Graphic	Symbol Placem	Simple			ture.		
Symbol Graphic Component Ref #: L	Symbol Placem Symbol Type: 9	Simple Component Ty	pe: Line - Styled	he geometry of the feat	ture.		
Symbol Graphic Component Ref #: L	Symbol Placem Symbol Type: 9	Simple Component Ty					
Symbol Graphic Component Ref #: L Description: Cya Parameters:	Symbol Placem Symbol Type: 9	Simple Component Ty	pe: Line - Styled				
Symbol Graphic Component Ref #: L Description: Cya Parameters:	Symbol Placem Symbol Type: 9	Component Ty ne (0.2mm wt, 2.0m	rpe: Line - Styled nm dash, 0.5mm gap)	Color Token: Dash Spacing:	Cyan		
Symbol Graphic Component Ref #: L Description: Cya Parameters: Line Weight: 0.2 Reference #: Description	Symbol Placem Symbol Type: 9	Component Tyne (0.2mm wt, 2.0m Dash Length:	rpe: Line - Styled nm dash, 0.5mm gap) 2.0mm	Color Token: Dash Spacing:	Cyan		
Symbol Graphic Component Ref #: L Description: Cya Parameters: Line Weight: 0.2 Reference #: Description	Symbol Placem Symbol Type: 9	Component Ty ne (0.2mm wt, 2.0m Dash Length:	pe: Line - Styled nm dash, 0.5mm gap) 2.0mm Symbol Rul	Color Token: Dash Spacing:	Cyan 0.5mm		
Symbol Graphic Component Ref #: L Description: Cya Parameters: Line Weight: 0.2 Reference #: Description PS-04205 River / inter	Symbol Placem Symbol Type: 9 00041 n 0.2mm Dashed Lir mm : mittent, dry (line)	Component Tyne (0.2mm wt, 2.0m	pe: Line - Styled nm dash, 0.5mm gap) 2.0mm Symbol Rul Criteria: Hydrologic Persistence [HY	Color Token: Dash Spacing:	Cyan 0.5mm		
Symbol Graphic Component Ref #: L Description: Cya Parameters: Line Weight: 0.2 Reference #: Description PS-04205 River / inter Label Placement Rules (see	Symbol Placem Symbol Type: 9 00041 n 0.2mm Dashed Lir mm cmittent, dry (line)	Component Ty ne (0.2mm wt, 2.0m Dash Length:	ppe: Line - Styled nm dash, 0.5mm gap) 2.0mm Symbol Rul Criteria: Hydrologic Persistence [HY	Color Token: Dash Spacing: es P] = (Dry [4], Intermitte	Cyan 0.5mm		
Symbol Graphic Component Ref #: L Description: Cya Parameters: Line Weight: 0.2 Reference #: Description PS-04205 River / inter Label Placement Rules (see Reference #: Description	Symbol Placem Symbol Type: 9 00041 n 0.2mm Dashed Lir mm : mittent, dry (line) e Annex J): LP-00 n:	Component Tyne (0.2mm wt, 2.0m Dash Length:	pe: Line - Styled nm dash, 0.5mm gap) 2.0mm Symbol Rul Criteria: Hydrologic Persistence [HY Label Rules 199	Color Token: Dash Spacing: es P] = (Dry [4], Intermitte iteria:	Cyan 0.5mm		
Symbol Graphic Component Ref #: L Description: Cya Parameters: Line Weight: 0.2 Reference #: Description PS-04205 River / inter Label Placement Rules (see Reference #: Description	Symbol Placem Symbol Type: 9 00041 n 0.2mm Dashed Lin mm cmittent, dry (line) e Annex J): LP-00 n: eermittent, dry (line	Component Tyne (0.2mm wt, 2.0m Dash Length:	ppe: Line - Styled nm dash, 0.5mm gap) 2.0mm Symbol Rul Criteria: Hydrologic Persistence [HY	Color Token: Dash Spacing: es P] = (Dry [4], Intermitte iteria:	Cyan 0.5mm	A - 2	

Label String: [Name]
Characteristics: 58

58 (Cyan, Condensed, Italic, 7-9 pt, Mixed case)

Symbol Samples

Quinn River

River Flow Arrow (No Code)

River Flow Arrow (point)

Symbol Placement Instructions: The symbol is manually placed inside surface rivers or parallel to curve rivers. Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Note: The arrowhead end of the symbol points in the direction of flow (towards the lower elevation).

Component Ref #: P00200 Component Type: Point - Shape Color Token: Cyan

Description: River flow arrow

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04649 River Flow Arrow (point) Portray when the direction of flow is not apparent.

Symbol Samples

Shown with River:

Shown with River:

Road (AP030)

Generalization Rules (see Annex J): GA-9999

Road / intact / divided / very wide median (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound

Symbol Graphic

Note: The symbol is a combination of two lines. Display Level from bottom to top: Component L00153, Component L00105. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00153 Component Type: Line - Simple Color Token: Black

Description: Black 0.6mm Solid Line

Parameters:

Line Weight: 0.6mm

Component Ref #: L00105 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.3mm Solid Line

Parameters:

Line Weight: 0.3mm

Symbol Rules

Reference #: Description: Criteria

PS-04877 Road / intact / divided / very wide

median (line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Divided [SEP] = Present [1001]

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17],

Unknown [0])

AND Text [TXT] = Component of Dual Carriageway; traffic flowing in one direction

AND Distance between the two components of the dual carriageway is >= 75m

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9993, LP-9999

Reference #: Description: Criteria:

PL-04877_1 Road / intact / divided / very wide median / > 4 lanes (line) Track or Lane Count [LTN] > 4 (total of the two corresponding travelled way

delineations)

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name] [Track or Lane Count] "LANES"

Characteristics: 27, 28, 27

closed in winter (line)

(line)

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04877_2 Road / intact / divided / very wide median / > 4 lanes / Track or Lane Count [LTN] > 4 (total of the two corresponding travelled way

delineations)

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] [Track or Lane Count] "LANES CLOSED IN WINTER"

Characteristics: 27, 28, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04877_3 Road / intact / divided / very wide median / <= 4 lanes Track or Lane Count [LTN] <= 4 (total of the two corresponding travelled way

delineations)

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name]
Characteristics: 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04877_4 Road / intact / divided / very wide median / <= 4 lanes / Track or Lane Count [LTN] <= 4 (total of the two corresponding travelled way

delineations)

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] "CLOSED IN WINTER"

Characteristics: 27, 27

closed in winter (line)

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

Shown as both elements of divided Road: EIXO MONUMENTAL 12 LANES

Road / intact / divided / wide median (curve)

Symbol Placement Instructions: The symbol is applied to a line equidistant between the two extracted traveled ways of the divided road.

Symbol Type: Compound

Symbol Graphic

Note: The symbol is a combination of four lines. Display Level from bottom to top: Component L00219, Component L00220, Component L00221, Component L00222. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Color Token:

Color Token:

Line - Simple L00219 Color Token: Black Component Ref #: Component Type: Black 1.45mm Solid Line

Component Type:

Component Type:

Description:

Parameters:

Line Weight:

1.45mm

Component Ref #: L00220

Description:

Dk-Brown1815 1.15mm Solid Line

Parameters:

Line Weight: 1.15mm

Component Ref #: L00221

Black 0.55mm Solid Line Description:

Parameters:

Line Weight: 0.55mm

Component Ref #: L00222 Component Type: Line - Simple Color Token: **PaperWhite**

PaperWhite 0.25mm Solid Line Description:

Parameters:

Line Weight: 0.25mm

Symbol Rules

Line - Simple

Line - Simple

Reference #: Criteria: Description:

PS-04570 Road / intact / divided / wide

median (curve)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Divided [SEP] = Present [1001]

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17],

Unknown [0])

AND Text [TXT] = Component of Dual Carriageway; traffic flowing in one direction

Distance between the two components of the dual carriageway is < 75m and >= 50m AND

Label Placement Rules (see Annex J): LP-3630, LP-9993, LP-9999

Criteria: Reference #: Description:

PL-04570 1

Road / intact / divided / wide median / > 4 lanes (line)

(curve)

Track or Lane Count [LTN] > 4 (total of the two corresponding travelled way

Dk-Brown1815

Black

delineations)

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name] [Track or Lane Count] "LANES"

Characteristics: 27, 28, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04570 2 Road / intact / divided / wide median / > 4 lanes / closed in

winter (curve)

Track or Lane Count [LTN] > 4 (total of the two corresponding travelled way

delineations)

Road Weather Restriction [WTC] = Closed in Winter [5] AND

[Name] [Track or Lane Count] "LANES CLOSED IN WINTER" Label String:

Characteristics: 27, 28, 27

> 27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

Road / intact / divided / wide median / <= 4 lanes (curve) PL-04570 3

Track or Lane Count [LTN] <= 4 (total of the two corresponding travelled way

delineations)

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name] Characteristics:

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04570_4 Road / intact / divided / wide median / <= 4 lanes / closed

in winter (curve)

Track or Lane Count [LTN] <= 4 (total of the two corresponding travelled way

delineations)

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] "CLOSED IN WINTER"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Component Type:

Symbol Samples

6 LANES

MARTIN LUTHER KING JR. 6 LANES

Road / intact / divided / narrow median (line)

Symbol Placement Instructions: The symbol is applied to a line equidistant between the two extracted traveled ways of the divided road.

Symbol Type: Compound



Symbol Graphic

Note: The symbol is a combination of three lines. Display Level from bottom to top: Component L00430, Component L00431, Component

Color Token:

Color Token:

Color Token:

Black

Black

Dk-Brown1815

L00007. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Line - Simple

Line - Simple

Component Ref #: Description:

L00430

Black 1.1mm Solid Line

Parameters:

Line Weight: 1.1mm

Component Ref #: L00431

Component Type: Dk-Brown1815 0.8mm Solid Line

Description:

Parameters:

Line Weight: 0.8mm

Line - Simple Component Ref #: L00007 Component Type:

Description: Black 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

Road / intact / divided / narrow PS-04369

median (line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Divided [SEP] = Present [1001]

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17],

Unknown [0])

AND Text [TXT] = Component of Dual Carriageway; traffic flowing in one direction Distance between the two components of the dual carriageway is < 50m AND

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9993, LP-9999

Reference #: Description: Road / intact / divided / narrow median / > 4 lanes / (curve) PL-04369_1

Criteria:

Track or Lane Count [LTN] > 4 (total of the two corresponding travelled way

delineations)

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name] [Track or Lane Count] "LANES"

Characteristics: 27, 28, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04369_2 Road / intact / divided / narrow median / > 4 lanes / closed

in winter (line)

Track or Lane Count [LTN] > 4 (total of the two corresponding travelled way

delineations)

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] [Track or Lane Count] "LANES CLOSED IN WINTER"

Characteristics: 27, 28, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04369_3 Road / intact / divided / narrow median / <= 4 lanes (line) Track or Lane Count [LTN] <= 4 (total of the two corresponding travelled way

delineations)

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name]
Characteristics: 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04369_4 Road / intact / divided / narrow median / <= 4 lanes / Track or Lane

closed in winter (line)

Track or Lane Count [LTN] <= 4 (total of the two corresponding travelled way

delineations)

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] "CLOSED IN WINTER"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

6 LANES WASHINGTON 6 LANES

Road / intact / all weather / hard surface / no median / >= 4 lanes / primary (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound

Symbol Graphic

Note: The symbol is a combination of two lines. Display Level from bottom to top: Component L00433, Component L00159. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00433 Component Type: Line - Simple Color Token: Black

Description: Black 0.9mm Solid Line

Parameters:

Line Weight: 0.9mm

Component Ref #: L00159 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.6mm Solid Line

Parameters:

Line Weight: 0.6mm

Symbol Rules

Reference #: Description: Criteria:

PS-04368 Road / intact / all weather / hard Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

surface / no median / >= 4 lanes /

primary (line)

AND Road Weather Restriction [WTC] = (All-weather [1], Closed in Winter [5])

AND Load-bearing Surface Type [RST] = Hard/Paved [1]

AND Divided [SEP] = (False [1000], Unknown [0])

AND Track or Lane Count [LTN] >= 4

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17],

Unknown [0])

AND Thoroughfare Class [HCT] = (National Motorway [3], Primary Route [1], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

lanes / primary (line)

Reference #: Description: Criteria:

PL-04368_1 Road / intact / all weather / hard surface / no median / > 4

Track or Lane Count [LTN] > 4

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name] [Track or Lane Count] "LANES"

Characteristics: 27, 28, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04368_2 Road / intact / all weather / hard surface / no median / > 4 Track or Lane Count [LTN] > 4

lanes / primary / closed in winter (line)

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] [Track or Lane Count] "LANES CLOSED IN WINTER"

Characteristics: 27, 28, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04368_3 Road / intact / all weather / hard surface / no median / 4 Track or Lane Count [LTN] = 4

lanes / primary (line)

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name]
Characteristics: 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04368_4 Road / intact / all weather / hard surface / no median / 4 Track or Lane Count [LTN] = 4

lanes / primary / closed in winter (line)

Track of Earle Count [E114]

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] "CLOSED IN WINTER"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

6 LANES FRANKLIN 6 LANES

Road / intact / all weather / hard surface / no median / >= 4 lanes / secondary (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound



Symbol Graphic

Note: The symbol is a combination of two lines. Display Level from bottom to top: Component L00433, Component L00374. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00433 Component Type: Line - Simple Color Token: Black

Description: Black 0.9mm Solid Line

Parameters:

Line Weight: 0.9mm

Component Ref #: L00374 Component Type: Line - Simple Color Token: Dk-Brown1815-54

Description: Dk-Brown1815-54 0.6mm Screened Line

Parameters:

Line Weight: 0.6mm

Screen Angle: 45 degrees

Screen Percent: 54%

Symbol Rules

Reference #: Description: Criteria:

PS-04373 Road / intact / all weather / hard surface / no median / >= 4 lanes /

secondary (line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Road Weather Restriction [WTC] = (All-weather [1], Closed in Winter [5])

AND Load-bearing Surface Type [RST] = Hard/Paved [1]

AND Divided [SEP] = (False [1000], Unknown [0])

AND Track or Lane Count [LTN] >= 4

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17],

Unknown [0])

AND Thoroughfare Class [HCT] = (Local Route [4], Secondary Route [2])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:

PL-04373_1 Road / intact / all weather / hard surface / no median / > 4

lanes / secondary (line)

AND Road Weather Restriction [WTC] = All-weather [1]

Track or Lane Count [LTN] > 4

Label String: [Name] [Track or Lane Count] "LANES"

Characteristics: 27, 28, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04373_2 Road / intact / all weather / hard surface / no median / > 4 Track or Lane Count [LTN] > 4

lanes / secondary / closed in winter (line)

AND

Label String: [Name] [Track or Lane Count] "LANES CLOSED IN WINTER"

Characteristics: 27, 28, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04373_3 Road / intact / all weather / hard surface / no median / 4 Track or Lane Count [LTN] <= 4

lanes / secondary (line)

AND Road Weather Restriction [WTC] = All-weather [1]

Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name]
Characteristics: 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04373_4 Road / intact / all weather / hard surface / no median / 4 Track or Lane Count [LTN] <= 4

lanes / secondary / closed in winter (line)

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] "CLOSED IN WINTER"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

6 LANES UNIVERSITY 6 LANES

Road / intact / all weather / hard surface / no median / 2 or 3 lanes / primary (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound

Symbol Graphic

Note: The symbol is a combination of two lines. Display Level from bottom to top: Component L00426, Component L00156. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Line - Simple Component Ref #: L00426 Component Type: Color Token: Black

Description:

Black 0.7mm Solid Line

Parameters:

Line Weight: 0.7mm

L00156 Line - Simple Color Token: Dk-Brown1815 Component Ref #: Component Type:

Description: Dk-Brown1815 0.5mm Solid Line

Parameters:

Line Weight: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04720 Road / intact / all weather / hard

surface / no median / 2 or 3 lanes /

primary (line)

AND Road Weather Restriction [WTC] = (All-weather [1], Closed in Winter [5])

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Load-bearing Surface Type [RST] = Hard/Paved [1]) AND Divided [SEP] = (False [1000], Unknown [0])

AND Track or Lane Count [LTN] = (2, 3)

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17],

Unknown [0])

AND Thoroughfare Class [HCT] = (National Motorway [3], Primary Route [1], Unknown [0])

Label Rules

AND

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:

PL-04720_1 Road / intact / all weather / hard surface / no median / 2 Track or Lane Count [LTN] = 2

lanes / primary (line)

Label String: [Name] Characteristics:

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04720 2 Road / intact / all weather / hard surface / no median / 2 Track or Lane Count [LTN] = 2

lanes / primary / closed in winter (line)

Road Weather Restriction [WTC] = Closed in Winter [5] AND

Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name] "CLOSED IN WINTER"

Characteristics:

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04720 3 Road / intact / all weather / hard surface / no median / 3 Track or Lane Count [LTN] = 3

lanes / primary (line)

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name] "3 LANES"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04720_4 Road / intact / all weather / hard surface / no median / 3 Track or Lane Count [LTN] = 3

lanes / primary / closed in winter (line)

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] "3 LANES CLOSED IN WINTER"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

ATCHISON

Road / intact / all weather / hard surface / no median / 2 or 3 lanes / secondary (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound

Symbol Graphic

Note: The symbol is a combination of two lines. Display Level from bottom to top: Component L00426, Component L00376. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00426 Component Type: Line - Simple Color Token: Black

Description:

Black 0.7mm Solid Line

Parameters:

Line Weight: 0.7mm

Component Ref #: L00376 Component Type: Line - Simple Color Token: Dk-Brown1815-54

Description: Dk-Brown1815-54 0.5mm Screened Line

Parameters:

Line Weight: 0.5mm

Screen Angle: 45 degrees

Screen Percent: 54%

Symbol Rules

Reference #: Description: Criteria:

PS-04722 Road / intact / all weather / hard surface / no median / 2 or 3 lanes /

secondary (line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Road Weather Restriction [WTC] = (All-weather [1], Closed in Winter [5])

AND Load-bearing Surface Type [RST] = Hard/Paved [1]

AND Divided [SEP] = (False [1000], Unknown [0])

AND Track or Lane Count [LTN] = (2, 3)

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17],

Unknown [0])

AND Thoroughfare Class [HCT] = (Local Route [4], Secondary Route [2])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:

PL-04722_1 Road / intact / all weather / hard surface / no median / 2 Track or Lane Count [LTN] = 2

AND

lanes / secondary (line)

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name]
Characteristics: 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04722_2 Road / intact / all weather / hard surface / no median / 2 Track or Lane Count [LTN] = 2

lanes / secondary / closed in winter (line)

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] "CLOSED IN WINTER"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04722_3 Road / intact / all weather / hard surface / no median / 3 Track or Lane Count [LTN] = 3

lanes / secondary (line)

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name] "3 LANES"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04722_4 Road / intact / all weather / hard surface / no median / 3 Track or Lane Count [LTN] = 3

lanes / secondary / closed in winter (line)

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] "3 LANES CLOSED IN WINTER"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

HUGHES

Road / intact / all weather / hard surface / no median / 1 lane / primary (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound

Symbol Graphic

Note: The symbol is a combination of two lines. Display Level from bottom to top: Component L00014, Component L00105. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00014 Component Type: Line - Simple Color Token: Black

Description: Black 0.5mm Solid Line

Parameters:

Line Weight: 0.5mm

Component Ref #: L00105 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.3mm Solid Line

Parameters:

Line Weight: 0.3mm

Symbol Rules

Reference #: Description: Criteria:

PS-04367 Road / intact / all weather / hard Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

surface / no median / 1 lane / primary (line)

AND Road Weather Restriction [WTC] = (All-weather [1], Closed in Winter [5])

AND Load-bearing Surface Type [RST] = Hard/Paved [1])

AND Divided [SEP] = (False [1000], Unknown [0])

AND Track or Lane Count [LTN] <= 1

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17],

Unknown [0])

AND Thoroughfare Class [HCT] = (National Motorway [3], Primary Route [1], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:

 $PL-04367_1 \qquad Road\ /\ intact\ /\ all\ weather\ /\ hard\ surface\ /\ no\ median\ /\ 1$

Road Weather Restriction [WTC] = All-weather [1]

lane / primary (line)

Label String: [Name]
Characteristics: 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04367_2 Road / intact / all weather / hard surface / no median / 1

Road Weather Restriction [WTC] = Closed in Winter [5]

lane / primary / closed in winter (line)

Label String: [Name] "CLOSED IN WINTER"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

MAPLE

Road / intact / all weather / hard surface / no median / 1 lane / secondary (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound

Symbol Graphic

Note: The symbol is a combination of two lines. Display Level from bottom to top: Component L00014, Component L00387. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00014 Component Type: Line - Simple Color Token: Black

Description: Black 0.5mm Solid Line

Parameters:

Line Weight: 0.5mm

Component Ref #: L00387 Component Type: Line - Simple Color Token: Dk-Brown1815-54

Description: Dk-Brown1815-54 0.3mm Screened Line

Parameters:

Line Weight: 0.3mm

Screen Angle: 45 degrees

Screen Percent: 54%

Symbol Rules

Reference #: Description: Criteria:

PS-04372 Road / intact / all weather / hard surface / no median / 1 lane /

surface / no median / 1 secondary (line) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Road Weather Restriction [WTC] = (All-weather [1], Closed in Winter [5])

AND Load-bearing Surface Type [RST] = Hard/Paved [1]

AND Divided [SEP] = (False [1000], Unknown [0])

AND Track or Lane Count [LTN] <= 1

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17],

Unknown [0])

AND Thoroughfare Class [HCT] = (Local Route [4], Secondary Route [2])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:

PL-04372_1 Road / intact / all weather / hard surface / no median / 1 Road Weather Restriction [WTC] = All-weather [1]

lane / secondary (line)

Label String: [Name] Characteristics: 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04372 2 Road / intact / all weather / hard surface / no median / 1 Road Weather Restriction [WTC] = Closed in Winter [5]

lane / secondary / closed in winter (line)

Label String: [Name] "CLOSED IN WINTER"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

VALLEY VIEW

Road / intact / all weather / loose surface / no median / >= 4 lanes / primary (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound



Symbol Graphic

Note: The symbol is a combination of three lines. Display Level from bottom to top: Component L00433, Component L00182, Component L00169. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

L00433 Line - Simple Component Ref #: Component Type: Color Token: Black

Description: Black 0.9mm Solid Line

Parameters:

Line Weight: 0.9mm

Component Ref #: L00182 Component Type: Line - Simple Color Token: **PaperWhite**

PaperWhite 0.6mm Solid Line Description:

Parameters:

Line Weight: 0.6mm

Component Ref #: L00169 Component Type: Line - Styled Color Token: Dk-Brown1815

Dk-Brown1815 0.6mm Dashed Line (0.6mm wt, 3.5mm dash, 1.5mm gap) Description:

Parameters:

Line Weight: Dash Length: 1.5mm 0.6mm3.5mm Dash Spacing:

AND

Symbol Rules

Reference #: Description:

PS-04371 Road / intact / all weather / loose

surface / no median / >= 4 lanes /

primary (line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Road Weather Restriction [WTC] = (All-weather [1], Closed in Winter [5]) AND Load-bearing Surface Type [RST] = (Loose/Unpaved [2], Temporary [8], Unknown [0])

AND Divided [SEP] = (False [1000], Unknown [0])

AND Track or Lane Count [LTN] >= 4

Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17], AND

Unknown [0])

AND Thoroughfare Class [HCT] = (National Motorway [3], Primary Route [1], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Criteria: Reference #: Description:

PL-04371_1 Road / intact / all weather / loose surface / no median / > 4 lanes / primary (line)

Track or Lane Count [LTN] > 4

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name] [Track or Lane Count] "LANES"

Characteristics: 27, 28, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04371_2 Road / intact / all weather / loose surface / no median / > 4

lanes / primary / closed in winter (line)

Track or Lane Count [LTN] > 4

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name] [Track or Lane Count] "LANES CLOSED IN WINTER"

Characteristics: 27, 28, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04371_3 Road / intact / all weather / loose surface / no median / 4

lanes / primary (line)

Track or Lane Count [LTN] = 4

Label String: [Name]
Characteristics: 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04371_4 Road / intact / all weather / loose surface / no median / 4

Track or Lane Count [LTN] = 4

lanes / primary / closed in winter (line)

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] "CLOSED IN WINTER"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

AND





CONNORS 6 LANES

Road / intact / all weather / loose surface / no median / >= 4 lanes / secondary (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound



Note: The symbol is a combination of three lines. Display Level from bottom to top: Component L00433, Component L00182, Component L00436. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00433 Component Type: Line - Simple Color Token: Black

Description: Black 0.9mm Solid Line

Parameters:

Line Weight: 0.9mm

Component Ref #: L00182 Component Type: Line - Simple Color Token: PaperWhite

Description: PaperWhite 0.6mm Solid Line

Parameters:

Line Weight: 0.6mm

Component Ref #: L00436 Component Type: Line - Styled Color Token: Dk-Brown1815-54

Description: Dk-Brown1815-54 0.6mm Screened Dashed Line (0.6mm wt, 3.5mm, 1.5mm gap)

Parameters:

Line Weight: 0.6mm Dash Length: 3.5mm Dash Spacing: 1.5mm

Screen Angle: 45 degrees
Screen Percent: 54%

Symbol Rules

Reference #: Description: Criteria:

PS-04376 Road / intact / all weather / loose surface / no median / >= 4 lanes /

secondary (line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Road Weather Restriction [WTC] = (All-weather [1], Closed in Winter [5])

AND Load-bearing Surface Type [RST] = (Loose/Unpaved [2], Temporary [8], Unknown [0])

AND Divided [SEP] = (False [1000], Unknown [0])

AND Track or Lane Count [LTN] >= 4

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17],

Unknown [0])

AND Thoroughfare Class [HCT] = (Local Route [4], Secondary Route [2])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:

PL-04376_1 Road / intact / all weather / loose surface / no median / > 4 lanes / secondary (line)

Track or Lane Count [LTN] > 4

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name] [Track or Lane Count] "LANES"

Characteristics: 27, 28, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04376_2 Road / intact / all weather / loose surface / no median / > 4

lanes / secondary / closed in winter (line)

Track or Lane Count [LTN] > 4

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] [Track or Lane Count] "LANES CLOSED IN WINTER"

Characteristics: 27, 28, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case) 28 (Black, Light Condensed, Italic, 6 pt, Lower case)

PL-04376_3 Road / intact / all weather / loose surface / no median / 4

lanes / secondary (line)

Track or Lane Count [LTN] <= 4

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name]
Characteristics: 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04376_4 Road / intact / all weather / loose surface / no median / 4

lanes / secondary / closed in winter (line)

Track or Lane Count [LTN] <= 4

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] "CLOSED IN WINTER"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

PARK 6 LANES

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound



Symbol Graphic

Note: The symbol is a combination of three lines. Display Level from bottom to top: Component L00426, Component L00186, Component L00192. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00426 Component Type: Line - Simple Color Token: Black

Description: Black 0.7mm Solid Line

Parameters:

Line Weight: 0.7mm

Component Ref #: L00186 Component Type: Line - Simple Color Token: PaperWhite

Description: PaperWhite 0.5mm Solid Line

Parameters:

Line Weight: 0.5mm

Component Ref #: L00192 Component Type: Line - Styled Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.5mm Dashed Line (0.5mm wt, 3.5mm dash, 1.5mm gap)

Parameters:

Line Weight: 0.5mm Dash Length: 3.5mm Dash Spacing: 1.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04721 Road / intact / all weather / loose Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

surface / no median / 2 or 3 lanes /

primary (line)

AND Road Weather Restriction [WTC] = (All-weather [1], Closed in Winter [5])

AND Load-bearing Surface Type [RST] = (Loose/Unpaved [2], Temporary [8], Unknown [0])

AND Divided [SEP] = (False [1000], Unknown [0])

AND Track or Lane Count [LTN] = (2, 3)

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17],

Unknown [0])

AND Thoroughfare Class [HCT] = (National Motorway [3], Primary Route [1], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:

PL-04721_1 Road / intact / all weather / loose surface / no median / 2

lanes / primary (line)

Track or Lane Count [LTN] = 2

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name]
Characteristics: 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04721_2 Road / intact / all weather / loose surface / no median / 2 Track or Lane Count [LTN] = 2

lanes / primary / closed in winter (line)

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] "CLOSED IN WINTER"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04721_3 Road / intact / all weather / loose surface / no median / 3 Track or Lane Count [LTN] = 3

lanes / primary (line)

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name] "3 LANES"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04721_4 Road / intact / all weather / loose surface / no median / 3 lanes / primary / closed in winter (line)

Track or Lane Count [LTN] = 3

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] "3 LANES CLOSED IN WINTER"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples





Road / intact / all weather / loose surface / no median / 2 or 3 lanes / secondary (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound



Symbol Graphic

Note: The symbol is a combination of three lines. Display Level from bottom to top: Component L00426, Component L00186, Component L00378. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00426 Component Type: Line - Simple Color Token: Black

Description: Black 0.7mm Solid Line

Parameters:

Line Weight: 0.7mm

Component Ref #: L00186 Component Type: Line - Simple Color Token: PaperWhite

Description: PaperWhite 0.5mm Solid Line

Parameters:

Line Weight: 0.5mm

Component Ref #: L00378 Component Type: Line - Styled Color Token: Dk-Brown1815-54

Description: Dk-Brown1815-54 0.5mm Screened Dashed Line (0.5mm wt, 3.5mm, 1.5mm gap)

Parameters:

Line Weight: 0.5mm Dash Length: 3.5mm Dash Spacing: 1.5mm

Screen Angle: 45 degrees

Screen Percent: 54%

Symbol Rules

Reference #: Description: Criteria:

PS-04723 Road / intact / all weather / loose Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) surface / no median / 2 or 3 lanes /

secondary (line)

AND Road Weather Restriction [WTC] = (All-weather [1], Closed in Winter [5])

AND Load-bearing Surface Type [RST] = (Loose/Unpaved [2], Temporary [8], Unknown [0])

AND Divided [SEP] = (False [1000], Unknown [0])

AND Track or Lane Count [LTN] = (2, 3)

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17],

Unknown [0])

AND Thoroughfare Class [HCT] = (Local Route [4], Secondary Route [2])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:

PL-04723_1 Road / intact / all weather / loose surface / no median / 2 Track or Lane Count [LTN] = 2

lanes / secondary (line)

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name]
Characteristics: 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04723_2 Road / intact / all weather / loose surface / no median / 2 Track or Lane Count [LTN] = 2

lanes / secondary / closed in winter (line)

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] "CLOSED IN WINTER"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04723_3 Road / intact / all weather / loose surface / no median / 3 Track or Lane Count [LTN] = 3

lanes / secondary (line)

AND Road Weather Restriction [WTC] = All-weather [1]

Label String: [Name] "3 LANES"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04723_4 Road / intact / all weather / loose surface / no median / 3 Track or Lane Count [LTN] = 3

lanes / secondary / closed in winter (line)

AND Road Weather Restriction [WTC] = Closed in Winter [5]

Label String: [Name] "3 LANES CLOSED IN WINTER"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

CLOSED IN WINTER

Road / intact / all weather / loose surface / no median / 1 lane / primary (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound

Symbol Graphic

Note: The symbol is a combination of three lines. Display Level from bottom to top: Component L00014, Component L00166, Component

L00191. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00014 Component Type: Line - Simple Color Token: Black

Description: Black 0.5mm Solid Line

Parameters:

Line Weight: 0.5mm

Component Ref #: L00166 Component Type: Line - Simple Color Token: PaperWhite

Description: PaperWhite 0.3mm Solid Line

Parameters:

Line Weight: 0.3mm

Component Ref #: L00191 Component Type: Line - Styled Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.3mm Dashed Line (0.3mm wt, 3.5mm dash, 1.5mm gap)

Parameters:

Line Weight: 0.3mm Dash Length: 3.5mm Dash Spacing: 1.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04370 Road / intact / all weather / loose surface / no median / 1 lane / primary (line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Road Weather Restriction [WTC] = (All-weather [1], Closed in Winter [5])

AND Load-bearing Surface Type [RST] = (Loose/Unpaved [2], Temporary [8], Unknown [0])

AND Divided [SEP] = (False [1000], Unknown [0])

AND Track or Lane Count [LTN] <= 1

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17],

Unknown [0])

AND Thoroughfare Class [HCT] = (National Motorway [3], Primary Route [1], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:

PL-04370_1 Road / intact / all weather / loose surface / no median / 1 Road Weather Restriction [WTC] = All-weather [1]

lane / primary (line)

Label String: [Name]
Characteristics: 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04370_2 Road / intact / all weather / loose surface / no median / 1 Road Weather Restriction [WTC] = Closed in Winter [5]

lane / primary / closed in winter (line)

Label String: [Name] "CLOSED IN WINTER"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

NAI

Road / intact / all weather / loose surface / no median / 1 lane / secondary (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound

Symbol Graphic

Note: The symbol is a combination of three lines. Display Level from bottom to top: Component L00014, Component L00166, Component L00382. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00014 Component Type: Line - Simple Color Token: Black

Description: Black 0.5mm Solid Line

Parameters:

Line Weight: 0.5mm

Component Ref #: L00166 Component Type: Line - Simple Color Token: PaperWhite

Description: PaperWhite 0.3mm Solid Line

Parameters:

Line Weight: 0.3mm

Component Ref #: L00382 Component Type: Line - Styled Color Token: Dk-Brown1815-54

Description: Dk-Brown1815-54 0.3mm Screened Dashed Line (0.3mm wt, 3.5mm, 1.5mm gap)

Parameters:

Line Weight: 0.3mm Dash Length: 3.5mm Dash Spacing: 1.5mm

Screen Angle: 45 degrees
Screen Percent: 54%

Symbol Rules

Reference #: Description: Criteria:

PS-04375 Road / intact / all weather / loose surface / no median / 1 lane / secondary (line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Road Weather Restriction [WTC] = (All-weather [1], Closed in Winter [5])

AND Load-bearing Surface Type [RST] = (Loose/Unpaved [2], Temporary [8], Unknown [0])

AND Divided [SEP] = (False [1000], Unknown [0])

AND Track or Lane Count [LTN] <= 1

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17],

Unknown [0])

AND Thoroughfare Class [HCT] = (Local Route [4], Secondary Route [2])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:

PL-04375_1 Road / intact / all weather / loose surface / no median / 1 Road Weather Restriction [WTC] = All-weather [1]

lane / secondary (line)

Label String: [Name]
Characteristics: 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04375 2 Road / intact / all weather / loose surface / no median / 1 Road Weather Restriction [WTC] = Closed in Winter [5]

lane / secondary / closed in winter (line)

Label String: [Name] "CLOSED IN WINTER"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

CLOSED IN WINTER

Road / intact / fair weather (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound

Symbol Graphic

Note: The symbol is a combination of two lines. Display Level from bottom to top: Component L00014, Component L00166. No symbol is

portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00014 Component Type: Line - Simple Color Token: Black

Description: Black 0.5mm Solid Line

Parameters:

Line Weight: 0.5mm

Component Ref #: L00166 Component Type: Line - Simple Color Token: PaperWhite

Description: PaperWhite 0.3mm Solid Line

Parameters:

Line Weight: 0.3mm

Symbol Rules

Reference #: Description: Criteria

PS-04366 Road / intact / fair weather (line) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Road Weather Restriction [WTC] = (Fair-weather [2], Unknown [0], Winter Only [3])

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17],

Unknown [0])

AND Thoroughfare Class [HCT] = (Local Route [4], National Motorway [3], Primary Route [1], Secondary Route

[2], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

Reference #: Description: Criteria:

PL-04366_1 Road / intact / fair weather (line) Road Weather Restriction[WTC] = (Fair-weather [2], Other [999], Unknown [0])

Label String: [Name]
Characteristics: 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

PL-04366_2 Road / intact / fair weather / closed in winter (line) Road Weather Restriction [WTC] = Winter Only [3]

Label String: [Name] "WINTER ONLY"

Characteristics: 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

FIRE TOWER ROAD

Road / intact / street / hard surface (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound



Symbol Graphic

Note: The symbol is a combination of two lines. Display Level from bottom to top: Component L00014, Component L00166. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40]. This symbol is the default symbol for streets in Built Up Areas if not differentiated by Load-bearing Surface Type [RST].

Component Ref #: L00014 Component Type: Line - Simple Color Token: Black

Description: Black 0.5mm Solid Line

Parameters:

Line Weight: 0.5mm

Component Ref #: L00166 Component Type: Line - Simple Color Token: PaperWhite

Description: PaperWhite 0.3mm Solid Line

Parameters:

Line Weight: 0.3mm

Symbol Rules

Reference #: Description: Criteria:

PS-04573 Road / intact / street / hard surface

(line)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Load-bearing Surface Type [RST] = (Hard/Paved [1], Unknown [0])

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17],

Unknown [0])

AND Is wholly contained within the limits of a Built-up Area and is not a "through-route"

Symbol Samples

Road / intact / street / loose surface (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound

Symbol Graphic

Note: The symbol is a combination of three lines. Component L00166 is aligned to the geometry of the feature. The center of Component L00007 is aligned 0.2mm from one side of the geometry of the feature and the center of Component L00089 is aligned 0.2mm from the other side of the geometry of the feature. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black

Description: Black 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Component Ref #: L00166 Component Type: Line - Simple Color Token: PaperWhite

Description: PaperWhite 0.3mm Solid Line

Parameters:

Line Weight: 0.3mm

Component Ref #: L00089 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 1.0mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 1.0mm

Symbol Rules

Reference #: Description: Criteria:

PS-04690 Road / intact / street / loose Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) surface (line)

AND Load-bearing Surface Type [RST] = (Loose/Unpaved [2], Temporary [8])

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom

[17], Unknown [0])

AND Is wholly contained within the limits of a Built-up Area and is not a "through-route"

Symbol Samples

Road / not intact / median (line)

Symbol Placement Instructions: The symbol is applied to a line equidistant between the two extracted traveled ways of the divided road.

Symbol Type: Compound



Symbol Graphic

Note: The symbol is a combination of four lines. Display Level from bottom to top: Component L00439, Component L00440, Component L00183, Component L00170. Gaps in the lines are coincident. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Component Ref #: L00439 Component Type: Line - Simple Color Token: PaperWhite

Description: PaperWhite 1.1mm Solid Line

Parameters:

Line Weight: 1.1mm

Component Ref #: L00440 Component Type: Line - Styled Color Token: Black

Description: Black 1.1mm Dashed Line (1.1mm wt, 2.5mm dash, 0.5mm gap)

Parameters:

Line Weight: 1.1mm Dash Length: 2.5mm Dash Spacing: 0.5mm

Component Ref #: Component Type: Line - Simple Color Token: **PaperWhite** L00183

Description: PaperWhite 0.8mm Solid Line

Parameters:

Line Weight: 0.8mm

Component Ref #: Line - Styled 100170 Component Type: Color Token: Black

Black 0.1mm Dashed Line (0.1mm wt, 2.5mm dash, 0.5mm gap) Description:

Parameters:

Line Weight: 0.1mm Dash Length: 2.5mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04572 Road / not intact / median (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

AND Divided [SEP] = True [1001]

AND Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17],

Unknown [0])

AND Text [TXT] = Component of Dual Carriageway; traffic flowing in one direction

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999

Reference #: Description: Criteria: PL-04572_1 Road / not intact / median (line) N/A

> Label String: [Name] "("[Condition of Facility]")"

Characteristics: 27, 27, 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

(CONSTRUCTION) _____(DAMAGED)

Road / not intact / no median (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound

Symbol Graphic

Component Ref #:

Note: The symbol is a combination of three lines. Display Level from bottom to top: Component L00427, Component L00428, Component L00186. No symbol is portrayed if the Vertical Relative Location [LOC] = Below Ground Surface [40].

Color Token:

PaperWhite

Line - Simple

Component Type: L00427 Description: PaperWhite 0.7mm Solid Line

Parameters:

Line Weight: 0.7mm

Line - Styled Component Ref #: L00428 Color Token: Component Type: Black

Description: Black 0.7mm Dashed Line (0.7mm wt, 2.5mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.7mm Dash Length: 2.5mm Dash Spacing: 0.5mm

Component Ref #: Component Type: Line - Simple Color Token: L00186 **PaperWhite**

Description: PaperWhite 0.5mm Solid Line

Parameters:

Line Weight: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04574 Road / not intact / no median (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

AND Divided [SEP] = (False [1000], Unknown [0]) Vertical Relative Location [LOC] = (Above Surface [45], On Surface [44], On Waterbody Bottom [17], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9950, LP-9999

Reference #: Description: Criteria:
PL-04574_1 Road / not intact / no median (line) N/A

AND

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 27, 27, 27, 27

27 (Black, Light Condensed, Italic, 6 pt, Upper case)

Symbol Samples

(CONSTRUCTION)

(DESTROYED)

Road Route Marker (No Code)

Road Route Marker / international (point)

Symbol Placement Instructions: The symbol is manually placed on the road feature. Origin: Center of symbol.

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00267 Component Type: Point - Simple Color Token: Black

Description: Road route marker international

Parameters:

Line Weight: 0.2mm

Length: 4.5mm long; 2.5mm wide

Note: The component is an open rectangle.

Symbol Rules

Reference #: Description: Criter

PS-04638 Road Route Marker / international

(point)

Road (AP030) and designated with an international route number.

N/A

Label Placement Rules (see Annex J): LP-3996

Reference #: Description: Criteria:

PL-04638_1 Road Route Marker / international (point)

Label String: [Name]

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Label Rules

A1

Shown with Road:

Road Route Marker / national motorway (point)

		Symbol Placement Instructions:	The symbol is manually	placed on the road featu	re. Origin: Center of symbol.	
	`	Symbol Type: Simple				
Symbol	Granhic					
Symbol	Старпіс					
Componer Description Paramete Line Weig	n: Road rou	S Component Ite marker national motorway r	• •	Color Token:	Black	
Length:	4.5mm	long; 2.25mm wide				
Note:	The con	nponent is an open rectangle.				
			Symbol R	ules		
Reference #: PS-04623	Description: Road Route Mar motorway (point		Criteria: Road (AP030) and design	nated with a national mot	orway route number.	
			Label Rules			
	ent Rules (see Ann	nex J): LP-3996				
Reference #: PL-04623_1		arkar / national materway (no		Criteria: N/A		
PL-04625_1	Road Route Wi	arker / national motorway (po	intj	N/A		
	Label S	tring: [Name]				
	Character	istics: 1 1 (Black, Condensed, 6	pt. Mixed case)			
		_ (,,	Symbol Sam	nles		
			Symbol Sum	pies —		
	M2		Shown with Road:			
			M2			
Road Route	e Marker / na	tional (point)				
	2	Symbol Placement Instructions:	The symbol is manually	placed on the road featu	re. Origin: Center of symbol.	
	9	Symbol Type: Simple				
Complement.	Consultin					
Symbol	Grapnic					
Compone Descriptio <u>Paramete</u>	n: Road rou	Se Component Ite marker national non-USA	Type: Point - Shape	Color Token:	Black	
Note:	See Ann	nex H for detailed drawing instru	uctions.			
			Symbol R	ules		
Reference #:	Description:	han / national	Criteria:			
PS-04639	Road Route Mar (point)	ker / national	Road (AP030) and design	ated with an national rou	ite number.	
Label Disser	ont Dulos (see A : :	ovelle In 2000	Label Rules			
	ent Rules (see Ann	ex J): LP-3996		Cuitauia		
Reference #: PL-04639_1		arker / national (point)		Criteria: N/A		
rL-U4039_1	NUAU NUUTE IVI	arker / Hational (point)		IN/A		
	Label St	tring: [Name]				
	Character	istics: 1	at Mar and annual			

Symbol Samples





Road Route Marker / local, secondary (point)

Symbol Placement Instructions: The symbol is manually placed on the road feature. Origin: Center of symbol.

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00160 Component Type: Point - Simple Color Token: Black

Description: Road route marker local/secondary

Parameters:

Diameter: 3.8mm
Line Weight: 0.1mm

Note: The component is an open circle.

Symbol Rules

Reference #: Description: Criteria:

PS-04640 Road Route Marker / local,

secondary (point)

Road (AP030) and designated with a local or secondary route number.

Label Rules

Label Placement Rules (see Annex J): LP-3996

Reference #: Description: Criteria:

PL-04640_1 Road Route Marker / local, secondary (point) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples






Roadside Rest Area (AQ135)

Generalization Rules (see Annex J): GA-9999, GC-9999

Roadside Rest Area / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #:

L00210

Component Type: Line - Styled

Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm

Dash Length:

1.0mm

Dash Spacing:

0.5mm

			Symbol F	Rules	
Reference #:	Description:	(Criteria:		
PS-04150	Roadside Rest Area / al	l (area)	All		
			Label Rules	S	
Label Placeme	ent Rules (see Annex J):	LP-3506, LP-4813, LP-99	50, LP-9999		
Reference #:	Description:			Criteria:	
PL-04150_1	Roadside Rest Area /	intact (area)		Condition of Facility [FUN] =	= (Fully Functional [6], Unknown [0])
	Label String:	[Name] "Rest area"			
	Characteristics:	1, 1 1 (Black, Condensed, 6 pt,	Mixed case)		
PL-04150_2	Roadside Rest Area /		, wince ease;	Condition of Facility [FLIN] =	(Abandoned [2], Damaged [13], Destroyed [3],
1 2 0 4 2 5 0 _ 2	noudside nest ined y	not intact (area)		Dismantled [4], Under Cons	
	Label String:	[Name] "Rest Area" "("[Condition of Facility]")"			
	Characteristics:	1, 1, 22, 22, 22 1 (Black, Condensed, 6 pt, 22 (Black, Condensed, 6 p			
			Symbol Sar	nples	
Rest area		[] Wad		worth Rest Stop	Rest area (destroyed)
) a a dai da D		n a intl			
koadside K	est Area / intact (
		Placement Instructions:	Origin: Center of symb	001	
	Symbol	Type: Simple			
Symbol (Graphic				
Componer	nt Ref #: P00006	Component Ty	rpe: Point - Simple	Color Token:	Black
Description	n: Black filled squa	are with all sides 0.8mm			
<u>Parameter</u> Length:	<u>rs:</u> 0.8mm				
Note:		nt is a square and is filled wi	ith the solid color		
Note.	The componer	it is a square and is filled wi			
Deference #	Description		Symbol F	Rules	
Reference #: PS-04604	Description: Roadside Rest Area / in		Criteria:	INI /Fully Franchisms [C] Lie	[0]
F3-04004	Roduside Rest Alea / III	tact (point)		JN] = (Fully Functional [6], Ur	iknown [U])
Label Placeme	ent Rules (see Annex J):	LP-3505	Label Rules	5	
		2. 3333		Cuthoute	
Reference #:	Description:	:		Criteria:	
PL-04604_1	Roadside Rest Area /	intact (point)		N/A	
	Label String:	"Rest area"			
	Characteristics:	1			
		1 (Black, Condensed, 6 pt	, Mixed case)		
			Symbol Sar	nples	

Rest area

Roadside Rest Area / not intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00173 Component Type: Point - Shape Color Token: Black/Black-12

Description: Not intact square 0.8mm

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04920 Roadside Rest Area / not intact Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

(point) Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:

PL-04920_1 Roadside Rest Area / not intact (point) N/A

Label String: "Rest area"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Rest area

Rock Formation (DB160)

Generalization Rules (see Annex J): GA-9999

Rock Formation / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00069; 0.8mm

Symbol Graphic

Note: Component P00069 is perpendicular to and on the downhill side of the edge of Component L00023.

Component Ref #: L00023 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Component Ref #: P00069 Component Type: Point - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 1.0mm length line with a 0.2mm lineweight

Parameters:

Line Weight: 0.2mm
Length: 1.0mm

Symbol Rules

Reference #: Description: Criteria:

PS-04256 Rock Formation / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:

PL-04256_1 Rock Formation / all (area)

N/A

Label String: [Name]
Characteristics: 8

8 (Black, Condensed, Italic, 6-16 pt, Mixed case)

Symbol Samples

Щ

Chief Mountain

Rock Formation / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00069 has an initial offset of 0.4mm; after that 0.8mm.

тити

Symbol Graphic Note: Component P00069 is perpendicular to and on the downhill side of the edge of Component L00023.

Component Ref #: L00023 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Component Ref #: P00069 Component Type: Point - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 1.0mm length line with a 0.2mm lineweight

Parameters:

Line Weight: 0.2mm
Length: 1.0mm

Label Placement Rules (see Annex J):

Symbol Rules

Reference #: Description: Criteria:
PS-04088 Rock Formation / all (line) All

Label Rules

Reference #: Description: Criteria:

PL-04088_1 Rock Formation / all (line) N/A

LP-3630, LP-9999

Label String: [Name]
Characteristics: 5

5 (Black, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Delicate Arch

Rock Formation / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: Point - Shape Color Token: Dk-Brown1815 P00071 Component Type:

Description: Rock formation

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria: PS-04257

Rock Formation / all (point) Αll

Label Rules

LP-3505, LP-9999 Label Placement Rules (see Annex J):

Criteria: Reference #: Description: PL-04257_1 Rock Formation / all (point) N/A

> Label String: [Name] Characteristics: 5

> > 5 (Black, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Chimney Rock

Roundhouse (AN076)

Generalization Rules (see Annex J): GC-9993

Roundhouse / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: A00006 Component Type: Area - Fill Color Token: Black

Description: Black solid fill

Parameters:

Note: The surface geometry is filled with the solid color.

Symbol Rules

Criteria: Reference #: Description: Roundhouse / all (area) PS-04605 ΑII

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria: PL-04605_1 Roundhouse / all (area) N/A

> Label String: "Roundhouse"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples





Roundhouse / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Point - Simple Component Ref #: P00053 Component Type: Color Token: Black

Description: Black 0.8mm diameter filled circle

Parameters:

Diameter: 0.8mm

Note: The component is a circle and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria: Roundhouse / all (point) PS-04606

ΑII

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:

PL-04606_1 Roundhouse / all (point) N/A

> "Roundhouse" Label String:

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples


Label Rules

Roundhouse

Ruins (AL200)

Generalization Rules (see Annex J): GA-9999, GC-9999

Ruins / all (area)



Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

L00210 Line - Styled Component Ref #: Component Type: Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.5mm 0.1mm Dash Length: 1.0mm Dash Spacing:

Symbol Rules

Reference #: Description: Criteria:

PS-04092	Ruins / all (area)	All				
		Label Rules				
Label Placem	nent Rules (see Annex J):	LP-3506, LP-4813, LP-9999				
Reference #: Description:		Criteria:				
PL-04092_1	Ruins / all (area)	N/A				
	Label String:	[Name] "Ruins"				
	Characteristics:	1, 1				
		1 (Black, Condensed, 6 pt, Mixed case)				
		Symbol Samples				
	Ruins	Lehigh Valley Roundhouse Ruins				
Duine / all	/:t\					
Ruins / all		ol Placement Instructions: Origin: Center of symbol				
		of Type: Simple				
	Symbo	Type: Simple				
Symbol	Graphic					
Compone	ent Ref #: P00265	Component Type: Point - Shape Color Token: Black				
Description	on: Ruins	Sometime (per section)				
Paramete Note:		for detailed drawing instructions.				
Reference #:	Description:	Symbol Rules Criteria:				
PS-04093	Ruins / all (point)	All				
		Label Rules				
Label Placem	nent Rules (see Annex J):	LP-3505, LP-9999				
Reference #:		Criteria:				
PL-04093_1	Ruins / all (point)	N/A				
	Label String:	[Name]				
Characteristics:						
		1 (Black, Condensed, 6 pt, Mixed case)				
		Symbol Samples				
	۵	Ruins of Aquadilla				
		··				
Runway	(CDOFF)					
KUNWAV	しいわいううし					

Generalization Rules (see Annex J): GA-9999, GC-9994

Runway / intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Note: Label for Runway surface is combined with the label for the associated Land Aerodrome.

Component Ref #: A00002 Component Type: Area - Fill Color Token: Blue072

Description: Blue072 solid fill

Parameters:

Note: The surface geometry is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04428 Runway / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-9990

Reference #: Description: Criteria:

PL-04428_1 Runway / intact / hard surface (area) Load-bearing Surface Type [RST] = Hard/Paved [1]

Label String: "Hard surface"

Characteristics: 24

24 (Blue072, Condensed, 7 pt, Mixed case)

PL-04428_2 Runway / intact / soft surface (area) Load-bearing Surface Type [RST] = (Grass/Sod (soft) [5], Loose/Unpaved [2],

Unimproved [6])

Label String: "Soft surface"

Characteristics: 24

24 (Blue072, Condensed, 7 pt, Mixed case)

PL-04428_3 Runway / intact / unknown surfce (area) Load-bearing Surface Type [RST] = (Other [999], Unknown [0])

Label String: "Surface unknown"

Characteristics: 24

24 (Blue072, Condensed, 7 pt, Mixed case)

Symbol Samples



Runway / not intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: Component L00217 is applied to the perimeter and is filled with Component A00123. Label for Runway surface is combined with the label for the associated Land Aerodrome.

Component Ref #: A00123 Component Type: Area - Fill Color Token: Blue072-42

Description: Blue072-42 area fill

Parameters:

Screen Angle: 45 degrees
Screen Percent: 42%

Component Ref #: L00217 Component Type: Line - Simple Color Token: Blue072

Description: Blue072 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

PS-04951 Runway / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-9990

Reference #: Description: Criteria:

PL-04951_1 Runway / not intact / hard surface (area) Load-bearing Surface Type [RST] = Hard/Paved [1]

Label String: "Hard surface"

Characteristics: 24

24 (Blue072, Condensed, 7 pt, Mixed case)

PL-04951_2 Runway / not intact / soft surface (area) Load-bearing Surface Type [RST] = (Grass/Sod (soft) [5], Loose/Unpaved [2],

Unimproved [6])

Label String: "Soft surface"

Characteristics: 24

24 (Blue072, Condensed, 7 pt, Mixed case)

PL-04951_3 Runway / not intact / unknown surface (area) Load-bearing Surface Type [RST] = (Other [999], Unknown [0])

Label String: "Surface unknown"

Characteristics: 24

24 (Blue072, Condensed, 7 pt, Mixed case)

Symbol Samples

Surface unknown

Sabkha (BH160)

Generalization Rules (see Annex J): GA-9999

Sabkha / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00041 is applied to the perimeter and is filled with Component A00016.

Component Ref #: A00016 Component Type: Area - Pattern Color Token: Cyan Description: Cyan Sabkha Fill

Description:
Parameters:

Area Pattern: AP-103, see Annex I

Component Ref #: L00041 Component Type: Line - Styled Color Token: Cyan

Description: Cyan 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04209 Sabkha / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04209_1 Sabkha / all (area) N/A

Label String: [Name] Characteristics: 37

37 (Cyan, Condensed, Italic, 7-16 pt, Upper case)

Symbol Samples





Salt Evaporator (BH155)

Generalization Rules (see Annex J): GA-9999, GC-9999

Salt Evaporator / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00015 is applied to the perimeter and is filled with Component A00044.

Area - Pattern Component Ref #: A00044 Component Type: Color Token: Cyan

Description: Parameters: Cyan Salt Evaporator Fill

Area Pattern: No existing MIL_STD_2410 area pattern. See Annex I for detailed drawing instructions.

Component Ref #: L00015 Component Type: Line - Simple Color Token:

Cyan 0.2mm Solid Line Description:

Parameters:

Line Weight: 0.2mm

Symbol Rules

Cyan

Reference #: Description: Criteria: Salt Evaporator / all (area) PS-04208 ΑII

Symbol Samples



Salt Evaporator / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00157 Component Type: Point - Simple Color Token: Cyan

Description: Salt evaporator

Parameters:

Line Weight: 0.2mm 1.5mm Length:

Note: The component is an open square. Symbol Rules

Reference #: Description: Criteria:
PS-04607 Salt Evaporator / all (point) All

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04607_1 Salt Evaporator / all (point) N/A

Label String: "Salt evaporator"

Characteristics: 16

16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

☐ Salt evaporator

Salt Flat (BH150)

Generalization Rules (see Annex J): GA-9999

Salt Flat / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

 ${\color{red}\textbf{Note:}} \ \textbf{Component L00041} \ \textbf{is applied to the perimeter and is filled with Component A00020}.$

Component Ref #: A00020 Component Type: Area - Pattern Color Token: Cyan Description: Cyan Dry Drainage Fill

Description: Parameters:

Area Pattern: AP-95, see Annex I

Component Ref #: L00041 Component Type: Line - Styled Color Token: Cyan

Description: Cyan 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:
PS-04608 Salt Flat / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-4813, LP-9999

Reference #: Description: Criteria:
PL-04608_1 Salt Flat / all (area) N/A

Label String: [Name] "Salt flat"

Characteristics: 38, 38

38 (Cyan, Condensed, Italic, 6-16 pt, Mixed case)

Symbol Samples



Bonneville Salt Flats

Sand Dunes (DB170)

Generalization Rules (see Annex J): GA-9999

Sand Dunes / unknown (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: A00035 Component Type: Area - Pattern Color Token: Dk-Brown1815

Description: Dk-Brown1815 Sand Fill

Parameters:

Area Pattern: AP-95, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04258 Sand Dunes / unknown (area) Sand Dune Type [SDT] = Unknown [0]

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04258_1 Sand Dunes / unknown (area) N/A

Label String: [Name] "Dunes"

Characteristics: 7, 7

7 (Black, Condensed, Italic, 7-10 pt, Mixed case)

Symbol Samples



Little Sahara Dunes

Sand Dunes / crescent (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Note: The symbol is rotated to the Sand Dune Orientation (SDO) value.

Component Ref #: A00031 Component Type: Area - Pattern Color Token: Dk-Brown1815

Description: Dk-Brown1815 Crescent Sand Dunes Fill

Parameters:

Area Pattern: AP-108, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04259 Sand Dunes / crescent (area) Sand Dune Type [SDT] = (Crescent [1], Parabolic [5])

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04259_1 Sand Dunes / crescent (area) N/A

Label String: [Name]
Characteristics: 7

Symbol Samples





Sand Dunes / dome (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: A00042 Component Type: Area - Pattern Color Token: Dk-Brown1815

Description: Dk-Brown1815 Dome Sand Dunes Fill

Parameters:

Area Pattern: AP-126, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04264 Sand Dunes / dome (area) Sand Dune Type [SDT] = Dome [2]

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:

PL-04264_1 Sand Dunes / dome (area) N/A

Label String: [Name]
Characteristics: 7

7 (Black, Condensed, Italic, 7-10 pt, Mixed case)

Symbol Samples





Sand Dunes / transverse (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Note: The symbol is rotated to the Sand Dune Orientation (SDO) value.

Component Ref #: A00034 Component Type: Area - Pattern Color Token: Dk-Brown1815

Description: Dk-Brown1815 Transverse Sand Dunes Fill

Parameters:

Area Pattern: AP-127, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04260 Sand Dunes / transverse (area) Sand Dune Type [SDT] = (Dome and Transverse [8]), Transverse [3])

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

 Reference #:
 Description:
 Criteria:

 PL-04260_1
 Sand Dunes / transverse (area)
 N/A

Label String: [Name]
Characteristics: 7

7 (Black, Condensed, Italic, 7-10 pt, Mixed case)

Symbol Samples





Sand Dunes / linear (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic Note: The symbol is rotated to the Sand Dune Orientation (SDO) value.

Component Ref #: A00043 Component Type: Area - Pattern Color Token: Dk-Brown1815

Description: Dk-Brown1815 Linear Sand Dunes Fill

Parameters:

Area Pattern: AP-118, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04261 Sand Dunes / linear (area) Sand Dune Type [SDT] = Linear [4]

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04261_1 Sand Dunes / linear (area) N/A

Label String: [Name]
Characteristics: 7

7 (Black, Condensed, Italic, 7-10 pt, Mixed case)

Symbol Samples



Waĥiba Sands

Sand Dunes / ripple (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Note: The symbol is rotated to the Sand Dune Orientation (SDO) value.

Component Ref #: A00032 Component Type: Area - Pattern Color Token: Dk-Brown1815

Description: Dk-Brown1815 Ripple Sand Dunes Fill

Parameters:

Area Pattern: AP-112, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04262 Sand Dunes / ripple (area) Sand Dune Type [SDT] = Ripple [6]

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04262_1 Sand Dunes / ripple (area) N/A

Label String: [Name]
Characteristics: 7

7 (Black, Condensed, Italic, 7-10 pt, Mixed case)

Symbol Samples






Sand Dunes / star (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: A00033 Component Type: Area - Pattern Color Token: Dk-Brown1815

Description: Dk-Brown1815 Star Sand Dunes Fill

Parameters:

Area Pattern: AP-120, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04263 Sand Dunes / star (area) Sand Dune Type [SDT] = Star [7]

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04263_1 Sand Dunes / star (area) N/A

Label String: [Name]
Characteristics: 7

7 (Black, Condensed, Italic, 7-10 pt, Mixed case)

Symbol Samples





Seawall (BB230)

Generalization Rules (see Annex J): GA-9999

Seawall / all (line)

Symbol Graphic

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Component Ref #:

L00009

Black 0.2mm Solid Line

Component Type:

Criteria:

Αll

Line - Simple

Color Token:

Black

Description: Parameters:

Line Weight:

0.2mm

Symbol Rules

Reference #: Description:
PS-04748 Seawall / all (line)

Symbol Samples

Shown with Land Water Boundary and Tidal Water:

Settlement (AL105)

Generalization Rules (see Annex J): GA-9999

Settlement / intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00007 is applied to the perimeter and is filled with Component A00122.

Component Ref #: A00122 Component Type: Area - Fill Color Token: Dk-Brown1815-12

Description: Dk-Brown1815-12 area fill

Parameters:

Screen Angle: 45 degrees

Screen Percent: 12%

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black

Description: Black 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

PS-04085 Settlement / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04085_1 Settlement / intact (area) N/A

Label String: [Name]
Characteristics: 41

41 (Black, Condensed, 6-12 pt, Mixed case)

Symbol Samples

Mesquakie Indian Settlement

Settlement / not intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Note: Component L00007 is applied to the perimeter and is filled with Component A00063.

Component Ref #: A00063 Component Type: Area - Pattern Color Token: Dk-Brown1815-54

Description: Dk-Brown1815-54 Not Intact BUA Screened Fill

Parameters:

Area Pattern: LP-6, see Annex I
Screen Angle: 45 degrees
Screen Percent: 54%

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black

Description: Black 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

PS-04053 Settlement / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-9950, LP-9999

Reference #: Description: Criteria:
PL-04053_1 Settlement / not intact (area) N/A

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 41, 22, 22, 22

41 (Black, Condensed, 6-12 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

(destroyed)

Yamit (destroyed)

Settlement / all (point)

Symbol Placement Instructions: Text label only. No graphic parameters

Symbol Type: Simple

[NAM]

Symbol Graphic

Symbol Rules

Reference #: Description: Criteria:
PS-04086 Settlement / all (point) All

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04086_1 Settlement / intact (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

> Label String: [Name] Characteristics: 1

> > 1 (Black, Condensed, 6 pt, Mixed case)

PL-04086_2 Settlement / not intact (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 1, 22, 22, 22

> 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

> > Symbol Samples

Taos Pueblo Jamestown (abandoned)

Settling Pond (AC030)

Generalization Rules (see Annex J): GA-9999

Settling Pond / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: Component L00007 is applied to the perimeter and is filled with Component A00007.

Component Ref #: A00007 Component Type: Area - Fill Color Token: Cyan-31

Cyan-31 area fill Description:

Parameters:

45 degrees Screen Angle: Screen Percent: 31%

L00007 Line - Simple Component Ref #: Component Type: Color Token: Black Black 0.1mm Solid Line

Description:

Parameters:

Line Weight: 0.1mm

Symbol Rules

Criteria: Reference #: Description: PS-04292 Settling Pond / all (area) Αll

Symbol Samples

Settling Pond / all (point)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00288 Component Type: Point - Shape Color Token: Black/Cyan-31

Description: Settling pond

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:
PS-04220 Settling Pond / all (point) All

Symbol Samples

Shanty Town (AL208)

Generalization Rules (see Annex J): GA-9999

Shanty Town / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: A00014 Component Type: Area - Pattern Color Token: Black-42

Description: Black-42 Shantytown Screened Fill

Parameters:

Area Pattern: AP-132, see Annex I
Screen Angle: 45 degrees

Screen Percent: 42%

Symbol Rules

Reference #: Description: Criteria:

PS-04071 Shanty Town / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04071_1 Shanty Town / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Name]
Characteristics: 41

41 (Black, Condensed, 6-12 pt, Mixed case)

PL-04071_2 Shanty Town / not intact (area)

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under Construction [1])

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 41, 22, 22, 22

41 (Black, Condensed, 6-12 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

Dharavi

Abaco (destroyed)

Shed (AL019)

Generalization Rules (see Annex J): GA-9999, GC-9994

Shed / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: A00006 Component Type: Area - Fill Color Token: Black

Description: Black solid fill

Parameters:

Note: The surface geometry is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:
PS-04615 Shed / all (area) All

Symbol Samples

Shed / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00050 Component Type: Point - Simple Color Token: Black

Description: Black filled square with all sides 0.5mm

Parameters:

Length: 0.5mm

Note: The component is a square and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:
PS-04616 Shed / all (point) All

Symbol Samples

Ski Jump (AK150)

Generalization Rules (see Annex J): GA-9999

Ski Jump / non-obstruction (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00032 Component Type: Line - Styled Color Token: Black

Description: Black 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04625 Ski Jump / non-obstruction (line) Height Above Surface Level [HGT] < 46

Label Rules

Label Placement Rules (see Annex J): LP-3630

 Reference #:
 Description:
 Criteria:

 PL-04625_1
 Ski Jump / non-obstruction (line)
 N/A

Label String: "Ski jump"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Ski jump

Ski Jump / obstruction (line)

 $\label{thm:continuity} \textbf{Symbol Placement Instructions:} \qquad \textbf{The symbol is applied to the geometry of the feature.}$

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00006 Component Type: Line - Simple Color Token: Blue072

Description: Blue072 0.73mm Solid Line

Parameters:

Line Weight: 0.73mm

Symbol Rules

Reference #: Description: Criteria

PS-04928 Ski Jump / obstruction (line) Height Above Surface Level [HGT] >= 46

Label Rules

Label Placement Rules (see Annex J): LP-9991

Reference #: Description: Criteria:
PL-04928_1 Ski Jump / obstruction (line) N/A

Label String: "Ski jump"

[Highest Elevation]

"("[Height Above Surface Level]")"

Characteristics: 15

46 95, 95, 95

15 (Blue072, Condensed, 6 pt, Mixed case) 46 (Blue072, Condensed, Bold, 6 pt, Lower case)

Symbol Samples

Ski jump **228** (77)

Ski Jump / non-obstruction (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00274 Component Type: Point - Shape Color Token: Black

Description: Ski jump

Parameters:

Note: See Annex H for detailed drawing instructions.

Reference #: Description: Criteria:

PS-04626 Ski Jump / non-obstruction (point) Height Above Surface Level [HGT] < 46

Symbol Samples

Л

Ski Jump / obstruction (point)

Symbol Placement Instructions: Origin: Center of open circle

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00113 Component Type: Point - Shape Color Token: Blue072

Description: Vertical obstruction linear

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04929 Ski Jump / obstruction (point) Height Above Surface Level [HGT] >= 46

Label Rules

Label Placement Rules (see Annex J): LP-9992

Reference #: Description: Criteria:

PL-04929_1 Ski Jump / obstruction (point) N/A

Label String: "Ski jump"
[Highest Elevation]

"("[Height Above Surface Level]")"

Characteristics: 15

46 95, 95, 95

15 (Blue072, Condensed, 6 pt, Mixed case) 46 (Blue072, Condensed, Bold, 6 pt, Lower case)

Symbol Samples



Slipway (BB240)

Generalization Rules (see Annex J): GA-9999

Slipway / dry (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Note: This symbol is portrayed in conjunction with the Tidal Water symbol and shall mask out the Tidal Water symbol.

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black

Description:

Black 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

PS-04750 Slipway / dry (area) Water Level Effect [WLE] = (Always Dry [2], Floating [8], Not Applicable [998], Other [999], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04750_1 Slipway / dry (area) N/A

Label String: "Slipway"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Slipway

Shown with Land Water Boundary and Tidal Water: Slipway

Slipway / not dry (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Note: The symbol is shown in conjunction with Tidal Water symbol and shall not mask out the Tidal Water symbol.

Component Ref #: A00048 Component Type: Area - Fill Color Token: Black-12

Description: Black-12 area fill

Parameters:

Screen Angle: 15 degrees Screen Percent: 12%

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04751 Slipway / not dry (area) Water Level Effect [WLE] = (Always Submerged [3], Covers and Uncovers [4], Partly Submerged [1])

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria: PL-04751_1 Slipway / not dry (area) N/A

> Label String: "Slipway"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Component Type:

Symbol Samples

Shown with Land Water Boundary and Tidal Water: Slipway

Sluice Gate (BI040)

Generalization Rules (see Annex J): GA-9999

Sluice Gate / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Line - Simple

Color Token:

Black

Symbol Type: Simple



Component Ref #: Description:

Black 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Symbol Rules Reference #: Description: Criteria: PS-04224 Sluice Gate / all (line) ΑII Label Rules Label Placement Rules (see Annex J): LP-3505 Reference #: Description: Criteria: PL-04224_1 Sluice Gate / all (line) N/A "Sluice gate" Label String: Characteristics: 1 1 (Black, Condensed, 6 pt, Mixed case) Symbol Samples Shown with Ditch: Sluice gate Sluice gate

Sluice Gate / all (point)

Symbol Placement Instructions: O

Origin: Apex of "V"

Symbol Type: Simple



Symbol Graphic

Note: Component P00105 is centered on the associated drainage symbol with apex pointing upstream.

Component Ref #: P00105 Component Type: Point - Shape Color Token: Black

Description: Lock/pedestrian bridge/sluice gate "V"

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04225 Sluice Gate / all (point) All

Symbol Samples

Shown with Ditch:

Black

Smokestack (AF010)

Smokestack / non-obstruction (point)

Symbol Placement Instructions: Origin: Center of open circle

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00140 Component Type: Point - Shape Color Token:

Description: Smokestack

Parameters:

Motor	Caa Annoy I	I for dotailed	drawing	instruction
Note:	see Annex F	I for detailed	arawing	instructions

Symbol Rules Reference #: Description:

PS-04301 Smokestack / non-obstruction

(point)

Height Above Surface Level [HGT] < 46

Symbol Samples

Snow Ice Field (BJ100)

Generalization Rules (see Annex J): GA-9999

Snow Ice Field / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: Component L00041 is applied to the perimeter and is filled with Component A00008.

Area - Fill

Color Token:

Cyan-04

Component Ref #: A00008 Cyan-04 area fill Description:

Parameters:

Screen Angle: 45 degrees

Screen Percent:

Component Ref #: L00041 Component Type: Line - Styled Color Token: Cyan

Component Type:

Cyan 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap) Description:

Parameters:

Dash Length: 2.0mm Dash Spacing: 0.5mm Line Weight: 0.2mm

Symbol Rules

Reference #: Description: Criteria: PS-04232 Snow Ice Field / all (area) ΑII

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Criteria: Reference #: Description: PL-04232_1 Snow Ice Field / all (area) N/A

> Label String: [Name] Characteristics:

> > 38 (Cyan, Condensed, Italic, 6-16 pt, Mixed case)

Symbol Samples

Juneau Ice Field

Soil Surface Region (DA010)

Generalization Rules (see Annex J):

Soil Surface Region / distorted surface (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Area - Pattern Color Token: Component Ref #: A00030 Component Type: Dk-Brown1815-54

Description: Dk-Brown1815-54 Distorted Surface Screened Fill

Parameters:

Area Pattern: AP-103, see Annex I

Screen Angle: 45 degrees Screen Percent: 54%

Symbol Rules

Reference #: Description:

Surface Material Type [SMC] = (Boulders [8], Lava [52], Rock [84]) PS-04235 Soil Surface Region / distorted

surface (area)

Label Rules

Label Placement Rules (see Annex J): LP-3506

Reference #: Description:

PL-04235_1 Soil Surface Region / distorted surface / boulders (area) Surface Material Type [SMC] = Boulders [3]

> Label String: "Boulders"

Characteristics:

5 (Black, Condensed, Italic, 6 pt, Mixed case)

PL-04235_2 Soil Surface Region / distorted surface / rocky (area) Surface Material Type [SMC] = Rock [84]

> Label String: "Rocky" 5

Characteristics:

5 (Black, Condensed, Italic, 6 pt, Mixed case)

PL-04235_3 Soil Surface Region / distorted surface / lava (area) Surface Material Type [SMC] = Lava [52]

> Label String: "Lava" Characteristics:

> > 5 (Black, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples





Soil Surface Region / gravel (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: A00036 Component Type: Area - Pattern Color Token: Dk-Brown1815

Dk-Brown1815 Gravel Fill Description:

Parameters:

Area Pattern: AP-99, see Annex I Symbol Rules

Reference #: Description: Criteria

PS-04237 Soil Surface Region / gravel (area) Surface Material Type [SMC] = (Gravel [46], Sand and Gravel [120])

Label Rules

Label Placement Rules (see Annex J): LP-3506

Reference #: Description: Criteria:

PL-04237_1 Soil Surface Region / gravel (area) Surface Material Type [SMC] = Sand and Gravel [120]

Label String: "Sand and gravel"

Characteristics: 5

5 (Black, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Soil Surface Region / sand (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: A00035 Component Type: Area - Pattern Color Token: Dk-Brown1815

Description: Dk-Brown1815 Sand Fill

Parameters:

Area Pattern: AP-95, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04238 Soil Surface Region / sand (area) Surface Material Type [SMC] = (Sand [88], Sand and Boulders [124], Sand and Mud [126])

Label Rules

Label Placement Rules (see Annex J): LP-3506

Reference #: Description: Criteria:

PL-04238_1 Soil Surface Region / sand / boulders (area) Surface Material Type [SMC] = Sand and Boulders [124]

Label String: "Sand and boulders"

Characteristics: 5

5 (Black, Condensed, Italic, 6 pt, Mixed case)

PL-04238_2 Soil Surface Region / sand / mud (area) Surface Material Type [SMC] = Sand and Mud [126]

Label String: "Sand and mud"

Characteristics: 5

5 (Black, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples



Soil Surface Region / other (area)

Symbol Placement Instructions: Text label only. No graphic parameters

Symbol Type: Simple

[SMC]

Symbol Graphic

Symbol Rules

Reference #: Description: Criteria:

PS-04880 Soil Surface Region / other (area) Surface Material Type [SMC] = (Asphalt [5], Concrete [21], Evaporite [122], Frozen Water [103], Ice

[257], Limestone [269], Loess [55], Mud [65], Oil [67], Other [999], Salt [87], Snow [258], Soil [104],

Jnknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3506

Reference #: Description: Criteria:

PL-04880_1 Soil Surface Region / other (area) Surface Material Type [SMC] = (Asphalt [5], Concrete [21], Evaporite [122],

Frozen Water [103], Ice [257], Limestone [269], Loess [55], Mud [65], Oil [67],

Salt [87], Snow [258])

Label String: [Surface Material Type]

Characteristics: 5

5 (Black, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Limestone

Solar Panel (AD020)

Solar Panel / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00010 Component Type: Point - Shape Color Token: Black

Description: Located object

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:
PS-04719 Solar Panel / all (point) All

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04719_1 Solar Panel / all (point) N/A

Label String: "Solar panel"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

 $_{\odot}$ Solar panel

Spillway (BH165) Generalization Rules (see Annex J): GA-9999, GC-9990 Spillway / all (area) Symbol Placement Instructions: The symbol is applied to the geometry of the feature. Symbol Type: Simple **Symbol Graphic** Line - Simple Component Ref #: L00007 Component Type: Color Token: Black Black 0.1mm Solid Line Description: Parameters: Line Weight: 0.1mm Symbol Rules Reference #: Description: Criteria: PS-04629 Spillway / all (area) ΑII Label Rules Label Placement Rules (see Annex J): LP-3505 Reference #: Criteria: Description: PL-04629_1 Spillway / all (area) N/A Label String: "Spillway" Characteristics: 1 (Black, Condensed, 6 pt, Mixed case) Symbol Samples Spillway Spillway / all (line) **Symbol Placement Instructions:** The symbol is applied to the geometry of the feature. Symbol Type: Simple **Symbol Graphic** Component Type: Component Ref #: Line - Simple Color Token: Black Black 0.25mm Solid Line Description: Parameters: Line Weight: 0.25mm Symbol Rules Reference #: Description: Criteria: PS-04630 Spillway / all (line) Αll Label Rules Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04630_1 Spillway / all (line) N/A

Label String: "Spillway"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Spillway

Sports Ground (AK040)

Generalization Rules (see Annex J): GA-9999

Sports Ground / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

S

Symbol Graphic

Note: Component L00361 is applied to the perimeter and is filled with Component A00101. The "S" is centered within the surface geometry of the feature.

Component Ref #: A00101 Component Type: Area - Fill Color Token: Green362-12

Description: Green362-12 area fill

<u>Parameters:</u>

Screen Angle: 45 degrees
Screen Percent: 12%

Component Ref #: L00361 Component Type: Line - Simple Color Token: Green362

Description: Green362 0.15mm Solid Line

Parameters:

Line Weight: 0.15mm

Symbol Rules

Reference #: Description: Criteria:
PS-04631 Sports Ground / all (area) All

Label Placement Rules (see Annex J): LP-3506

Label Rules

Reference #: Description: Criteria:
PL-04631_1 Sports Ground / all (area) N/A

Label String: "S"
Characteristics: 115

115 (Green, Condensed, 6 pt, Mixed case)

Symbol Samples

S

Sports Ground / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00210 Component Type: Point - Shape Color Token: Green362/Green362-1

Description: Sports ground

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04632 Sports Ground / all (point) All

Symbol Samples

S

Spot Elevation (CA030)

Spot Elevation / not water (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00081 Component Type: Point - Simple Color Token: Black

Description: Black 0.64mm diameter filled circle

Parameters:

Diameter: 0.64mm

Note: The component is a circle and is filled with the solid color

Symbol Rules

Reference #: Description: Criteria:

PS-04322 Spot Elevation / not water (point) Elevation Surface Category [ESC] = (Land [1], Snow Field and/or Ice-field [2], Vegetation [4], Unknown

[0])

Label Rules

Label Placement Rules (see Annex J): LP-0073

Reference #: Description: Criteria:

PL-04322_1 Spot Elevation / not water / land / highest on sheet (point) Elevation Surface Category [ESC] = (Land [1], Unknown [0], Vegetation [4])

Label String: [Highest Elevation]

Characteristics: 18

18 (Black, Condensed, Bold, 10 pt, Lower case)

PL-04322_2 Spot Elevation / not water / land / normal (point) Elevation Surface Category [ESC] = (Land [1], Unknown [0], Vegetation [4])

Label String: [Highest Elevation]

Characteristics: 25

25 (Black, Condensed, 8 pt, Lower case)

PL-04322_3 Spot Elevation / not water /snow, ice / highest on sheet

(point)

Label String: [Highest Elevation]

Characteristics: 17

17 (Cyan, Condensed, Bold, 10 pt, Lower case)

PL-04322_4 Spot Elevation / not water / snow, ice / normal (point)

Elevation Surface Category [ESC] = Snow Field and/or Ice-field [2]

Elevation Surface Category [ESC] = Snow Field and/or Ice-field [2]

Label String: [Highest Elevation]

Characteristics: 30

30 (Cyan, Condensed, 8 pt, Lower case)

Symbol Samples

*305 Highest on sheet:

Spot Elevation / water (point)

Symbol Placement Instructions: 7

Text label only. No graphic parameters

Symbol Type: Simple

[ZVH]

Symbol Graphic

Symbol Rules

Reference #: Description: Criteria:

PS-04613 Spot Elevation / water (point) Elevation Surface Category [ESC] = Inland Water [5]

Label Rules

Label Placement Rules (see Annex J): LP-3506

Reference #: Description: Criteria:
PL-04613_1 Spot Elevation / water (point) N/A

Label String: [Highest Elevation]

Characteristics: 30

30 (Cyan, Condensed, 8 pt, Lower case)

Symbol Samples

210

Shown with Inland Waterbody:

Stadium (AK160)

Generalization Rules (see Annex J): GA-9999, GC-9999

Stadium / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Line - Simple Color Token: Component Ref #: L00014 Component Type: Black Black 0.5mm Solid Line

Description:

Parameters:

Line Weight: 0.5mm

Symbol Rules

Criteria: Reference #: Description: PS-04061 Stadium / all (area) ΑII

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04061_1 Stadium / intact (area) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

> Label String: [Name] "Stadium"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Stadium / not intact (area) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], PL-04061_2

Dismantled [4], Under Construction [1])

[Name] "Stadium" "("[Condition of Facility]")" Label String:

Characteristics: 1, 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

Stadium

Bryant-Denny Stadium

Shown with VO Symbol:

Stadium / non-obstruction / intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: Component Type: Point - Simple Color Token: Black

Black filled square with all sides 0.8mm **Description:**

Parameters:

0.8mm Length:

The component is a square and is filled with the solid color. Note:

Symbol Rules

Reference #: Description: Criteria:

PS-04062 Stadium / non-obstruction / intact Height Above Surface Level [HGT] < 46

(point)

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Criteria: Reference #: Description: PL-04062_1 Stadium / non-obstruction / intact (point) N/A

> Label String: [Name] "Stadium"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Stadium Jordan-Hare Stadium

Stadium / non-obstruction / not intact (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00293 Component Type: Point - Shape Color Token: Black/Black-12

Description: Not intact square 0.6mm

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:
PS-04933 Stadium / non-obstruction / not Height A

Stadium / non-obstruction / not intact (point)

Height Above Surface Level [HGT] < 46

AND Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Symbol Samples

Steep Terrain Face (DB010)

Generalization Rules (see Annex J): GA-9999

Steep Terrain Face / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00065 has an initial offset of 0.0mm; after that 0.5mm.

Symbol Graphic

Note: Component P00065 is perpendicular to and on the downhill side of Component L00023.

Component Ref #: L00023 Component Type: Line - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Component Ref #: P00065 Component Type: Point - Simple Color Token: Dk-Brown1815

Description: Dk-Brown1815 0.5mm length line with a 0.1mm lineweight

Parameters:

Line Weight: 0.1mm
Length: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04240 Steep Terrain Face / all (line) All

Label Rules

Label Placement Rules (see Annex J): LP-3630, LP-9999

 Reference #:
 Description:
 Criteria:

 PL-04240_1
 Steep Terrain Face / all (line)
 N/A

Label String: [Name]
Characteristics: 5

5 (Black, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Vermilion Cliffs

Stopway (GB045)

Generalization Rules (see Annex J): GA-9999, GC-9994

Stopway / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

 ${\color{red}\textbf{Note:}} \ \textbf{Component L00217} \ \textbf{is applied to the perimeter and is filled with Component A00125}.$

Component Ref #: A00125 Component Type: Area - Fill Color Token: Blue072-12

Description: Blue072-12 area fill

Description:
Parameters:

Screen Angle: 45 degrees

Screen Percent: 12%

Component Ref #: L00217 Component Type: Line - Simple Color Token: Blue072

Description: Blue072 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:
PS-04633 Stopway / all (area) All

Symbol Samples

Storage Depot (AM010)

Generalization Rules (see Annex J): GA-9999, GC-9999

Storage Depot / all (area)

	l is applied to the geometry of the feature.
Symbol Type: Simple	
''	
Symbol Graphic	
Component Ref #: L00210 Component Type: Line Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5 Parameters:	e - Styled Color Token: Black Smm gap)
	mm Dash Spacing: 0.5mm
	Symbol Rules
Reference #: Description: Criteria:	
PS-04100 Storage Depot / all (area) All	
Label Placement Rules (see Annex J): LP-3506, LP-9999	abel Rules
Reference #: Description:	Criteria:
PL-04100_1 Storage Depot / on surface (area)	Vertical Relative Location [LOC] = (On Surface [44], Unknown [0])
	(004
Label String: "Storage depot"	
Characteristics: 1 1 (Black, Condensed, 6 pt, Mixed case	2)
PL-04100_2 Storage Depot / underground (area)	Vertical Relative Location [LOC] = Below Ground Surface [40]
Label String: "Underground storage depot"	
Characteristics: 1 1 (Black, Condensed, 6 pt, Mixed case	
Sy	ymbol Samples
Storage depot	Underground storage depot
Storage Depot / all (point)	
Symbol Placement Instructions: Origin: Cen	iter of symbol
Symbol Type: Simple	
Complet Carebia	
Symbol Graphic	
Description: Black filled square with all sides 0.8mm	nt - Simple Color Token: Black
Parameters: Length: 0.8mm	
Note: The component is a square and is filled with the solid	color.
	Symbol Rules
Reference #: Description: Criteria:	Symbol Hales
PS-04634 Storage Depot / all (point) All	
	abel Rules
Label Placement Rules (see Annex J): LP-3505	
Reference #: Description:	Criteria:
PL-04634_1 Storage Depot / on surface (point)	Vertical Relative Location [LOC] = (On Surface [44], Unknown [0])

Label String: "Storage depot"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04634_2 Storage Depot / underground (point)

Vertical Relative Location [LOC] = Below Ground Surface [40]

Label String: "Underground storage depot"

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

_ Storage depot

Underground storage depot

Storage Tank (AM070)

Generalization Rules (see Annex J): GC-9983, GC-9993

Storage Tank / non-obstruction / intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: A00006 Component Type: Area - Fill Color Token: Black

Description: Black solid fill

Parameters:

Note: The surface geometry is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:
PS-04115 Storage Tank / non-obstruction / Height Ab

intact (area)

prage Tank / non-obstruction / Height Above Surface Level [HGT] < 46

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04115_1 Storage Tank /

Storage Tank / non-obstruction / intact / not elevated Structure Shape [SSC] = (Cylindrical with Flat Top [65], Cylindrical with (area) Framework [59], Horizontal Capped Cylindrical [2], Obelisk [109], Other [999],

Pyramidal [12], Spherical [17], Unknown [0], Vertical Capped Cylindrical [4])

Label String: [Product]

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

PL-04115_2 Storage Tank / non-obstruction / intact / elevated (area) Structure Shape [SSC] = Spherical on Column [88]

Label String: [Product] "(elevated)"

Characteristics: 1, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

Water
• Water (elevated)

Storage Tank / non-obstruction / not intact (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic Note: Component L00007 is applied to the perimeter and is filled with Component A00064.

Area - Fill Component Ref #: Color Token: A00064 Component Type: Black-12 Description: Black-12 area fill

Screen Angle: 45 degrees Screen Percent: 12%

Component Ref #: Line - Simple Color Token: L00007 Component Type: Black

Description: Black 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:

Storage Tank / non-obstruction / PS-04935 Height Above Surface Level [HGT] < 46

not intact (area)

AND Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Symbol Samples



 \bigcirc

Storage Tank / non-obstruction / intact / other (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: Component Type: Point - Simple Color Token: P00053 Black

Description: Black 0.8mm diameter filled circle

Parameters:

Diameter: 0.8mm

Note: The component is a circle and is filled with the solid color.

<u> </u>	/m	hΛ	l Rul	Δc
- J	,,,,	\mathbf{v}	ı ıvu	163

Reference #: Description: Criteria:

Storage Tank / non-obstruction / PS-04116 Height Above Surface Level [HGT] < 46

intact / other (point)

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND (Product [PPO] = (Chemical [16], Gas [45], Oil [75], Other [999], Sewage [101], Water [122], Unknown

AND Structure Shape [SSC] = (Cylindrical with Flat Top [65], Cylindrical with Framework [59], Horizontal

Capped Cylindrical [2], Obelisk [109], Other [999], Pyramidal [12], Spherical [17], Unknown [0], Vertical

Capped Cylindrical [4]))

OR (Product [PPO] = (Chemical [16], Gas [45], Oil [75], Other [999], Petrol [46], Sewage [101], Unknown

[0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04116_1 Storage Tank / non-obstruction / intact / other / not

elevated (point)

AND Structure Shape [SSC] = (Cylindrical with Flat Top [65], Cylindrical with Framework [59], Horizontal Capped Cylindrical [2], Obelisk [109], Other [999], Pyramidal [12], Spherical [17], Unknown [0], Vertical Capped Cylindrical [4])

Product [PPO] = (Chemical [16], Gas [45], Petrol [46], Oil [75], Other [999],

Label String: [Product]

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04116 2 Storage Tank / non-obstruction / intact / other / elevated

(point)

Product [PPO] = (Chemical [16], Gas [45], Petrol [46], Oil [75], Other [999],

Sewage [101], Unknown [0])

AND Structure Shape [SSC] = (Spherical on Column [88])

Sewage [101], Unknown [0], Water [122])

Label String: [Product] "(elevated)"

Characteristics: 1, 22

> 1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

Gas (elevated)

Water

Storage Tank / non-obstruction / not intact (point)

Symbol Placement Instructions: Origin: Center of symbol

AND

Symbol Type: Simple

O

Symbol Graphic

Component Ref #: P00291 Point - Shape Color Token: Black/Black-12 Component Type:

Description: Not intact circle 0.8mm

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04936 Storage Tank / non-obstruction /

not intact (point)

Height Above Surface Level [HGT] < 46

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under

Construction [1])

Symbol Samples

Storage Tank / non-obstruction / water tower (point)

Symbol Placement Instructions: Origin: Center of open circle

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00142 Component Type: Point - Shape Color Token: Black/Cyan

Description: Water tower

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04614 Storage Tank / non-obstruction / Height Above Surface Level [HGT] < 46

water tower (point)

AND Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Product [PPO] = Water [122]

AND Structure Shape [SSC] = Spherical on Column [88]

Symbol Samples

1

Structural Pile (BD100)

Generalization Rules (see Annex J): GA-9999

Structural Pile / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

:....

Symbol Graphic

Note: Component P00047 is applied to the perimeter with a spacing of 0.8mm, center to center, and the area is filled with Component A00048. This symbol is portrayed in conjunction with the Tidal Water symbol and shall not mask out the Tidal Water symbol.

Component Ref #: A00048 Component Type: Area - Fill Color Token: Black-12

Description: Black-12 area fill

Parameters:

Screen Angle: 15 degrees

Screen Percent: 12%

Component Ref #: P00047 Component Type: Point - Simple Color Token: Black

Description: Black 0.25mm diameter filled circle

Parameters:

Diameter: 0.25mm

Note: The component is a circle and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:
PS-04174 Structural Pile / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-3506

Reference #: Description: Criteria:
PL-04174_1 Structural Pile / all (area) N/A

Label String: "Piles"
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples



Shown with Tidal Water:
.....Piles

Structural Pile / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00103 Component Type: Point - Simple Color Token: Black

Description: Dolphin/Snag/Structural pile

Parameters:

Diameter: 0.8mm
Line Weight: 0.15mm

Note: The component is an open circle.

Symbol Rules

Reference #: Description: Criteria:
PS-04175 Structural Pile / all (point) All

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria:
PL-04175_1 Structural Pile / all (point) N/A

Label String: "Pile"
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Pile

Shown with Tidal Water:

Surface Bunker (AM060)

Generalization Rules (see Annex J): GC-9985

Surface Bunker / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00283 Component Type: Point - Shape Color Token: Black/Dk-Brown1815

Description: Surface bunker

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:
PS-04114 Surface Bunker / all (point) All

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04114_1 Surface Bunker / all (point) N/A

Label String: [Product]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

当 Ammunition

Survey Point (ZB050)

Survey Point / geodetic (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00179 Component Type: Point - Shape Color Token: Black

Description: Survey point geodetic

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04491 Survey Point / geodetic (point) Survey Point Type [SUY] = Geodetic Point [5]

Label Rules

Label Placement Rules (see Annex J): LP-0073, LP-9999

Reference #: Description: Criteria:
PL-04491_1 Survey Point / geodetic / normal (point) N/A

Label String: [Name] [Base Elevation]

Characteristics: 21, 25

21 (Black, Condensed, 8 pt, Upper case) 25 (Black, Condensed, 8 pt, Lower case)

PL-04491_2 Survey Point / geodetic / highest (point) N/A

Label String: [Name] [Base Elevation]

Characteristics: 48, 18

48 (Black, Condensed, Bold, 10 pt, Upper case) 18 (Black, Condensed, Bold, 10 pt, Lower case)

Symbol Samples

[△] 1351

Highest on sheet: DAVIDSON 4021

Survey Point / non-geodetic (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00081 Component Type: Point - Simple Color Token: Black

Description: Black 0.64mm diameter filled circle

Parameters:

Diameter: 0.64mm

Note: The component is a circle and is filled with the solid color

Symbol Rules

Reference #: Description: Criteria:

PS-04492 Survey Point / non-geodetic (point) Survey Point Type [SUY] = (Astronomic Position [1], Benchmark [2], Cadastral Control Point [3], Camera

Station [4], Gravity Point [6], Magnetic Station [7], Other [999], Theodolite Station [8], Tidal Benchmark

[9], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-0073, LP-4813, LP-9999

Reference #: Description: Criteria:

PL-04492_1 Survey Point / non-geodetic / benchmark / normal (point) Survey Point Type [SUY] = Benchmark [2]

Label String: [Name] "BM" [Base Elevation]

Characteristics: 21, 21, 25

21 (Black, Condensed, 8 pt, Upper case) 25 (Black, Condensed, 8 pt, Lower case)

PL-04492_2 Survey Point / non-geodetic / known / normal (point) Survey Point Type [SUY] = (Astronomic Position [1], Cadastral Control Point [3],

Camera Station [4], Gravity Point [6], Magnetic Station [7], Theodolite Station

[8], Tidal Benchmark [9])

Label String: [Name] [Survey Point Type] [Base Elevation]

Characteristics: 21, 21, 25

21 (Black, Condensed, 8 pt, Upper case) 25 (Black, Condensed, 8 pt, Lower case)

PL-04492_3 Survey Point / non-geodetic / unknown / normal (point) Survey Point Type [SUY] = (Other [999], Unknown [0])

Label String: [Name] [Base Elevation]

Characteristics: 21, 25

21 (Black, Condensed, 8 pt, Upper case) 25 (Black, Condensed, 8 pt, Lower case)

PL-04492_4 Survey Point / non-geodetic / benchmark / highest (point) Survey Point Type [SUY] = Benchmark [2]

Label String: [Name] "BM" [Base Elevation]

Characteristics: 48, 48, 18

48 (Black, Condensed, Bold, 10 pt, Upper case) 18 (Black, Regular, Bold, 10 pt, Lower case)

PL-04492_5 Survey Point / non-geodetic / known / highest (point)

Survey Point Type [SUY] = (Astronomic Position [1], Cadastral Control Point [3], Camera Station [4], Gravity Point [6], Magnetic Station [7], Theodolite Station

[8], Tidal Benchmark [9])

Label String: [Name] [Survey Point Type] [Base Elevation]

Characteristics: 48, 48, 18

48 (Black, Condensed, Bold, 10 pt, Upper case) 18 (Black, Regular, Bold, 10 pt, Lower case) PL-04492_6 Survey Point / non-geodetic / unknown / highest (point)

Survey Point Type [SUY] = (Other [999], Unknown [0])

Label String: [Name] [Base Elevation]

Characteristics: 48, 18

48 (Black, Condensed, Bold, 10 pt, Upper case) 18 (Black, Regular, Bold, 10 pt, Lower case)

Symbol Samples

BM • 2645

Highest on sheet:

MOUNT ADAMS BM. 3742

Swamp (ED020)

Generalization Rules (see Annex J): GA-9999

Swamp / cypress (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00041 is applied to the perimeter and is filled with Components A00007 and A00047. Display level from bottom to top: Component A00007; Component A00047.

Component Ref #: A00007 Component Type: Area - Fill Color Token: Cyan-31

Description: Cyan-31 area fill

Parameters:

Screen Angle: 45 degrees
Screen Percent: 31%

Component Ref #: A00047 Component Type: Area - Pattern Color Token: Green362

Description: Green362 Scattered Trees Fill

Parameters:

Area Pattern: AP-44, see Annex I

Component Ref #: L00041 Component Type: Line - Styled Color Token: Cyan

Description: Cyan 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteri

PS-04313 Swamp / cypress (area) Vegetation Species [VSP] = (Cypress [8], Other [999], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04313_1 Swamp / cypress (area) N/A

Label String: [Name]
Characteristics: 39

39 (Black, Condensed, Italic, 7-16 pt, Upper case)

Symbol Samples



Shown with Land Water Boundary and Tidal Water:



Swamp / nipa (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00041 is applied to the perimeter and is filled with Components A00007 and A00024. Display level from bottom to top: Component A00007; Component A00024.

Component Ref #: A00007 Component Type: Area - Fill Color Token: Cyan-31 Cyan-31 area fill

Description:

Parameters:

Screen Angle: 45 degrees Screen Percent:

Area - Pattern Component Ref #: A00024 Component Type: Color Token: Green362

Description: Green362 Nipa Fill

Parameters:

Area Pattern: AP-7, see Annex I

Component Ref #: L00041 Component Type: Line - Styled Color Token: Cyan

Cyan 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap) Description:

Parameters:

Line Weight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04335 Swamp / nipa (area) Vegetation Species [VSP] = Nipa [22]

Label Rules


Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Criteria: Description: PL-04335_1 Swamp / nipa (area) N/A

> Label String: [Name] Characteristics:

> > 39 (Black, Condensed, Italic, 7-16 pt, Upper case)

Symbol Samples





Swimming Pool (AK170)

Generalization Rules (see Annex J): GA-9999, GC-9994, GC-9996

Cyan-31 area fill

Swimming Pool / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic Note: Component L00007 is applied to the perimeter and is filled with Component A00007.

Component Ref #: Area - Fill Color Token: A00007 Component Type: Cyan-31

Description: Parameters:

Screen Angle: 45 degrees Screen Percent: 31%

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black

Black 0.1mm Solid Line Description:

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria: Swimming Pool / all (area) PS-04635 ΑII

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria: PL-04635_1 Swimming Pool / all (area) N/A

> Label String: "Pool" Characteristics: 1

> > 1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

_ Pool

Swimming Pool / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: Point - Shape P00088 Color Token: Black/Cyan-31 Component Type:

Criteria:

Label Rules

Description: Swimming pool

Description:

Parameters:

Reference #:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

PS-04098 Swimming Pool / all (point) ΑII

Label Placement Rules (see Annex J): LP-3505

Criteria: Reference #: Description: PL-04098_1 Swimming Pool / all (point) N/A

> Label String: "Pool"

> > Characteristics: 1 (Black, Condensed, 6 pt, Mixed case)

> > > Symbol Samples

_ Pool

Taxiway (GB075)

Generalization Rules (see Annex J): GA-9999, GC-9994

Taxiway / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: Component L00217 is applied to the perimeter and is filled with Component A00125.

Component Ref #: A00125 Component Type: Area - Fill Color Token: Blue072-12

Description: Blue072-12 area fill

<u>Parameters:</u>

Screen Angle: 45 degrees
Screen Percent: 12%

Component Ref #: L00217 Component Type: Line - Simple Color Token: Blue072

Description: Blue072 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria:
PS-04321 Taxiway / all (area) All

Symbol Samples


Test Site (FA100)

Generalization Rules (see Annex J): GA-9999

Test Site / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:

PS-04314 Test Site / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-4813, LP-9999

Reference #: Description: Criteria:
PL-04314_1 Test Site / intact (area) N/A

Label String: [Name] "Test site"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Test site ——— Dugway Test Site

Thicket (EB020)

Generalization Rules (see Annex J): GA-9999

Thicket / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: A00027 Component Type: Area - Pattern Color Token: Green362

Description: Green362 Scrub / Thicket Fill

Parameters:

Area Pattern: AP-68, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04309 Thicket / all (area) All

Symbol Samples



Tidal Water (BA040)

Generalization Rules (see Annex J): GA-9999

Tidal Water / all (area)

 $\label{thm:continuous} \textbf{Symbol Placement Instructions:} \qquad \textbf{The symbol is applied to the geometry of the feature.}$

Symbol Type: Simple

Symbol Graphic

Component Ref #: A00007 Component Type: Area - Fill Color Token: Cyan-31

Description: Cyan-31 area fill

Parameters:

Screen Angle: 45 degrees
Screen Percent: 31%

Symbol Rules

Reference #: Description: Criteria:
PS-04165 Tidal Water / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04165_1 Tidal Water / all (area) N/A

Label String: [Name]
Characteristics: 59

59 (Cyan, Condensed, Italic, 8-18 pt, Upper case)

Symbol Samples

HUDSON BAY

Tower (AL241)

Tower / non-obstruction / communication (point)

Symbol Placement Instructions: Origin:

tructions: Origin: Center of open circle

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00155 Component Type: Point - Shape Color Token: Black

Description: Aerial/tower communication

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04561 Tower / non-obstruction / Height Above Surface Level [HGT] < 46

communication (point)

AND Tower Type [TTC] = (Cell Tower [19], Communication Tower [18])

Symbol Samples

A

Tower / non-obstruction / control (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00010 Component Type: Point - Shape Color Token: Black

Description: Located object

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteri

PS-04133 Tower / non-obstruction / control Height Above Surface Level [HGT] < 46 (point)

AND Tower Type [TTC] = Control Tower [16]

Tower Type [TTG] Control Tower [10

Label Rules

Label Placement Rules (see Annex J): LP-3505

Reference #: Description: Criteria: PL-04133_1 Tower / non-obstruction / control (point) N/A

Label String: "Control tower" Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

⊙ Control tower

Tower / non-obstruction / cooling (point)

Symbol Placement Instructions: Origin: Center of open circle

Symbol Type: Simple



Symbol Graphic

Point - Shape P00137 Color Token: Black Component Ref #: Component Type:

Description: Cooling tower

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria: Height Above Surface Level [HGT] < 46

PS-04035 Tower / non-obstruction / cooling

(point)

AND Tower Type [TTC] = Cooling Tower [8]

Symbol Samples

Ŷ

Tower / non-obstruction / light (point)

Symbol Placement Instructions: Origin: Center of open circle

Symbol Type: Simple



Symbol Graphic

Point - Shape Component Ref #: P00135 Component Type: Color Token: Black

Description: Lighthouse

Parameters:

See Annex H for detailed drawing instructions. Note:

Symbol Rules

Reference #: Description: Criteria:

PS-04171 Tower / non-obstruction / light Height Above Surface Level [HGT] < 46

(point)

Symbol Samples

}[<

Tower / non-obstruction / other (point)

Symbol Placement Instructions: Origin: Center of open circle

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00141 Component Type: Point - Shape Color Token: Black

Description: Tower non-communication

Parameters:

Reference #:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

PS-04096 Tower / non-obstruction / other Height Above Surface Level [HGT] < 46

(point)

Description:

AND Tower Type [TTC] = (Bridge Tower [1], Drop Tower [23], Fire Tower [12], Guard Tower [21], Industrial Tower [22], Lookout Tower [10], Mine Shaft Superstructure [26], Observation Tower [2], Other [999], Unknown [0])

Symbol Samples

Tower / non-obstruction / water (point)

Symbol Placement Instructions: Origin: Center of open circle

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00142 Component Type: Point - Shape Color Token: Black/Cyan

Description: Water tower

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04119 Tower / non-obstruction / water Height Above Surface Level [HGT] < 46

(point)

AND Tower Type [TTC] = Water Tower [6]

Symbol Samples

Î

Trail (AP050)

Generalization Rules (see Annex J): GA-9999

Trail / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: L00030 Component Type: Line - Styled Color Token: Black

Description: Black 0.2mm Dashed Line (0.2mm wt, 1.5mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 1.5mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:
PS-04129 Trail / all (line) All

Label Rules

Label Placement Rules (see Annex J): LP-3630

Reference #: Description: Criteria:

PL-04129_1 Trail / all (line) Road Weather Restriction [WTC] = Winter Only [3]

Label String: "Winter only"

Characteristics: 10

10 (Black, Light Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Winter only

Training Wall (BB140)

Generalization Rules (see Annex J): GA-9999

Training Wall / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Note: This symbol is portrayed in conjunction with the Tidal Water symbol and shall mask out the Tidal Water symbol.

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black

Description: Black 0.1mm Solid Line

Parameters:

Line Weight: 0.1mm

		Symbol Rules
Reference #: Description:		Criteria:
PS-04740 Training Wal		All
	., (,	
Label Discount Date (see	A 1) 12.3505	Label Rules
Label Placement Rules (see	Annex J): LP-3505	
Reference #: Description	n	Criteria:
PL-04740_1 Training W	/all / all (area)	N/A
Lab	oel String: "Jetty"	
Chara	acteristics: 1	
	1 (Black, Condensed, 6	pt, Mixed case)
		Symbol Samples
		Shown with Land Water Boundary and Tidal Water:
	Jetty	Jetty
Training Wall / all (lin	ne)	
	Symbol Placement Instructions:	The symbol is applied to the geometry of the feature.
	Symbol Type: Simple	
_		
Symbol Graphic		
	00009 Component of the	Type: Line - Simple Color Token: Black
Parameters:	()	
Line Weight: 0.2	mm	
Defendant Book and		Symbol Rules
Reference #: Description:		Criteria:
PS-04741 Training Wal	I / all (line)	All
		Label Rules
Label Placement Rules (see	Annex J): LP-3505	
Reference #: Description	n:	Criteria:
	/all / all (line)	N/A
TE 04741_1 Training W	an y an (inic)	N/A
Lah	pel String: "Jetty"	
	acteristics: 1	
Chara	1 (Black, Condensed, 6	pt, Mixed case)
		Symbol Samples
		Charge with Land Water Poundary and Tidal Water
Je	etty	Shown with Land Water Boundary and Tidal Water:
		Jetty

Transportation Station (AQ125)

Generalization Rules (see Annex J): GA-9999

Transportation Station / all (area)

l	,	I Placement Instructions: The symb I Type: Simple	ol is applied	to the geometry of the featur	re.
Symbol G	iraphic				
Component Description Parameters	Black 0.1mm D	Component Type: Lin ashed line (0.1mm wt, 1.0mm dash, 0.	ne - Styled .5mm gap)	Color Token:	Black
Line Weigh		Dash Length: 1.0	0mm	Dash Spacing:	0.5mm
D. C			Symbol I	Rules	
Reference #: PS-04144	Description: Transportation Station	/ all (area) Criteria:			
			abel Rule	S	
Label Placeme	nt Rules (see Annex J):	LP-3506, LP-4813, LP-9950, LP-999			
Reference #:	Description:			Criteria:	
PL-04144_1	Transportation Statio	on / intact / type known (area)			e [TRS] = (Aeronautical [1], Aqueduct [2], Bus [4], lestrian [9], Pipeline [10], Railway [12])
			AND	Condition of Facility [FUN] =	= (Fully Functional [6], Unknown [0])
	Label String:	[Name] [Transportation System Type	el "Station"		
	Characteristics:	1, 1, 1			
		1 (Black, Condensed, 6 pt, Mixed cas	se)		
PL-04144_2	Transportation Statio	on / intact / type unknown (area)		Transportation System Type [13], Unknown [0])	e [TRS] = (Not Applicable [998], Other [999], Road
			AND	Condition of Facility [FUN] =	= (Fully Functional [6], Unknown [0])
	Label String:	[Name] "Station"			
	Characteristics:	1, 1 1 (Black, Condensed, 6 pt, Mixed cas	se)		
PL-04144_3	Transportation Statio	on / not intact / type known (area)			e [TRS] = (Aeronautical [1], Aqueduct [2], Bus [4], lestrian [9], Pipeline [10], Railway [12])
			AND	Condition of Facility [FUN] = Dismantled [4], Under Cons	= (Abandoned [2], Damaged [13], Destroyed [3], truction [1])
	Label String:	[Name] [Transportation System Type	e] "Station"	"("[Condition of Facility]")"	
	Characteristics:	1, 1, 1, 22, 22, 22 1 (Black, Condensed, 6 pt, Mixed cas 22 (Black, Condensed, 6 pt, Lower ca	•		
PL-04144_4	Transportation Statio	on / not intact / type unknown (area)		Transportation System Type [13], Unknown [0])	e [TRS] = (Not Applicable [998], Other [999], Road
			AND	Condition of Facility [FUN] = Dismantled [4], Under Cons	= (Abandoned [2], Damaged [13], Destroyed [3], truction [1])
	Label String:	[Name] "Station" "("[Condition of Fa	acility]")"		
	Characteristics:	1, 1, 22, 22, 22 1 (Black, Condensed, 6 pt, Mixed cas 22 (Black, Condensed, 6 pt, Lower ca	•		
		S	ymbol Sai	mples	
		Š	,	F	
	Station		ال	Inion Station	

Transportation Station / intact / railway (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Note: The symbol is centered on top of and aligned with the associated Railway or Railway Sidetrack symbol.

Component Ref #: P00079 Component Type: Point - Shape Color Token: Black

Description: Railway station

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04408 Transportation Station / intact / Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

railway (point)

AND Transportation System Type [TRS] = Railway [12]

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04408 1 Transportation Station / intact / railway (point) N/A

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Shown with Railway: Benson Station

Transportation Station / intact / other (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00006 Component Type: Point - Simple Color Token: Black

Description: Black filled square with all sides 0.8mm

Parameters:

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04427 Transportation Station / intact / Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

other (point)

AND Transportation System Type [TRS] = (Aeronautical [1], Aqueduct [2], Bus [4], Canal [5], Maritime [7], Not

Applicable [998], Other [999], Pedestrian [9], Pipeline [10], Road [13], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:
PL-04427_1 Transportation Station / intact / other (point) N/A

Label String: [Name]

Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Foggy Bottom Station

Point of Rocks Water Transport

Transportation Station / not intact (point)

Symbol Placement Instructions:

Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00173 Point - Shape Color Token: Black/Black-12 Component Type:

Description: Not intact square 0.8mm

Parameters:

See Annex H for detailed drawing instructions. Note:

Symbol Rules

Reference #: Description: Criteria:

PS-04241 **Transportation Station / not intact** Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under (point)

Construction [1])

Symbol Samples

Tundra (BJ110)

Generalization Rules (see Annex J): GA-9999

Tundra / all (area)

Symbol Placement Instructions: Text label only. No graphic parameters

Symbol Type: Simple

TUNDRA

Symbol Graphic

Symbol Rules

Reference #: Description: Criteria: PS-04233 Tundra / all (area) ΑII

Label Rules

LP-0050, LP-3506 Label Placement Rules (see Annex J):

Reference #: Description: Criteria: PL-04233_1 Tundra / all (area) N/A

> Label String: "TUNDRA" Characteristics:

> > 39 (Black, Condensed, Italic, 7-16 pt, Upper case)

Symbol Samples

TUNDRA

Tunnel (AQ130)

Generalization Rules (see Annex J): GA-9999, GC-9979, GC-9992

Tunnel / road, taxiway (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component P00073 is fixed at the start and end of Component L00213 and is centered perpendicular to the lines, with each angled element facing away.

Component Ref #: L00213 Component Type: Line - Styled Color Token: Black
Description: Two parallel Black 0.2mm Dashed Lines (0.2mm wt, 1.0mm dash, 0.5mm gap) spaced 1.3mm apart

Parameters:

Line Weight: 0.2mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Note: The two parallel Black 0.2mm Dashed Lines are spaced 1.3mm apart from center to center

Component Ref #: P00073 Component Type: Point - Shape Color Token: Black

Description: Tunnel entrance not water

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04149 Tunnel / road, taxiway (line) Transportation System Type [TRS] = (Aeronautical [1], Bus [4], Road [13])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9999

Reference #: Description: Criteria.

PL-04149_1 Tunnel / road, taxiway / intact (line) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04149_2 Tunnel / road, taxiway / not intact (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

Shown with Road:

Salt Creek Tunnel

Tunnel / railway, pedestrian, other (line)

Symbol Placement Instructions.

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

}-----{

Symbol Graphic

Note: Component P00073 is fixed at the start and end of Component L00031 and is centered perpendicular to the line, with each angled element facing away.

Component Ref #: L00031 Component Type: Line - Styled Color Token: Black

Description: Black 0.2mm Dashed Line (0.2mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Component Ref #: P00073 Component Type: Point - Shape Color Token: Black

Description: Tunnel entrance not water

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04146 Tunnel / railway, pedestrian, other Transportation System Type [TRS] = (Not Applicable [998], Other [999], Pedestrian [9], Pipeline [10],

Railway [12], Unknown [0])

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04146_1 Tunnel / railway, pedestrian, other / intact (line) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Name]
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04146_2 Tunnel / railway, pedestrian, other / not intact (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])


Label String: [Name] "("[Condition of Facility]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

}----{



Tunnel / inland waterway / wide (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: Component P00074 is fixed at the start and end of Component L00214 and is centered perpendicular to the lines, with each angled element facing away.

Component Ref #: L00214 Component Type: Line - Styled Color Token: Cyan Description: Two parallel Cyan 0.2mm Dashed Lines (0.2mm wt, 1.0mm dash, 0.5mm gap) spaced 1.3mm apart

Parameters:

Line Weight: 0.2mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Note: The two parallel Cyan 0.2mm Dashed Lines are spaced 1.3mm apart from center to center

Component Ref #: Point - Shape Color Token: P00074 Component Type: Cyan

Description: Tunnel entrance water

Parameters:

Reference #:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

PS-04147

Tunnel / inland waterway / wide

(line)

Description:

Transportation System Type [TRS] = (Aqueduct [2], Canal [5], Maritime [7])

Width [WID] >= 25 AND

Criteria:

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9999

Criteria: Reference #: Description:

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) PL-04147_1 Tunnel / inland waterway / wide / intact (line)

> Label String: [Name] Characteristics:

> > 14 (Cyan, Condensed, 6 pt, Mixed case)

PL-04147_2 Tunnel / inland waterway / wide / not intact (line) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 14, 93, 93, 93

> 14 (Cyan, Condensed, 6 pt, Mixed case) 93 (Cyan, Condensed, 6 pt, Lower case)

> > **Symbol Samples**

Shown with Canal:]====(

ShandakenTunne

Tunnel / inland waterway / narrow (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Symbol Graphic

Note: Component P00074 is fixed at the start and end of Component L00040 and is centered perpendicular to the line, with each angled

element facing away.

Line - Styled Component Ref #: 100040 Component Type: Color Token: Cyan Description:

Cyan 0.2mm Dashed Line (0.2mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.2mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Point - Shape Component Ref #: P00074 Component Type: Color Token: Cyan

Description: Tunnel entrance water

Parameters:

See Annex H for detailed drawing instructions. Note:

Symbol Rules

Reference #: Description: Criteria:

PS-04148 Tunnel / inland waterway / narrow Transportation System Type [TRS] = (Aqueduct [2], Canal [5], Maritime [7])

(line)

Width [WID] < 25 AND

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9999

Reference #: Description Criteria:

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0]) PL-04148_1 Tunnel / inland waterway / narrow / intact (line)

Label String: [Name]
Characteristics: 14

14 (Cyan, Condensed, 6 pt, Mixed case)

PL-04148_2 Tunnel / inland waterway / narrow / not intact (line)

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 14, 93, 93, 93

14 (Cyan, Condensed, 6 pt, Mixed case) 93 (Cyan, Condensed, 6 pt, Lower case)

Symbol Samples

}----{

Shown with Canal:
Union Canal Tunnel

Vanishing Point (BH145)

Vanishing Point / disappearing (point)

Symbol Placement Instructions: Origin: Center of open circle

Symbol Type: Simple



Symbol Graphic

Note: The symbol connects to the end of the associated River feature. The open circle portion of symbol is oriented downstream.

Component Ref #: P00028 Component Type: Point - Shape Color Token: Cyan

Description: Vanishing point disappearing

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04206 Vanishing Point / disappearing Watercourse Sink Type [WST] = Disappearing [2]

(point)

Symbol Samples

Shown with River

Vanishing Point / dissipating (point)

Symbol Placement Instructions: Origin: Apex of "V"

Symbol Type: Simple



Symbol Graphic

Note: The apex of the symbol connects to the end of the associated River feature. The open side of the "V" is oriented downstream.

Component Ref #: P00059 Component Type: Point - Shape Color Token: Cyan

Description: Vanishing point dissipating

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description:

PS-04207

Vanishing Point / dissipating (point) Wa

Watercourse Sink Type [WST] = (Dissipating [1], Unknown [0])

Symbol Samples

>

Shown with River:

Vehicle Lot (AQ140)

Generalization Rules (see Annex J): GA-9999

Vehicle Lot / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Note: The "P" is centered within the surface geometry of the feature.

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria:
PS-04151 Vehicle Lot / all (area) All

5-04151 Vehicle Lot / all (alea)

Label Placement Rules (see Annex J): LP-3506

Reference #: Description: Criteria:
PL-04151_1 Vehicle Lot / all (area) N/A

Label String: "P"
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Label Rules

|_P_|

Vertical Obstruction (No Code)

Vertical Obstruction / single (point)

Symbol Placement Instructions: Origin: Center of dot

Symbol Type: Simple



Symbol Graphic

Note: If the symbol is moved away from the associated dot element, a Leader Line/aero blue is added connecting the symbol and the dot.

Component Ref #: P00008 Component Type: Point - Shape Color Token: Blue072

Description: Vertical obstruction

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04512 Vertical Obstruction / single (point) Height Above Surface Level [HGT] >= 46

AND Feature [Code] = (Bridge [AQ040], Catalytic Cracker [AC020], Communication Station [AT050], Crane

[AF040], Dam [BI020], Dish Aerial [AT010], Disposal Site [AB000], Electric Power Station [AD010], Flare Pipe [AF070], Fortification [AH050], General Building [AL015], Grain Elevator [AM030], Grain Storage Structure [AM020], Memorial Monument [AL130], Mineral Pile [AM040], Mooring Mast [AQ110], Offshore Platform [BD110], Processing Facility [AC000], Rig [AA040], Smokestack [AF010], Stadium [AK160], Storage Tank [AM070], Tower [AL241], Water Intake Tower [BI050], Wind Turbine [AJ051],

Windmill [AJ050])

Label Rules

Label Placement Rules (see Annex J): LP-9992

Reference #: Description: Criteria:

PS-04512_1 Vertical Obstruction / single / onshore (point) Structures that are located onshore

Label String: [Feature Name]
[Highest Elevation]

cight Above Curfoce Lovell"\"

"("[Height Above Surface Level]")"

Characteristics: 15 46

95, 95, 95

15 (Blue072, Condensed, 6 pt, Mixed case) 46 (Blue072, Condensed, Bold, 6 pt, Lower case) 95 (Blue072, Condensed, 6 pt, Lower case)

PS-04512 2 Vertical Obstruction / single / offshore (point) Structures that are located offshore

Label String: [Feature Name]

"("[Height Above Surface Level]")"

Characteristics: 15

95, 95, 95

15 (Blue072, Condensed, 6 pt, Mixed case) 95 (Blue072, Condensed, 6 pt, Lower case)

Symbol Samples





Vertical Obstruction / multiple (point)

Symbol Placement Instructions: Origin: Center of dot

Symbol Type: Simple



Symbol Graphic

Note: If the symbol is moved away from the associated dot element, a Leader Line/aero blue is added connecting the symbol and the dot.

Component Ref #: P00101 Component Type: Point - Shape Color Token: Blue072

Description: Vertical obstruction multiple

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04513 Vertical Obstruction / multiple Use this symbol to replace a group of single vertical obstruction symbols as needed.

(point)

Label Rules

Label Placement Rules (see Annex J): LP-9992

Reference #: Description: Criteria:

PS-04513_1 Vertical Obstruction / multiple / onshore / same (point) Same structures that are located onshore

Label String: [Feature Name]"s"

[Highest Elevation]

"("[Height Above Surface Level]")"

Characteristics: 15, 95

46 95, 95, 95

15 (Blue072, Condensed, 6 pt, Mixed case) 46 (Blue072, Condensed, Bold, 6 pt, Lower case) 95 (Blue072, Condensed, 6 pt, Lower case)

PS-04513_2 Vertical Obstruction / multiple / onshore / different (point) Different structures that are located onshore

Label String: [Highest Elevation]

"("[Height Above Surface Level]")"

Characteristics: 46

95, 95, 95

46 (Blue072, Condensed, Bold, 6 pt, Lower case) 95 (Blue072, Condensed, 6 pt, Lower case)

PS-04513_3 Vertical Obstruction / multiple / offshore / same (point) Structures that are located offshore

Label String: [Feature Name]"s"

"("[Height Above Surface Level]")"

Characteristics: 15, 95

95, 95, 95

15 (Blue072, Condensed, 6 pt, Mixed case) 95 (Blue072, Condensed, 6 pt, Lower case)

PS-04513_4 Vertical Obstruction / multiple / offshore / different (point) Different structures that are located offshore

Label String: "("[Height Above Surface Level]")"

Characteristics: 95, 95, 95

95 (Blue072, Condensed, 6 pt, Lower case)

Symbol Samples







Vineyard (EA050)

Generalization Rules (see Annex J): GA-9999

Vineyard / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: A00029 Component Type: Area - Pattern Color Token: Green362

Description: Green362 Vineyard / Hops Fill

Parameters:

Area Pattern: AP-77, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04306	Vineyard / all (area)	All
		Label Rules
Label Placeme	ent Rules (see Annex J):	LP-3506, LP-9999
Reference #:	Description:	Criteria:
PL-04306_1	Vineyard / all (area)	N/A
	Label String:	[Name]
	Characteristics:	1
		1 (Black, Condensed, 6 pt, Mixed case)
		Symbol Samples
		Sugarleaf Vineyards:

Void Collection Area (ZD020)

Generalization Rules (see Annex J):

Void Collection Area / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature. Symbol Type: Simple **Symbol Graphic**

Line - Styled Component Ref #: L00210 Component Type: Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Symbol Rules

Reference #: Description: Criteria: PS-04319 Void Collection Area / all (area)

ΑII

Label Placement Rules (see Annex J): LP-0050, LP-3506

Reference #: Description: Criteria: PL-04319_1 Void Collection Area / all (area) N/A

> Label String: "DATA INCOMPLETE"

Characteristics:

40 (Black, Condensed, 6-16 pt, Upper case)

Symbol Samples

Label Rules

DATA INCOMPLETE

Volcano (DB180)

Generalization Rules (see Annex J): GA-9999

Volcano / all (area)

Symbol Placement Instructions: Text label only. No graphic parameters

Symbol Type: Simple



Symbol Graphic

Symbol Rules

Reference #: Description: Criteria:

PS-04941 Volcano / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04941_1 Volcano / all (area) N/A

Label String: [Name]
Characteristics: 7

7 (Black, Condensed, Italic 7-10 pt, Mixed case)

Symbol Samples

Mount Rainier

Volcano / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00064 Component Type: Point - Shape Color Token: Dk-Brown1815

Criteria:

Description: Volcano

Description:

Parameters:

Reference #:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

PS-04667 Volcano / all (point) All

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9999

Reference #: Description: Criteria:

PL-04667 1 Volcano / all (point) N/A

Label String: [Name]
Characteristics: 5

5 (Black, Condensed, Italic 6 pt, Mixed case)

Symbol Samples



Wall (AL260)

Generalization Rules (see Annex J): GA-9999

Wall / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex

Repeating Point and Interval: Component P00149 has an initial offset of 1.0mm; after that 2.0mm.

Symbol Graphic

Note: Longest axis of Component P00149 is centered on and perpendicular to L00008.

Component Ref #: L00008 Component Type: Line - Simple Color Token: Black

Description: Black 0.15mm Solid Line

Parameters:

Line Weight: 0.15mm

Component Ref #: P00149 Component Type: Point - Simple Color Token: Black

Description: Black 0.35mm length line with a 0.45mm lineweight

Parameters:

Line Weight: 0.45mm
Length: 0.35mm

Symbol Rules

Reference #: Description: Criteria:
PS-04099 Wall / all (line) All

Symbol Samples

.....

Water Aerodrome (GB065)

Generalization Rules (see Annex J): GA-9999

Water Aerodrome / all (area)

Symbol Placement Instructions:

Symbol Type: Complex

The symbol is applied to the geometry of the feature.

Symbol Graphic

Note: Component L00210 is applied to the perimeter and component P00257 shall be placed entirely within the associated Lake, Reservoir, River, or Tidal Water feature. Component L00210 shall be suppressed where coincident with Component P00257. Component P00257 shall not be shown if there is an associated Seaplane Run.

Component Ref #: L00210 Component Type: Line - Styled Color Token: Black

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Parameters:

Line Weight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Component Ref #: P00257 Component Type: Point - Shape Color Token: Blue072

Description: Water aerodrome

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:
PS-04569 Water Aerodrome / all (area) All

Label Rules

Label Placement Rules (see Annex J): LP-3506, LP-4813, LP-9950, LP-9990, LP-9999

Reference #: Description: Criteria:

PL-04569_1 Water Aerodrome / intact (area)

Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Name] [ICAO Location Indicator] "Seaplane base"

[Aerodrome Elevation]

Characteristics: 24, 29, 24

26

24 (Blue072, Condensed, 7 pt, Mixed case) 26 (Blue072, Condensed, 7 pt, Lower case) 29 (Blue072, Condensed, 7 pt, Upper case)

PL-04569_2 Water Aerodrome / not intact (area)

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Label String: [Name] [ICAO Location Indicator] "Seaplane base"

"("[Condition of Facility]")"
[Aerodrome Elevation]

Characteristics: 24, 29, 24

26, 26, 26 26

24 (Blue072, Condensed, 7 pt, Mixed case) 26 (Blue072, Condensed, 7 pt, Lower case) 29 (Blue072, Condensed, 7 pt, Upper case)

Symbol Samples







Water Aerodrome / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Note: Component P00257 shall be placed entirely within the associated Lake, Reservoir, River, or Tidal Water feature. Component P00257 shall not be shown if there is an associated Seaplane Run (but retain labeling).

Component Ref #: P00257 Component Type: Point - Shape Color Token: Blue072

Description: Water aerodrome

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04318 Water Aerodrome / all (point)

All

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9950, LP-9990, LP-9999

Reference #: Description: Criteria:

PL-04318_1 Water Aerodrome / intact (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Label String: [Name] [ICAO Location Indicator] "Seaplane base"

[Aerodrome Elevation]

Characteristics: 24, 29, 24

26

24 (Blue072, Condensed, 7 pt, Mixed case) 26 (Blue072, Condensed, 7 pt, Lower case) 29 (Blue072, Condensed, 7 pt, Upper case)

PL-04318 2 Water Aerodrome / not intact (point)

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3], Dismantled [4], Under Construction [1])

[Name] [ICAO Location Indicator] "Seaplane base"

"("[Condition of Facility]")" [Aerodrome Elevation]

24, 29, 24 Characteristics:

26, 26, 26 26

24 (Blue072, Condensed, 7 pt, Mixed case) 26 (Blue072, Condensed, 7 pt, Lower case) 29 (Blue072, Condensed, 7 pt, Upper case)

Symbol Samples

Seaplane base

Lake Hood PALH Seaplane Base 71

Shown with Land Water Boundary and Tidal Water: Seaplane base


Water Gate (BI041)

Generalization Rules (see Annex J): GA-9999

Water Gate / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #: L00009

Black 0.2mm Solid Line

Description: Parameters:

Line Weight: 0.2mm

Symbol Rules

Label Rules

Color Token:

Black

Line - Simple

Reference #: Description: Criteria:

PS-04769 Water Gate / all (line) ΑII

LP-3505 Label Placement Rules (see Annex J):

Reference #: Description: Criteria: PL-04769_1 Water Gate / all (line) N/A

Label String: "Water gate"

Characteristics:

1 (Black, Condensed, 6 pt, Mixed case)

Component Type:

Symbol Samples

Water gate

Shown with Ditch: Water gate

Water Gate / all (point)

Symbol Placement Instructions: Origin: Apex of "V"

Symbol Type: Simple



Symbol Graphic

Note: Component P00105 is centered on the associated drainage symbol with apex pointing upstream.

Component Ref #: P00105 Component Type: Point - Shape Color Token: Black Description: Lock/pedestrian bridge/sluice gate "V"

Parameters:

Note: See Annex H for detailed drawing instructions.

Reference #: Description: Criteria:

PS-04770 Water Gate / all (point) All

Symbol Samples

Symbol Rules

Shown with Ditch:

Water Intake Tower (BI050)

Water Intake Tower / non-obstruction (point)

Symbol Placement Instructions: Origin: Center of open circle

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00148 Component Type: Point - Shape Color Token: Black

Description: Water intake tower

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04226 Water Intake Tower / non-Height Above Surface Level [HGT] < 46

obstruction (point)

Symbol Samples

Shown with Dam and River:



Water Treatment Bed (BH040)

Generalization Rules (see Annex J): GA-9999

Water Treatment Bed / all (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Complex



Symbol Graphic

Note: Component L00007 is applied to the perimeter and is filled with Component A00007.

Component Ref #: A00007 Area - Fill Color Token: Component Type: Cyan-31

Description: Parameters:

Screen Angle: 45 degrees Screen Percent: 31%

Component Ref #: L00007 Component Type: Line - Simple Color Token: Black

Black 0.1mm Solid Line Description:

Cyan-31 area fill

Parameters:

Line Weight: 0.1mm

Symbol Rules

Reference #: Description: Criteria: PS-04183 Water Treatment Bed / all (area) ΑII

Symbol Samples

Waterfall (BH180)

Generalization Rules (see Annex J): GA-9999

Waterfall / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Component Ref #:

L00015

Component Type:

Line - Simple

Color Token:

Cyan

Description:

Cyan 0.2mm Solid Line

Parameters:

Line Weight: 0.2mm

Symbol Rules

Reference #: Criteria: Description: PS-04212 Waterfall / all (line) ΑII

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria: PL-04212_1 Waterfall / all (line) N/A

> Label String: [Name] "Falls" 16.16 Characteristics:

> > 16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples



Waterfall / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Note: The symbol is orientated perpendicular to the associated drainage feature.

Criteria:

Component Ref #: Component Type: Point - Simple Color Token: Cyan

Description: Cyan 1.5mm length line with a 0.2mm lineweight

Parameters:

Reference #:

Line Weight: 0.2mm Length: 1.5mm

Description:

Symbol Rules

PS-04213 Waterfall / all (point) ΑII

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria: PL-04213_1 Waterfall / all (point) N/A

> Label String: [Name] "Falls" Characteristics: 16, 16

16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

Symbol Samples

Shown with River: , Falls , Desoto Falls , Falls

Well (AA050)

Well / non-water / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00009 Component Type: Point - Simple Color Token: Black

Description: Non-water well

Parameters:

Diameter: 1.0mm Line Weight: 0.15mm

Note: The component is an open circle. Symbol Rules

Reference #: Description: Criteria:

PS-04273 Well / non-water / all (point) Product [PPO] = (Gas [45], Multiple [996], Oil [75], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04273_1 Well / non-water / intact / gas (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Product [PPO] = Gas [45]

Label String: "Gas"
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04273_2 Well / non-water / intact / oil (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Product [PPO] = Oil [75]

Label String: "Oil"
Characteristics: 1

1 (Black, Condensed, 6 pt, Mixed case)

PL-04273_3 Well / non-water / not intact / gas (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

AND Product [PPO] = Gas [45]

Label String: "Gas" "("[Condition of Facility]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04273_4 Well / non-water / not intact / oil (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

AND Product [PPO] = Oil [75]

Label String: "Oil" "("[Condition of Facility]")"

Characteristics: 1, 22, 22, 22

1 (Black, Condensed, 6 pt, Mixed case) 22 (Black, Condensed, 6 pt, Lower case)

PL-04273_5 Well / non-water / not intact / other (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

AND Product [PPO] = (Multiple [996], Unknown [0])

Label String: "("[Condition of Facility]")"

Characteristics: 22, 22, 22

22 (Black, Condensed, 6 pt, Lower case)

Symbol Samples

o Oil o Gas (damaged)

Well / water / perennial (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Point - Simple Component Ref #: P00041 Component Type: Color Token: Cyan

Description: Cyan 0.8mm diameter filled circle

Parameters:

Diameter: 0.8mm

Note: The component is a circle and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04050 Well / water / perennial (point) Product [PPO] = Water [122]

> AND Hydrologic Persistence [HYP] = Perennial [1]

> > Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04050_1 Well / water / perennial / intact / other (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

> AND Water Type [SCC] = Not Applicable [998], Other [999], Potable [9], Unknown [0]

Label String: [Name] Characteristics: 16

16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

PL-04050_2 Well / water / perennial / intact / alkaline (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

> Water Type [SCC] = Alkaline [1] AND

Label String: [Name] "(alkaline)"

Characteristics: 16, 23

> 16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case)

PL-04050 3 Well / water / perennial / intact / salt (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

> AND Water Type [SCC] = (Mineral [4], Salty [10])

Label String: [Name] "(salt)" Characteristics: 16, 23

16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

23 (Cyan, Condensed, Italic, 6 pt, Lower case)

PL-04050 4 Well / water / perennial / not intact / other (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

Water Type [SCC] = Not Applicable [998], Other [999], Potable [9], Unknown [0] AND

Label String: [Name] "("[Condition of Facility]")"

Characteristics: 16, 23, 23, 23

> 16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case)

PL-04050 5 Well / water / perennial / not intact / alkaline (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

AND Water Type [SCC] = Alkaline [1]

Label String: [Name] "(alkaline)" "("[Condition of Facility]")"

Characteristics: 16, 23, 23, 23, 23

16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case)

PL-04050_6 Well / water / perennial / not intact / salt (point)

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

AND Water Type [SCC] = (Mineral [4], Salty [10])

Label String: [Name] "(salt)" "("[Condition of Facility]")"

Characteristics: 16, 23, 23, 23, 23

16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case)

Symbol Samples

• Greensburg Well (alkaline)

Well / water / intermittent, dry (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple



Symbol Graphic

Component Ref #: P00040 Component Type: Point - Simple Color Token: Cyan

Description: Qanat/Water well intermittent

Parameters:

Diameter: 1.0mm
Line Weight: 0.15mm

Note: The component is an open circle.

Symbol Rules

Reference #: Description: Criteria:

PS-04051 Well / water / intermittent, dry

(point)

Product [PPO] = Water [122]

AND Hydrologic Persistence [HYP] = (Dry [4], Intermittent [2], Unknown [0])

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-9950, LP-9999

Reference #: Description: Criteria:

PL-04051_1 Well / water / intermittent, dry / intact / other (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Water Type [SCC] = Not Applicable [998], Other [999], Potable [9], Unknown [0]

Label String: [Name]
Characteristics: 16

16 (Cyan, Condensed, Italic, 6 pt, Mixed case)

PL-04051_2 Well / water / intermittent, dry / intact / alkaline (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

AND Water Type [SCC] = Alkaline [1]

Label String: [Name] "(alkaline)"

Characteristics:

16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case)

PL-04051_3 Well / water / intermittent, dry / intact / salt (point) Condition of Facility [FUN] = (Fully Functional [6], Unknown [0])

Water Type [SCC] = (Mineral [4], Salty [10]) AND

[Name] "(salt)" Label String: Characteristics:

16, 23

16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case)

PL-04051_4 Well / water / intermittent, dry / not intact / other (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

AND Water Type [SCC] = Not Applicable [998], Other [999], Potable [9], Unknown [0]

[Name] "("[Condition of Facility]")" Label String:

Characteristics: 16, 23, 23, 23

16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case)

PL-04051 5 Well / water / intermittent, dry / not intact / alkaline

(point)

Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

AND Water Type [SCC] = Alkaline [1]

Label String: [Name] "(alkaline)" "("[Condition of Facility]")"

Characteristics: 16, 23, 23, 23, 23

> 16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case)

PL-04051 6 Well / water / intermittent, dry / not intact / salt (point) Condition of Facility [FUN] = (Abandoned [2], Damaged [13], Destroyed [3],

Dismantled [4], Under Construction [1])

AND Water Type [SCC] = (Mineral [4], Salty [10])

[Name] "(salt)" "("[Condition of Facility]")" Label String:

Characteristics: 16, 23, 23, 23, 23

> 16 (Cyan, Condensed, Italic, 6 pt, Mixed case) 23 (Cyan, Condensed, Italic, 6 pt, Lower case)

> > Symbol Samples

o Woodingdean Well

Famous Well (salt) (destroyed,

Wind Turbine (AJ051)

Wind Turbine / non-obstruction (point)

Symbol Placement Instructions: Origin: Center of open circle

Symbol Type: Simple



Parameters:

Symbol Graphic

Component Ref #: P00143 Description:

Wind turbine

Component Type: Point - Shape Color Token:

Black

Note: See Annex H for detailed drawing instructions.

Reference #: Description: Criteria:

PS-04054 Wind Turbine / non-obstruction

(maint)

Height Above Surface Level [HGT] < 46

(point)

Symbol Samples

\$

Windmill (AJ050)

Windmill / non-obstruction (point)

Symbol Placement Instructions:

Origin: Center of open circle

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00144 Component Type: Point - Shape Color Token: Black

Description: Windmill

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04049 Windmill / non-obstruction (point) Height Above Surface Level [HGT] < 46

Symbol Samples

≬

Wood (EC030)

Generalization Rules (see Annex J): GA-9999

Wood / unknown (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

Symbol Graphic

Component Ref #: A00009 Component Type: Area - Fill Color Token: Green362-31

Description: Green362-31 area Fill

Parameters:

Screen Angle: 45 degrees
Screen Percent: 31%

Symbol Rules

Reference #: Description: Criteria:

PS-04795 Wood / unknown (area) Canopy Cover [DMT] >= 51

AND Foliage Type [TRE] = (Unknown[0])

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04795 1 Wood / unknown (area) N/A

Label String: [Name]
Characteristics: 3

3 (Black, Condensed, 6-16 pt, Mixed case)

Symbol Samples

Monongahela National Forest

Wood / evergreen (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound



Symbol Graphic

Note: Components A00009 and A00012 are combined into one symbol. Display level from bottom to top: Component A00009; Component

A00012.

Component Ref #: A00009 Component Type: Area - Fill Color Token: Green362-31

Description: Green362-31 area Fill

Parameters:

Screen Angle: 45 degrees
Screen Percent: 31%

Component Ref #: A00012 Component Type: Area - Pattern Color Token: Green362

Description: Green362 Evergreen Tree Fill

Parameters:

Area Pattern: AP-60, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04796 Wood / evergreen (area) Canopy Cover [DMT] >= 51

AND Foliage Type [TRE] = Evergreen [2]

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04796_1 Wood / evergreen (area) N/A

Label String: [Name]
Characteristics: 3

3 (Black, Condensed, 6-16 pt, Mixed case)

Symbol Samples






Wood / deciduous (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound



Symbol Graphic

Note: Components A00009 and A00011 are combined into one symbol. Display level from bottom to top: Component A00009; Component A00011.

Color Token:

Green362

Component Ref #: A00009 Component Type: Area - Fill Color Token: Green362-31

Description: Green362-31 area Fill

Parameters: Screen Angle:

45 degrees

Screen Percent: 31%

Screen Percent. 51%

Component Ref #: A00011 Component Type: Description: Green362 Deciduous Tree Fill

Parameters:

Area Pattern: AP-54, see Annex I

Symbol Rules

Area - Pattern

Reference #: Description: Criteria:

PS-04797 Wood / deciduous (area) Canopy Cover [DMT] >= 51

AND Foliage Type [TRE] = Deciduous [1]

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04797_1 Wood / deciduous (area) N/A

Label String: [Name]
Characteristics: 3

3 (Black, Condensed, 6-16 pt, Mixed case)

Symbol Samples





Wood / mixed (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Compound



Symbol Graphic

Note: Components A00009 and A00013 are combined into one symbol. Display level from bottom to top: Component A00009; Component A00013.

Component Ref #: A00009 Component Type: Area - Fill Color Token: Green362-31

Description: Green362-31 area Fill

Parameters:

Screen Angle: 45 degrees

Screen Percent: 31%

Component Ref #: A00013 Component Type: Area - Pattern Color Token: Green362

Description: Green362 Mixed Tree Fill

Parameters:

Area Pattern: AP-63, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04798 Wood / mixed (area) Canopy Cover [DMT] >= 51

AND Foliage Type [TRE] = Mixed [3]

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:

PL-04798_1 Wood / mixed (area) N/A

Label String: [Name]
Characteristics: 3

3 (Black, Condensed, 6-16 pt, Mixed case)

Symbol Samples





Wood / scattered (area)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple



Symbol Graphic

Component Ref #: A00047 Component Type: Area - Pattern Color Token: Green362

Description: Green362 Scattered Trees Fill

Parameters:

Area Pattern: AP-44, see Annex I

Symbol Rules

Reference #: Description: Criteria:

PS-04799 Wood / scattered (area) Canopy Cover [DMT] < 51

Label Rules

Label Placement Rules (see Annex J): LP-0050, LP-3506, LP-9999

Reference #: Description: Criteria:
PL-04799_1 Wood / scattered (area) N/A

Label String: [Name]

Characteristics: 3

3 (Black, Condensed, 6-16 pt, Mixed case)

Symbol Samples





Wood / all (line)

Symbol Placement Instructions: The symbol is applied to the geometry of the feature.

Symbol Type: Simple

000000000000000

Symbol Graphic

Note: Component P00111 is applied with a spacing of 0.5mm, center to center. The interval is such that the consecutive circles touch edges (centers of circles are 0.5mm apart).

Component Ref #: P00111 Component Type: Point - Simple Color Token: Green362

Description: Forest/curve

Parameters:

Diameter: 0.5mm
Line Weight: 0.1mm

Note: The component is an open circle.

Symbol Rules

Reference #: Description: Criteria:
PS-04800 Wood / all (line) All

Symbol Samples

Wood / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

4

Symbol Graphic

Component Ref #: P00030 Component Type: Point - Shape Color Token: Green362

Description: Tree other

Parameters:

Note: See Annex H for detailed drawing instructions.

Symbol Rules

Reference #: Description: Criteria:

PS-04808 Wood / all (point) All

Symbol Samples

4

Wreck (BD180)

Wreck / all (point)

Symbol Placement Instructions: Origin: Center of open circle Symbol Type: Simple **Symbol Graphic** Point - Shape Component Ref #: P00206 Component Type: Color Token: Black Description: Wreck Parameters: Note: See Annex H for detailed drawing instructions. Symbol Rules Reference #: Description: Criteria: PS-04659 Wreck / all (point) Αll Symbol Samples Shown with Tidal Water: Zoo (AK180) Generalization Rules (see Annex J): GA-9999, GC-9999 Zoo / all (area) The symbol is applied to the geometry of the feature. **Symbol Placement Instructions:** Symbol Type: Simple **Symbol Graphic** Line - Styled Component Ref #: L00210 Component Type: Color Token: Black Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap) Parameters: Dash Length: 1.0mm Line Weight: 0.1mm Dash Spacing: 0.5mm Symbol Rules Description: Criteria: Reference #: PS-04065 Zoo / all (area) ΑII Label Rules Label Placement Rules (see Annex J): LP-3506, LP-4813, LP-9999 Reference #: Description: Criteria: PL-04065_1 Zoo / all (area) N/A Label String: [Name] "Zoo" Characteristics: 1, 1 1 (Black, Condensed, 6 pt, Mixed case) Symbol Samples San Diego Zoo Zoo

Zoo / all (point)

Symbol Placement Instructions: Origin: Center of symbol

Symbol Type: Simple

Symbol Graphic

Component Ref #: P00006 Component Type: Point - Simple Color Token: Black

Description: Black filled square with all sides 0.8mm

Parameters:

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

Symbol Rules

Reference #: Description: Criteria:

PS-04511 Zoo / all (point) All

Label Rules

Label Placement Rules (see Annex J): LP-3505, LP-4813, LP-9999

Reference #: Description: Criteria:
PL-04511_1 Zoo / all (point) N/A

Label String: [Name] "Zoo"

Characteristics: 1, 1

1 (Black, Condensed, 6 pt, Mixed case)

Symbol Samples

Zoo Nashville Zoo

STD-DP-14-025 29 May 2015

Annex B - Feature Symbol Quick Reference Guide

This annex provides an abbreviated listing of each feature symbol from Annex A. Symbol graphics in this Annex are examples only and may not show every instance of potential labeling. Representative labels are shown only for those symbols which always require labeling. Some symbols may require varying descriptive labels based on attribution (i.e. "Gas" or "Oil" for the Product [PPO] attribute on Well/nonwater), and/or proper names when available. See Annex A for specific symbol and label rules.

Symbol	Number	Feature Code	Sample Graphic	Page
Administrative Boundary / international (line)	PS-04002	FA000	CANADA UNITED STATES OF AMERICA	A - 1
Administrative Boundary / other separation (line)	PS-04001	FA000	LEBANON DEMARCATION LINE ISRAEL	A - 1
Administrative Boundary / no defined boundary (line)	PS-04450	FA000	PAKISTAN NO DEFINED BOUNDARY INDIA	A - 3
Administrative Division / first-order (area)	PS-04005	FA003	NORTHERN TERRITORY SOUTHERN TERRITORY	A - 3
Administrative Division / second-order (area)	PS-04006	FA003	COBB FULTON	A - 4
Administrative Division / other (area)	PS-04007	FA003	HARRISON CONCORD	A - 5
Aeronautical Obstacle / single (point)	PS-04516	GB220	Aircraft hanger 72 (63)	A - 6
Aeronautical Obstacle / multiple (point)	PS-04517	GB220	Flagpoles 77 (67)	A - 6

Symbol	Number	Feature Code	Sample Graphic	Page
Aeronautical Radio Navigation Service / all (point)	PS-04675	GA034	⊙ Radio aid	A - 7
Aircraft Hangar / intact (area)	PS-04456	GB230	Hangar	A - 8
Aircraft Hangar / not intact (area)	PS-04039	GB230		A - 9
Aircraft Hangar / intact (point)	PS-04455	GB230	■ Hangar	A - 9
Aircraft Hangar / not intact (point)	PS-04040	GB230	a	A - 10
Aircraft Revetment / all (line)	PS-04008	GB050		A - 10
Aircraft Revetment / all (point)	PS-04037	GB050	\$	A - 11
Amusement Park / all (area)	PS-04009	AK030	Amusement park	A - 11
Amusement Park / intact (point)	PS-04459	AK030	■ Amusement park	A - 12

Symbol	Number	Feature Code	Sample Graphic	Page
Amusement Park / not intact (point)	PS-04883	AK030	Amusement park	A - 12
Approach Lighting System / all (point)	PS-04674	GB485	⊙ Approach lighting system	A - 13
Apron / all (area)	PS-04010	GB015		A - 14
Aqueduct / intact (area)	PS-04461	вно10	AQUEDUCT	A - 14
Aqueduct / not intact (area)	PS-04462	BH010	AQUEDUCT (DESTROYED)	A - 15
Aqueduct / on ground (line)	PS-04011	BH010	Aqueduct	A - 16
Aqueduct / elevated (line)	PS-04012	вно10	→ Aqueduct <	A - 16
Aqueduct / underground / without qanat shafts (line)	PS-04013	BH010	<u>Aqueduct</u>	A - 17

Symbol	Number	Feature Code	Sample Graphic	Page
Aqueduct / underground / with qanat shafts (line)	PS-04463	ВН010	000	A - 18
Aqueduct / all (point)	PS-04242	BH010	0	A - 19
Archeological Site / all (area)	PS-04017	AL012	[] Archeological site	A - 19
Archeological Site / all (point)	PS-04018	AL012	⊙ Archeological site	A - 20
Beach / pebble (area)	PS-04753	BA050		A - 20
Beach / sand (area)	PS-04754	BA050		A - 21
Beach / all (point)	PS-04755	BA050	Red Beach	A - 21
Berthing Structure / dry (area)	PS-04744	BB190	Pier	A - 22
Berthing Structure / not dry (area)	PS-04745	BB190	Quay	A - 23

Symbol	Number	Feature Code	Sample Graphic	Page
Berthing Structure / dry (line)	PS-04746	BB190	Pier	A - 23
Berthing Structure / not dry (line)	PS-04747	BB190	Wharf	A - 24
Bog / all (area)	PS-04021	BH015		A - 24
Breakwater / dry (area)	PS-04756	BB041	Breakwater	A - 25
Breakwater / not dry (area)	PS-04757	BB041	Breakwater	A - 26
Breakwater / dry (line)	PS-04758	BB041	Breakwater	A - 26
Breakwater / not dry (line)	PS-04759	BB041	Breakwater	A - 27
Bridge / fixed / non-pedestrian (line)	PS-04130	AQ040		A - 27
Bridge / non-fixed / non-pedestrian (line)	PS-04131	AQ040	<u></u>	A - 28

Symbol	Number	Feature Code	Sample Graphic	Page
Bridge / pedestrian (line)	PS-04132	AQ040	→	A - 29
Bridge / fixed / non-pedestrian (point)	PS-04470	AQ040	×	A - 30
Bridge / non-fixed / non-pedestrian (point)	PS-04650	AQ040	×	A - 30
Bridge / pedestrian (point)	PS-04645	AQ040	×	A - 31
Built Up Area / intact / dense (area)	PS-04068	AL020		A - 32
Built Up Area / intact / sparse or moderate (area)	PS-04069	AL020		A - 33
Built Up Area / not intact (area)	PS-04070	AL020	(destroyed)	A - 34
Built Up Area / all (point)	PS-04072	AL020	Monroe	A - 34
Cableway / non-obstruction (line)	PS-04155	AT041	<u>Cableway</u>	A - 35

Symbol	Number	Feature Code	Sample Graphic	Page
Cableway / obstruction (line)	PS-04158	AT041	Cableway 242 (72)	A - 36
Cairn / all (point)	PS-04073	AL025	& Cairn	A - 36
Camp / all (area)	PS-04481	AI030	Camp	A - 37
Camp / all (point)	PS-04480	AI030	∧ ^{Camp}	A - 38
Camp Site / all (area)	PS-04022	AK060	Campsite	A - 38
Camp Site / all (point)	PS-04482	AK060	∧ ^{Campsite}	A - 39
Canal / intact / perennial (area)	PS-04023	ВН020	CANAL	A - 39
Canal / intact / intermittent, dry (area)	PS-04024	ВН020		A - 40
Canal / not intact (area)	PS-04025	ВН020	CANAL (CONSTRUCTION)	A - 41

Symbol	Number	Feature Code	Sample Graphic	Page
Canal / intact / perennial (line)	PS-04026	BH020	Canal	A - 42
Canal / not intact / intermittent, dry (line)	PS-04027	ВН020	Canal (construction)	A - 43
Cane / all (area)	PS-04028	EC010	n. n. n. n. n. n. n. n. n. n. n. n.	A - 44
Cart Track / all (line)	PS-04128	AP010		A - 44
Catalytic Cracker / non-obstruction / intact (point)	PS-04029	AC020	■ Catalytic cracker	A - 45
Catalytic Cracker / non-obstruction / not intact (point)	PS-04752	AC020	в	A - 46
Causeway Structure / all (line)	PS-04136	AQ063	CAUSEWAY	A - 46
Cave Mouth / all (point)	PS-04032	DB029	-≺	A - 47

Symbol	Number	Feature Code	Sample Graphic	Page
Cemetery / other (area)	PS-04078	AL030		A - 47
Cemetery / buddhism (area)	PS-04075	AL030		A - 48
Cemetery / christian (area)	PS-04076	AL030	[<u>]</u>	A - 49
Cemetery / islam (area)	PS-04074	AL030	[<u>-Y</u> -]	A - 49
Cemetery / judaism (area)	PS-04077	AL030		A - 50
Cemetery / other (point)	PS-04083	AL030	Δ	A - 50
Cemetery / buddhism (point)	PS-04080	AL030	u	A - 51
Cemetery / christian (point)	PS-04079	AL030	ţ	A - 52
Cemetery / islam (point)	PS-04081	AL030	Y	A - 52

Symbol	Number	Feature Code	Sample Graphic	Page
Cemetery / judaism (point)	PS-04082	AL030	Ţ	A - 53
Checkpoint / all (point)	PS-04033	AH070	€	A - 53
Circular Irrigation System / all (area)	PS-04303	AJ010	Circular irrigation system	A - 54
Cistern / all (point)	PS-04052	BI010		A - 54
Cleared Way / all (area)	PS-04853	EC040	{NO SYMBOL}	A - 55
Communication Line / non-obstruction (line)	PS-04729	AT060	· · · · · · · · · · · · · · · · · · ·	A - 55
Communication Line / obstruction (line)	PS-04730	AT060	Communication line 242 (72)	A - 56
Communication Station / non-obstruction (area)	PS-04726	AT050	Communication station	A - 57

Symbol	Number	Feature Code	Sample Graphic	Page
Communication Station / non-obstruction / intact (point)	PS-04727	AT050	Communication station	A - 57
Communication Station / non-obstruction / not intact (point)	PS-04728	AT050	Communication station	A - 58
Conveyor / non-obstruction (line)	PS-04034	AF020	<u>Conveyor</u>	A - 59
Conveyor / obstruction (line)	PS-04886	AF020	Conveyor 243 (71)	A - 59
Conveyor / non-obstruction (point)	PS-04887	AF020	O Conveyor	A - 60
Conveyor / obstruction (point)	PS-04888	AF020	Conveyor 245 (72)	A - 60
Crane / non-obstruction (point)	PS-04038	AF040	•	A - 61
Crevasse / all (area)	PS-04496	BJ031	Crevasse	A - 61

Symbol	Number	Feature Code	Sample Graphic	Page
Crevasse / all (line)	PS-04497	BJ031	Crevasse	A - 62
Crevice / all (area)	PS-04498	DB061	Crevice	A - 63
Crevice / all (line)	PS-04499	DB061	Crevice	A - 63
Crop Land / dry crops (area)	PS-04304	EA010		A - 64
Crop Land / irrigated crops (area)	PS-04019	EA010		A - 65
Culvert / all (point)	PS-04705	AQ065	><	A - 65
Cut / all (line)	PS-04243	DB070		A - 66
Cut Line / all (line)	PS-04244	DB071		A - 66
Dam / hard (area)	PS-04214	BI020	Dam	A - 67

Symbol	Number	Feature Code	Sample Graphic	Page
Dam / loose (area)	PS-04215	BI020	Dam	A - 68
Dam / hard / transportation (line)	PS-04217	BI020	Dam	A - 68
Dam / loose / transportation (line)	PS-04502	BI020	Dam	A - 69
Dam / hard / no transportation (line)	PS-04216	BI020		A - 70
Dam / loose / no transportation (line)	PS-04429	BI020		A - 70
Dam / hard (point)	PS-04218	BI020	-	A - 71
Dam / loose (point)	PS-04430	BI020	-	A - 71
Dish Aerial / non-obstruction (point)	PS-04152	AT010	¥	A - 72
Disposal Site / non-obstruction (area)	PS-04278	AB000	Disposal site	A - 72

Symbol	Number	Feature Code	Sample Graphic	Page
Ditch / perennial (area)	PS-04179	вн030		A - 73
Ditch / intermittent, dry (area)	PS-04180	вн030		A - 74
Ditch / perennial (line)	PS-04181	ВН030		A - 74
Ditch / intermittent, dry (line)	PS-04182	ВН030		A - 75
Dragon's Teeth / all (area)	PS-04503	AL060	Dragon's teeth	A - 75
Dragon's Teeth / all (line)	PS-04504	AL060	———— Dragon's teeth	A - 76
Dry Dock / all (area)	PS-04168	BB090	Dry dock	A - 77
Electric Power Station / all (area)	PS-04293	AD010	Power plant	A - 77
Electric Power Station / intact (point)	PS-04294	AD010	Power plant	A - 78

Symbol	Number	Feature Code	Sample Graphic	Page
Electric Power Station / not intact (point)	PS-04896	AD010	Power plant	A - 79
Elevation Contour / land / index (line)	PS-04342	CA010		A - 79
Elevation Contour / land / index / approximate (line)	PS-04343	CA010		A - 80
Elevation Contour / land / intermediate (line)	PS-04346	CA010		A - 81
Elevation Contour / land / intermediate / approximate (line)	PS-04347	CA010		A - 82
Elevation Contour / land / half auxiliary (line)	PS-04350	CA010		A - 82
Elevation Contour / land / quarter auxiliary (line)	PS-04360	CA010		A - 83
Elevation Contour / land / mound / index (line)	PS-04358	CA010	200	A - 84

Symbol	Number	Feature Code	Sample Graphic	Page
Elevation Contour / land / mound / intermediate (line)	PS-04359	CA010	180	A - 85
Elevation Contour / land / depression / index (line)	PS-04354	CA010	100	A - 86
Elevation Contour / land / depression / intermediate (line)	PS-04356	CA010		A - 87
Elevation Contour / land / depression / auxiliary (line)	PS-04362	CA010	(10)	A - 87
Elevation Contour / snow, ice / index (line)	PS-04344	CA010		A - 88
Elevation Contour / snow, ice / index / approximate (line)	PS-04345	CA010	300	A - 89
Elevation Contour / snow, ice / intermediate (line)	PS-04348	CA010		A - 90
Elevation Contour / snow, ice / intermediate / approximate (line)	PS-04349	CA010		A - 91

Symbol	Number	Feature Code	Sample Graphic	Page
Elevation Contour / snow, ice / half auxiliary (line)	PS-04351	CA010		A - 91
Elevation Contour / snow, ice / quarter auxiliary (line)	PS-04361	CA010		A - 92
Elevation Contour / snow, ice / mound / index (line)	PS-04738	CA010	200	A - 93
Elevation Contour / snow, ice / mound / intermediate (line)	PS-04739	CA010	180	A - 94
Elevation Contour / snow, ice / depression / index (line)	PS-04355	CA010	100	A - 95
Elevation Contour / snow, ice / depression / intermediate (line)	PS-04357	CA010		A - 96
Elevation Contour / snow, ice / depression / auxiliary (line)	PS-04363	CA010	(10)	A - 97
Embankment / all (area)	PS-04246	DB090		A - 98

Symbol	Number	Feature Code	Sample Graphic	Page
Embankment / fill (line)	PS-04248	DB090		A - 98
Embankment / with transportation (line)	PS-04250	DB090		A - 99
Embankment / without transportation (line)	PS-04251	DB090		A - 99
Engineered Earthwork / all (line)	PS-04508	AH025	Trench	A - 100
Entrance and/or Exit / all (point)	PS-04725	AQ090)	A - 101
Esker / all (line)	PS-04509	DB100	Esker	A - 101
Extraction Mine / intact / not peat (area)	PS-04266	AA010	*	A - 102
Extraction Mine / not intact / not peat (area)	PS-04267	AA010	[*]	A - 104
Extraction Mine / peat (area)	PS-04268	AA010	Peat cuttings	A - 105

Symbol	Number	Feature Code	Sample Graphic	Page
Extraction Mine / intact / not peat (point)	PS-04269	AA010	*	A - 106
Extraction Mine / not intact / not peat (point)	PS-04270	AA010	*	A - 108
Extraction Mine / peat (point)	PS-04271	AA010	Peat cuttings	A - 110
Facility / all (area)	PS-04280	AL010	_	A - 110
Facility / intact (point)	PS-04286	AL010	Government •	A - 112
Facility / not intact (point)	PS-04291	AL010	_ Transport	A - 113
Fairground / all (area)	PS-04057	AK090	[] Fairgrounds	A - 114
Fairground / all (point)	PS-04510	AK090	Fairgrounds	A - 114
Fence / all (line)	PS-04084	AL070	x—x—x—x—x—x—x—x—x	A - 115

Symbol	Number	Feature Code	Sample Graphic	Page
Ferry Crossing / all (line)	PS-04137	AQ070	Ferry	A - 115
Ferry Crossing / all (point)	PS-04531	AQ070	Ferry	A - 116
Firing Range / all (area)	PS-04532	FA015	Firing range	A - 116
Firing Range / all (point)	PS-04838	FA015	⊙ Firing range	A - 117
Fish Farm Facility / all (area)	PS-04184	BH051	Fish farm	A - 118
Fish Farm Facility / intact (point)	PS-04530	BH051	F ish farm	A - 118
Fish Farm Facility / not intact (point)	PS-04673	BH051	□ Fish farm	A - 119
Flare Pipe / non-obstruction (point)	PS-04041	AF070	ĺ	A - 120
Flume / on surface (line)	PS-04773	вн060	Flume	A - 120

Symbol	Number	Feature Code	Sample Graphic	Page
Flume / below surface (line)	PS-04774	ВН060	Flume	A - 121
Ford / all (point)	PS-04186	ВН070	Ford	A - 121
Forest Clearing / all (area)	PS-04852	EC060	{NO SYMBOL}	A - 122
Fortification / all (area)	PS-04046	AH050	д	A - 122
Fortification / all (point)	PS-04047	AH050	д	A - 123
General Building / non-obstruction / intact / generic or important (area)	PS-04680	AL015	-	A - 124
General Building / non-obstruction / intact / christian (area)	PS-04681	AL015	<u> </u>	A - 125
General Building / non-obstruction / intact / islam (area)	PS-04682	AL015	ĭ	A - 125

Symbol	Number	Feature Code	Sample Graphic	Page
General Building / non-obstruction / intact / pagoda (area)	PS-04683	AL015	±	A - 126
General Building / non-obstruction / intact / stupa (area)	PS-04684	AL015	A	A - 127
General Building / non-obstruction / intact / judaism (area)	PS-04685	AL015	Ī	A - 127
General Building / non-obstruction / intact / temple (area)	PS-04686	AL015	#	A - 128
General Building / non-obstruction / intact / house of worship (area)	PS-04687	AL015	House of worship	A - 129
General Building / non-obstruction / intact / school (area)	PS-04688	AL015	<u></u>	A - 130
General Building / non-obstruction / intact / hospital (area)	PS-04689	AL015	⊕	A - 130

Symbol	Number	Feature Code	Sample Graphic	Page
General Building / non-obstruction / intact / diplomatic (area)	PS-04691	AL015	£	A - 131
General Building / non-obstruction / intact / petrol sale (area)	PS-04708	AL015	Ÿ	A - 132
General Building / non-obstruction / not intact (area)	PS-04692	AL015		A - 132
General Building / non-obstruction / intact / generic (point)	PS-04693	AL015		A - 133
General Building / non-obstruction / intact / important (point)	PS-04694	AL015	■ Police	A - 134
General Building / non-obstruction / intact / christian (point)	PS-04695	AL015	‡	A - 135
General Building / non-obstruction / intact / minaret (point)	PS-04696	AL015	Š	A - 135

Symbol	Number	Feature Code	Sample Graphic	Page
General Building / non-obstruction / intact / islam (point)	PS-04697	AL015	Y	A - 136
General Building / non-obstruction / intact / pagoda (point)	PS-04698	AL015	÷	A - 137
General Building / non-obstruction / intact / stupa (point)	PS-04699	AL015	۵	A - 137
General Building / non-obstruction / intact / judaism (point)	PS-04700	AL015	ī	A - 138
General Building / non-obstruction / intact / temple (point)	PS-04701	AL015	н	A - 139
General Building / non-obstruction / intact / house of worship (point)	PS-04704	AL015	House of worship	A - 139
General Building / non-obstruction / intact / school (point)	PS-04706	AL015	1	A - 140

Symbol	Number	Feature Code	Sample Graphic	Page
General Building / non-obstruction / intact / hospital (point)	PS-04707	AL015	•	A - 141
General Building / non-obstruction / intact / diplomatic (point)	PS-04476	AL015	₽	A - 141
General Building / non-obstruction / intact / petrol sale (point)	PS-04709	AL015	Y	A - 142
General Building / non-obstruction / not intact (point)	PS-04714	AL015	D	A - 143
Geologic Fault / all (line)	PS-04252	DB110	Fault	A - 143
Geophysical Prospecting Grid / all (line)	PS-04899	FA090		A - 144
Geopolitical Entity / other (area)	PS-04537	FA002	DEMILITARIZED ZONE	A - 144
Geopolitical Entity / buffer zone (area)	PS-04876	FA002	GIBRALTAR-SPAIN NEUTRAL ZONE	A - 145

Symbol	Number	Feature Code	Sample Graphic	Page
Geothermal Outlet / all (area)	PS-04253	DB115	Geothermal outlet	A - 146
Geothermal Outlet / all (point)	PS-04254	DB115	Geothermal outlet	A - 146
Glacier / all (area)	PS-04228	BJ030		A - 147
Golf Course / all (area)	PS-04058	AK100	Golf course	A - 148
Grain Elevator / non-obstruction / intact (area)	PS-04106	AM030	■ Grain elevator	A - 148
Grain Elevator / non-obstruction / not intact (area)	PS-04781	AM030	Grain elevator	A - 149
Grain Elevator / non-obstruction (point)	PS-04105	AM030	⊙ Grain elevator	A - 150
Grain Storage Structure / non-obstruction / intact (area)	PS-04101	AM020	■ Silo	A - 150

Symbol	Number	Feature Code	Sample Graphic	Page
Grain Storage Structure / non-obstruction / not intact (area)	PS-04784	AM020	Silo	A - 151
Grain Storage Structure / non-obstruction (point)	PS-04102	AM020	⊙ Silo	A - 152
Grassland / all (area)	PS-04030	EB010	is the tale tale tale tale tale tale tale tal	A - 152
Greenhouse / all (area)	PS-04396	AJ110		A - 153
Greenhouse / all (point)	PS-04397	AJ110	8	A - 153
Groin / dry (area)	PS-04760	BB043	Groin	A - 154
Groin / not dry (area)	PS-04761	BB043	Groin	A - 154
Groin / dry (line)	PS-04762	BB043	Groin	A - 155

Symbol	Number	Feature Code	Sample Graphic	Page
Groin / not dry (line)	PS-04763	BB043	Groin	A - 156
Gully / all (area)	PS-04566	DB200	Coley Gully	A - 156
Gully / all (line)	PS-04567	DB200	Water Mill Gully	A - 157
Harbour / all (area)	PS-04602	BB005	Pearl Harbor	A - 157
Hazardous Rock / exposed (point)	PS-04658	BD130	*	A - 158
Heating Facility / all (area)	PS-04299	AD050	Heating facility	A - 158
Heating Facility / intact (point)	PS-04300	AD050	■ Heating facility	A - 159
Heating Facility / not intact (point)	PS-04907	AD050	_в Heating facility	A - 159
Hedgerow / all (line)	PS-04307	EA020		A - 160

Symbol	Number	Feature Code	Sample Graphic	Page
Helipad / non-hospital (point)	PS-04326	GB030	Θ	A - 161
Helipad / hospital (point)	PS-04327	GB030	H	A - 161
Heliport / all (area)	PS-04328	GB035	Palmetto Heliport 290	A - 162
Holding Pen / all (area)	PS-04048	AJ030	Holding pen	A - 163
Holding Pen / all (point)	PS-04542	AJ030		A - 163
Hop Field / all (area)	PS-04316	EA055	Hops:	A - 164
Hut / all (point)	PS-04545	AL099	•	A - 164
Hydrocarbons Field / all (area)	PS-04548	AA052	Hydrocarbons field	A - 165
Ice Cliff / all (line)	PS-04229	BJ040		A - 165

Symbol	Number	Feature Code	Sample Graphic	Page
Ice Peak / all (point)	PS-04230	BJ060		A - 166
Ice Route / all (line)	PS-04138	AQ075	ICE ROUTE	A - 166
Island / all (area)	PS-04164	BA030	MAUI	A - 167
Lake / perennial (area)	PS-04764	вн080		A - 168
Lake / intermittent, dry (area)	PS-04765	вн080		A - 168
Land Aerodrome / all (area)	PS-04317	GB005	Washington Dulles Intl KIAD Hard surface 75	A - 169
Land Subject To Inundation / not controlled (area)	PS-04192	вно90		A - 170
Land Subject To Inundation / controlled (area)	PS-04193	вно90		A - 171
Land Water Boundary / other (line)	PS-04162	BA010		A - 171

Number	Feature Code	Sample Graphic	Page
PS-04163	BA010		A - 172
PS-04315	GB040	⊙ Launch pad	A - 172
PS-04948	No Code		A - 173
PS-04949	No Code		A - 173
PS-04950	No Code		A - 174
PS-04221	BI030	Lock	A - 174
PS-04222	BI030	< <	A - 175
PS-04223	BI030	«	A - 175
PS-04302	ED030		A - 176
	PS-04163 PS-04315 PS-04949 PS-04950 PS-04221 PS-04222	PS-04163 BA010 PS-04315 GB040 PS-04948 No Code PS-04949 No Code PS-04950 No Code PS-04221 BI030 PS-04222 BI030	PS-04163 BA010

Symbol	Number	Feature Code	Sample Graphic	Page
Mariculture Site / all (area)	PS-04767	BH050	Mariculture site	A - 177
Mariculture Site / intact (point)	PS-04779	ВН050	Mariculture site	A - 177
Mariculture Site / not intact (point)	PS-04780	ВН050	_n Mariculture site	A - 178
Maritime Signal Station / intact (point)	PS-04599	BB155	Signal station	A - 178
Maritime Signal Station / not intact (point)	PS-04103	BB155	□ Signal station	A - 179
Marsh / all (area)	PS-04312	ED010		A - 180
Memorial Monument / non-obstruction (point)	PS-04087	AL130	•	A - 181
Military Installation / all (area)	PS-04324	SU001	MILITARY INSTALLATION	A - 181
Military Installation / intact (point)	PS-04325	SU001	Military installation	A - 182

Symbol	Number	Feature Code	Sample Graphic	Page
Military Installation / not intact (point)	PS-04913	SU001	Military installation	A - 183
Mineral Pile / non-obstruction (area)	PS-04109	AM040	[] Mineral pile	A - 183
Mineral Pile / non-obstruction (point)	PS-04110	AM040	⊙ Mineral pile	A - 184
Mooring Mast / non-obstruction (point)	PS-04139	AQ110	6™	A - 185
Moraine / all (area)	PS-04227	BJ020		A - 185
Mountain Pass / all (point)	PS-04255	DB150) (1362	A - 186
Named Location / all (point)	PS-04323	ZD040	BADLANDS	A - 186
Natural Pool / perennial (point)	PS-04210	BH170	?	A - 187
Natural Pool / intermittent, dry (point)	PS-04211	BH170	Ŷ	A - 187

Symbol	Number	Feature Code	Sample Graphic	Page
Oasis / all (area)	PS-04310	EC020	Oasis	A - 188
Oasis / all (point)	PS-04654	EC020	*	A - 189
Offshore Platform / non-obstruction (point)	PS-04201	BD110	□ Platform	A - 189
Orchard / all (area)	PS-04305	EA040		A - 190
Park / all (area)	PS-04059	AK120	Park	A - 190
Park / all (point)	PS-04594	AK120	_≡ Park	A - 191
Particle Accelerator / all (area)	PS-04090	AL140	Particle accelerator	A - 192
Particle Accelerator / all (line)	PS-04597	AL140	Particle accelerator	A - 192
Penstock / on surface (line)	PS-04194	ВН110	<u>Penstock</u>	A - 193

Symbol	Number	Feature Code	Sample Graphic	Page
Penstock / below surface (line)	PS-04195	BH110	Penstock	A - 193
Penstock / above surface (line)	PS-04196	BH110	→ Penstock ←	A - 194
Pipeline / on surface / not water (line)	PS-04329	AQ113		A - 195
Pipeline / on surface / water (line)	PS-04330	AQ113		A - 195
Pipeline / below surface / not water (line)	PS-04331	AQ113		A - 196
Pipeline / below surface / water (line)	PS-04332	AQ113	→ — →	A - 197
Pipeline / above surface / not water (line)	PS-04333	AQ113	→	A - 198
Pipeline / above surface / water (line)	PS-04334	AQ113	≻••	A - 198
Point of Change / all (point)	PS-04857	No Code	I	A - 199

Symbol	Number	Feature Code	Sample Graphic	Page
Power Line / non-obstruction (line)	PS-04433	AT030	- 1 1	A - 200
Power Line / obstruction (line)	PS-04474	AT030	Powerline 242 (72)	A - 200
Power Substation / all (area)	PS-04297	AD030	[- <u>4</u> -]	A - 201
Power Substation / all (point)	PS-04298	AD030	ź	A - 202
Processing Facility / all (area)	PS-04410	AC000	Processing facility	A - 202
Processing Facility / intact (point)	PS-04411	AC000	Processing facility	A - 203
Processing Facility / not intact (point)	PS-04412	AC000	Processing facility	A - 204
Protection Shed / all (line)	PS-04558	AL210	Protection shed	A - 205
Protection Shed / all (point)	PS-04563	AL210	Protection shed	A - 206

Symbol	Number	Feature Code	Sample Graphic	Page
Public Square / all (area)	PS-04091	AL170	Union Square	A - 206
Pumping Station / all (area)	PS-04142	AQ116	Pumping station	A - 207
Pumping Station / intact (point)	PS-04143	AQ116	Pumping station	A - 207
Pumping Station / not intact (point)	PS-04917	AQ116	Pumping station	A - 208
Pylon / non-obstruction (point)	PS-04866	AT042	⊙ Pylon	A - 209
Pylon / obstruction (point)	PS-04947	AT042	Pylon 213 (49)	A - 209
Quarry / intact (area)	PS-04669	AA012	Quarry	A - 210
Quarry / not intact (area)	PS-04670	AA012	Quarry	A - 211
Quarry / intact (point)	PS-04671	AA012	☆ ^{Quarry}	A - 212

Symbol	Number	Feature Code	Sample Graphic	Page
Quarry / not intact (point)	PS-04672	AA012	ॐ ^{Quarry}	A - 213
Racetrack / all (line)	PS-04060	AK130	Racetrack	A - 214
Radar Station / intact (point)	PS-04159	AT045	Radar station	A - 215
Radar Station / not intact (point)	PS-04918	AT045	_ Radar station	A - 215
Railway / intact / broad, standard / electrified / >= 2 tracks (line)	PS-04383	AN010	-1 1 1-	A - 216
Railway / intact / broad, standard / electrified / 1 track (line)	PS-04382	AN010		A - 217
Railway / intact / narrow / electrified / >= 2 tracks (line)	PS-04385	AN010	-7 <u>- 11 7- 11 7-</u>	A - 218
Railway / intact / narrow / electrified / 1 track (line)	PS-04384	AN010		A - 219

Symbol	Number	Feature Code	Sample Graphic	Page
Railway / intact / broad, standard / non- electrified / >= 2 tracks (line)	PS-04378	AN010		A - 220
Railway / intact / broad, standard / non- electrified / 1 track (line)	PS-04377	AN010		A - 222
Railway / intact / narrow / non-electrified / >= 2 tracks (line)	PS-04395	AN010	- 11 - 11 - 11 -	A - 223
Railway / intact / narrow / non-electrified / 1 track (line)	PS-04394	AN010		A - 224
Railway / not intact / broad, standard / electrified / >= 2 tracks (line)	PS-04391	AN010	(CONSTRUCTION)	A - 225
Railway / not intact / broad, standard / electrified / 1 track (line)	PS-04390	AN010	——————————————————————————————————————	A - 226
Railway / not intact / narrow / electrified / >= 2 tracks (line)	PS-04393	AN010	(CONSTRUCTION)	A - 227

Symbol	Number	Feature Code	Sample Graphic	Page
Railway / not intact / narrow / electrified / 1 track (line)	PS-04392	AN010	(DAMAGED)	A - 228
Railway / not intact / broad, standard / non- electrified / >= 2 tracks (line)	PS-04387	AN010	——————————————————————————————————————	A - 229
Railway / not intact / broad, standard / non- electrified / 1 track (line)	PS-04386	AN010	(CONSTRUCTION)	A - 230
Railway / not intact / narrow / non-electrified / >= 2 tracks (line)	PS-04389	AN010	(CONSTRUCTION)	A - 231
Railway / not intact / narrow / non-electrified / 1 track (line)	PS-04388	AN010	(CONSTRUCTION)	A - 233
Railway / intact / railway in road (line)	PS-04379	AN010		A - 234
Railway / not intact / railway in road (line)	PS-04439	AN010	(DAMAGED)	A - 234
Railway / intact / carline (line)	PS-04380	AN010	-+ + + + + + + -	A - 235

Symbol	Number	Feature Code	Sample Graphic	Page
Railway / not intact / carline (line)	PS-04438	AN010	(CONSTRUCTION)	A - 236
Railway / dismantled, destroyed (line)	PS-04381	AN010	Dismantled railway	A - 237
Railway Sidetrack / intact / broad, standard / electrified (line)	PS-04124	AN050		A - 237
Railway Sidetrack / intact / narrow / electrified (line)	PS-04125	AN050		A - 238
Railway Sidetrack / intact / broad, standard / non-electrified (line)	PS-04122	AN050		A - 239
Railway Sidetrack / intact / narrow / non- electrified (line)	PS-04123	AN050		A - 239
Railway Sidetrack / not intact / broad, standard / electrified (line)	PS-04442	AN050		A - 240
Railway Sidetrack / not intact / narrow / electrified (line)	PS-04443	AN050		A - 241

Symbol	Number	Feature Code	Sample Graphic	Page
Railway Sidetrack / not intact / broad, standard / non-electrified (line)	PS-04440	AN050		A - 241
Railway Sidetrack / not intact / narrow / non- electrified (line)	PS-04441	AN050		A - 242
Railway Sidetrack / intact / railway in road (line)	PS-04953	AN050		A - 242
Railway Sidetrack / not intact / railway in road (line)	PS-04954	AN050		A - 243
Railway Sidetrack / dismantled, destroyed (line)	PS-04919	AN050		A - 244
Railway Turntable / all (point)	PS-04127	AN075	0	A - 244
Railway Yard / all (area)	PS-04126	AN060	POTOMAC RAILWAY YARD	A - 245
Rapids / all (area)	PS-04197	BH120	Rapids	A - 245

Symbol	Number	Feature Code	Sample Graphic	Page
Rapids / all (line)	PS-04198	BH120	Rapids	A - 246
Rapids / all (point)	PS-04199	BH120	≘ Rapids	A - 247
Recreational Pier / all (area)	PS-04063	AK190	Pier	A - 247
Recreational Pier / all (line)	PS-04064	AK190	Pier	A - 248
Recycling Site / all (area)	PS-04279	AB010	[] Recycling site	A - 248
Reef / exposed (area)	PS-04663	BD120	Econology of the second of the	A - 249
Reef / exposed (line)	PS-04662	BD120		A - 250
Reef / exposed (point)	PS-04661	BD120	*	A - 250
Reservoir / intact / perennial (area)	PS-04785	BH130		A - 251

Symbol	Number	Feature Code	Sample Graphic	Page
Reservoir / intact / intermittent, dry (area)	PS-04786	BH130		A - 252
Reservoir / not intact (area)	PS-04787	BH130		A - 252
Rice Field / all (area)	PS-04200	BH135		A - 253
Rig / non-obstruction (point)	PS-04272	AA040	*	A - 254
River / perennial (area)	PS-04202	BH140		A - 254
River / intermittent, dry (area)	PS-04203	BH140		A - 255
River / perennial (line)	PS-04204	BH140		A - 256
River / intermittent, dry (line)	PS-04205	BH140		A - 256
River Flow Arrow (point)	PS-04649	No Code	→	A - 257

Symbol	Number	Feature Code	Sample Graphic	Page
Road / intact / divided / very wide median (line)	PS-04877	AP030		A - 257
Road / intact / divided / wide median (curve)	PS-04570	AP030		A - 258
Road / intact / divided / narrow median (line)	PS-04369	AP030		A - 260
Road / intact / all weather / hard surface / no median / >= 4 lanes / primary (line)	PS-04368	AP030		A - 261
Road / intact / all weather / hard surface / no median / >= 4 lanes / secondary (line)	PS-04373	AP030		A - 262
Road / intact / all weather / hard surface / no median / 2 or 3 lanes / primary (line)	PS-04720	AP030		A - 264
Road / intact / all weather / hard surface / no median / 2 or 3 lanes / secondary (line)	PS-04722	AP030		A - 265
Road / intact / all weather / hard surface / no median / 1 lane / primary (line)	PS-04367	AP030		A - 266

Symbol	Number	Feature Code	Sample Graphic	Page
Road / intact / all weather / hard surface / no median / 1 lane / secondary (line)	PS-04372	AP030		A - 267
Road / intact / all weather / loose surface / no median / >= 4 lanes / primary (line)	PS-04371	AP030		A - 268
Road / intact / all weather / loose surface / no median / >= 4 lanes / secondary (line)	PS-04376	AP030		A - 269
Road / intact / all weather / loose surface / no median / 2 or 3 lanes / primary (line)	PS-04721	AP030		A - 270
Road / intact / all weather / loose surface / no median / 2 or 3 lanes / secondary (line)	PS-04723	AP030		A - 272
Road / intact / all weather / loose surface / no median / 1 lane / primary (line)	PS-04370	AP030		A - 273
Road / intact / all weather / loose surface / no median / 1 lane / secondary (line)	PS-04375	AP030		A - 274
Road / intact / fair weather (line)	PS-04366	AP030		A - 275

276
276
277
278
279
279
280
281
281

Symbol	Number	Feature Code	Sample Graphic	Page
Roadside Rest Area / intact (point)	PS-04604	AQ135	■ Rest area	A - 282
Roadside Rest Area / not intact (point)	PS-04920	AQ135	Rest area	A - 282
Rock Formation / all (area)	PS-04256	DB160	₩	A - 283
Rock Formation / all (line)	PS-04088	DB160	шшшш	A - 284
Rock Formation / all (point)	PS-04257	DB160	*	A - 284
Roundhouse / all (area)	PS-04605	AN076	Roundhouse	A - 285
Roundhouse / all (point)	PS-04606	AN076	• Roundhouse	A - 286
Ruins / all (area)	PS-04092	AL200	[Ruins	A - 286
Ruins / all (point)	PS-04093	AL200	÷	A - 287

Symbol	Number	Feature Code	Sample Graphic	Page
Runway / intact (area)	PS-04428	GB055	Hard surface	A - 287
Runway / not intact (area)	PS-04951	GB055	Surface unknown	A - 288
Sabkha / all (area)	PS-04209	BH160		A - 289
Salt Evaporator / all (area)	PS-04208	BH155		A - 290
Salt Evaporator / all (point)	PS-04607	BH155	□ Salt evaporator	A - 290
Salt Flat / all (area)	PS-04608	BH150	Salt flat	A - 291
Sand Dunes / unknown (area)	PS-04258	DB170	Dunes	A - 292
Sand Dunes / crescent (area)	PS-04259	DB170		A - 292
Sand Dunes / dome (area)	PS-04264	DB170		A - 293

Page
A - 293
A - 294
A - 294
A - 295
A - 295
A - 296
A - 297
A - 297
A - 298

Symbol	Number	Feature Code	Sample Graphic	Page
Settling Pond / all (point)	PS-04220	AC030		A - 298
Shanty Town / all (area)	PS-04071	AL208		A - 299
Shed / all (area)	PS-04615	AL019	-	A - 300
Shed / all (point)	PS-04616	AL019		A - 300
Ski Jump / non-obstruction (line)	PS-04625	AK150	Ski jump	A - 301
Ski Jump / obstruction (line)	PS-04928	AK150	Ski jump 228 (77)	A - 301
Ski Jump / non-obstruction (point)	PS-04626	AK150	А	A - 302
Ski Jump / obstruction (point)	PS-04929	AK150	Ski jump 245 (72)	A - 302
Slipway / dry (area)	PS-04750	BB240	Slipway	A - 303

Symbol	Number	Feature Code	Sample Graphic	Page
Slipway / not dry (area)	PS-04751	BB240	Slipway	A - 304
Sluice Gate / all (line)	PS-04224	BI040	Sluice gate	A - 304
Sluice Gate / all (point)	PS-04225	BI040	<	A - 305
Smokestack / non-obstruction (point)	PS-04301	AF010	F	A - 305
Snow Ice Field / all (area)	PS-04232	BJ100		A - 306
Soil Surface Region / distorted surface (area)	PS-04235	DA010	Racky"	A - 306
Soil Surface Region / gravel (area)	PS-04237	DA010		A - 307
Soil Surface Region / sand (area)	PS-04238	DA010		A - 308
Soil Surface Region / other (area)	PS-04880	DA010	Limestone	A - 308

Symbol	Number	Feature Code	Sample Graphic	Page
Solar Panel / all (point)	PS-04719	AD020	⊙ Solar panel	A - 309
Spillway / all (area)	PS-04629	BH165	Spillway	A - 310
Spillway / all (line)	PS-04630	BH165	S <u>pillwa</u> y	A - 310
Sports Ground / all (area)	PS-04631	AK040	S	A - 311
Sports Ground / all (point)	PS-04632	AK040	(5)	A - 311
Spot Elevation / not water (point)	PS-04322	CA030	*305	A - 312
Spot Elevation / water (point)	PS-04613	CA030	210	A - 313
Stadium / all (area)	PS-04061	AK160	Stadium	A - 313
Stadium / non-obstruction / intact (point)	PS-04062	AK160	Stadium ■	A - 314

Symbol	Number	Feature Code	Sample Graphic	Page
Stadium / non-obstruction / not intact (point)	PS-04933	AK160		A - 315
Steep Terrain Face / all (line)	PS-04240	DB010		A - 315
Stopway / all (area)	PS-04633	GB045		A - 316
Storage Depot / all (area)	PS-04100	AM010	Storage depot	A - 316
Storage Depot / all (point)	PS-04634	AM010	■ Storage depot	A - 317
Storage Tank / non-obstruction / intact (area)	PS-04115	AM070	● Water	A - 318
Storage Tank / non-obstruction / not intact (area)	PS-04935	AM070	0	A - 318
Storage Tank / non-obstruction / intact / other (point)	PS-04116	AM070	• Water	A - 319

Symbol	Number	Feature Code	Sample Graphic	Page
Storage Tank / non-obstruction / not intact (point)	PS-04936	AM070	o	A - 320
Storage Tank / non-obstruction / water tower (point)	PS-04614	AM070		A - 320
Structural Pile / all (area)	PS-04174	BD100	Piles	A - 321
Structural Pile / all (point)	PS-04175	BD100	° Pile	A - 322
Surface Bunker / all (point)	PS-04114	AM060	出	A - 322
Survey Point / geodetic (point)	PS-04491	ZB050	[△] 1351	A - 323
Survey Point / non-geodetic (point)	PS-04492	ZB050	BM • 2645	A - 324
Swamp / cypress (area)	PS-04313	ED020		A - 325

Symbol	Number	Feature Code	Sample Graphic	Page
Swamp / nipa (area)	PS-04335	ED020		A - 325
Swimming Pool / all (area)	PS-04635	AK170	_{ca} Pool	A - 326
Swimming Pool / all (point)	PS-04098	AK170	_{es} Pool	A - 327
Taxiway / all (area)	PS-04321	GB075		A - 327
Test Site / all (area)	PS-04314	FA100	Test site	A - 328
Thicket / all (area)	PS-04309	EB020		A - 329
Tidal Water / all (area)	PS-04165	BA040		A - 329
Tower / non-obstruction / communication (point)	PS-04561	AL241	&	A - 330
Tower / non-obstruction / control (point)	PS-04133	AL241	⊙ Control tower	A - 330

Symbol	Number	Feature Code	Sample Graphic	Page
Tower / non-obstruction / cooling (point)	PS-04035	AL241		A - 331
Tower / non-obstruction / light (point)	PS-04171	AL241	**	A - 331
Tower / non-obstruction / other (point)	PS-04096	AL241	Į	A - 332
Tower / non-obstruction / water (point)	PS-04119	AL241	1	A - 332
Trail / all (line)	PS-04129	AP050		A - 333
Training Wall / all (area)	PS-04740	BB140	Jetty	A - 333
Training Wall / all (line)	PS-04741	BB140	Jetty	A - 334
Transportation Station / all (area)	PS-04144	AQ125	Station	A - 334
Transportation Station / intact / railway (point)	PS-04408	AQ125	· ·	A - 335

Symbol	Number	Feature Code	Sample Graphic	Page
Transportation Station / intact / other (point)	PS-04427	AQ125	•	A - 336
Transportation Station / not intact (point)	PS-04241	AQ125	D D	A - 337
Tundra / all (area)	PS-04233	BJ110	TUNDRA	A - 337
Tunnel / road, taxiway (line)	PS-04149	AQ130) - (A - 338
Tunnel / railway, pedestrian, other (line)	PS-04146	AQ130	}(A - 338
Tunnel / inland waterway / wide (line)	PS-04147	AQ130) -(A - 339
Tunnel / inland waterway / narrow (line)	PS-04148	AQ130) {	A - 340
Vanishing Point / disappearing (point)	PS-04206	BH145	•	A - 341
Vanishing Point / dissipating (point)	PS-04207	BH145	>	A - 341

Symbol	Number	Feature Code	Sample Graphic	Page
Vehicle Lot / all (area)	PS-04151	AQ140	[_P_]	A - 342
Vertical Obstruction / single (point)	PS-04512	No Code	Catalytic cracker 72 (63)	A - 342
Vertical Obstruction / multiple (point)	PS-04513	No Code	Towers 77 (67)	A - 343
Vineyard / all (area)	PS-04306	EA050		A - 344
Void Collection Area / all (area)	PS-04319	ZD020	DATA INCOMPLETE	A - 345
Volcano / all (area)	PS-04941	DB180	Mount Rainier	A - 345
Volcano / all (point)	PS-04667	DB180	*	A - 346
Wall / all (line)	PS-04099	AL260	· · · · · · · · · · · · · · · · · · ·	A - 347
Water Aerodrome / all (area)	PS-04569	GB065	Seaplane base	A - 347

Symbol	Number	Feature Code	Sample Graphic	Page
Water Aerodrome / all (point)	PS-04318	GB065	Seaplane base 3	A - 348
Water Gate / all (line)	PS-04769	BI041	Water gate	A - 349
Water Gate / all (point)	PS-04770	BI041	<	A - 349
Water Intake Tower / non-obstruction (point)	PS-04226	BI050	Ą	A - 350
Water Treatment Bed / all (area)	PS-04183	BH040		A - 350
Waterfall / all (line)	PS-04212	BH180	✓ Falls	A - 351
Waterfall / all (point)	PS-04213	BH180	, Falls	A - 352
Well / non-water / all (point)	PS-04273	AA050	0	A - 352
Well / water / perennial (point)	PS-04050	AA050	•	A - 353

Symbol	Number	Feature Code	Sample Graphic	Page
Well / water / intermittent, dry (point)	PS-04051	AA050	0	A - 355
Wind Turbine / non-obstruction (point)	PS-04054	AJ051	‡	A - 356
Windmill / non-obstruction (point)	PS-04049	AJ050	ă	A - 357
Wood / unknown (area)	PS-04795	EC030		A - 357
Wood / evergreen (area)	PS-04796	EC030	Δ Δ Δ	A - 358
Wood / deciduous (area)	PS-04797	EC030	a. a. a. a. a. a. a. a. a. a. a. a. a. a	A - 359
Wood / mixed (area)	PS-04798	EC030	Δ., Δ., Q., Δ., Δ., Q.,	A - 359
Wood / scattered (area)	PS-04799	EC030	[3] 3 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	A - 360
Wood / all (line)	PS-04800	EC030	000000000000000000000000000000000000000	A - 360

Symbol	Number	Feature Code	Sample Graphic	Page
Wood / all (point)	PS-04808	EC030	Ø.	A - 361
Wreck / all (point)	PS-04659	BD180	*	A - 361
Zoo / all (area)	PS-04065	AK180	[Zoo]	A - 362
Zoo / all (point)	PS-04511	AK180	Zoo •	A - 362

Annex C - Color

This Annex presents the mapping from a specific color token to Pantone color names, the SPC ink codes, and CMYK values. The colors presented in each row of the table are approximately equivalent. This mapping allows considerable flexibility in identifying equivalent colors in a variety of methodologies. The color token name provides a link to Annex A and Annex C.

Color tokens can be replaced with different tokens if maps require different viewing conditions. This annex provides both the standard red-light readable and alternative red-light and blue/green-light readable color tokens where applicable.

The Pantone and SPC colors are normative/required because they provide the best consistency for lithographic printing. CMYK colors are provided as an alternative and are informative. CMYK values in the color tables may be altered as necessary in order to best match the intended Pantone/SPC colors.

NOTE: red-light and red and blue/green-light readability cannot be absolutely assured when using CMYK process printing/plotting.

Color Token Name	Color Description	Pantone Ink Code	Red-Light	Red & Blue / Green-Light	С	M	Υ	K	SPC Ink Code
Black	Black	Process Black U	✓	✓	0	0	0	100	58600
Black-07	Black 7%	Process Black U	~	\checkmark	0	0	0	7	58600
Black-12	Black 12%	Process Black U	✓	\checkmark	0	0	0	12	58600
Black-21	Black 21%	Process Black U	~	\checkmark	0	0	0	21	58600
Black-42	Black 42%	Process Black U	✓	\checkmark	0	0	0	42	58600
Black-54	Black-54%	Process Black U	~	✓	0	0	0	54	58600
Blue072	Blue	Blue 072 U	✓	✓	75	70	1	0	46351
Blue072-12	Blue 12%	Blue 072 U	~	✓	9	8	0	0	46351
Blue072-42	Blue 42%	Blue 072 U	~	✓	32	29	0	0	46351
Cyan	Cyan	Process Cyan U	~		100	0	0	0	48253
Cyan-04	Cyan 4%	Process Cyan U	✓		4	0	0	0	48253
Cyan-31	Cyan 31%	Process Cyan U	✓		31	0	0	0	48253
Dk-Blue662	Dark-Blue	662 U		✓	96	63	0	12	46961
Dk-Blue662-04	Dark-Blue 4%	662 U		✓	4	3	0	0	46961
Dk-Blue662-31	Dark-Blue 31%	662 U		✓	30	20	0	4	46961
Dk-Brown1815	Dark Brown	1815 U	✓	✓	40	100	100	0	61121
Dk-Brown1815-07	Dark-Brown 7%	1815 U	✓	✓	3	7	7	0	61121
Dk-Brown1815-12	Dark-Brown 12%	1815 U	✓	✓	5	12	12	0	61121
Dk-Brown1815-21	Dark-Brown 21%	1815 U	✓	✓	8	21	21	0	61121
Dk-Brown1815-42	Dark-Brown 42%	1815 U	✓	✓	17	42	42	0	61121
Dk-Brown1815-54	Dark-Brown 54%	1815 U	✓	✓	22	54	54	0	61121
Green355	Green	355 U		✓	80	0	80	7	51022
Green355-07	Green 7%	355 U		✓	6	0	6	0	51022
Green355-12	Green 12%	355 U		✓	10	0	10	1	51022
Green355-31	Green 31%	355 U		✓	25	0	25	2	51022
Green355-42	Green 42%	355 U		✓	34	0	34	3	51022
Green362	Green	362 U	✓		76	4	76	0	52813
Green362-07	Green 7%	362 U	~		5	0	5	0	52813
Green362-12	Green 12%	362 U	✓		9	0	9	0	52813
Green362-31	Green 31%	362 U	~		24	1	24	0	52813
Green362-42	Green 42%	362 U	✓		32	2	32	0	52813

Annex D - Text Characteristics

The Text Characteristics associated with the label information provided in Annex A is detailed in this Annex. The Characteristic ID provides the link to Label Rules in Annex A. The Color token name provides the link to Annex C, Color information.

Note – in order to meet both red-light and blue/green-light readable requirements, Cyan and Green362 text shall be changed to Dk-Blue662 and Green355 respectively.

Text Characteristic #	Color Token	Font Style	Bold	Italic	Font Size	Case	Sample Usage(s)
1	Black	Condensed			6	Mixed case	point features (descriptive), pass
3	Black	Condensed			6-16	Mixed case	vegetation
4	Black	Condensed			6-16	Lower case	vegetation
5	Black	Condensed		✓	6	Mixed case	rock, man made features
6	Black	Condensed		✓	6-9	Mixed case	crevice, reef (curve)
7	Black	Condensed			7-10	Mixed case	sand dunes, volcano
8	Black	Condensed		✓	6-16	Mixed case	rock formation (surface)
10	Black	Light Condensed		✓	6	Mixed case	trail, RR turntable
12	Black	Condensed		✓	6-16	Upper case	island, reef (surface), cape, peninsula
14	Cyan	Condensed			6	Mixed case	pipeline, tunnel (water)
15	Blue072	Condensed			6	Mixed case	VO
16	Cyan	Condensed		✓	6	Mixed case	named water features (blue)
17	Cyan	Condensed	✓		10	Lower case	snow spot elev highest
18	Black	Condensed	✓		10	Lower case	survey pt, land spot elev highest
19	Cyan	Condensed		✓	7	Lower case	snow contour
20	Dk-Brown1815	Condensed		✓	7	Lower case	land contour
21	Black	Condensed			8	Upper case	administrative
22	Black	Condensed			6	Lower case	point feature descriptive
23	Cyan	Condensed		✓	6	Lower case	water features (descriptive)
24	Blue072	Condensed			7	Mixed case	aerodromes, heliport
25	Black	Condensed			8	Lower case	survey pt, land spot elev normal
26	Blue072	Condensed			7	Lower case	aerodromes, heliport, channel
27	Black	Light Condensed		✓	6	Upper case	RR, road
28	Black	Light Condensed		✓	6	Lower case	trail, RR (gauges, turntable & yard) descriptive
29	Blue072	Condensed			7	Upper case	aerodromes, navaids
30	Cyan	Condensed			8	Lower case	snow, water spot elev normal
32	Cyan	Condensed		✓	6-9	Mixed case	crevasse
33	Cyan	Condensed		\checkmark	7-16	Lower case	inland water descriptive
35	Black	Condensed		\checkmark	6	Lower case	inland water descriptive (man-made)
37	Cyan	Condensed		\checkmark	7-16	Upper case	river & inland water (surface)
38	Cyan	Condensed		✓	6-16	Mixed case	other water areas
39	Black	Condensed		✓	7-16	Upper case	mangrove, nipa, tundra
40	Black	Condensed			6-16	Upper case	data incomplete
41	Black	Condensed			6-12	Mixed case	shanty town
42	Black	Condensed			8	Mixed case	bua 5th class
45	Black	Light Condensed			6-16	Upper case	named location
46	Blue072	Condensed	✓		6	Lower case	vo (ZVH)
47	Black	Condensed	✓		14	Upper case	bua 1st class
48	Black	Condensed	✓		10	Upper case	administrative boundary, bua 2nd class
49	Black	Condensed	✓		10	Mixed case	bua 3rd class
50	Black	Condensed			10	Mixed case	bua 4th class
57	Cyan	Condensed		✓	7-10	Mixed case	tidal water (small)
37	Cyaii	••••••					
58	Cyan	Condensed		✓	7-9	Mixed case	river (curve)
				✓	7-9 8-18	Mixed case Upper case	river (curve) tidal water (large)

Text Characteristic #	Color Token	Font Style	Bold	Italic	Font Size	Case	Sample Usage(s)
92	Dk-Brown1815	Condensed		✓	7	Upper case	land contour
93	Cyan	Condensed			6	Lower case	tunnel (water)
95	Blue072	Condensed			6	Lower case	vo (HGT)
103	Black	Regular	✓	✓	16-18	Upper case	regional mountain range
104	Black	Regular		✓	12-14	Upper case	small mountain range
105	Black	Regular		✓	8-10	Mixed case	single mountain
106	Black	Light Condensed		✓	7-8	Mixed case	small gap, hill, spur
107	Black	Light Condensed		✓	10-18	Upper case	large terrain (plains, desert, ravine, gorge)
108	Black	Light Condensed		✓	7-10	Mixed case	small terrain (plains, desert, ravine, gorge)
109	Dk-Brown1815	Light Condensed			6-16	Upper case	tribal name
110	Black	Condensed			10-14	Mixed case	dispersed village
111	Black	Light Condensed			10	Mixed case	scattered village
112	Black	Condensed			8	Mixed case	suburban area
113	Black	Light Condensed			8	Mixed case	farmstead
114	Black	Condensed		✓	8	Mixed case	coastal points
115	Green362	Condensed			6	Mixed case	sports ground

Annex E – Area Components

Each of the area components used in Annex A have been listed only once in this Annex.

A00003 Description: Blac072 solid fill Note: The surface geometry is filled with the solid color: A00005 Description: Dk-Brown1815-42 area fill Color Token: Dk-Brown1815-42 Screen Percent: 42% Screen Angle: 45 degrees A00006 Description: Elack solid fill Note: The surface geometry is filled with the solid color. A00007 Description: Cyan-31 area fill Color Token: Cyan-31 Screen Percent: 31% Screen Angle: 45 degrees A00008 Description: Cyan-44 area fill Color Token: Cyan-44 Screen Percent: 43% Screen Angle: 45 degrees A00009 Description: Green 362-31 area fill Color Token: Cyan-44 Screen Percent: 45% Screen Percent: 31% Screen Percent: 32% Screen Percent:	Area - Fill	
Note: The surface geometry is filled with the solid color. A00005 Description: Dk-Brown1815-42 area fill Color Token: Dk-Brown1815-42 Screen Argie: 45 degrees A00006 Description: Black solid fill Note: The surface geometry is filled with the solid color. A00007 Description: Cyan-31 area fill Color Token: Cyan-31 Screen Percent: 31% Screen Argie: 45 degrees A00008 Description: Cyan-04 area fill Color Token: Cyan-04 Screen Argie: 45 degrees A00009 Description: Green 362-31 area fill Color Token: Cyan-04 Screen Argie: 45 degrees A00009 Description: Green 362-31 area fill Color Token: Green 362-31 Screen Argie: 45 degrees A00008 Description: Black-12 area fill Color Token: Green 362-31 Screen Argie: 45 degrees A00008 Description: Black-12 area fill Color Token: Green 362-31 Screen Argie: 45 degrees A00008 Description: Black-12 area fill Color Token: Green 362-32 Screen Argie: 45 degrees A00009 Description: Black-12 area fill Color Token: Green 362-32 Screen Argie: 45 degrees A00009 Description: Green 362-42 area fill Color Token: Green 362-42 Screen Argie: 45 degrees A00009 Description: Green 362-42 area fill Color Token: Green 362-42 Screen Argie: 45 degrees A000060 Description: Black-12 area fill Color Token: Green 362-42 Screen Argie: 45 degrees A000064 Description: Black-12 area fill Color Token: Black-12 Screen Argie: 45 degrees A000064 Description: Black-12 area fill Color Token: Black-12 Screen Argie: 45 degrees A000064 Description: Black-12 area fill Color Token: Black-12 Screen Argie: 45 degrees	A00002	
A00005 Description: Dk-Brown1815-42 area fill Color Token: Dk-Brown1815-42 Screen Percent: 42% Screen Angle: 45 degrees A00006 Description: Black solid fill Note: The surface geometry is filled with the solid color. A00007 Description: Cyan-31 area fill Color Token: Cyan-31 Screen Percent: 31% Screen Angle: 45 degrees A00008 Description: Cyan-04 area fill Color Token: Cyan-04 Screen Angle: 45 degrees A00009 Description: Green362-31 area Fill Color Token: Green362-31 Screen Percent: 31% Screen Angle: 45 degrees A00008 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 31% Screen Angle: 45 degrees A00008 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00008 Description: Green362-42 area fill Color Token: Black-12 Screen Angle: 45 degrees A00009 Description: Green362-42 area fill Color Token: Black-12 Screen Angle: 45 degrees A00009 Description: Green362-42 area fill Color Token: Black-12 Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Black-12 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 45 degrees A00010	Description: Blue072 solid fill	Color Token: Blue072
Description: Dk-Brown1815-42 area fill A00006 Description: Black solid fill Note: The surface geometry is filled with the solid color. A00007 Description: Cyan-31 area fill Color Token: Cyan-31 Screen Percent: 31% Screen Angle: 45 degrees A00008 Description: Cyan-04 area fill Color Token: Cyan-04 Screen Percent: 31% Screen Angle: 45 degrees A00009 Description: Green362-31 area fill Color Token: Cyan-04 Screen Percent: 31% Screen Angle: 45 degrees A00009 Description: Green362-31 area fill Color Token: Green362-31 Screen Percent: 31% Screen Angle: 45 degrees A00048 Description: Black-12 area fill Color Token: Green362-31 Screen Percent: 12% Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Percent: 42% Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 7% Screen Angle: 45 degrees	Note: The surface geometry is filled with the solid color.	
A00006 Description: Black solid fill Note: The surface geometry is filled with the solid color. A00007 Description: Cyan-31 area fill Color Token: Cyan-31 Screen Angle: 45 degrees A00008 Description: Cyan-04 area fill Color Token: Cyan-04 Screen Angle: 45 degrees A00009 Description: Green362-31 area Fill Color Token: Cyan-04 Screen Angle: 45 degrees A00009 Description: Green362-31 area Fill Color Token: Green362-31 Screen Angle: 45 degrees A00009 Description: Black-12 area fill Color Token: Green362-31 Screen Angle: 45 degrees A00009 Description: Black-12 area fill Color Token: Green362-31 Screen Angle: 45 degrees A00009 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 15 degrees A00009 Description: Green362-42 area fill Color Token: Green362-42 Screen Angle: 45 degrees A00009 Description: Black-12 area fill Color Token: Green362-42 Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Dk-Brown1815-07 Screen Percent: 12% Screen Angle: 45 degrees	A00005	
A00006 Description: Black solid fill Note: The surface geometry is filled with the solid color. A00007 Description: Cyan-31 area fill Color Token: Cyan-31 Screen Percent: 31% Screen Angle: 45 degrees A00008 Description: Cyan-04 area fill Color Token: Cyan-04 Screen Percent: 4% Screen Percent: 4% Screen Percent: 31% Screen Angle: 45 degrees A00009 Description: Green362-31 area Fill Color Token: Green362-31 Screen Percent: 31% Screen Angle: 45 degrees A00048 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Percent: 42% Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Percent: 12%	Description: Dk-Brown1815-42 area fill	Color Token: Dk-Brown1815-42
A00006 Description: Black solid fill Note: The surface geometry is filled with the solid color. A00007 Description: Cyan-31 area fill Color Token: Cyan-31 Screen Percent: 31% Screen Angle: 45 degrees A00008 Description: Cyan-04 area fill Color Token: Cyan-04 Screen Percent: 4% Screen Angle: 45 degrees A00009 Description: Green362-31 area Fill Color Token: Green362-31 Screen Percent: 4% Screen Angle: 45 degrees A00048 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Percent: 42% Screen Angle: 45 degrees A00059 Description: Green362-42 area fill Color Token: Black-12 Screen Percent: 42% Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Percent: 7% Screen Percent: 12%		Screen Percent: 42%
Description: Black solid fill Note: The surface geometry is filled with the solid color. A00007 Description: Cyan-31 area fill Color Token: Cyan-31 Screen Percent: 31% Screen Angle: 45 degrees A00008 Description: Cyan-04 area fill Color Token: Cyan-04 Screen Angle: 45 degrees A00009 Description: Green362-31 area Fill Color Token: Green362-31 Screen Percent: 31% Screen Angle: 45 degrees A00048 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Percent: 42% Screen Angle: 15 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Black-12 Screen Percent: 42% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 42% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees		Screen Angle: 45 degrees
Note: The surface geometry is filled with the solid color. A00007 Description: Cyan-31 area fill Color Token: Cyan-31 Screen Percent: 31% Screen Angle: 45 degrees A00008 Description: Cyan-04 area fill Color Token: Cyan-04 Screen Percent: 4% Screen Angle: 45 degrees A00009 Description: Green362-31 area Fill Color Token: Green362-31 Screen Percent: 31% Screen Angle: 45 degrees A00048 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Percent: 42% Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Black-12 Screen Percent: 42% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 42% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees	A00006	
A00007 Description: Cyan-31 area fill Color Token: Cyan-31 Screen Percent: 31% Screen Angle: 45 degrees A00008 Description: Cyan-04 area fill Color Token: Cyan-04 Screen Percent: 49% Screen Angle: 45 degrees A00009 Description: Green362-31 area Fill Color Token: Green362-31 Screen Percent: 31% Screen Angle: 45 degrees A00048 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 45 degrees	Description: Black solid fill	Color Token: Black
Description: Cyan-31 area fill Color Token: Cyan-31 Screen Percent: 31% Screen Angle: 45 degrees A00008 Description: Cyan-04 area fill Color Token: Cyan-04 Screen Percent: 4% Screen Angle: 45 degrees A00009 Description: Green362-31 area Fill Color Token: Green362-31 Screen Percent: 31% Screen Angle: 45 degrees A00048 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Dk-Brown1815-07 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 45 degrees	Note: The surface geometry is filled with the solid color.	
A00008 Description: Cyan-04 area fill Color Token: Cyan-04 Screen Angle: 45 degrees A00009 Description: Green362-31 area Fill Color Token: Cyan-04 Screen Angle: 45 degrees Color Token: Cyan-04 Screen Angle: 45 degrees Color Token: Green362-31 Screen Percent: 31% Screen Angle: 45 degrees A00048 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Black-12 Screen Angle: 15 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Dk-Brown1815-07 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Dk-Brown1815-07 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 45 degrees A00064 Color Token: Black-12 Screen Angle: 45 degrees	A00007	
A00008 Description: Cyan-04 area fill Color Token: Cyan-04 Screen Percent: 4% Screen Angle: 45 degrees A00009 Description: Green362-31 area Fill Color Token: Green362-31 Screen Percent: 31% Screen Percent: 31% Screen Angle: 45 degrees A00048 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Percent: 42% Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Percent: 12% Screen Percent: 12% Screen Percent: 12% Screen Angle: 45 degrees	Description: Cyan-31 area fill	Color Token: Cyan-31
A00008 Description: Cyan-04 area fill Color Token: Cyan-04 Screen Percent: 4% Screen Angle: 45 degrees A00009 Description: Green362-31 area Fill Color Token: Green362-31 Screen Percent: 31% Screen Angle: 45 degrees A00048 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Percent: 42% Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00101		Screen Percent: 31%
Description: Cyan-04 area fill Color Token: Cyan-04 Screen Percent: 4% Screen Angle: 45 degrees A00009 Description: Green362-31 area Fill Color Token: Green362-31 Screen Percent: 31% Screen Angle: 45 degrees A00048 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Percent: 42% Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Black-12 Screen Percent: 42% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Dk-Brown1815-07 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees		Screen Angle: 45 degrees
Screen Percent: 4% Screen Angle: 45 degrees A00009 Description: Green362-31 area Fill Color Token: Green362-31 Screen Percent: 31% Screen Angle: 45 degrees A00048 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Percent: 42% Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00064	A00008	
A00009 Description: Green362-31 area Fill Color Token: Green362-31 Screen Percent: 31% Screen Angle: 45 degrees A00048 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Percent: 42% Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00061 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Percent: 12% Screen Percent: 12% Screen Percent: 12% Screen Percent: 12% Screen Percent: 12% Screen Percent: 12% Screen Percent: 12% Screen Percent: 12% Screen Angle: 45 degrees	Description: Cyan-04 area fill	Color Token: Cyan-04
A00009 Description: Green362-31 area Fill Color Token: Green362-31 Screen Percent: 31% Screen Angle: 45 degrees A00048 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Percent: 42% Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees		Screen Percent: 4%
Description: Green362-31 area Fill Color Token: Green362-31 Screen Percent: 31% Screen Angle: 45 degrees A00048 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Angle: 15 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Dk-Brown1815-07 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00101		Screen Angle: 45 degrees
A00048 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Percent: 42% Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Percent: 12% Screen Angle: 45 degrees A00101	A00009	
A00048 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Percent: 42% Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00101	Description: Green362-31 area Fill	Color Token: Green362-31
A00048 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Percent: 42% Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Percent: 12% Screen Percent: 12% Screen Angle: 45 degrees A00101		Screen Percent: 31%
Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 15 degrees A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Percent: 42% Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 45 degrees A00101		Screen Angle: 45 degrees
A00059 Description: Green362-42 area fill A00060 Description: Dk-Brown1815-07 area fill Color Token: Green362-42 Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Dk-Brown1815-07 Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 45 degrees A00101	A00048	
A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Percent: 42% Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00101	Description: Black-12 area fill	Color Token: Black-12
A00059 Description: Green362-42 area fill Color Token: Green362-42 Screen Percent: 42% Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00101		Screen Percent: 12%
Description: Green362-42 area fill Color Token: Green362-42 Screen Percent: 42% Screen Angle: 45 degrees A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00101		Screen Angle: 15 degrees
A00060 Description: Dk-Brown1815-07 area fill A00064 Description: Black-12 area fill Color Token: Dk-Brown1815-07 Screen Angle: 45 degrees Color Token: Dk-Brown1815-07 Screen Angle: 45 degrees Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00101	A00059	
A00060 Description: Dk-Brown1815-07 area fill A00064 Description: Black-12 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00101	Description: Green362-42 area fill	Color Token: Green362-42
A00060 Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00101		Screen Percent: 42%
Description: Dk-Brown1815-07 area fill Color Token: Dk-Brown1815-07 Screen Percent: 7% Screen Angle: 45 degrees A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00101		Screen Angle: 45 degrees
A00064 Description: Black-12 area fill Color Token: Black-12 Screen Angle: 45 degrees Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00101	A00060	
A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00101	Description: Dk-Brown1815-07 area fill	Color Token: Dk-Brown1815-07
A00064 Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00101		Screen Percent: 7%
Description: Black-12 area fill Color Token: Black-12 Screen Percent: 12% Screen Angle: 45 degrees A00101		Screen Angle: 45 degrees
Screen Percent: 12% Screen Angle: 45 degrees A00101	A00064	
A00101	Description: Black-12 area fill	Color Token: Black-12
A00101		Screen Percent: 12%
		Screen Angle: 45 degrees
Description: Green362-12 area fill Color Token: Green362-12	A00101	
	Description: Green362-12 area fill	Color Token: Green362-12

Screen Percent: 12%
Screen Angle: 45 degrees

A00121

Description: Dk-Brown1815-21 area fill Color Token: Dk-Brown1815-21

Screen Percent: 21%
Screen Angle: 45 degrees

A00122

Description: Dk-Brown1815-12 area fill Color Token: Dk-Brown1815-12

Screen Percent: 12%
Screen Angle: 45 degrees

A00123

Description: Blue072-42 area fill Color Token: Blue072-42

Screen Percent: 42%
Screen Angle: 45 degrees

A00125

Description: Blue072-12 area fill Color Token: Blue072-12

Screen Percent: 12%
Screen Angle: 45 degrees

A00127

Description: Green362-07 area fill Color Token: Green362-07

Screen Percent: 7%
Screen Angle: 45 degrees

Area - Pattern

A00001

Description: Black Peat Fill Color Token: Black

Area Pattern: AP-129, see Annex I

A00011

Description: Green362 Deciduous Tree Fill Color Token: Green362

Area Pattern: AP-54, see Annex I

A00012

Description: Green362 Evergreen Tree Fill Color Token: Green362

Area Pattern: AP-60, see Annex I

A00013

Description: Green362 Mixed Tree Fill Color Token: Green362

Area Pattern: AP-63, see Annex I

A00014

Description: Black-42 Shantytown Screened Fill Color Token: Black-42

Screen Percent: 42%

Area Pattern: AP-132, see Annex I Screen Angle: 45 degrees

A00015

Description: Cyan Land Subject to Inundation Fill Color Token: Cyan

Area Pattern: AP-10, see Annex I

A00016

Description: Cyan Sabkha Fill Color Token: Cyan

Area Pattern: AP-103, see Annex I

A00017

Description: Cyan Glacier Fill Color Token: Cyan

Area Pattern: AP-104, see Annex I

A00018

Description: Cyan Bog, Marsh Fill Color Token: Cyan

Area Pattern: AP-12, see Annex I

A00019

Description: Cyan Rice Fill Color Token: Cyan

Area Pattern: AP-4, see Annex I

A00020

Description: Cyan Dry Drainage Fill Color Token: Cyan

Area Pattern: AP-95, see Annex I

A00024

Description: Green362 Nipa Fill Color Token: Green362

Area Pattern: AP-7, see Annex I

A00025

Description: Green362 Mangrove Fill Color Token: Green362

Area Pattern: AP-8, see Annex I

A00027

Description: Green362 Scrub / Thicket Fill Color Token: Green362

Area Pattern: AP-68, see Annex I

A00028

Description: Green362 Orchard / Plantation Fill Color Token: Green362

Area Pattern: AP-74, see Annex I

A00029

Description: Green362 Vineyard / Hops Fill Color Token: Green362

Area Pattern: AP-77, see Annex I

A00030

Description: Dk-Brown1815-54 Distorted Surface Screened Fill Color Token: Dk-Brown1815-54

Screen Percent: 54%

Area Pattern: AP-103, see Annex I Screen Angle: 45 degrees

A00031

Description: Dk-Brown1815 Crescent Sand Dunes Fill Color Token: Dk-Brown1815

Area Pattern: AP-108, see Annex I

A00032

Description: Dk-Brown1815 Ripple Sand Dunes Fill Color Token: Dk-Brown1815

Area Pattern: AP-112, see Annex I

A00033

Description: Dk-Brown1815 Star Sand Dunes Fill Color Token: Dk-Brown1815

Area Pattern: AP-120, see Annex I

A00034

Description: Dk-Brown1815 Transverse Sand Dunes Fill Color Token: Dk-Brown1815

Area Pattern: AP-127, see Annex I

A00035

Description: Dk-Brown1815 Sand Fill Color Token: Dk-Brown1815

Area Pattern: AP-95, see Annex I

A00036

Description: Dk-Brown1815 Gravel Fill Color Token: Dk-Brown1815

Area Pattern: AP-99, see Annex I

A00042

Description: Dk-Brown1815 Dome Sand Dunes Fill Color Token: Dk-Brown1815

Area Pattern: AP-126, see Annex I

A00043

Description: Dk-Brown1815 Linear Sand Dunes Fill Color Token: Dk-Brown1815

Area Pattern: AP-118, see Annex I

A00044

Description: Cyan Salt Evaporator Fill Color Token: Cyan

Area Pattern: No existing MIL_STD_2410 area pattern. See Annex I for detailed drawing

instructions.

A00047

Description: Green362 Scattered Trees Fill Color Token: Green362

Area Pattern: AP-44, see Annex I

A00050

Description: Green362 Cane Fill Color Token: Green362

Area Pattern: AP-86, see Annex I

A00061

Description: Dk-Brown1815 Diagonal Line Fill Color Token: Dk-Brown1815

Area Pattern: LP-3, see Annex I

A00062

Description: Cyan Diagonal Line Fill Color Token: Cyan

Area Pattern: LP-3, see Annex I

A00063

Description: Dk-Brown1815-54 Not Intact BUA Screened Fill Color Token: Dk-Brown1815-54

Screen Percent: 54%

Area Pattern: LP-6, see Annex I Screen Angle: 45 degrees

A00065

Description: Cyan Rapids Pattern Color Token: Cyan

Area Pattern: AP-105, see Annex I

A00118

Description: Green362 Cropland dot fill Color Token: Green362

Area Pattern: No existing MIL_STD_2410 area pattern. See Annex I for detailed drawing

instructions.

A00124

Description: Green362 Greenhouse Fill Color Token: Green362

Area Pattern: LP-6, see Annex I

A00126

Description: Green362 Grassland Fill Color Token: Green362

Area Pattern: No existing MIL_STD_2410 area pattern. See Annex I for detailed drawing

instructions.

Annex F – Line Components

Each of the line components used in Annex A have been listed only once in this Annex.

29 May 2015 Line - Simple L00005 Color Token: Blue072 Description: Blue072 0.4mm Solid Line Lineweight: 0.4mm L00006 Color Token: Blue072 Description: Blue072 0.73mm Solid Line Lineweight: 0.73mm L00007 Color Token: Black Description: Black 0.1mm Solid Line Lineweight: 0.1mm L00008 Color Token: Black Description: Black 0.15mm Solid Line Lineweight: 0.15mm L00009 Color Token: Black Description: Black 0.2mm Solid Line Lineweight: 0.2mm L00010 Description: Black 0.25mm Solid Line Color Token: Black Lineweight: 0.25mm L00011 Color Token: Black Description: Black 0.3mm Solid Line Lineweight: 0.3mm L00013 Color Token: Black Description: Black 0.4mm Solid Line 0.4mm Lineweight: L00014 Color Token: Black Description: Black 0.5mm Solid Line Lineweight: 0.5mm L00015 Description: Cyan 0.2mm Solid Line Color Token: Cyan Lineweight: 0.2mm L00016 Description: Cyan 0.3mm Solid Line Color Token: Cyan Lineweight: 0.3mm L00017 Color Token: Cyan Description: Cyan 0.4mm Solid Line

0.4mm

Lineweight:

Color Token: Black Description: Two parallel Black 0.3mm Solid Lines

Lineweight: 0.3mm

Note: Spacing is variable based on the width of the overpassing feature.

L00021

Color Token: Green362 Description: Green362 0.2mm Solid Line

0.2mm Lineweight:

L00023

Color Token: Dk-Brown1815 Description: Dk-Brown1815 0.2mm Solid Line

Lineweight: 0.2mm

L00024

Color Token: Dk-Brown1815 Description: Dk-Brown1815 0.25mm Solid Line

Lineweight: 0.25mm

L00105

Color Token: Dk-Brown1815 Description: Dk-Brown1815 0.3mm Solid Line

Lineweight: 0.3mm

L00107

Description: Dk-Brown1815 0.1mm Solid Line Color Token: Dk-Brown1815

Lineweight: 0.1mm

L00108

Description: Cyan 0.1mm Solid Line Color Token: Cyan

Lineweight: 0.1mm

L00123

Color Token: Dk-Brown1815-54 Description: Dk-Brown1815-54 2.0mm Screened Line

2.0mm Lineweight: Screen Angle: 60 degrees

Screen Percent: 54%

L00126

Color Token: Dk-Brown1815-42 Description: Dk-Brown1815-42 2.0mm Screened Line

Lineweight: 2.0mm Screen Angle: 60 degrees

Screen Percent: 42%

L00145

Description: 0mm Line weight line. This is a place holder for lines that do not have any line Color Token: N/A

component only a point element at each end of the line.

Lineweight: 0.0mm

L00153

Description: Black 0.6mm Solid Line Color Token: Black

Lineweight: 0.6mm

Description: Dk-Brown1815 0.5mm Solid Line Color Token: Dk-Brown1815

Lineweight: 0.5mm

L00159

Description: Dk-Brown1815 0.6mm Solid Line Color Token: Dk-Brown1815

Lineweight: 0.6mm

L00166

Description: PaperWhite 0.3mm Solid Line Color Token: PaperWhite

Lineweight: 0.3mm

L00182

Description: PaperWhite 0.6mm Solid Line Color Token: PaperWhite

Lineweight: 0.6mm

L00183

Description: PaperWhite 0.8mm Solid Line Color Token: PaperWhite

Lineweight: 0.8mm

L00186

Description: PaperWhite 0.5mm Solid Line Color Token: PaperWhite

Lineweight: 0.5mm

L00195

Description: Dk-Brown1815 0.4mm Solid Line Color Token: Dk-Brown1815

Lineweight: 0.4mm

L00200

Description: Black 1.5mm Solid Line Color Token: Black

Lineweight: 1.5mm

L00217

Description: Blue072 0.1mm Solid Line Color Token: Blue072

Lineweight: 0.1mm

L00219

Description: Black 1.45mm Solid Line Color Token: Black

Lineweight: 1.45mm

L00220

Description: Dk-Brown1815 1.15mm Solid Line Color Token: Dk-Brown1815

Lineweight: 1.15mm

L00221

Description: Black 0.55mm Solid Line Color Token: Black

Lineweight: 0.55mm

L00222

Description: PaperWhite 0.25mm Solid Line Color Token: PaperWhite

MGCP Portrayal Standard, Annex F (v2.0.1)

Lineweight: 0.25mm

L00231

Description: PaperWhite 0.45mm Solid Line Color Token: PaperWhite

Lineweight: 0.45mm

L00232

Description: Black 0.75mm Solid Line Color Token: Black

Lineweight: 0.75mm

L00240

Description: Dk-Brown1815 0.15mm Solid Line Color Token: Dk-Brown1815

Lineweight: 0.15mm

L00241

Description: Two parallel Dk-Brown1815 0.15mm Solid Lines Color Token: Dk-Brown1815

Lineweight: 0.15mm

Note: Spacing is variable based on the width of the overpassing feature. The minimum space between each line and the linear portion

of the over passing feature shall be 0.2 mm.

L00247

Description: Two parallel Dk-Brown1815 0.3mm Solid Lines Color Token: Dk-Brown1815

Lineweight: 0.3mm

Note: Spacing is variable based on the width of the overpassing feature.

L00248

Description: Cyan 0.25mm Solid Line Color Token: Cyan

Lineweight: 0.25mm

L00361

Description: Green362 0.15mm Solid Line Color Token: Green362

Lineweight: 0.15mm

L00374

Description: Dk-Brown1815-54 0.6mm Screened Line Color Token: Dk-Brown1815-54

Lineweight: 0.6mm
Screen Angle: 45 degrees

Screen Percent: 54%

L00376

L00387

Description: Dk-Brown1815-54 0.5mm Screened Line Color Token: Dk-Brown1815-54

Lineweight: 0.5mm
Screen Angle: 45 degrees
Screen Percent: 54%

Description: Dk-Brown1815-54 0.3mm Screened Line

Lineweight: 0.3mm
Screen Angle: 45 degrees
Screen Percent: 54%

MGCP Portrayal Standard, Annex F (v2.0.1)

Color Token: Dk-Brown1815-54

Description: Cyan 0.9mm Solid Line Color Token: Cyan

Lineweight: 0.9mm

L00426

Description: Black 0.7mm Solid Line Color Token: Black

Lineweight: 0.7mm

L00427

Description: PaperWhite 0.7mm Solid Line Color Token: PaperWhite

Lineweight: 0.7mm

L00430

Description: Black 1.1mm Solid Line Color Token: Black

Lineweight: 1.1mm

L00431

Description: Dk-Brown1815 0.8mm Solid Line Color Token: Dk-Brown1815

Lineweight: 0.8mm

L00433

Description: Black 0.9mm Solid Line Color Token: Black

Lineweight: 0.9mm

L00439

Description: PaperWhite 1.1mm Solid Line Color Token: PaperWhite

Lineweight: 1.1mm

L00444

Description: Dk-Brown1815-42 1.0mm Screened Line Color Token: Dk-Brown1815-42

Lineweight: 1.0mm
Screen Angle: 60 degrees

Screen Percent: 42%

L00445

Description: Blue072 0.25mm Solid Line Color Token: Blue072

Lineweight: 0.25mm

L00451

Description: Black surface lock "V" (0.15mm wt)

Color Token: Black

Lineweight: 0.15mm

Note: Each leg is equal and based on width of the surface geometry, and is connected to form a "V" at a 90 degree angle.

L00455

Description: Black-42 1.0mm Screened Line Color Token: Black-42

Lineweight: 1.0mm
Screen Angle: 60 degrees
Screen Percent: 42%

Line - Styled

Description: Black 0.1mm Dashed Line (0.1mm wt, 2.0mm dash, 0.5mm gap)

Color Token: Black

Lineweight: 0.1mm Dash Length: 2.0mm Dash Spacing: 0.5mm

L00030

Description: Black 0.2mm Dashed Line (0.2mm wt, 1.5mm dash, 0.5mm gap)

Color Token: Black

Lineweight: 0.2mm Dash Length: 1.5mm Dash Spacing: 0.5mm

L00031

Description: Black 0.2mm Dashed Line (0.2mm wt, 1.0mm dash, 0.5mm gap)

Color Token: Black

Lineweight: 0.2mm Dash Length: 1.0mm Dash Spacing: 0.5mm

L00032

Description: Black 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap)

Color Token: Black

Lineweight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

L00035

Description: Black 0.25mm Dashed Line (0.25mm wt, 3.5mm dash, 0.5mm gap)

Color Token: Black

Lineweight: 0.25mm Dash Length: 3.5mm Dash Spacing: 0.5mm

L00036

Description: Black 0.3mm Dashed Line (0.3mm wt, 2.0mm dash, 0.5mm gap)

Color Token: Black

Lineweight: 0.3mm Dash Length: 2.0mm Dash Spacing: 0.5mm

L00039

Description: Black 0.3mm Dashed Line (0.3mm wt, 5.9mm dash, 0.5mm gap)

Color Token: Black

Lineweight: 0.3mm Dash Length: 5.9mm Dash Spacing: 0.5mm

L00040

Description: Cyan 0.2mm Dashed Line (0.2mm wt, 1.0mm dash, 0.5mm gap)

Color Token: Cyan

Lineweight: 0.2mm Dash Length: 1.0mm Dash Spacing: 0.5mm

L00041

Description: Cyan 0.2mm Dashed Line (0.2mm wt, 2.0mm dash, 0.5mm gap)

Color Token: Cyan

Lineweight: 0.2mm Dash Length: 2.0mm Dash Spacing: 0.5mm

L00042

Description: Cyan 0.2mm Dashed Line (0.2mm wt, 5.0mm dash, 0.5mm gap)

Color Token: Cyan

Lineweight: 0.2mm Dash Length: 5.0mm Dash Spacing: 0.5mm

L00045

Description: Cyan 0.4mm Dashed Line (0.4mm wt, 2.0mm dash, 0.5mm gap)

Color Token: Cyan

Lineweight: 0.4mm Dash Length: 2.0mm Dash Spacing: 0.5mm

L00089

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 1.0mm gap)

Color Token: Black

Lineweight: 0.1mm Dash Length: 1.0mm Dash Spacing: 1.0mm

L00109

Description: Dk-Brown1815 0.1mm Dashed Line (0.1mm wt, 3.0mm dash, 0.5mm gap) Color Token: Dk-Brown1815

MGCP Portrayal Standard, Annex F (v2.0.1)

Lineweight: 0.1mm Dash Length: 3.0mm Dash Spacing: 0.5mm

L00110

Description: Cyan 0.1mm Dashed Line (0.1mm wt, 3.0mm dash, 0.5mm gap) Color Token: Cyan

Lineweight: 0.1mm Dash Length: 3.0mm Dash Spacing: 0.5mm

L00117

Description: Dk-Brown1815 0.1mm Dashed Line (0.1mm wt, 1.5mm dash, 0.5mm gap) Color Token: Dk-Brown1815

Lineweight: 0.1mm Dash Length: 1.5mm Dash Spacing: 0.5mm

L00118

Description: Cyan 0.1mm Dashed Line (0.1mm wt, 1.5mm dash, 0.5mm gap)

Color Token: Cyan

Lineweight: 0.1mm Dash Length: 1.5mm Dash Spacing: 0.5mm

L00122

Description: Black 0.5mm Dashed Line (0.5mm wt, 7.0mm dash, 2-2.0mm dashes, 1.0mm gaps) Color Token: Black

Lineweight: 0.5mm Dash Length: 7.0mm Dash Spacing: 1.0mm

Dash 2 Length: 2.0mm
Dash 3 Length: 2.0mm
Dash 3 Spacing: 1.0mm
Dash 3 Spacing: 1.0mm

Note: The line style is a 7.0mm dash, 1.0mm gap, 2.0mm dash, 1.0mm gap, 2.0mm dash, 1.0mm gap, then the pattern repeats.

L00133

Description: Black 0.3mm Dashed Line (0.3mm wt, 7.0mm dash, 3.4mm gap)

Color Token: Black

Lineweight: 0.3mm Dash Length: 7.0mm Dash Spacing: 3.4mm

L00169

Description: Dk-Brown1815 0.6mm Dashed Line (0.6mm wt, 3.5mm dash, 1.5mm gap)

Color Token: Dk-Brown1815

Lineweight: 0.6mm Dash Length: 3.5mm Dash Spacing: 1.5mm

L00170

Description: Black 0.1mm Dashed Line (0.1mm wt, 2.5mm dash, 0.5mm gap)

Color Token: Black

Lineweight: 0.1mm Dash Length: 2.5mm Dash Spacing: 0.5mm

L00176

Description: Dk-Brown1815 0.2mm Dashed Line (0.2mm wt, 5.0mm dash, 0.5mm gap)

Color Token: Dk-Brown1815

Lineweight: 0.2mm Dash Length: 5.0mm Dash Spacing: 0.5mm

L00177

Description: Dk-Brown1815 0.1mm Dashed Line (0.1mm wt, 5.0mm dash, 0.5mm gap) Color Token: Dk-Brown1815

Lineweight: 0.1mm Dash Length: 5.0mm Dash Spacing: 0.5mm

L00178

Description: Cyan 0.1mm Dashed Line (0.1mm wt, 5.0mm dash, 0.5mm gap)

Color Token: Cyan

Lineweight: 0.1mm Dash Length: 5.0mm Dash Spacing: 0.5mm

L00191

Description: Dk-Brown1815 0.3mm Dashed Line (0.3mm wt, 3.5mm dash, 1.5mm gap)

Color Token: Dk-Brown1815

Lineweight: 0.3mm Dash Length: 3.5mm Dash Spacing: 1.5mm

L00192

Description: Dk-Brown1815 0.5mm Dashed Line (0.5mm wt, 3.5mm dash, 1.5mm gap)

Color Token: Dk-Brown1815

Lineweight: 0.5mm Dash Length: 3.5mm Dash Spacing: 1.5mm

L00198

Description: Black 0.15mm Dashed Line (0.15mm wt, 3.3mm dash, 0.5mm gap)

Color Token: Black

Lineweight: 0.15mm Dash Length: 3.3mm Dash Spacing: 0.5mm

L00205

Description: Black 0.15mm Dashed Line (0.15mm wt, 5.4mm dash, 1.0mm gap)

Color Token: Black

Lineweight: 0.15mm Dash Length: 5.4mm Dash Spacing: 1.0mm

L00210

Description: Black 0.1mm Dashed line (0.1mm wt, 1.0mm dash, 0.5mm gap)

Color Token: Black

Lineweight: 0.1mm Dash Length: 1.0mm Dash Spacing: 0.5mm

L00213

Description: Two parallel Black 0.2mm Dashed Lines (0.2mm wt, 1.0mm dash, 0.5mm gap) spaced Color Token: Black

1.3mm apart

Lineweight: 0.2mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Note: The two parallel Black 0.2mm Dashed Lines are spaced 1.3mm apart from center to center

L00214

Description: Two parallel Cyan 0.2mm Dashed Lines (0.2mm wt, 1.0mm dash, 0.5mm gap) spaced Color Token: Cyan

1.3mm apart

Lineweight: 0.2mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Note: The two parallel Cyan 0.2mm Dashed Lines are spaced 1.3mm apart from center to center

L00230

Description: Black 0.75mm Dashed Line (0.75mm wt, 5.9mm dash, 0.5mm gap)

Color Token: Black

Lineweight: 0.75mm Dash Length: 5.9mm Dash Spacing: 0.5mm

L00235

Description: Cyan 0.3mm Dashed Line (0.3mm wt, 1.0mm dash, 0.5mm gap)

Color Token: Cyan

Lineweight: 0.3mm Dash Length: 1.0mm Dash Spacing: 0.5mm

L00237

Description: Black 0.25mm Dashed Line (0.25mm wt, 5.0mm dash, 1.0mm gap)

Color Token: Black

Lineweight: 0.25mm Dash Length: 5.0mm Dash Spacing: 1.0mm

L00243

Description: Black 0.3mm Dashed Line (0.3mm wt, 4.0mm dash, 1.0mm gap)

Color Token: Black

Lineweight: 0.3mm Dash Length: 4.0mm Dash Spacing: 1.0mm

L00246

Description: Cyan 0.1mm Dashed Line (0.1mm wt, 2.0mm dash, 0.5mm gap)

Color Token: Cyan

Lineweight: 0.1mm Dash Length: 2.0mm Dash Spacing: 0.5mm

L00253

Description: Dk-Brown1815 0.5mm Dashed Line (0.5mm wt, 2-2.0mm dashes, 7.0mm dash, 1.0mm Color Token: Dk-Brown1815

gaps)

Lineweight: 0.5mm Dash Length: 2.0mm Dash Spacing: 1.0mm

Dash 2 Length: 2.0mm
Dash 3 Length: 7.0mm
Dash 3 Spacing: 1.0mm

Note: The line style is a 2.0mm dash, 1.0mm gap, 2.0mm dash, 1.0mm gap, 7.0mm dash, 1.0mm gap, then the pattern repeats.

L00368

Description: Green362 0.15mm Dashed Line (0.15mm wt, 1.0mm dash, 0.5mm gap) Color Token: Green362

Lineweight: 0.15mm Dash Length: 1.0mm Dash Spacing: 0.5mm

L00378

Description: Dk-Brown1815-54 0.5mm Screened Dashed Line (0.5mm wt, 3.5mm, 1.5mm gap) Color Token: Dk-Brown1815-54

Lineweight: 0.5mm Dash Length: 3.5mm Dash Spacing: 1.5mm

Screen Angle: 45 degrees

Screen Percent: 54%

L00382

Description: Dk-Brown1815-54 0.3mm Screened Dashed Line (0.3mm wt, 3.5mm, 1.5mm gap) Color Token: Dk-Brown1815-54

Lineweight: 0.3mm Dash Length: 3.5mm Dash Spacing: 1.5mm

Screen Angle: 45 degrees

Screen Percent: 54%

L00398

Description: Black 0.4mm Dashed Line (0.4mm wt, 3.0mm dash, 1.0mm gap)

Color Token: Black

Lineweight: 0.4mm Dash Length: 3.0mm Dash Spacing: 1.0mm

L00404

Description: Black 0.2mm Dashed Line (0.2mm wt, 4.0mm dash, 1.0mm gap)

Color Token: Black

Lineweight: 0.2mm Dash Length: 4.0mm Dash Spacing: 1.0mm

L00405

Description: Cyan 0.2mm Dashed Line (0.2mm wt, 4.0mm dash, 1.0mm gap)

Color Token: Cyan

Lineweight: 0.2mm Dash Length: 4.0mm Dash Spacing: 1.0mm

L00428

Description: Black 0.7mm Dashed Line (0.7mm wt, 2.5mm dash, 0.5mm gap)

Color Token: Black

Lineweight: 0.7mm Dash Length: 2.5mm Dash Spacing: 0.5mm

L00436

Description: Dk-Brown1815-54 0.6mm Screened Dashed Line (0.6mm wt, 3.5mm, 1.5mm gap)

Color Token: Dk-Brown1815-54

Lineweight: 0.6mm Dash Length: 3.5mm Dash Spacing: 1.5mm

Screen Angle: 45 degrees

Screen Percent: 54%

L00440

Description: Black 1.1mm Dashed Line (1.1mm wt, 2.5mm dash, 0.5mm gap)

Color Token: Black

Lineweight: 1.1mm Dash Length: 2.5mm Dash Spacing: 0.5mm

L00442

Description: Black 0.15mm Dashed Line (0.15mm wt, 3.0mm dash, 1.0mm gap)

Color Token: Black

Lineweight: 0.15mm Dash Length: 3.0mm Dash Spacing: 1.0mm

L00447

Description: Black 0.15mm Dashed Line (0.15mm wt, 2.0mm dash, 0.5mm gap)

Color Token: Black

Lineweight: 0.15mm Dash Length: 2.0mm Dash Spacing: 0.5mm

L00448

Description: Black 0.3mm Dashed Line (0.3mm wt, 7.0mm dash, 5.3mm gap)

Color Token: Black

Lineweight: 0.3mm Dash Length: 7.0mm Dash Spacing: 5.3mm

L00449

Description: Black 0.3mm Dashed Line (0.3mm wt, 7.0mm dash, 7.2mm gap)

Color Token: Black

Lineweight: 0.3mm Dash Length: 7.0mm Dash Spacing: 7.2mm

L00450

Description: Black 0.15mm Dashed line (0.15mm wt, 3.0mm dash, 2.0mm gap)

Color Token: Black

Lineweight: 0.15mm Dash Length: 3.0mm Dash Spacing: 2.0mm

L00452

Description: Black-54 0.2mm Screened Dashed Line (0.2mm wt, 1.0mm dash, 0.5mm gap)

Color Token: Black-54

Lineweight: 0.2mm Dash Length: 1.0mm Dash Spacing: 0.5mm

Screen Angle: 45 degrees
Screen Percent: 54%

STD-DP-14-025 29 May 2015

Annex G – Point Components

Each of the point components used in Annex A have been listed only once in this Annex.

Point - Shape

P00001

Description: Extraction mine intact not peat Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00002

Description: Extraction mine not intact not peat Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00005

Description: Camp/campsite Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00008

Description: Vertical obstruction Color Token: Blue072

Note: See Annex H for detailed drawing instructions.

P00010

Description: Located object Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00012

Description: Building hospital Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00013

Description: Building Christian cross Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00014

Description: Building Islamic crescent Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00016

Description: Building school flag Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00017

Description: Building Judaism "T" Color Token: Black

Description: Building temple Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00019

Description: Building pagoda Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00020

Description: Pylon Color Token: Blue072

Note: See Annex H for detailed drawing instructions.

P00022

Description: Cairn Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00026

Description: Natural pool perennial Color Token: Cyan

Note: See Annex H for detailed drawing instructions.

P00027

Description: Geothermal outlet Color Token: Dk-Brown1815

Note: See Annex H for detailed drawing instructions.

P00028

Description: Vanishing point disappearing Color Token: Cyan

Note: See Annex H for detailed drawing instructions.

P00029

Description: Mountain pass Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00030

Description: Tree other Color Token: Green362

Note: See Annex H for detailed drawing instructions.

P00031

Description: Building stupa Color Token: Black

Description: Natural pool intermittent Color Token: Cyan

Note: See Annex H for detailed drawing instructions.

P00035

Description: Basin gate/lock Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00045

Description: Pipeline elevated "V" Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00058

Description: Pipeline water elevated "V" Color Token: Cyan

Note: See Annex H for detailed drawing instructions.

P00059

Description: Vanishing point dissipating Color Token: Cyan

Note: See Annex H for detailed drawing instructions.

P00064

Description: Volcano Color Token: Dk-Brown1815

Note: See Annex H for detailed drawing instructions.

P00066

Description: Ice peak not frozen water Color Token: Dk-Brown1815

Note: See Annex H for detailed drawing instructions.

P00071

Description: Rock formation Color Token: Dk-Brown1815

Note: See Annex H for detailed drawing instructions.

P00073

Description: Tunnel entrance not water Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00074

Description: Tunnel entrance water Color Token: Cyan

Description: Building Christian Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00076

Description: Building Islamic Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00077

Description: Building Judaism Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00079

Description: Railway station Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00084

Description: Extraction mine peat Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00088

Description: Swimming pool Color Token: Black/Cyan-31

Note: See Annex H for detailed drawing instructions.

P00089

Description: Helipad at hospital Color Token: Blue072

Note: See Annex H for detailed drawing instructions.

P00090

Description: Helipad Color Token: Blue072

Note: See Annex H for detailed drawing instructions.

P00095

Description: Hazardous rock/reef Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00101

Description: Vertical obstruction multiple Color Token: Blue072

Description: Lock/pedestrian bridge/sluice gate "V" Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00106

Description: Culvert double "V" Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00108

Description: Fortified building Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00113

Description: Vertical obstruction linear Color Token: Blue072

Note: See Annex H for detailed drawing instructions.

P00118

Description: Building school Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00131

Description: Crane Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00132

Description: Building checkpoint Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00133

Description: Dish aerial Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00135

Description: Lighthouse Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00136

Description: Memorial monument Color Token: Black

Description: Cooling tower Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00138

Description: Power substation Color Token: Black/Blue072-42

Note: See Annex H for detailed drawing instructions.

P00140

Description: Smokestack Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00141

Description: Tower non-communication Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00142

Description: Water tower Color Token: Black/Cyan

Note: See Annex H for detailed drawing instructions.

P00143

Description: Wind turbine Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00144

Description: Windmill Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00145

Description: Flare pipe Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00148

Description: Water intake tower Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00155

Description: Aerial/tower communication Color Token: Black

Description: Rig inland Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00163

Description: Offshore construction point Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00165

Description: Motor vehicle station Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00171

Description: Greenhouse Color Token: Black/Green362-42

Note: See Annex H for detailed drawing instructions.

P00173

Description: Not intact square 0.8mm Color Token: Black/Black-12

Note: See Annex H for detailed drawing instructions.

P00179

Description: Survey point geodetic Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00183

Description: Cave mouth Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00184

Description: Building minaret Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00186

Description: Building diplomatic Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00188

Description: Bridge fixed Color Token: Black

Description: Rapids Color Token: Cyan

Note: See Annex H for detailed drawing instructions.

P00198

Description: Mooring mast Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00200

Description: River flow arrow Color Token: Cyan

Note: See Annex H for detailed drawing instructions.

P00201

Description: Bridge pedestrian Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00202

Description: Bridge not fixed Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00206

Description: Wreck Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00207

Description: Reef arc Color Token: Black-54

Note: See Annex H for detailed drawing instructions.

P00208

Description: Aqueduct/penstock/water race "V" Color Token: Cyan

Note: See Annex H for detailed drawing instructions.

P00210

Description: Sports ground Color Token: Green362/Green362-12

Note: See Annex H for detailed drawing instructions.

P00238

Description: Railway turntable Color Token: Black

Description: Cemetery/tomb Christian Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00254

Description: Cemetery/tomb Islam Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00255

Description: Cemetery/tomb Judaism Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00257

Description: Water aerodrome Color Token: Blue072

Note: See Annex H for detailed drawing instructions.

P00260

Description: Oasis Color Token: Green362

Note: See Annex H for detailed drawing instructions.

P00265

Description: Ruins Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00268

Description: Road route marker national non-USA Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00271

Description: Cemetery/tomb other Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00272

Description: Cemetery/tomb Buddhism Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00274

Description: Ski jump Color Token: Black

Description: Motor vehicle station symbol Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00277

Description: Railway tick narrow double Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00278

Description: Railway tick broad double Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00279

Description: Railway tick narrow electrified Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00280

Description: Railway tick broad electrified Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00281

Description: Railway tick narrow electrified double Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00282

Description: Railway tick broad electrified double Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00283

Description: Surface bunker Color Token: Black/Dk-Brown1815

Note: See Annex H for detailed drawing instructions.

P00285

Description: Building diplomatic flag Color Token: Black

Note: See Annex H for detailed drawing instructions.

P00286

Description: Fence "X" Color Token: Black

Description: Settling pond Color Token: Black/Cyan-31

Note: See Annex H for detailed drawing instructions.

P00291

Description: Not intact circle 0.8mm Color Token: Black/Black-12

Note: See Annex H for detailed drawing instructions.

P00292

Description: Vertical obstruction pylon Color Token: Blue072

Note: See Annex H for detailed drawing instructions.

P00293

Description: Not intact square 0.6mm Color Token: Black/Black-12

Note: See Annex H for detailed drawing instructions.

P00294

Description: Radio aid Color Token: Blue072

Note: See Annex H for detailed drawing instructions.

P00295

Description: Aircraft revetment Color Token: Dk-Brown1815

Note: See Annex H for detailed drawing instructions.

P00296

Description: Building hospital symbol Color Token: Black

Note: See Annex H for detailed drawing instructions.

Point - Simple

P00006

Description: Black filled square with all sides 0.8mm Color Token: Black

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

P00007

Description: Cyan filled square with all sides 0.8mm Color Token: Cyan

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

P00009

Description: Non-water well Color Token: Black

Diameter: 1.0mm Lineweight: 0.15mm

Note: The component is an open circle.

P00038

Description: Black 0.75mm length line with a 0.15mm lineweight Color Token: Black

Lineweight: 0.15mm

Length: 0.75mm

P00040

Description: Qanat/Water well intermittent Color Token: Cyan

Diameter: 1.0mm Lineweight: 0.15mm

Note: The component is an open circle.

P00041

Description: Cyan 0.8mm diameter filled circle Color Token: Cyan

Diameter: 0.8mm

Note: The component is a circle and is filled with the solid color.

P00044

Description: Black 1.5mm length line with a 0.15mm lineweight Color Token: Black

Lineweight: 0.15mm

Length: 1.5mm

P00047

Description: Black 0.25mm diameter filled circle Color Token: Black

Diameter: 0.25mm

Note: The component is a circle and is filled with the solid color.

P00048

Description: Bridge non-fixed open circle Color Token: Black

Lineweight: 0.2mm

Note: The diameter of the open circle is variable based on the width of the overpassing feature.

P00050

Description: Black filled square with all sides 0.5mm Color Token: Black

Length: 0.5mm

Note: The component is a square and is filled with the solid color.

P00053

Description: Black 0.8mm diameter filled circle Color Token: Black

Diameter: 0.8mm

Note: The component is a circle and is filled with the solid color.

P00055

Description: Cyan 0.5mm length line with a 0.1mm lineweight Color Token: Cyan

Lineweight: 0.1mm

Length: 0.5mm

P00061

Description: Cyan 1.5mm length line with a 0.2mm lineweight Color Token: Cyan

Lineweight: 0.2mm

Length: 1.5mm

P00065

Description: Dk-Brown1815 0.5mm length line with a 0.1mm lineweight Color Token: Dk-Brown1815

Lineweight: 0.1mm

Length: 0.5mm

P00067

Description: Dk-Brown1815 0.8mm length line with a 0.15mm lineweight Color Token: Dk-Brown1815

Lineweight: 0.15mm

Length: 0.8mm

P00069

Description: Dk-Brown1815 1.0mm length line with a 0.2mm lineweight Color Token: Dk-Brown1815

Lineweight: 0.2mm

Length: 1.0mm

P00081

Description: Black 0.64mm diameter filled circle Color Token: Black

Diameter: 0.64mm

Note: The component is a circle and is filled with the solid color

P00082

Description: Black 0.4mm diameter filled circle Color Token: Black

Diameter: 0.4mm

Note: The component is a circle and is filled with the solid color.

P00103

Description: Dolphin/Snag/Structural pile Color Token: Black

Diameter: 0.8mm Lineweight: 0.15mm

Note: The component is an open circle.

P00111

Description: Forest/curve Color Token: Green362

Diameter: 0.5mm Lineweight: 0.1mm

Note: The component is an open circle.

P00125

Description: Cyan 0.7mm diameter filled circle Color Token: Cyan

Diameter: 0.7mm

Note: The component is a circle and is filled with the solid color.

P00146

Description: Green362 filled square with all sides 0.8mm Color Token: Green362

Length: 0.8mm

Note: The component is a square and is filled with the solid color.

P00149

Description: Black 0.35mm length line with a 0.45mm lineweight Color Token: Black

Lineweight: 0.45mm

Length: 0.35mm

P00152

Description: Black 2.5mm length line with a 1.5mm lineweight Color Token: Black

Lineweight: 1.5mm

Length: 2.5mm

P00153

Description: Black 2.0mm length line with a 0.15mm lineweight Color Token: Black

Lineweight: 0.15mm

Length: 2.0mm

P00157

Description: Salt evaporator Color Token: Cyan

Lineweight: 0.2mm

Length: 1.5mm

Note: The component is an open square.

P00158

Description: Road route marker national motorway non-USA Color Token: Black

Lineweight: 0.1mm

Length: 4.5mm long; 2.25mm wide

Note: The component is an open rectangle.

P00160

Description: Road route marker local/secondary Color Token: Black

Diameter: 3.8mm Lineweight: 0.1mm

Note: The component is an open circle.

P00167

Description: Cyan 0.25mm diameter filled circle Color Token: Cyan

Diameter: 0.25mm

Note: The component is a circle and is filled with the solid color.

P00168

Description: Holding pen Color Token: Dk-Brown1815

Lineweight: 0.15mm

Length: 0.8mm

Note: The component is an open square.

P00174

Description: Dk-Brown1815 0.5mm length line with 0.15mm lineweight Color Token: Dk-Brown1815

Lineweight: 0.15mm

Length: 0.5mm

P00175

Description: Dragons teeth Color Token: Black

Lineweight: 0.3mm

Length: 1.0mm

Note: The component is an open square.

Description: Black 0.7mm diameter filled circle Color Token: Black

Diameter: 0.7mm

Note: The component is a circle and is filled with the solid color.

P00235

Description: Green362 0.35mm length line with a 0.45mm lineweight Color Token: Green362

Lineweight: 0.45mm

Length: 0.35mm

P00267

Description: Road route marker international Color Token: Black

Lineweight: 0.2mm

Length: 4.5mm long; 2.5mm wide

Note: The component is an open rectangle.

P00269

Description: Black 1.5mm length line with a 0.4mm lineweight Color Token: Black

Lineweight: 0.4mm

Length: 1.5mm

P00270

Description: Dk-Brown1815 1.5mm length line with a 0.4mm lineweight Color Token: Dk-Brown1815

Lineweight: 0.4mm

Length: 1.5mm

P00284

Description: Hut Color Token: Black

Lineweight: 0.1mm

Length: 0.6mm

Note: The component is an open square.

P00287

Description: Blue072 0.8mm diameter open circle Color Token: Blue072

Diameter: 0.8mm Lineweight: 0.25mm

Note: The component is an open circle.

STD-DP-14-025 29 May 2015

Annex H – Detailed Drawing Instructions

This Annex contains detailed drawing instructions for the point shape components used in Annex A for symbols that could not be easily explained in a small set of parameters. The pictures shown in this Annex are not to scale, but have been enlarged to make it easier to view the drawing. Unless otherwise noted in the Symbol Placement Instructions in Annex A, all symbol components provided in Annex H are shown in their default orientation of 0 degrees (i.e. to the south neatline).

In Annex H, there are a number of point components or symbols that have "open" or white areas. It is intended that underlying symbology (such as vegetation) would not show through any of these white openings, but rather the component would mask out underlying symbols, not allowing it to fill any of the open or white portions of the symbol. For example, the open or white portion of the Tower symbol would mask the underlying Built-up Area tint, not allowing it to fill any open portion of the Tower symbol.


See section 6.10 for Component Reference numbers in Annex H that contain an open or white area as part of the symbol.

Description: Aerial/tower communication

Component Ref #: P00155 Color Token: Black

Origin: Center of open circle

Overall component height: 3.45mm
Overall component width: 1.70mm
Diameter of open circle: 0.60mm
Lineweight of open circle: 0.10mm
Lineweight (all or other): 0.15mm




Description: Aircraft revetment

Component Ref #: P00295 Color Token: Dk-Brown1815

Origin: Center of symbol

Overall component height: 2.25mm
Overall component width: 2.25mm
Diameter of open circle: 1.25mm
Lineweight of open circle: 0.15mm
Length of stem or segment: 0.50mm
Lineweight of ticks: 0.15mm
Angle between elements: 90°




Description: Aqueduct/penstock/water race "V"

Component Ref #: P00208 Color Token: Cyan

Origin: Apex of "V"

Length of stem or segment: 0.90mm
Lineweight (all or other): 0.30mm
Angle between elements: 90°

Note: Apex is where the lines connect to form a "V".




Description: Basin gate/lock

Component Ref #: P00035 Color Token: Black

Origin: Center of symbol

Overall component height: 1.45mm
Overall component width: 1.25mm
Length of stem or segment: 0.80mm
Lineweight (all or other): 0.15mm
Angle between elements: 90°
Space between elements: 0.50mm




Description: Bridge fixed

Component Ref #: P00188 Color Token: Black

Origin: Center of symbol

Length of stem or segment: 1.50mm
Lineweight of stem or base: 0.30mm
Lineweight of ticks: 0.15mm



Description: Bridge not fixed


Component Ref #: P00202 Color Token: Black

Origin: Center of symbol

Lineweight of open circle: 0.20mm
Length of stem or segment: 1.50mm
Lineweight of stem or base: 0.30mm
Lineweight of ticks: 0.15mm

Note: Diameter of open circle is variable based on the width

of the space between the lines.




Description: Bridge pedestrian

Component Ref #: P00201 Color Token: Black

Origin: Center of symbol

Length of stem or segment: 1.50mm
Lineweight of ticks: 0.15mm
Lineweight (all or other): 0.30mm




Description: Building checkpoint

Component Ref #: P00132 Color Token: Black

Origin: Center of symbol

Overall component height: 1.75mm
Overall component width: 1.75mm
Diameter of open circle: 1.75mm
Lineweight (all or other): 0.15mm
Space between elements: 0.20mm

Note: Horizontal lines are centered in the circle




Description: Building Christian

Component Ref #: P00075 Color Token: Black

Origin: Center of solid square

Overall component height: 1.60mm
Overall component width: 0.80mm
Lineweight (all or other): 0.20mm
Angle between elements: 90°

Note: Solid square 0.50mm each side.




Description: **Building Christian cross**

Component Ref #: P00013 Color Token: Black

Origin: Center of base of staff

Overall component height: 1.10mm Overall component width: 0.80mm Lineweight (all or other): 0.20mm Angle between elements: 90°




Description: **Building diplomatic**

Component Ref #: P00186 Color Token: Black

Origin: Center of solid square

Overall component height: 2.00mm Overall component width: 0.90mm Lineweight (all or other): 0.15mm Angle between elements:

Note: Solid square 0.50mm each side.




Description: **Building diplomatic flag**

Component Ref #: P00285 Color Token: Black

Origin: Center of base of staff

Overall component height: 1.50mm Overall component width: 0.90mm Lineweight (all or other): 0.15mm Angle between elements: 90°



Description: Building hospital


Component Ref #: P00012 Color Token: Black

Origin: Center of symbol

Overall component height: 1.75mm
Overall component width: 1.75mm
Diameter of solid circle: 1.75mm
Lineweight (all or other): 0.25mm
Angle between elements: 90°

Note: White cross bars are 1.25mm centered within solid

circle.



Description: Building hospital symbol


Component Ref #: P00296 Color Token: Black

Origin: Center of symbol

Overall component height: 2.25mm
Overall component width: 2.25mm
Diameter of solid circle: 1.75mm
Lineweight of open circle: 0.10mm
Lineweight (all or other): 0.25mm
Angle between elements: 90°

Note: White cross bars are 1.25mm centered within solid

circle. Lineweight of white circle 0.15mm




Description: Building Islamic

Component Ref #: P00076 Color Token: Black

Origin: Center of solid square

Overall component height: 1.60mm
Overall component width: 0.90mm
Lineweight (all or other): 0.20mm
Angle between elements: 90°

Note: Solid square 0.50mm each side.




Description: Building Islamic crescent

Component Ref #: P00014 Color Token: Black

Origin: Center of base of staff

Overall component height: 1.10mm
Overall component width: 0.90mm
Lineweight (all or other): 0.20mm
Angle between elements: 90°

Note: Half circle is centered on staff




Description: Building Judaism

Component Ref #: P00077 Color Token: Black

Origin: Center of solid square

Overall component height: 1.60mm
Overall component width: 0.80mm
Lineweight (all or other): 0.20mm
Angle between elements: 90°

Note: Solid square 0.50mm each side.




Description: Building Judaism "T"

Component Ref #: P00017 Color Token: Black

Origin: Center of symbol

Overall component height: 1.10mm
Overall component width: 0.80mm
Length of stem or segment: 0.90mm
Lineweight (all or other): 0.20mm
Angle between elements: 90°




Description: Building minaret

Component Ref #: P00184 Color Token: Black

Origin: Center of open circle

Overall component height: 2.35mm
Overall component width: 1.25mm
Diameter of solid circle: 0.30mm
Diameter of open circle: 1.25mm
Lineweight of open circle: 0.15mm
Length of stem or segment: 0.2mm
Angle between elements: 90°



Description: Building pagoda


Component Ref #: P00019 Color Token: Black

Origin: Center of symbol

Overall component height: 1.65mm
Overall component width: 1.10mm
Lineweight (all or other): 0.20mm

Note: A white 0.40mm square is placed 0.20mm from

bottom. Arc radii is o.44mm.




Description: Building school

Component Ref #: P00118 Color Token: Black

Origin: Center of solid square

Overall component height: 1.70mm
Overall component width: 0.90mm
Lineweight (all or other): 0.20mm

Note: Solid square 0.50mm each side.




Description: Building school flag

Component Ref #: P00016 Color Token: Black

Origin: Center of base of staff

Overall component height: 1.20mm
Overall component width: 0.90mm
Lineweight (all or other): 0.20mm



Description: Building stupa


Component Ref #: P00031 Color Token: Black

Origin: Center of symbol

Overall component height: 1.80mm
Overall component width: 1.50mm
Lineweight (all or other): 0.15mm

Grid square size: 0.10mm x 0.10mm

Note: Steeple top radius is 0.04mm




Description: Building temple

Component Ref #: P00018 Color Token: Black

Origin: Center of symbol

Overall component height: 1.36mm
Overall component width: 1.86mm
Lineweight (all or other): 0.20mm

Note: Large arc radius 0.43mm. Small arc radius 0.35mm.




Description: Cairn

Component Ref #: P00022 Color Token: Black

Origin: Center of open circle

Overall component height: 1.65mm
Overall component width: 2.00mm
Diameter of open circle: 0.50mm
Lineweight of open circle: 0.10mm
Lineweight of stem or base: 0.10mm

Note: Large circle diameters is 0.90mm. Lineweight 0.13mm.




Description: Camp/campsite

Component Ref #: P00005

Origin: Center of symbol

Overall component height: 1.85mm
Overall component width: 1.55mm
Length of stem or segment: 2.00mm
Lineweight (all or other): 0.15mm
Angle between elements: 45°

Color Token: Black




Description: Cave mouth

Component Ref #: P00183 Color Token: Black

Origin: Center of symbol

Overall component height: 1.10mm
Overall component width: 2.00mm
Length of stem or segment: 1.50mm
Lineweight (all or other): 0.20mm
Angle between elements: 135°




Description: Cemetery/tomb Buddhism

Component Ref #: P00272 Color Token: Black

Origin: Center of symbol

Overall component height: 1.00mm
Overall component width: 1.50mm
Lineweight (all or other): 0.25mm
Angle between elements: 90°




Description: Cemetery/tomb Christian

Component Ref #: P00253 Color Token: Black

Origin: Center of symbol

Overall component height: 2.00mm
Overall component width: 1.10mm
Lineweight (all or other): 0.25mm
Angle between elements: 90°




Description: Cemetery/tomb Islam

Component Ref #: P00254 Color Token: Black

Origin: Center of symbol

Overall component height: 2.00mm
Overall component width: 1.30mm
Lineweight (all or other): 0.25mm
Angle between elements: 90°

Note: Half circle is centered on staff




Description: Cemetery/tomb Judaism

Component Ref #: P00255 Color Token: Black

Origin: Center of symbol

Overall component height: 2.00mm
Overall component width: 0.80mm
Lineweight (all or other): 0.25mm
Angle between elements: 90°



Description: Cemetery/tomb other

Component Ref #: P00271 Color Token: Black


Origin: Center of symbol

Overall component height: 1.45mm
Overall component width: 2.00mm
Lineweight (all or other): 0.25mm

Grid square size: 0.20mm x 0.20mm

Note: Top of symbol is the upper part of an ellipse 1.00mm

wide by 1.1 mm high



Description: Cooling tower

Component Ref #: P00137 Color Token: Black


Origin: Center of open circle

Overall component height: 2.50mm
Overall component width: 1.75mm
Diameter of open circle: 0.60mm
Lineweight of open circle: 0.10mm

Grid square size: 0.20mm x 0.20mm

Note: Width at top 1.10mm. Width at narrowest part

 $0.80mm. \ \ Width \ at \ bottom \ 1.75mm$




Description: Crane

Component Ref #: P00131 Color Token: Black

Origin: Center of open circle

Overall component height: 1.40mm
Overall component width: 1.80mm
Diameter of open circle: 1.40mm
Lineweight of open circle: 0.15mm
Length of stem or segment: 1.10mm
Lineweight (all or other): 0.15mm




Description: Culvert "V"

Component Ref #: P00107 Color Token: Black

Origin: Apex of "V"

Length of stem or segment: 1.00mm Lineweight (all or other): 0.20mm Angle between elements: 90°

Note: Apex is where the lines connect to form a "V".



Description: Culvert double "V"


Component Ref #: P00106 Color Token: Black

Origin: Center of symbol

Length of stem or segment: 1.00mm Lineweight (all or other): 0.20mm Angle between elements: 90°

Note: Spacing between "V" elements is variable based on

the width of the corresponding transportation feature.



Description: Dish aerial

Component Ref #: P00133 Color Token: Black


Origin: Center of open circle

Overall component height: 2.40mm
Overall component width: 1.25mm
Diameter of open circle: 0.60mm
Lineweight of open circle: 0.10mm
Lineweight of stem or base: 0.10mm
Lineweight (all or other): 0.10mm

Grid square size: 0.20mm x 0.20mm

Note: Length of base 1.00mm. Body tapers from 0.35mm to

0.65mm at the base




Description: Extraction mine intact not peat

Component Ref #: P00001 Color Token: Black

Origin: Center of symbol

Overall component height: 1.85mm
Overall component width: 1.85mm
Lineweight (all or other): 0.25mm



Description: Extraction mine not intact not peat

Component Ref #: P00002 Color Token: Black

Origin: Center of symbol

Overall component height: 1.85mm
Overall component width: 1.85mm
Lineweight (all or other): 0.25mm




Description: Extraction mine peat

Component Ref #: P00084 Color Token: Black

Origin: Center of symbol

Overall component height: 2.00mm
Overall component width: 4.50mm
Lineweight (all or other): 0.10mm

Note: Each rectangle 1.50mm x 1.00mm




Description: Fence "X"

Component Ref #: P00286 Color Token: Black

Origin: Center of symbol

Overall component height: 1.00mm
Overall component width: 1.00mm
Length of stem or segment: 1.00mm
Lineweight (all or other): 0.15mm
Angle between elements: 90°




Description: Flare pipe

Component Ref #: P00145 Color Token: Black

Origin: Center of open circle

Overall component height: 2.60mm
Overall component width: 1.00mm
Diameter of open circle: 0.60mm
Lineweight of open circle: 0.10mm
Lineweight of stem or base: 0.10mm

Grid square size: 0.10mm x 0.10mm



Description: Fortified building

Component Ref #: P00108 Color Token: Black

Open square 0.80mm each side.

Origin: Center of symbol

Overall component height: 1.50mm
Overall component width: 1.50mm
Length of stem or segment: 0.50mm
Lineweight (all or other): 0.10mm

Note:

45°
90°

0.50 mm


Description: Geothermal outlet

Component Ref #: P00027 Color Token: Dk-Brown1815

Origin: Center of solid circle

Overall component height: 2.70mm
Overall component width: 0.80mm
Lineweight (all or other): 0.20mm

Grid square size: 0.20mm x 0.20mm



Description: Greenhouse


Component Ref #: P00171 Color Token: Black/Green362-42

Origin: Center of symbol

Overall component height: 0.60mm
Overall component width: 0.60mm
Lineweight (all or other): 0.10mm

Note: Outline is Black. Fill is Green362-42 (42% screen, 45°

angle)




Description: Hazardous rock/reef

Component Ref #: P00095 Color Token: Black

Origin: Center of symbol

Overall component height: 1.50mm
Overall component width: 1.50mm
Length of stem or segment: 1.50mm
Lineweight (all or other): 0.10mm
Angle between elements: 60°



Description: Helipad

Component Ref #: P00090 Color Token: Blue072

Origin: Center of symbol

Overall component height: 3.00mm
Overall component width: 3.00mm
Diameter of open circle: 3.00mm
Lineweight (all or other): 0.25mm

Note: The "H" is formed by two 1.50mm vertical lines and

one 1.20mm horizontal line.



Description: Helipad at hospital

Component Ref #: P00089 Color Token: Blue072

Origin: Center of symbol

Overall component height: 3.00mm
Overall component width: 3.00mm
Lineweight (all or other): 0.25mm

Note: The "H" is formed by two 1.50mm vertical lines and

one 1.20mm horizontal line.




Description: Ice peak not frozen water

Component Ref #: P00066 Color Token: Dk-Brown1815

Origin: Center of symbol

Overall component height: 2.70mm
Overall component width: 2.70mm
Length of stem or segment: 0.60mm
Lineweight (all or other): 0.15mm
Angle between elements: 45°

Note: Ticks emanate from a 1.50mm circle



Description: Lighthouse

Component Ref #: P00135 Color Token: Black


Origin: Center of open circle

Overall component height: 3.10mm
Overall component width: 2.65mm
Diameter of open circle: 0.60mm
Lineweight of open circle: 0.10mm
Lineweight of ticks: 0.15mm

Note: Four 0.90mm "rays" rotated 30, 150, 210, and 330

degrees. A white 0.30mm square is placed 0.10mm

from top.




Description: Located object

Component Ref #: P00010 Color Token: Black

Origin: Center of symbol

Overall component height: 1.25mm
Overall component width: 1.25mm
Diameter of solid circle: 0.30mm
Diameter of open circle: 1.25mm
Lineweight of open circle: 0.15mm




Description: Lock/pedestrian bridge/sluice gate "V"

Component Ref #: P00105 Color Token: Black

Origin: Apex of "V"

Length of stem or segment: 0.80mm
Lineweight (all or other): 0.15mm
Angle between elements: 90°

Note: Apex is where the lines connect to form a "V".



Description: Memorial monument


Component Ref #: P00136 Color Token: Black

Origin: Center of symbol

Overall component height: 1.50mm
Overall component width: 1.50mm
Diameter of open circle: 1.50mm
Lineweight of open circle: 0.10mm

Note: Equilateral triangle fits within open circle and is

1.20mm on each side




Description: Mooring mast

Component Ref #: P00198 Color Token: Black

Origin: Center of open circle

Overall component height: 2.00mm
Overall component width: 1.65mm
Diameter of open circle: 0.60mm
Lineweight of open circle: 0.10mm
Length of stem or segment: 1.40mm
Lineweight of stem or base: 0.10mm




Description: Motor vehicle station

Component Ref #: P00165 Color Token: Black

Origin: Center of solid square

Overall component height: 2.10mm
Overall component width: 1.10mm
Length of stem or segment: 0.60mm
Lineweight (all or other): 0.15mm
Angle between elements: 60°

Note: Solid square 0.50mm each side.




Description: Motor vehicle station symbol

Component Ref #: P00275 Color Token: Black

Origin: Center of base of staff

Overall component height: 1.60mm
Overall component width: 1.10mm
Length of stem or segment: 0.60mm
Lineweight (all or other): 0.15mm
Angle between elements: 60°



Description: Mountain pass

Component Ref #: P00029 Color Token: Black


Origin: Center of symbol

Overall component height: 4.20mm
Overall component width: 2.82mm

Note: Space between inner and outer arc radii forms the

symbol. Inner arc radii is 3.50mm. Outer arc radii is

5.00mm.




Description: Natural pool intermittent

Component Ref #: P00032 Color Token: Cyan

Origin: Center of open circle

Overall component height: 2.90mm
Overall component width: 1.00mm
Diameter of open circle: 1.00mm
Lineweight of open circle: 0.15mm
Lineweight (all or other): 0.20mm

Grid square size: 0.20mm x 0.20mm



Description: Natural pool perennial

Component Ref #: P00026 Color Token: Cyan

Origin: Center of solid circle

Overall component height: 2.70mm
Overall component width: 0.80mm
Diameter of solid circle: 0.8mm
Lineweight (all or other): 0.20mm

Grid square size: 0.20mm x 0.20mm




Description: Not intact circle 0.8mm

Component Ref #: P00291 Color Token: Black/Black-12

Origin: Center of symbol

Overall component height: 0.80mm
Overall component width: 0.80mm
Diameter of open circle: 0.80mm
Lineweight (all or other): 0.10mm

Note: Fill is Black-12 (12% screen 45° angle)




Description: Not intact square 0.6mm

Component Ref #: P00293 Color Token: Black/Black-12

Origin: Center of symbol

Overall component height: 0.60mm
Overall component width: 0.60mm
Lineweight (all or other): 0.10mm

Note: Fill is Black-12 (12% screen 45° angle)




Description: Not intact square 0.8mm

Component Ref #: P00173 Color Token: Black/Black-12

Origin: Center of symbol

Overall component height: 0.80mm
Overall component width: 0.80mm
Lineweight (all or other): 0.10mm

Note: Fill is Black-12 (12% screen 45° angle)




Description: Oasis

Component Ref #: P00260 Color Token: Green362

Origin: Center of symbol

Overall component height: 3.00mm
Overall component width: 2.70mm
Lineweight of stem or base: 0.20mm

Grid square size: 0.20mm x 0.20mm




Description: Offshore construction point

Component Ref #: P00163 Color Token: Black

Origin: Center of symbol

Overall component height: 1.20mm
Overall component width: 1.20mm
Diameter of solid circle: 0.20mm
Lineweight (all or other): 0.10mm




Description: Pipeline elevated "V"

Component Ref #: P00045 Color Token: Black

Origin: Apex of "V"

Length of stem or segment: 0.70mm
Lineweight (all or other): 0.20mm
Angle between elements: 90°

Note: Apex is where the lines connect to form a "V".




Description: Pipeline water elevated "V"

Component Ref #: P00058 Color Token: Cyan

Origin: Apex of "V"

Length of stem or segment: 0.70mm Lineweight (all or other): 0.20mm Angle between elements: 90°

Note: Apex is where the lines connect to form a "V".



Description: Power substation


Component Ref #: P00138 Color Token: Black/Blue072-42

Origin: Center of symbol

Overall component height: 2.50mm
Overall component width: 1.00mm
Lineweight (all or other): 0.15mm
Angle between elements: 60°

Note: Outline is Black. Fill is Blue072-42 (42% screen 45°

angle).




Description: Pylon

Component Ref #: P00020 Color Token: Blue072

Origin: Center of symbol

Overall component height: 3.00mm
Overall component width: 1.00mm




Description: Radio aid

Component Ref #: P00294 Color Token: Blue072

Origin: Center of symbol

Overall component height: 1.90mm
Overall component width: 1.90mm
Diameter of solid circle: 0.40mm
Diameter of open circle: 1.90mm
Lineweight of open circle: 0.30mm



1.00 mm Description: **Railway station** Component Ref #: P00079 Color Token: Black Origin: Center of symbol Overall component height: 1.00mm Overall component width: 1.00mm Lineweight (all or other): 0.10mm Note: Open square 1.00mm each side. Solid square 0.50mm each side. 0.50 mm Description: Railway tick broad double Component Ref #: P00278 Color Token: Black Origin: Center of symbol Overall component height: 1.50mm Overall component width: 0.80mm Length of stem or segment: 1.50mm Lineweight (all or other): 0.15mm Space between elements: 0.50mm 0.50 mm 0.70 mm Description: Railway tick broad electrified Component Ref #: P00280 Color Token: Black Origin: Center of symbol Overall component height: 1.50mm 90° Overall component width: 0.70mm Length of stem or segment: 1.50mm Lineweight (all or other): 0.15mm Angle between elements: Length of top segment 0.70mm Note:


Description: Railway tick broad electrified double

Component Ref #: P00282 Color Token: Black

Origin: Center of symbol

Overall component height: 1.50mm
Overall component width: 1.90mm
Length of stem or segment: 1.50mm
Lineweight (all or other): 0.15mm
Angle between elements: 90°
Space between elements: 0.50mm

Note: Length of top segment 0.70mm




Description: Railway tick narrow double

Component Ref #: P00277 Color Token: Black

Origin: Center of symbol

Overall component height: 0.75mm
Overall component width: 0.80mm
Length of stem or segment: 0.75mm
Lineweight (all or other): 0.15mm
Space between elements: 0.50mm




Description: Railway tick narrow electrified

Component Ref #: P00279 Color Token: Black

Origin: Center of symbol

Overall component height: 0.75mm
Overall component width: 0.70mm
Length of stem or segment: 0.75mm
Lineweight (all or other): 0.15mm
Angle between elements: 90°

Note: Length of top segment 0.70mm




Description: Railway tick narrow electrified double

Component Ref #: P00281 Color Token: Black

Origin: Center of symbol

Overall component height: 0.75mm
Overall component width: 1.90mm
Length of stem or segment: 0.75mm
Lineweight (all or other): 0.15mm
Angle between elements: 90°
Space between elements: 0.50mm

Note: Length of top segment 0.70mm



Description: Railway turntable


Component Ref #: P00238 Color Token: Black

Origin: Center of symbol

Overall component height: 1.50mm
Overall component width: 1.50mm
Diameter of open circle: 1.50mm
Lineweight of open circle: 0.15mm
Lineweight (all or other): 0.15mm

Note: Interior line orientation is 45° centered inside the

circle




Description: Rapids

Component Ref #: P00195 Color Token: Cyan

Origin: Center of symbol

Overall component height: 0.90mm
Overall component width: 1.30mm
Length of stem or segment: 1.30mm
Lineweight (all or other): 0.20mm
Space between elements: 0.50mm



Description: Reef arc


Component Ref #: P00207 Color Token: Black-54

Origin: Center of symbol

Overall component height: 0.75mm
Overall component width: 0.70mm
Lineweight (all or other): 0.10mm
Angle between elements: 11°

Note: Arc radius 0.20mm. Symbol is Black-54 (54% screen

45° angle).



Description: Rig inland


Component Ref #: P00162 Color Token: Black

Origin: Center of open circle

Overall component height: 2.30mm
Overall component width: 1.60mm
Diameter of open circle: 0.60mm
Lineweight of open circle: 0.10mm

Grid square size: 0.20mm x 0.20mm

Note: Base leg end radius is 1.125mm. Tip radius is 0.25mm.



Description: River flow arrow

Component Ref #: P00200 Color Token: Cyan

Origin: Center of symbol

Overall component height: 1.50mm
Overall component width: 9.00mm
Lineweight (all or other): 0.25mm

Grid square size: 0.20mm x 0.20mm




Description: Road route marker national non-USA

Component Ref #: P00268 Color Token: Black

Origin: Center of symbol

Overall component height: 2.25mm
Overall component width: 4.50mm
Lineweight (all or other): 0.10mm

Note: Arc radius 0.70mm




Description: Rock formation

Component Ref #: P00071 Color Token: Dk-Brown1815

Origin: Center of symbol

Overall component height: 1.44mm
Overall component width: 1.44mm
Diameter of open circle: 0.25mm
Length of stem or segment: 0.60mm
Lineweight (all or other): 0.25mm
Angle between elements: 60°

Note: Ticks emanate from a 0.25mm circle




Description: Ruins

Component Ref #: P00265 Color Token: Black

Origin: Center of symbol

Overall component height: 1.20mm
Overall component width: 1.20mm
Diameter of solid circle: 0.40mm
Angle between elements: 60°
Space between elements: 0.40mm




Description: Settling pond

Component Ref #: P00288 Color Token: Black/Cyan-31

Origin: Center of symbol

Overall component height: 0.80mm
Overall component width: 0.80mm
Lineweight (all or other): 0.10mm

Note: Outline is Black. Fill is Cyan-31 (31% screen 45° angle)



Description: Ski jump

Component Ref #: P00274 Color Token: Black

Origin: Center of symbol


Overall component height: 2.00mm
Overall component width: 2.50mm
Lineweight (all or other): 0.20mm

Grid square size: 0.20mm x 0.20mm

Note: Width of top 0.40mm. Width of bottom of thick base 1.00mm. Height of thick base to apex of ramp

1.50mm. Angle between ramp and thick base is 25

degrees.




Description: Smokestack

Component Ref #: P00140 Color Token: Black

Origin: Center of open circle

Overall component height: 2.50mm
Overall component width: 1.25mm
Diameter of open circle: 0.60mm
Lineweight of open circle: 0.10mm
Lineweight of stem or base: 0.10mm



Description: Sports ground

Component Ref #: P00210 Color Token: Green362/Green362-12


Origin: Center of symbol

Overall component height: 1.50mm
Overall component width: 1.50mm
Lineweight (all or other): 0.15mm

Note:

Fill is Green362-12 (12% screen 45° angle). Green, 6 pt. condensed, upper case "S" is centered within

square.



Description: Surface bunker

Component Ref #: P00283 Color Token: Black/Dk-Brown1815


Origin: Center of symbol

Overall component height: 1.50mm
Overall component width: 2.20mm
Lineweight of ticks: 0.15mm
Lineweight (all or other): 0.10mm

Note:

Tick spacing (intersecting the ellipse) is 0.35mm. Angle of sides 65 and 115 degrees. Base is Black. Rays are

Dk-Brown1815.




Description: Survey point geodetic

Component Ref #: P00179 Color Token: Black

Origin: Center of symbol

Overall component height: 1.30mm
Overall component width: 1.50mm
Diameter of solid circle: 0.30mm
Length of stem or segment: 1.50mm
Lineweight (all or other): 0.10mm
Angle between elements: 60°




Description: Swimming pool

Component Ref #: P00088 Color Token: Black/Cyan-31

Origin: Center of symbol

Overall component height: 0.50mm
Overall component width: 1.00mm
Lineweight (all or other): 0.10mm

Note: Outline is Black. Fill is Cyan-31 (31% screen 45° angle)




Description: Tower non-communication

Component Ref #: P00141 Color Token: Black

Origin: Center of open circle

Overall component height: 2.75mm
Overall component width: 1.00mm
Diameter of open circle: 0.60mm
Lineweight of open circle: 0.10mm
Lineweight of stem or base: 0.10mm
Lineweight (all or other): 0.15mm




Description: Tree other

Component Ref #: P00030 Color Token: Green362

Origin: Center of symbol

Overall component height: 2.50mm
Overall component width: 1.65mm
Lineweight (all or other): 0.20mm

Grid square size: 0.20mm x 0.20mm




Description: Tunnel entrance not water

Component Ref #: P00073 Color Token: Black

Origin: Center of symbol

Overall component height: 2.85mm
Overall component width: 0.65mm
Length of stem or segment: 2.00mm
Lineweight (all or other): 0.20mm
Angle between elements: 45°

Note: Tick length 0.60mm



Description: Vanishing point disappearing


Component Ref #: P00028 Color Token: Cyan

Origin: Center of symbol

Overall component height: 1.50mm
Overall component width: 1.50mm
Diameter of solid circle: 1.50mm
Diameter of open circle: 0.50mm

Note: Open circle is offset 0.35mm from center of the

symbol




Description: Vanishing point dissipating

Component Ref #: P00059 Color Token: Cyan

Origin: Apex of "V"

Length of stem or segment: 1.00mm Lineweight (all or other): 0.20mm Angle between elements: 90°

Note: Apex is where the lines connect to form a "V".




Description: Vertical obstruction

Component Ref #: P00008 Color Token: Blue072

Origin: Center of solid circle

Overall component height: 3.70mm
Overall component width: 2.85mm
Diameter of solid circle: 0.40mm

Note: Base leg end radius is 1.125mm. Tip radius is 0.25mm.



Description: Vertical obstruction linear


Component Ref #: P00113 Color Token: Blue072

Origin: Center of open circle

Overall component height: 4.00mm
Overall component width: 4.16mm
Diameter of open circle: 0.60mm
Lineweight of open circle: 0.10mm
Lineweight (all or other): 0.20mm

Grid square size: 0.20mm x 0.20mm

Note: Base leg end radius is 1.125mm. Tip radius is 0.25mm.



Description: Vertical obstruction multiple

Component Ref #: P00101 Color Token: Blue072


Origin: Center of solid circle

Overall component height: 3.70mm
Overall component width: 4.16mm
Diameter of solid circle: 0.50mm

Grid square size: 0.20mm x 0.20mm

Note: Base leg end radius is 1.125mm. Tip radius is 0.25mm.

Bottom arc radius is 1.85mm




Description: Vertical obstruction pylon

Component Ref #: P00292 Color Token: Blue072

Origin: Center of open circle

Overall component height: 4.00mm
Overall component width: 2.85mm
Diameter of open circle: 0.60mm
Lineweight of open circle: 0.10mm

Note: Base leg end radius is 1.125mm. Tip radius is 0.25mm.




Description: Volcano

Component Ref #: P00064 Color Token: Dk-Brown1815

Origin: Center of symbol

Overall component height: 3.0mm
Overall component width: 3.0mm
Diameter of open circle: 1.0mm
Lineweight of open circle: 0.10mm
Length of stem or segment: 1.0mm
Lineweight (all or other): 0.10mm
Angle between elements: 45°




Description: Water aerodrome

Component Ref #: P00257 Color Token: Blue072

Origin: Center of symbol

Overall component height: 5.0mm
Overall component width: 5.0mm
Diameter of open circle: 5.0mm
Lineweight of open circle: 0.40mm

Grid square size: 0.20mm x 0.20mm




Description: Water intake tower

Component Ref #: P00148 Color Token: Black

Origin: Center of solid circle

Overall component height: 2.25mm
Overall component width: 1.25mm
Diameter of open circle: 0.60mm
Lineweight of open circle: 0.10mm
Lineweight of stem or base: 0.10mm

Note: Body tapers from 0.60mm to 0.80mm at the base




Description: Water tower

Component Ref #: P00142 Color Token: Black/Cyan

Origin: Center of open circle

Overall component height: 2.75mm
Overall component width: 1.00mm
Diameter of open circle: 0.60mm
Lineweight of open circle: 0.10mm
Lineweight of stem or base: 0.10mm
Lineweight (all or other): 0.15mm

Note: Outline is black. Fill of circle at top is solid cyan.



Description: Wind turbine

Component Ref #: P00143 Color Token: Black

Origin: Center of open circle


Overall component height: 3.00mm
Overall component width: 1.75mm
Diameter of open circle: 0.60mm
Lineweight of open circle: 0.10mm
Length of stem or segment: 1.40mm
Lineweight of stem or base: 0.10mm
Lineweight (all or other): 0.20mm

Grid square size: 0.20mm x 0.20mm

Note: Length of base 1.00mm. Blades at widest point

0.25mm. Blade length 1.05mm. Angle between

blades is 120 degrees



Description: Windmill

Component Ref #: P00144 Color Token: Black

Origin: Center of open circle


Overall component height: 2.40mm
Overall component width: 1.20mm
Diameter of open circle: 0.60mm
Lineweight of open circle: 0.10mm
Lineweight of stem or base: 0.10mm
Lineweight (all or other): 0.15mm

Grid square size: 0.20mm x 0.20mm

Note: Length of base 1.20mm. Body is joined at the top and

expands to 0.75mm. Vane length is 1.30mm. Acute angle between vanes is 84 degrees; obtuse angle

between vanes is 96 degrees.




Description: Wreck

Component Ref #: P00206 Color Token: Black

Origin: Center of open circle

Overall component height: 1.96mm
Overall component width: 3.41mm
Diameter of open circle: 0.20mm
Lineweight (all or other): 0.20mm



STD-DP-14-025 29 May 2015

Annex I – Patterns


Samples of the patterns referenced in Annex A are provided in this annex. The Component Reference number provides the link in Annex A to where the pattern is included as part of a symbol. Since most of the area patterns were inherited from the MIL-STD-2410, a historical reference has been made in the document for each of the patterns in Annex I to identify its original pattern number in the MIL-STD-2410. For example, the field "MIL-STD-2410 Reference: AP-95" means that the area pattern was originally AP-95 in the MIL-STD-2410 document. The reader may wish to reference the listed area pattern in the MIL-STD-2410 for additional information.

All pattern samples provided in Annex I are shown in their default orientation (0 degrees). Some area patterns will require rotation to correctly portray the depicted features with ground truth (for example Sand Dunes).

Description: Black Peat Fill

Component Reference: A00001

MIL-STD-2410 Reference: AP-129




Description: Black-42 Shantytown Screened Fill

Component Reference: A00014

MIL-STD-2410 Reference: AP-132


Note: A 42%, 120D, 45 degree angle screen is applied to the area pattern.



Description: Cyan Bog, Marsh Fill

Component Reference: A00018

MIL-STD-2410 Reference: AP-12




Description: Cyan Diagonal Line Fill

Component Reference: A00062

MIL-STD-2410 Reference: LP-3


Note: 35% coverage, 40L, 135 degree angle lines.



Description: Cyan Dry Drainage Fill


Component Reference: A00020

MIL-STD-2410 Reference: AP-95



Description: Cyan Glacier Fill

Component Reference: A00017




Description: Cyan Land Subject to Inundation Fill

Component Reference: A00015

MIL-STD-2410 Reference: AP-10

Description: Cyan Rapids Pattern


Component Reference: A00065



Description: Cyan Rice Fill


Component Reference: A00019

MIL-STD-2410 Reference: AP-4



Description: Cyan Sabkha Fill

Component Reference: A00016




Description: Cyan Salt Evaporator Fill

Component Reference: A00044

MIL-STD-2410 Reference: No existing MIL_STD_2410 area pattern.

Note: Specific parameters include - Line weight: 0.2mm; Length: 1.5mm; Grid squares: 1.5mm x 1.5mm. A grid pattern is comprised of 1.5mm x 1.5mm squares. Grid alignment is parallel to longest axis of the perimeter line and

centered.




Description: Dk-Brown1815 Crescent Sand Dunes Fill

Component Reference: A00031

MIL-STD-2410 Reference: AP-108

Note: Sand Dune Orientation (SDO) value of area pattern symbol sample is 0

degrees. Black arrow indicates prevailing wind direction.




Description: Dk-Brown1815 Diagonal Line Fill

Component Reference: A00061

MIL-STD-2410 Reference: LP-3

Note: 35% coverage, 40L, 135 degree angle lines



Description: Dk-Brown1815 Dome Sand Dunes Fill


Component Reference: A00042



Description: Dk-Brown1815 Gravel Fill

Component Reference: A00036

MIL-STD-2410 Reference: AP-99




Description: Dk-Brown1815 Linear Sand Dunes Fill

Component Reference: A00043

MIL-STD-2410 Reference: AP-118

Note: Sand Dune Orientation (SDO) value of area pattern symbol sample is 0

degrees. Black arrow indicates prevailing wind direction.




Description: Dk-Brown1815 Ripple Sand Dunes Fill

Component Reference: A00032

MIL-STD-2410 Reference: AP-112


Note: Sand Dune Orientation (SDO) value of area pattern symbol sample is 0

degrees. Black arrow indicates prevailing wind direction.



Description: Dk-Brown1815 Sand Fill


Component Reference: A00035



Description: Dk-Brown1815 Star Sand Dunes Fill

Component Reference: A00033

MIL-STD-2410 Reference: AP-120




Description: Dk-Brown1815 Transverse Sand Dunes Fill

Component Reference: A00034

MIL-STD-2410 Reference: AP-127

Note: Sand Dune Orientation (SDO) value of area pattern symbol sample is 0

degrees. Black arrow indicates prevailing wind direction.




MGCP Portrayal Standard, Annex I (v2.0.1) I - 10 Description: Dk-Brown1815-54 Distorted Surface Screened Fill

Component Reference: A00030

MIL-STD-2410 Reference: AP-103

Note: A 54%, 120D, 45 degree angle screen is applied to the area pattern.




Description: Dk-Brown1815-54 Not Intact BUA Screened Fill

Component Reference: A00063

MIL-STD-2410 Reference: LP-6

Note: 38% coverage, 34L, 45/135 degree angle lines and pattern is screened (54%


screen, 120D, 45 degree angle)



Description: Green362 Cane Fill

Component Reference: A00050

MIL-STD-2410 Reference: AP-86




Description: Green362 Cropland dot fill


Component Reference: A00118

MIL-STD-2410 Reference: No existing MIL_STD_2410 area pattern.

Note: Green362 0.2mm diameter dots. See diagram for specific parameters.

Entire pattern is rotated to 30 degrees.






MGCP Portrayal Standard, Annex I (v2.0.1)

Description: Green362 Deciduous Tree Fill

Component Reference: A00011

MIL-STD-2410 Reference: AP-54



Description: Green362 Evergreen Tree Fill

Component Reference: A00012

Description: Green362 Grassland Fill

Component Reference: A00126

MIL-STD-2410 Reference: No existing MIL_STD_2410 area pattern.

Note: Match sample pattern provided.


THE REPORT OF TH

Description: Green362 Greenhouse Fill

Component Reference: A00124

MIL-STD-2410 Reference: LP-6


Note: 38% coverage, 34L, 45/135 degree angle lines



Description: Green362 Mangrove Fill

Component Reference: A00025

MIL-STD-2410 Reference: AP-8




Description: Green362 Mixed Tree Fill

Component Reference: A00013

Description: Green362 Nipa Fill

Component Reference: A00024


MIL-STD-2410 Reference: AP-7



Description: Green362 Orchard / Plantation Fill

Component Reference: A00028

MIL-STD-2410 Reference: AP-74



Description: Green362 Scattered Trees Fill


Component Reference: A00047

MIL-STD-2410 Reference: AP-44

Description: Green362 Scrub / Thicket Fill

Component Reference: A00027


MIL-STD-2410 Reference: AP-68



Description: Green362 Vineyard / Hops Fill

Component Reference: A00029

MIL-STD-2410 Reference: AP-77



Annex J - Generalization and Label Rules

The generalization and label rules associated with individual feature symbols in Annex A are listed here by rule number, grouped by its 2-letter rule category designator and then sequentially within that group. Rules are listed once, though a particular rule may be associated with multiple feature symbols.

Generalization rules may modify the geospatial data being input into the portrayal process to achieve the desired result.

- **GA** Generalization Aggregation rules blend or combine identical contiguous features.
- **GC** Generalization Change rules indicate when a geometry will be altered or changed from one delineation to another.

Label rules indicate how labels are placed with respect to their related geometry and/or symbol.

LP - Label Placement rules indicate the initial baseline placement of labels used as a part of a symbol, prior to finishing activities.

GA - Generalization Aggregation rules

GA-9999 Contiguous line/curve and area/surface features that have matching symbol criteria and label string outputs shall be blended to form a single feature.

GC - Generalization Change rules

- GC-9978 For area/surface General Buildings (AL015) with a Feature Function (FFN) of Hospital or House of Worship Type (HWT) of Minaret, Pagoda, Stupa, or Temple; and if the area (ARA) is less than the square meters indicated for the scale (1:50,000 -- 5,625 sq. m; 1:100,000 -- 22,500 sq. m), the area/surface delineation shall be replaced with a point delineation. The point delineation shall be placed at the centroid of the area/surface feature.
- GC-9979 Replace the area/surface delineation with a line/curve delineation. The line/curve delineation shall be placed equidistant from each side of the length of the area/surface feature.
- GC-9981 If the length (LEN) is less than the number of meters indicated for the scale (1:50,000 -- 50 m; 1:100,000 -- 100 m), then the length shall be increased to that number of meters. If the width (WID) is less than the indicated number of meters for the scale (1:50,000 -- 40 m; 1:100,000 -- 80 m), then the width shall be increased to that number of meters. Lengths and widths shall be increased equally in each direction from the centroid of the area/surface feature.
- GC-9982 If the area (ARA) is less than the square meters indicated for the scale (1:50,000 -- 62,500 sq. m; 1:100,000 -- 250,000 sq. m), the area/surface delineation shall be replaced with a point delineation. The point delineation shall be placed at the centroid of the area/surface feature.
- GC-9983 If Height Above surface Level (HGT) > = 46 meters, then the area/surface delineation shall be replaced with a point delineation. The point delineation shall be placed at the centroid of the area/surface feature.
- GC-9985 Replace the area/surface delineation with a point delineation. The point delineation shall be placed at the centroid of the area/surface feature.
- GC-9986 Replace the line/curve delineation with a point delineation. The point delineation shall be placed at the midpoint of the line/curve feature
- GC-9988 If the length (LEN) is less than the number of meters indicated for the scale (1:50,000 -- 125 m; 1:100,000 -- 250 m), then length shall be increased to that number of meters. Lengths shall be increased equally in each direction from the midpoint of the line/curve feature.
- GC-9989 If the width (WID) is less than the number of meters indicated for the scale (1:50,000 -- 50 m; 1:100,000 -- 100 m), the area/surface delineation shall be replaced with a line/curve delineation. The line/curve delineation shall be placed equidistant from each side of the length of the area/surface feature.
- GC-9990 If the width (WID) is less than the number of meters indicated for the scale (1:50,000 -- 25 m; 1:100,000 -- 50 m), the area/surface delineation shall be replaced with a line/curve delineation. The line/curve delineation shall be placed equidistant from each side of the length of the area/surface feature.
- GC-9991 If the length (LEN) is less than the number of meters indicated for the scale (1:50,000 -- 25 m; 1:100,000 -- 50 m), then the length shall be increased to that number of meters. Lengths shall be increased equally in each direction from the center of the line/curve feature.
- GC-9992 If the length (LEN) is less than the number of meters indicated for the scale (1:50,000 -- 100 m; 1:100,000 -- 200 m), then the length shall be increased to that number of meters. Lengths shall be increased equally in each direction from the midpoint of the line/curve feature.
- GC-9993 If the surface area (ARA), after applying GC-9994, where applicable, is less than the square meters indicated for the scale (1:50,000 -- 1,600 sq. m; 1:100,000 -- 6,400 sq. m), the area/surface delineation shall be replaced with a point delineation. The point delineation shall be placed at the centroid of the area/surface feature.
- GC-9994 If the width (WID) is less than the number of meters indicated for the scale (1:50,000 -- 25 m; 1:100,000 -- 50 m), then the width shall be increased to that number of meters. Widths shall be increased equally in each direction from the centroid of the area/surface feature.
- GC-9995 If the width of crest (WOC) or width (WID) is less than the number of meters indicated for the scale (1:50,000 -- 100 m;

- 1:100,000 -- 200 m), the area/surface delineation shall be replaced with a line/curve delineation. The line/curve delineation shall be placed equidistant from each side of the length of the area/surface feature.
- GC-9996 If the length (LEN) is less than the number of meters indicated for the scale (1:50,000 -- 50 m; 1:100,000 -- 100 m), then length shall be increased to that number of meters. Lengths shall be increased equally in each direction from the midpoint of the line/curve feature.
- GC-9997 If the length (LEN) is less than the number of meters indicated for the scale (1:50,000 -- 75 m; 1:100,000 -- 150 m), then the length shall be increased to that number of meters. Lengths shall be increased equally in each direction from the midpoint of the line/curve feature.
- GC-9999 If the area (ARA) is less than the square meters indicated for the scale (1:50,000 -- 15,625 sq. m; 1:100,000 -- 62,500 sq. m), the area/surface delineation shall be replaced with a point delineation. The point delineation shall be placed at the centroid of the area/surface feature.

LP - Label Placement rules

- LP-0050 Variable type sizes shall be placed for area/surface features per area/surface sizes at map/chart scale: 6 point ≤ 770 mm sq. area and ≤ 14 mm width; 7 point ≤ 2,300 mm sq. area and ≤ 28 mm width; 8 point ≤ 3,600 mm sq. area and ≤ 36 mm width; 9 point ≤ 5,200 mm sq. area and ≤ 44 mm width; 10 point ≤ 9,800 mm sq. area and ≤ 62 mm width; 12 point ≤ 16,650 mm sq. area and ≤ 84 mm width; 14 point ≤ 25,000 mm sq. area and ≤105 mm width; 16 point ≤ 36,000 mm sq. area and ≤125 mm width; 18 point > 36,000 mm sq. area and >125 mm width. The type size may be adjusted depending on the length of the character string. However in no case shall the type size be less than 6 point.
- LP-0051 Variable type sizes shall be used for line/curve features per line/curve length at map/chart scale: 6 point ≤ 80 mm length; 7 point 81-120 mm length; 8 point 121-160 mm length; 9 point > 160 mm length. The type size may be adjusted depending on the length of the character string. However in no case shall the type size be less than 6 point.
- LP-0062 Area/surface Aqueduct, (BH010), Canal (BH020), Ditch (BH030), and River (BH140), shall be labeled with upper case type centered within its limits, with type size proportional to the width (WID) of the feature.
- LP-0073 The Highest Elevation (ZVH) label for Spot Elevation (CA030) and the Base Elevation (BEL) label for Survey Point (ZB035) shall be placed 0.5 mm from the respective symbol, parallel to the south neatline. The top of the label aligns to the horizontal center and to the right of the symbol [southeast]. If there is an additional label for either feature, it is placed 0.5 mm above and aligned with the elevation label.
- LP-3505 The label for point features, and small line/curve and area/surface features, shall be placed 0.5 mm from the respective symbol, parallel to the south neatline. The bottom of the label aligns to the horizontal center and to the right of the symbol [northeast].
- LP-3506 The label for area/surface features shall be centered within the feature, parallel to the south neatline.
- LP-3630 The label for line/curve features shall be placed 0.5 mm above, parallel to, and centered on the respective symbol.
- LP-3987 Elevation Contour (CA010) labels shall be centered on the axis of the Elevation Contour line with the top of the label towards the higher elevation.
- LP-3996 Road Route Marker (no code) symbols shall be shown centered on the associated Ice Route (AQ075) and Road (AP030) symbol and positioned parallel to the south neatline. The route identification shall be centered within the route marker, reading left to right.
- LP-4813 If any generic term (exact or similar) contained in a label string (attribute value or descriptive term) appears in a geographic name (NAM), the term(s) shall not be shown as part of the label, i.e. "[Panama Canal] [Canal]" would be "Panama Canal"; "[Ahvaz Oil Field] [hydrocarbons field]" would be "Ahvaz Oil Field"; [Norfolk Navy Base] [military installation] would be "Norfolk Navy Base"; "[Rosecroft Raceway] [racetrack]" would be "Rosecroft Raceway"; "[Navy Pier] [recreational pier]" would be "Navy Pier"; "[Ace Recycling Center] [recycling site]" would be "Ace Recycling Center"; "[Red Bull Arena] [stadium]" would be "Red Bull Arena"; "[Smithsonian National Zoological Park] [zoo]" would be "Smithsonian National Zoological Park".
- LP-9950 If a label string contains the attribute "[Condition of Facility]" and the enumerant value is "Under Construction", then "Under Construction" shall be changed to "Construction" in the label string.

- LP-9990 A combined label shall be shown for each Land Aerodrome (GB005) and its associated Runway(s) (GB055). The label shall consist of elements of the label string for the Land Aerodrome (official AAFIF name, ICAO identification, physical condition) followed by the label string for the associated Runway (surface composition), followed by the aerodrome elevation. When a land aerodrome consists of more than one runway, the surface composition for the longest intact runway shall be shown. If all runways are not intact, the surface composition for the longest runway shall be shown. The label for Land Aerodrome and associated Runway is centered within the Land Aerodrome, parallel to the south neatline. The label string elements are stacked vertically, 0.5 mm apart, and centered to each other.
- LP-9991 The label string elements for line/curve vertical obstructions shall be stacked vertically, 0.5 mm apart, centered to each other and are placed 0.5 mm above, parallel to, and centered on the respective symbol.
- LP-9992 The label for point vertical obstructions and offshore features shall be placed 0.5 mm to the right of the symbol, parallel to the south neatline. The label string elements shall be stacked vertically, 0.5 mm apart, and centered to each other. The vertical center of the stacked elements shall align to the vertical axis of the symbol.
- LP-9993 If Divided (SEP) is True (1001) for a Road, the Lane Count (LTN) of the two travelled way delineations are added together and this total shall be used for the "LTN" portion of the label string.
- LP-9994 The label string elements for Administrative Boundary (FA000) features where there is "No Defined Boundary" (BST = 4) shall be stacked vertically, 0.5 mm apart, and centered to each other. The stacked elements shall be aligned parallel to the south neatline.
- LP-9995 The labels for Administrative Boundary (FA000) features shall be placed 0.5 mm from and parallel to the Administrative Boundary symbol. The labels shall be aligned across the Administrative Boundary from each other with each label on the respective side of the Administrative Boundary.
- LP-9996 The labels for Administrative Division (FA003) features shall be placed 0.5 mm from and parallel to the inside edge of the area/surface feature. The labels shall be aligned with any adjacent Administrative Division with the same BAL (BGN Administrative Level) attribute.
- LP-9997 Variable type sizes shall be used for linear surface features, at map/chart scale: 7 point ≤ 65 mm length; 8 point 66-80 mm length; 9 point 81-100 mm length; 10 point 101-120 mm length; 12 point 121-160 mm length; 14 point 161-200 mm length; 16 point >200 mm length. The type size may be adjusted depending on the length of the character string. However in no case shall the type size be less than 6 point.
- LP-9998 The "H" in the helipad symbol shall be oriented correctly when read from the south neatline.
- LP-9999 If any attribute value is Unknown (0), Multiple (996), Not Populated (997), Not Applicable (998), or Other (999), the label string for that attribute shall not be shown and any remaining part of the label string is appropriately adjusted. For mixed case labels, only the first letter of the first word in a label string shall be capitalized, except when part of a proper name (NAM).

Annex K – Glossary

The following annex contains definitions of commonly used terms found within this Portrayal Standard.

Area - Fill

• A fill screen or pattern depicted within an area symbol.

Area - Pattern (AP)

• A unique and continuous graphic pattern depicted within an area symbol. Area patterns applicable to this standard are defined in MIL-STD-2410.

Arrow

• A symbol or component of a symbol indicating direction, or a vector.

Attribute

A characteristic of a feature.

Cased

Two parallel lines representing a linear feature.

Centroid

• The geometric center of the object's shape.

Color

• The quality of an object or substance with respect to light reflected by the object, usually determined visually by measurement of hue, saturation, and brightness of the reflected light; saturation or chroma; hue.

Color Token

• A name by which a color is known. Color tokens are associated with different colors optimized for the viewing condition, such as red-light readable, or red and blue/green-light readable.

Component

An area, line or point geometry used in the construction of a symbol.

Concatenate

• To link or join together, especially in a chain or series.

Dash Spacing

• The distance between two consecutive dashes.

Distance between lines/line spacing

Distance measured from closest edges of two lines

Feature

• An abstraction of a real world phenomenon.

Fill

• The appropriate color or pattern depicted within or overprinting the symbol.

Font

• The characteristic or form of a typeface.

Label

• Labels consist of a variety of terminology and abbreviations, descriptive, or identifying, that are either free-standing (geographic names, text description), or directly associated with a graphic symbol (point, line, area).

Line Weight

• The thickness of a line (in millimeters) measured between outside edges.

Line Fill

• A line pattern (LP) depicted within the bounding outlines of an area symbol.

Line Pattern (LP)

• A unique and continuous graphic pattern depicted within an area symbol. Line patterns applicable to this standard are defined in MIL-STD 2410.

Line Style

• A group of parameters (e.g. line weight, color, dash length, dash spacing) which defines the appearance of the symbology (or portion of a symbology) applied to a linear component.

Lower case

 All letters of a word or words are in lower case text. All numbers are considered lower case text in this standard.

Mixed case

The first letter in the first word entry is a capital letter, followed by all lower case text.

Open circle

 A circle whose dimensions are measured across the circle, outside perimeter edge to outside perimeter edge.

Open square

 A square whose dimensions are measured across the square, outside perimeter edge to outside perimeter edge.

Origin (of symbol)

The place on a symbol that corresponds to the geographic location of the object it represents.

Perimeter

• The limits of an area feature as centered on the peripheral edge of that feature.

Portrayal

• The presentation of information to users.

Portrayal specification

• A collection of operations applied to the feature instance to portray it.

Screen

• A regular pattern of dots, defined by a predetermined percentage (100% being solid) used to create tones of a given color.

Shape

• A unique graphic symbol with a fixed geometry and used primarily for point features. Shape specifications are defined in Annex H.

Symbol

An object that represents information.

Symbol parameter

Basic drawing instructions needed to construct the symbol graphic.

Symbol rule

A rule that is applied to the feature to determine which portrayal specification to use.

Tick

 A short line located at specific intervals along a linear symbol and normally positioned perpendicular to that line.

Type

• The letters, numbers, diacritics, etc., associated with labels.

Type size

• The size of type, measured in point size.

Type style

• Specifications on capitalization and appearance of the type, such as normal, light, bold, italic and condensed.

Upper case

• All letters of a word or words are in capital letters.

Annex L – Feature Symbol Index

The features symbolized in Annex A are listed here based on two different sort orders. The first index is sorted alphabetically by **DFDD Feature Name/Alternate Name**. Included with this listing are alternate (or "former") names by which the community may traditionally know the feature/symbol as. The second index is sorted by **Feature Code** (DFDD-like Code).

The page numbers in the Feature Symbol Index provide the location in Annex A where the given feature information begins. If there is more than one symbol for the selected feature, the reader may have to scroll down through the document to locate the symbol which he/she is interested in reviewing.

Note – the bookmark tool on the left panel of the PDF also provides hyperlinks to each feature and symbol.

DFDD Feature Name / Alternate Name	DFDD Feature Name	Feature Code	Page
Administrative Boundary	Administrative Boundary	FA000	A-1
Administrative Division	Administrative Division	FA003	A-3
Aerial	Tower	AL241	A-330
Aerial Cableway	Cableway	AT041	A-35
Aerial, Dish	Dish Aerial	AT010	A-72
Aerodrome, Land	Land Aerodrome	GB005	A-169
Aerodrome, Water	Water Aerodrome	GB065	A-347
Aeronautical Obstacle	Aeronautical Obstacle	GB220	A-6
Aeronautical Obstacle	Vertical Obstruction	No Code	A-342
Aeronautical Radio Navigation Service	Aeronautical Radio Navigation Service	GA034	A-7
Aircraft Hangar	Aircraft Hangar	GB230	A-8
Aircraft Revetment	Aircraft Revetment	GB050	A-10
Airfield	Land Aerodrome	GB005	A-169
Amusement Park	Amusement Park	AK030	A-11
Animal Park	Zoo	AK180	A-362
Animal Pen	Holding Pen	AJ030	A-163
Approach Lighting System	Approach Lighting System	GB485	A-13
Apron	Apron	GB015	A-14
Aqueduct	Aqueduct	BH010	A-14
Archeological Site	Archeological Site	AL012	A-19
Athletic Field	Sports Ground	AK040	A-311
Bamboo	Cane	EC010	A-44
Beach	Beach	BA050	A-20
Benchmark	Survey Point	ZB050	A-323
Berthing Structure	Berthing Structure	BB190	A-22
Bluff	Steep Terrain Face	DB010	A-315
Bog	Bog	BH015	A-24
Boundary, Administrative	Administrative Boundary	FA000	A-1
Boundary, Land Water	Land Water Boundary	BA010	A-171
Breakwater	Breakwater	BB041	A-25
Bridge	Bridge	AQ040	A-27
Bridge Tower	Tower	AL241	A-330
Bucket Elevator	Conveyor	AF020	A-59
Building	General Building	AL015	A-124
Building, Fortified	Fortification	AH050	A-122
Built Up Area	Built Up Area	AL020	A-32
Bunker, Surface	Surface Bunker	AM060	A-322
Cable, Communication	Communication Line	AT060	A-55
Cable, Power Line	Power Line	AT030	A-200
Cableway	Cableway	AT041	A-35
Cairn	Cairn	AL025	A-36

builted by DFDD realure Name/Antenial	e ivallie		,
DFDD Feature Name / Alternate Name	DFDD Feature Name	Feature Code	Page
Camp	Camp	AI030	A-37
Camp Site	Camp Site	AK060	A-38
Canal	Canal	BH020	A-39
Cane	Cane	EC010	A-44
Car Line, Railway	Railway	AN010	A-216
Car Park	Vehicle Lot	AQ140	A-342
Cart Track	Cart Track	AP010	A-44
Catalytic Cracker	Catalytic Cracker	AC020	A-45
Causeway Structure	Causeway Structure	AQ063	A-46
Cave Dwelling	Cave Mouth	DB029	A-47
Cave Mouth	Cave Mouth	DB029	A-47
Cemetery	Cemetery	AL030	A-47
Checkpoint	Checkpoint	AH070	A-53
Chimney	Smokestack	AF010	A-305
Church	General Building	AL015	A-124
Cinder Cone	Volcano	DB180	A-345
Circular Irrigation System	Circular Irrigation System	AJ010	A-54
Cistern	Cistern	BI010	A-54
Cleared Way	Cleared Way	EC040	A-55
Clearing, Forest	Forest Clearing	EC060	A-122
Cliff	Steep Terrain Face	DB010	A-315
Cliff, Ice	Ice Cliff	BJ040	A-165
Coastal Shoreline	Land Water Boundary	BA010	A-171
Communication Line	Communication Line	AT060	A-55
Communication Station	Communication Station	AT050	A-57
Consulate	General Building	AL015	A-124
Contour, Elevation	Elevation Contour	CA010	A-79
Control Point	Survey Point	ZB050	A-323
Control Tower	Tower	AL241	A-330
Conveyor	Conveyor	AF020	A-59
Conveyor Cable	Cableway	AT041	A-35
Cooling Facility	Facility	AL010	A-110
Cooling Tower	Tower	AL241	A-330
Corral	Holding Pen	AJ030	A-163
Crane	Crane	AF040	A-61
Crevasse	Crevasse	BJ031	A-61
Crevice	Crevice	DB061	A-63
Crop Land	Crop Land	EA010	A-64
Cultivated Land	Crop Land	EA010	A-64
Culvert	Culvert	AQ065	A-65
Cut Line	Cut Line	DB071	A-66

DFDD Feature Name / Alternate Name	DFDD Feature Name	Feature Code	Page
Dam	Dam	BI020	A-67
Defensive Revetment	Aircraft Revetment	GB050	A-10
Depot, Storage	Storage Depot	AM010	A-316
Depression Contour	Elevation Contour	CA010	A-79
Dike/Dyke	Dam	BI020	A-67
Diplomatic Building	General Building	AL015	A-124
Disappearing Stream	Vanishing Point	BH145	A-341
Dish Aerial	Dish Aerial	AT010	A-72
Disposal Site	Disposal Site	AB000	A-72
Dissipating Stream	Vanishing Point	BH145	A-341
Distorted Surface	Soil Surface Region	DA010	A-306
Ditch	Ditch	BH030	A-73
Divided Highway	Road	AP030	A-257
Dragon's Teeth	Dragon's Teeth	AL060	A-75
Dry Dock	Dry Dock	BB090	A-77
Dunes, Sand	Sand Dunes	DB170	A-292
Dyke	Embankment	DB090	A-98
Earthwork, Engineered	Engineered Earthwork	AH025	A-100
Electric Power Distribution Line	Power Line	AT030	A-200
Electric Power Plant	Electric Power Station	AD010	A-77
Electric Power Station	Electric Power Station	AD010	A-77
Electric Power Substation	Power Substation	AD030	A-201
Electric Power Transmission Line	Power Line	AT030	A-200
Elevation Contour	Elevation Contour	CA010	A-79
Elevation, Spot	Spot Elevation	CA030	A-312
Embankment	Embankment	DB090	A-98
Embassy	General Building	AL015	A-124
Engineered Earthwork	Engineered Earthwork	AH025	A-100
Entrance and/or Exit	Entrance and/or Exit	AQ090	A-101
Escarpment	Cut Line	DB071	A-66
Escarpment	Steep Terrain Face	DB010	A-315
Esker	Esker	DB100	A-101
Extraction Mine	Extraction Mine	AA010	A-102
Extraction Mine/Quarry	Quarry	AA012	A-210
Facility	Facility	AL010	A-110
Facility, Fish Farm	Fish Farm Facility	BH051	A-118
Facility, Heating	Heating Facility	AD050	A-158
Facility, Processing	Processing Facility	AC000	A-202
Fairground	Fairground	AK090	A-114
Falls, Water	Waterfall	BH180	A-351
Farm, Fish	Fish Farm Facility	BH051	A-118

Farminand Crop Land EA010 A-64 Faultine Geologic Fault BR110 A-145 Ferry Crossing Ferry Crossing AL070 A-15 Ferry Crossing Ferry Crossing AL070 A-15 Filtration Beds Water Treatment Bed BH040 A-350 Filtring Range Feroda A-15 Firing Range FE0040 A-55 Fish Farm Facility Fish Farm Facility BH051 A-18 Filtre Pipe Flare Pipe AF070 A-120 Flood Control Structure Dam BI020 A-67 Flood Control Structure Water Gate BI041 A-34 Flow Arrow, River River Flow Arrow No Code A-27 Flume Flume BH060 A-12 Foundation Penstock BH110 A-13 Ford Frail AP050 A-33 Ford Frail AP050 A-33 Ford Frail AP050 A-122 Fortribed	orted by bibb reature italie, Altern	ate itailie		
Faultiline Geologic Fault B110 A 143 Fence AL070 A 115 Ferry Crossing Ferry Crossing AL070 A 115 Filtration Beds Water Treatment Bed BH040 A 350 Filtration Beds Water Treatment Bed BH040 A 350 Filtrag Range Firing Range FO040 A 55 Filing Range Firing Range AD15 A 116 Filsh Farm Facility Filsh Farm Facility BH051 A 116 Filsh Farm Facility BH051 A 116 A 116 Filsh Farm Facility BH051 A 116 A 116 Flore Pipe Flare Pipe AF070 A 120 Flood Control Structure Dam A 607 A 120 Flood Control Structure Water Gate BI002 A 67 Flood Control Structure Water Gate BI004 A 237 Flood Control Structure Ridge AB040 A 237 Flood Control Structure Bu104 A 343 Flow Arrow, River	DFDD Feature Name / Alternate Name			
Fence Fence ALO70 A-115 Ferry Crossing Ferry Crossing AOO70 A-115 Filtration Beds Water Treatment Bed BH040 A-355 Firebreak Cleared Way EC040 A-55 Firing Range Firing Range FA015 A-116 Fish Farm Facility BH051 A-118 Flare Pipe Floro Pipe AF070 A-128 Flood Control Structure Dam BH061 A-47 Flood Control Structure Water Gate BI041 A-349 Flow Arrow, River Bluer Blue BH060 A-125 Flume Plume BH060 A-126 Flume Bridge AQ040 A-27 Forbridge Bridge AQ040 A-27 Forbath Trail AP050 A-33 Ford Ford BH170 A-112 Forst Clearing CC060 A-122 Fortification AP050 A-122 Fortificat Building		·	EA010	A-64
Ferry Crossing Ferry Crossing AQ070 A.115 Filtration Beds Water Treatment Bed BH040 A.350 Firebreak Cleared Way EC040 A.55 Firing Range Firing Range Ford A.116 Fish Farm Facility Fish Farm Facility BH051 A.18 Flare Pipe Flare Pipe AF070 A.120 Flood Control Structure Water Gate BI041 A.349 Flood Control Structure River Flow Arrow No Code A.257 Flume Flume BH060 A.120 Flume Penstock BH110 A.130 Flume Brodge A0040 A.27 Fototpath Trail AP050 A.33 Ford Brodge A0040 A.27 Forest Clearing Forest Clearing E060 A.122 Fortification Fortification AH050 A.122 Fortification Fortification AH050 A.122 Fortification Fortifi	Faultline	Geologic Fault	DB110	A-143
Filtration Beds Water Treatment Bed 8H040 A-350 Firebreak Cleared Way EC040 A-55 Firing Range Firing Range Firing Range FA015 A-116 Fish Farm Facility Fish Farm Facility H050 A-120 Flord Control Structure Dam 81020 A-67 Flood Control Structure Water Gate 81041 A-349 Flood Arrow, River River Flow Arrow No Code A-120 Flume Flume 81060 A-120 Flume Penstock 8H110 A-193 Footbridge Bridge AQ040 A-27 Footbrald Trall AQ040 A-27 Forest Wood EC030 A-357 Forest Clearing Forst Clearing EC060 A-122 Fortification Fortification AH050 A-122 Fortification Fortification AH050 A-122 Fortification Fortification AH050 A-122 Ful	Fence	Fence	AL070	A-115
Firebreak Cleared Way EC040 A.55 Firing Range Firing Range FA015 A.16 Fish Farm Facility Fish Farm Facility BH051 A.18 Fishe Pipe Flare Pipe AF070 A.120 Flood Control Structure Dam Bi020 A.67 Flood Control Structure Water Gate Bi041 A.349 Flow Arrow, River Flume BH060 A.120 Flume Flume BH060 A.120 Flume Penstock BH110 A.90 Footbridge Bridge A.0040 A.27 Footpath Trail AP050 A.33 Ford Ford AP050 A.33 Ford Ford BH070 A.121 Forest Clearing EC080 A.122 Fortification Fortification AH050 A.122 Full Storage Facility Fortification AH050 A.122 Full Storage Facility Fortification AM050 A.122	Ferry Crossing	Ferry Crossing	AQ070	A-115
Firing Range Firing Range FA015 A-116 Fish Farm Facility Fish Farm Facility BH051 A-128 Flare Pipe Flare Pipe AF070 A-120 Flood Control Structure Dam BI020 A-67 Flood Control Structure Water Gate BI041 A-349 Flow Arrow, River River Flow Arrow No Code A-257 Flume Flume BH060 A-120 Flume Penstock BH110 A-190 Footpath Trail A0040 A-27 Footpath Trail AP050 A-333 Ford Ford BH070 A-121 Forest Clearing EC060 A-122 Fortflication AH050 A-122 Fortflied Building Fortflication AH050 A-122 Full Storage Facility Facility AL010 A-110 Full Storage Facility Facility AL010 A-124 Gas Field Hydrocarbons Field AN040 A-254	Filtration Beds	Water Treatment Bed	BH040	A-350
Fish Farm Facility Fish Farm Facility BH051 A.128 Flore Pipe Flare Pipe AF070 A.120 Flood Control Structure Dam BI0020 A.67 Flood Control Structure Water Gate BI041 A.349 Flow Arrow, River River Flow Arrow No Code A.257 Flume Penstock BH110 A.130 Flottidge Bridge A0040 A.27 Footpath Trail AP050 A.333 Ford Ford BH070 A.121 Forest Geof A.122 Forest Clearing Ford BH070 A.122 Forest Glaring Forest Clearing EC060 A.122 Fortification Fortification AM050 A.122 Fortified Building Fortification AM050 A.122 Fortified Building Fortification AM050 A.122 Fortified Building Fortification AM050 A.122 Gas Fail Building AM0	Firebreak	Cleared Way	EC040	A-55
Flare Pipe Flare Pipe AF070 A 120 Flood Control Structure Dam Bi020 A-67 Flood Control Structure Water Gate Bi041 A-349 Flow Arrow, River River Flow Arrow No Code A-257 Flume BH060 A-120 Flour Penstock BH110 A-193 Footpat Trail A0040 A-27 Fortdridge Ford M050 A-333 Ford Ford BH070 A-122 Fortget Ford BH070 A-122 Forest Clearing EC030 A-357 Forest Clearing Fortfication AH050 A-122 Fortfication Fortfication AH050 A-122 Fortficate Building Fortficate Building AL050 A-122 <t< td=""><td>Firing Range</td><td>Firing Range</td><td>FA015</td><td>A-116</td></t<>	Firing Range	Firing Range	FA015	A-116
Flood Control Structure Dam Bi020 A-67 Flood Control Structure Water Gate BI041 A-349 Flow Arrow, River River Flow Arrow No Code A-257 Flume Flume BH060 A-120 Flume Penstock BH110 A-193 Footbridge Bridge AQ040 A-27 Footpath Trail AP050 A-333 Ford BH070 A-121 Forest Clearing EC030 A-357 Forest Clearing EC060 A-122 Fortification AH050 A-122 Fortificed building Fortification AH050 A-122 Fortificed building Fortification AH050 A-122 Full Storage Facility Fortification AH050 A-122 Full Storage Facility Fortification AH050 A-122 Gas Field Hydrocarbons Field AU010 A-104 Gas Station General Building AU015 A-124 G	Fish Farm Facility	Fish Farm Facility	BH051	A-118
Flood Control Structure Water Gate 81041 A-349 Flow Arrow, River River Flow Arrow No Code A-257 Flume Flume BH060 A-120 Flume Penstock BH110 A-193 Footbridge Bridge AQ040 A-27 Footpath Trail AP050 A-333 Ford BH070 A-121 Forest Wood EC030 A-357 Forest Clearing Forest Clearing EC060 A-122 Fortification Fortification AH050 A-122 Fortification for Fortification AH050 A-122 Fortification for Fortification AH050 A-122 Fortification for Fortification AH050 A-122 Fortification for Fortification AH050 A-122 Fortification for Fortification AH050 A-122 Fortification for Fortification AH050 A-122 Fortification for Fortification AH050 A-122 Fortification for fortification	Flare Pipe	Flare Pipe	AF070	A-120
Flow Arrow, River River Flow Arrow No Code A 257 Flume Flume BH060 A 120 Flume Penstock BH110 A 193 Footpridge Bridge AQ040 A 27 Footpath Trail AP050 A 333 Ford Ford BH070 A 121 Forest Wood EC030 A 357 Forest Clearing Forest Clearing EC060 A 122 Fortification Fortification AH050 A 122 Full Storage Facility Facility AL010 A 100 Fuel Storage Facility Facility AL010 A 110 Gas Field Hydrocarbons Field AA052 A 165 Gas Field Hydrocarbons Field AA0452 A 165 Gas Station General Building AL015 A 124 Gate, Sluice Bi040 A 304 Gate, Sluice Bi041 A 349 General Building AL015 A 124 Georeal Building <td>Flood Control Structure</td> <td>Dam</td> <td>BI020</td> <td>A-67</td>	Flood Control Structure	Dam	BI020	A-67
Flume Flume BH060 A.120 Flume Penstock BH110 A.193 Footbridge Bridge AQ040 A.27 Footpath Trail AP050 A.333 Ford Ford BH070 A.121 Forest Wood EC030 A.322 Forest Clearing EC060 A.122 Fortificating Fortification AH050 A.122 Fortified Building Fortification AH050 A.122 Fortified Building Fortification AH050 A.122 Full Storage Facility Facility AL010 A.110 Fumarole Geothermal Outlet DB115 A.146 Gas Field Hydrocarbons Field AA052 A.165 Gas Rig Rig AA040 A.224 Gas Station General Building AL015 A.124 Gate, Mater Water Gate BI041 A.349 Gate, Sluice BI041 A.344 General Building <td>Flood Control Structure</td> <td>Water Gate</td> <td>BI041</td> <td>A-349</td>	Flood Control Structure	Water Gate	BI041	A-349
Flume Penstock BH110 A-193 Footbridge Bridge AQ040 A-27 Footpath Trail AP050 A-333 Ford Ford BH070 A-121 Forest Wood EC030 A-357 Forest Clearing EC060 A-122 Fortification AH050 A-122 Fortified Building Fortification AH050 A-122 Fortified Building Fortification AH050 A-122 Fuel Storage Facility Facility AL010 A-110 Gas Stalon Bull Storage Studie AM030 A-254 Gas Station Geother Mal Outlet Bl041 A-349 Gate, Water Sluice Gate Bl040 A-349	Flow Arrow, River	River Flow Arrow	No Code	A-257
Footbridge Bridge AQ040 A-27 Footpath Trail AP050 A-333 Ford Ford BH070 A-121 Forest Wood EC030 A-357 Forest Clearing Forest Clearing EC060 A-122 Fortification AH050 A-122 Fortification AH050 A-122 Fortification AH050 A-122 Fortification AH050 A-122 Fuel Storage Facility Facility AL010 A-110 Fuel Storage Facility Facility AL010 A-110 Gas Field Hydrocarbons Field AA052 A-165 Gas Field Hydrocarbons Field AA052 A-165 Gas Rig Rig AA040 A-254 Gas Station General Building AL015 A-124 Gate, Sluice Bl040 A-304 Gate, Water Bl041 A-349 General Building AL015 A-124 Geolegic Fault<	Flume	Flume	BH060	A-120
Footpath Trail AP050 A-333 Ford Ford 8H070 A-121 Forest Wood EC030 A-357 Forest Clearing Forest Clearing EC060 A-122 Fortification Fortification AH050 A-122 Fortified Building Fortification AH050 A-122 Fuel Storage Facility Facility AL010 A-110 Fundarole Geothermal Outlet DB115 A-146 Gas Field Hydrocarbons Field A052 A-165 Gas Rig A040 A-254 Gas Station General Building AL015 A-124 Gate, Sluice Sluice Gate BI040 A-304 Gate, Water Water Gate BI041 A-349 General Building AL015 A-124 Geologic Fault BI041 A-134 Geologic Fault BI041 A-134 Geophysical Prospecting Grid FA090 A-144 Geophysical Prospecting Grid FA	Flume	Penstock	BH110	A-193
Ford Ford 8H070 A-121 Forest Wood EC030 A-357 Forest Clearing Forest Clearing EC060 A-122 Fortification Fortification AH050 A-122 Fortified Building Fortification AH050 A-122 Fuel Storage Facility Facility AL010 A-110 Fumarole Geothermal Outlet DB115 A-146 Gas Field Hydrocarbons Field AA052 A-165 Gas Rig Rig AA040 A-254 Gas Station General Building AL015 A-124 Gate, Sluice Sluice Gate BI040 A-304 Gate, Water Water Gate BI041 A-349 General Building AL015 A-124 Geologic Fault Geologic Fault DB101 A-143 Geophysical Data Track Line Geophysical Prospecting Grid FA090 A-144 Geophysical Prospecting Grid Geophysical Prospecting Grid FA090 A-144 Geo	Footbridge	Bridge	AQ040	A-27
Forest Wood EC030 A-357 Forest Clearing Forest Clearing EC060 A-122 Fortification Fortification AH050 A-122 Fortified Building Fortification AH050 A-122 Fuel Storage Facility Facility AL010 A-110 Fumarole Geothermal Outlet DB115 A-146 Gas Field Hydrocarbons Field AA052 A-165 Gas Rig AA040 A-254 Gas Station General Building AL015 A-124 Gate, Sluice Sluice Gate BI040 A-304 Gate, Water Water Gate BI041 A-349 General Building AL015 A-124 Geologic Fault Geologic Fault DB110 A-143 Geophysical Data Track Line Geologic Fault FA090 A-144 Geophysical Prospecting Grid Geophysical Prospecting Grid FA090 A-144 Geothermal Feature Geothermal Outlet DB115 A-146 Geyser	Footpath	Trail	AP050	A-333
Forest Clearing Forest Clearing EC060 A-122 Fortification Fortification AH050 A-122 Fortified Building Fortification AH050 A-122 Fuel Storage Facility Facility AL010 A-110 Fumarole Geothermal Outlet DB115 A-146 Gas Field Hydrocarbons Field AA052 A-165 Gas Rig Rig AA040 A-254 Gate, Sluice Blude Gate Bl040 A-304 Gate, Sluice Bl041 A-349 General Building AL015 A-124 Geologic Fault Geologic Fault Bl101 A-143 Geologic Fault Bel041 A-143 Geophysical Data Track Line Geologic Fault B110 A-144 Geophysical Prospecting Grid FA090 A-144 Geophysical Prospecting Grid FA090 A-144 Geothermal Feature Geothermal Outlet B8115 A-146 Geothermal Outlet B8115 A-146	Ford	Ford	BH070	A-121
Fortification Fortification AH050 A-122 Fortified Building Fortification AH050 A-122 Fuel Storage Facility Facility AL010 A-110 Fumarole Geothermal Outlet DB115 A-146 Gas Field Hydrocarbons Field AA052 A-165 Gas Rig AA040 A-254 Gas Station General Building AL015 A-124 Gate, Sluice Sluice Gate BI040 A-304 Gate, Water Water Gate BI041 A-349 General Building General Building AL015 A-124 Geologic Fault Geologic Fault DB110 A-143 Geophysical Data Track Line Geophysical Prospecting Grid FA090 A-144 Geophysical Prospecting Grid FA090 A-144 Geophysical Prospecting Grid FA090 A-144 Geothermal Gutlet DB115 A-146 Geothermal Outlet Geothermal Outlet DB115 A-146 Geyser Geothermal Outlet	Forest	Wood	EC030	A-357
Fortified Building Fortification AH050 A-122 Fuel Storage Facility Facility Facility AL010 A-110 Fumarole Geothermal Outlet DB115 A-146 Gas Field Hydrocarbons Field AA052 A-165 Gas Rig Rig AA040 A-254 Gas Station General Building AL015 A-124 Gate, Sluice Gate Bl040 A-304 Gate, Water Gate Bl040 A-304 Gate, Water Gate Bl041 A-349 General Building AL015 A-124 Geologic Fault Geologic Fault DB110 A-143 Geophysical Data Track Line Geophysical Prospecting Grid FA090 A-144 Geophysical Prospecting Grid FA090 A-144 Geophysical Prospecting Grid FA090 A-144 Geothermal Feature Geothermal Outlet DB115 A-146 Geothermal Outlet DB115 A-146 Geothermal Outlet Geothermal Outlet DB115 A-146 Geothermal Outlet Geothermal Outlet AL016 Geothermal Outlet AL017 Geothermal Outlet AL017 Geothermal Outlet AL017 Geothermal Outlet AL018 Geoth	Forest Clearing	Forest Clearing	EC060	A-122
Fuel Storage Facility Facility AL010 A-110 Fumarole Geothermal Outlet DB115 A-146 Gas Field Hydrocarbons Field AA052 A-165 Gas Rig Rig AA040 A-254 Gas Station General Building AL015 A-124 Gate, Sluice Sluice Gate B1040 A-304 Gate, Water Water Gate B1041 A-349 General Building General Building AL015 A-124 Geologic Fault Geologic Fault DB110 A-143 Geophysical Data Track Line Geophysical Prospecting Grid FA090 A-144 Geophysical Prospecting Grid Geophysical Prospecting Grid FA090 A-144 Geophysical Entity FA002 A-144 Geophysical Entity FA002 A-144 Geothermal Outlet DB115 A-146 Geothermal Outlet DB115 A-146 Geothermal Outlet DB115 A-146 Glacier Glocier BJ030 A-14	Fortification	Fortification	AH050	A-122
Fumarole Geothermal Outlet DB115 A-146 Gas Field Hydrocarbons Field AA052 A-165 Gas Rig Rig AA040 A-254 Gas Station General Building AL015 A-124 Gate, Sluice Stuice Sluice Gate BI040 A-304 Gate, Water Water Gate Bi041 A-349 General Building AL015 A-124 Geologic Fault Geologic Fault DB110 A-143 Geophysical Data Track Line Geophysical Prospecting Grid FA090 A-144 Geophysical Prospecting Grid FA090 A-144 Geophysical Prospecting Grid FA090 A-144 Geophysical Prospecting Grid FA090 A-144 Geophysical Prospecting Grid FA090 A-144 Geothermal Feature Geothermal Outlet DB115 A-146 Geothermal Outlet Geothermal Outlet DB115 A-146 Geothermal Outlet Geothermal Outlet DB115 A-146 Geothermal Outlet Geothermal Outlet DB115 A-146 Glacier Glacier BJ030 A-147 Golf Course AK100 A-148 Grain Elevator Grain Elevator AM030 A-148 Grain Storage Structure GAM030 A-148	Fortified Building	Fortification	AH050	A-122
Gas FieldHydrocarbons FieldAA052A-165Gas RigRigAA040A-254Gas StationGeneral BuildingAL015A-124Gate, SluiceSluice GateBI040A-304Gate, WaterWater GateBI041A-349General BuildingGeneral BuildingAL015A-124Geologic FaultGeologic FaultDB110A-143Geophysical Data Track LineGeophysical Prospecting GridFA090A-144Geophysical Prospecting GridFA090A-144Geophysical Prospecting GridFA002A-144Geothermal FeatureGeothermal OutletDB115A-146Geothermal OutletDB115A-146Geothermal OutletDB115A-146GlacierGeothermal OutletDB115A-146GlacierGlacierBJ030A-147Golf CourseGolf CourseAK100A-148Grain ElevatorAM030A-148Grain Storage StructureAM020A-150	Fuel Storage Facility	Facility	AL010	A-110
Rig Rig AA040 A-254 Gas Station General Building AL015 A-124 Gate, Sluice Stuice Sluice Gate BI040 A-304 Gate, Water BI041 A-349 General Building AL015 A-124 Geologic Fault Geologic Fault DB110 A-143 Geophysical Data Track Line Geophysical Prospecting Grid FA090 A-144 Geophysical Prospecting Grid FA090 A-144 Geophysical Entity Geophitical Entity FA002 A-144 Geothermal Feature Geothermal Outlet DB115 A-146 Geothermal Outlet Geothermal Outlet DB115 A-146 Geyser Geothermal Outlet DB115 A-146 Glacier Glacier Glacier BJ030 A-147 Golf Course AK100 A-148 Grain Elevator Grain Elevator AM030 A-148 Grain Storage Structure AM020 A-150	Fumarole	Geothermal Outlet	DB115	A-146
Gas Station General Building AL015 A-124 Gate, Sluice Gate Sluice Gate BI040 A-304 Gate, Water Water Gate BI041 A-349 General Building General Building AL015 A-124 Geologic Fault Geologic Fault DB110 A-143 Geophysical Data Track Line Geophysical Prospecting Grid FA090 A-144 Geophysical Prospecting Grid FA090 A-144 Geophysical Prospecting Grid FA090 A-144 Geophysical Entity FA002 A-144 Geothermal Feature Geothermal Outlet DB115 A-146 Geothermal Outlet Geothermal Outlet DB115 A-146 Geyser Geothermal Outlet DB115 A-146 Glacier Glacier BJ030 A-147 Golf Course Golf Course AK100 A-148 Grain Elevator AM030 A-148 Grain Storage Structure AM020 A-150	Gas Field	Hydrocarbons Field	AA052	A-165
Gate, Sluice Gate Sluice Gate BI040 A-304 Gate, Water Gate Water Gate BI041 A-349 General Building General Building AL015 A-124 Geologic Fault Geophysical Data Track Line Geophysical Prospecting Grid FA090 A-144 Geophysical Prospecting Grid FA090 A-144 Geophysical Prospecting Grid FA090 A-144 Geophical Entity FA002 A-144 Geothermal Feature Geothermal Outlet DB115 A-146 Geothermal Outlet Geothermal Outlet DB115 A-146 Geothermal Outlet DB115 A-146 Geothermal Outlet DB115 A-146 Geothermal Outlet DB115 A-146 Geothermal Outlet DB115 A-146 Geothermal Outlet DB115 A-146 Geothermal Outlet DB115 A-146 Geothermal Outlet DB115 A-146 Geothermal Outlet DB115 A-146 Geothermal Outlet DB115 A-146 Geothermal Outlet DB115 A-146 Glacier Glacier BJ030 A-147 Golf Course AK100 A-148 Grain Elevator Grain Elevator AM030 A-148 Grain Elevator Grain Elevator AM030 A-148 Grain Storage Structure AM020 A-150	Gas Rig	Rig	AA040	A-254
Gate, WaterWater GateBI041A-349General BuildingGeneral BuildingAL015A-124Geologic FaultGeologic FaultDB110A-143Geophysical Data Track LineGeophysical Prospecting GridFA090A-144Geophysical Prospecting GridFA090A-144Geophysical Prospecting GridFA002A-144Geophitical EntityGeophitical EntityFA002A-144Geothermal FeatureGeothermal OutletDB115A-146Geothermal OutletGeothermal OutletDB115A-146GeyserGeothermal OutletDB115A-146GlacierGlacierBJ030A-147Golf CourseGolf CourseAK100A-148Grain ElevatorGrain ElevatorAM030A-148Grain Storage StructureAM020A-150	Gas Station	General Building	AL015	A-124
General BuildingGeneral BuildingAL015A-124Geologic FaultGeologic FaultDB110A-143Geophysical Data Track LineGeophysical Prospecting GridFA090A-144Geophysical Prospecting GridFA090A-144Geophysical EntityGeophysical EntityFA002A-144Geothermal FeatureGeothermal OutletDB115A-146Geothermal OutletGeothermal OutletDB115A-146GeyserGeothermal OutletDB115A-146GlacierGlacierBJ030A-147Golf CourseGolf CourseAK100A-148Grain ElevatorGrain ElevatorAM030A-148Grain Storage StructureGrain Storage StructureAM020A-150	Gate, Sluice	Sluice Gate	BI040	A-304
Geologic FaultGeologic FaultDB110A-143Geophysical Data Track LineGeophysical Prospecting GridFA090A-144Geophysical Prospecting GridFA090A-144Geophysical Prospecting GridFA090A-144Geopolitical EntityFA002A-144Geothermal FeatureGeothermal OutletDB115A-146Geothermal OutletGeothermal OutletDB115A-146GeyserGeothermal OutletDB115A-146GlacierGlacierBJ030A-147Golf CourseGolf CourseAK100A-148Grain ElevatorGrain ElevatorAM030A-148Grain Storage StructureAM020A-150	Gate, Water	Water Gate	BI041	A-349
Geologic FaultGeologic FaultDB110A-143Geophysical Data Track LineGeophysical Prospecting GridFA090A-144Geophysical Prospecting GridFA090A-144Geophysical Prospecting GridFA090A-144Geopolitical EntityFA002A-144Geothermal FeatureGeothermal OutletDB115A-146Geothermal OutletGeothermal OutletDB115A-146GeyserGeothermal OutletDB115A-146GlacierGlacierBJ030A-147Golf CourseGolf CourseAK100A-148Grain ElevatorGrain ElevatorAM030A-148Grain Storage StructureAM020A-150	General Building	General Building	AL015	A-124
Geophysical Prospecting Grid Geophysical Prospecting Grid FA090 A-144 Geopolitical Entity FA002 A-144 Geothermal Feature Geothermal Outlet DB115 A-146 Geothermal Outlet Geothermal Outlet DB115 A-146 Geyser Geothermal Outlet DB115 A-146 Glacier Glacier BJ030 A-147 Golf Course Golf Course AK100 A-148 Grain Elevator Grain Elevator AM030 A-148 Grain Storage Structure Geophysical Prospecting Grid FA090 A-150	Geologic Fault	Geologic Fault	DB110	A-143
Geophysical Prospecting Grid Geophysical Prospecting Grid FA090 A-144 Geopolitical Entity Geopolitical Entity FA002 A-144 Geothermal Feature Geothermal Outlet DB115 A-146 Geothermal Outlet Geothermal Outlet DB115 A-146 Geyser Geothermal Outlet DB115 A-146 Glacier Glacier BJ030 A-147 Golf Course Golf Course AK100 A-148 Grain Elevator Grain Elevator AM030 A-148 Grain Storage Structure Geophysical Prospecting Grid FA090 A-150	Geophysical Data Track Line	Geophysical Prospecting Grid	FA090	A-144
Geothermal FeatureGeothermal OutletDB115A-146Geothermal OutletGeothermal OutletDB115A-146GeyserGeothermal OutletDB115A-146GlacierGlacierBJ030A-147Golf CourseGolf CourseAK100A-148Grain ElevatorGrain ElevatorAM030A-148Grain Storage StructureGrain Storage StructureAM020A-150	Geophysical Prospecting Grid	Geophysical Prospecting Grid	FA090	A-144
Geothermal FeatureGeothermal OutletDB115A-146Geothermal OutletGeothermal OutletDB115A-146GeyserGeothermal OutletDB115A-146GlacierGlacierBJ030A-147Golf CourseGolf CourseAK100A-148Grain ElevatorGrain ElevatorAM030A-148Grain Storage StructureGrain Storage StructureAM020A-150				A-144
Geothermal OutletGeothermal OutletDB115A-146GeyserGeothermal OutletDB115A-146GlacierGlacierBJ030A-147Golf CourseGolf CourseAK100A-148Grain ElevatorGrain ElevatorAM030A-148Grain Storage StructureGrain Storage StructureAM020A-150				A-146
GeyserGeothermal OutletDB115A-146GlacierGlacierBJ030A-147Golf CourseGolf CourseAK100A-148Grain ElevatorGrain ElevatorAM030A-148Grain Storage StructureGrain Storage StructureAM020A-150	Geothermal Outlet	Geothermal Outlet		A-146
Glacier Glacier BJ030 A-147 Golf Course Golf Course AK100 A-148 Grain Elevator Grain Elevator AM030 A-148 Grain Storage Structure Grain Storage Structure AM020 A-150				A-146
Golf Course Golf Course AK100 A-148 Grain Elevator Grain Elevator AM030 A-148 Grain Storage Structure Grain Storage Structure AM020 A-150	·			A-147
Grain Elevator Grain Elevator AM030 A-148 Grain Storage Structure Grain Storage Structure AM020 A-150				A-148
Grain Storage Structure Grain Storage Structure AM020 A-150				
	Grassland	Grassland	EB010	A-152

DFDD Feature Name / Alternate Name	DFDD Feature Name	Feature Code	Page
Grave, Isolated	Cemetery	AL030	A-47
Gravel	Moraine	BJ020	A-185
Gravel	Soil Surface Region	DA010	A-306
Greenhouse	Greenhouse	AJ110	A-153
Groin	Groin	BB043	A-154
Ground Surface	Soil Surface Region	DA010	A-306
Gully	Gully	DB200	A-156
Hangar, Aircraft	Aircraft Hangar	GB230	A-8
Harbour	Harbour	BB005	A-157
Hardstand	Apron	GB015	A-14
Hazardous Rock	Hazardous Rock	BD130	A-158
Heating Facility	Heating Facility	AD050	A-158
Hedgerow	Hedgerow	EA020	A-160
Helipad	Helipad	GB030	A-161
Heliport	Heliport	GB035	A-162
High Tension Power Transmission Line	Power Line	AT030	A-200
Highway	Road	AP030	A-257
Highway Route Marker	Road Route Marker	No Code	A-279
Historical Site	Archeological Site	AL012	A-19
Holding Pen	Holding Pen	AJ030	A-163
Hop Field	Hop Field	EA055	A-164
Horizontal Control Point	Survey Point	ZB050	A-323
Hospital	General Building	AL015	A-124
Hot Spring	Geothermal Outlet	DB115	A-146
Hulk	Wreck	BD180	A-361
Hut	Hut	AL099	A-164
Hydrocarbon Products Facility	Processing Facility	AC000	A-202
Hydrocarbons Field	Hydrocarbons Field	AA052	A-165
Ice Cliff	Ice Cliff	BJ040	A-165
Ice Field	Snow Ice Field	BJ100	A-306
Ice Peak	Ice Peak	BJ060	A-166
Ice Route	Ice Route	AQ075	A-166
Incline Railway	Railway	AN010	A-216
Inland Waterbody	Lake	BH080	A-168
Inland Waterbody	Reservoir	BH130	A-251
Irrigation System, Circular	Circular Irrigation System	AJ010	A-54
Island	Island	BA030	A-167
Isolated Tree	Wood	EC030	A-357
Jetty	Training Wall	BB140	A-333
Kanat/Karez	Aqueduct	BH010	A-14
Lake	Lake	BH080	A-168

and a second sec		_	D :
DFDD Feature Name / Alternate Nam		Feature Code	Page
Land Aerodrome	Land Aerodrome	GB005	A-169
Land Subject To Inundation	Land Subject To Inundation	BH090	A-170
Land Water Boundary	Land Water Boundary	BA010	A-171
Launch Pad	Launch Pad	GB040	A-172
Leader Line	Leader Line	No Code	A-173
Levee	Embankment	DB090	A-98
Lighthouse	Tower	AL241	A-330
Lighting System, Approach	Approach Lighting System	GB485	A-13
Lock	Lock	BI030	A-174
Mangrove Swamp	Mangrove Swamp	ED030	A-176
Manmade Shoreline	Seawall	BB230	A-295
Mariculture Site	Mariculture Site	BH050	A-177
Maritime Signal Station	Maritime Signal Station	BB155	A-178
Marsh	Marsh	ED010	A-180
Mast	Tower	AL241	A-330
Mast, Mooring	Mooring Mast	AQ110	A-185
Memorial Monument	Memorial Monument	AL130	A-181
Military Installation	Military Installation	SU001	A-181
Minaret	General Building	AL015	A-124
Mine	Extraction Mine	AA010	A-102
Mine/Quarry	Quarry	AA012	A-210
Mineral Pile	Mineral Pile	AM040	A-183
Monument	Memorial Monument	AL130	A-181
Mooring Mast	Mooring Mast	AQ110	A-185
Moraine	Moraine	BJ020	A-185
Mosque	General Building	AL015	A-124
Motor Vehicle Station	General Building	AL015	A-124
Motorway	Road	AP030	A-257
Mountain Pass	Mountain Pass	DB150	A-186
Named Location	Named Location	ZD040	A-186
Native Settlement	Settlement	AL105	A-296
Natural Pool	Natural Pool	BH170	A-187
Nipa	Swamp	ED020	A-325
Non Water Well	Well	AA050	A-352
Nunatak	Ice Peak	BJ060	A-166
Oasis	Oasis	EC020	A-188
Obstruction, Aeronautical	Aeronautical Obstacle	GB220	A-188
Obstruction, Vertical	Vertical Obstruction	No Code	A-342
Offshore Construction	Offshore Platform	BD110	A-342 A-189
Offshore Platform	Offshore Platform	BD110 BD110	A-189 A-189
Oil Field	Hydrocarbons Field		
Oli Field	riyurocarbons rielu	AA052	A-165

DFDD Feature Name / Alternate Name	DFDD Feature Name	Feature Code	Page
Oil Rig	Rig	AA040	A-254
Open Water, Inland	Lake	BH080	A-168
Open Water, Inland	Reservoir	BH130	A-251
Open Water, Tidal	Tidal Water	BA040	A-329
Orchard	Orchard	EA040	A-190
Overpass	Bridge	AQ040	A-27
Overrun	Stopway	GB045	A-316
Pagoda	General Building	AL015	A-124
Parapet	Engineered Earthwork	AH025	A-100
Park	Park	AK120	A-190
Park, Amusement	Amusement Park	AK030	A-11
Park, Animal	Zoo	AK180	A-362
Parking Lot	Vehicle Lot	AQ140	A-342
Particle Accelerator	Particle Accelerator	AL140	A-192
Pass, Mountain	Mountain Pass	DB150	A-186
Penstock	Penstock	BH110	A-193
Petrol Station	General Building	AL015	A-124
Pier	Recreational Pier	AK190	A-247
Pile	Structural Pile	BD100	A-321
Pinnacle	Rock Formation	DB160	A-283
Pipe, Flare	Flare Pipe	AF070	A-120
Pipeline	Pipeline	AQ113	A-195
Place Name	Named Location	ZD040	A-186
Placer Mine	Extraction Mine	AA010	A-102
Plantation	Orchard	EA040	A-190
Platform, Offshore	Offshore Platform	BD110	A-189
Plaza	Public Square	AL170	A-206
Point of Change	Point of Change	No Code	A-199
Pond	Lake	BH080	A-168
Pond, Settling	Settling Pond	AC030	A-298
Pool, Natural	Natural Pool	BH170	A-187
Pool, Swimming	Swimming Pool	AK170	A-326
Power Distribution Line	Power Line	AT030	A-200
Power Line	Power Line	AT030	A-200
Power Station	Electric Power Station	AD010	A-77
Power Substation	Power Substation	AD030	A-201
Power Transformer Station	Power Substation	AD030	A-201
Power Transmission Line	Power Line	AT030	A-200
Processing Facility	Processing Facility	AC000	A-202
Promenade	Recreational Pier	AK190	A-247
Prospect, Mine	Extraction Mine	AA010	A-102

Page A-205 A-206 A-207 A-209 A-14 A-102 A-210 A-22 A-214 A-215
A-206 A-207 A-209 A-14 A-102 A-210 A-22 A-214
A-207 A-209 A-14 A-102 A-210 A-22 A-214
A-209 A-14 A-102 A-210 A-22 A-214
A-14 A-102 A-210 A-22 A-214
A-102 A-210 A-22 A-214
A-210 A-22 A-214
A-22 A-214
A-214
Δ-215
/ (213
A-330
A-7
A-216
A-216
A-285
A-237
A-334
A-244
A-245
A-303
A-100
A-245
A-247
A-248
A-100
A-249
A-202
A-251
A-281
A-10
A-253
A-254
A-254
A-257
A-341
A-257
A-279
A-166
A-281
A-158
A-283

DFDD Feature Name / Alternate Name	DFDD Feature Name	Feature Code	Page
Roundhouse	Roundhouse	AN076	A-285
Route Marker	Road Route Marker	No Code	A-279
Row of Trees	Wood	EC030	A-357
Ruins	Ruins	AL200	A-286
Runway	Runway	GB055	A-287
Sabkha	Sabkha	BH160	A-289
Salt Evaporator	Salt Evaporator	BH155	A-290
Salt Flat	Salt Flat	BH150	A-291
Salt Pan	Salt Flat	BH150	A-291
Sand	Soil Surface Region	DA010	A-306
Sand Dunes	Sand Dunes	DB170	A-292
Scattered Trees	Wood	EC030	A-357
School	General Building	AL015	A-124
Scrub	Thicket	EB020	A-329
Seaplane Anchorage/Base	Water Aerodrome	GB065	A-347
Seawall	Seawall	BB230	A-295
Settlement	Settlement	AL105	A-296
Settling Pond	Settling Pond	AC030	A-298
Shanty Town	Shanty Town	AL208	A-299
Shed	Shed	AL019	A-300
Shoreline	Land Water Boundary	BA010	A-171
Shoreline Construction	Berthing Structure	BB190	A-22
Shoreline Construction	Breakwater	BB041	A-25
Shoreline Construction	Groin	BB043	A-154
Shoreline Construction	Recreational Pier	AK190	A-247
Shoreline Construction	Seawall	BB230	A-295
Shoreline Construction	Training Wall	BB140	A-333
Shoreline Ramp	Slipway	BB240	A-303
Shrine	General Building	AL015	A-124
Siding, Railway	Railway Sidetrack	AN050	A-237
Signal Station, Maritime	Maritime Signal Station	BB155	A-178
Silo, Grain	Grain Storage Structure	AM020	A-150
Ski Jump	Ski Jump	AK150	A-301
Ski Lift	Cableway	AT041	A-35
Slipway	Slipway	BB240	A-303
Sluice Gate	Sluice Gate	BI040	A-304
Smokestack	Smokestack	AF010	A-305
Snow Ice Field	Snow Ice Field	BJ100	A-306
Snowshed	Protection Shed	AL210	A-205
Soil Surface Region	Soil Surface Region	DA010	A-306
Solar Panel	Solar Panel	AD020	A-309

often by Drbb reature Name/Alternate			_
DFDD Feature Name / Alternate Name	DFDD Feature Name	Feature Code	Page
Spillway	Spillway	BH165	A-310
Sports Ground	Sports Ground	AK040	A-311
Spot Elevation	Spot Elevation	CA030	A-312
Spring	Natural Pool	BH170	A-187
Spring, Hot	Geothermal Outlet	DB115	A-146
Spur	Railway	AN010	A-216
Square, Public	Public Square	AL170	A-206
Stadium	Stadium	AK160	A-313
Station, Communication	Communication Station	AT050	A-57
Station, Electric Power	Electric Power Station	AD010	A-77
Station, Motor Vehicle	General Building	AL015	A-124
Station, Pumping	Pumping Station	AQ116	A-207
Station, Radar	Radar Station	AT045	A-215
Station, Transportation	Transportation Station	AQ125	A-334
Steep Terrain Face	Steep Terrain Face	DB010	A-315
Stockyard	Holding Pen	AJ030	A-163
Stopway	Stopway	GB045	A-316
Storage Bunker, Surface	Surface Bunker	AM060	A-322
Storage Depot	Storage Depot	AM010	A-316
Storage Facility, Fuel	Facility	AL010	A-110
Storage Tank	Storage Tank	AM070	A-318
Stream	River	BH140	A-254
Street	Road	AP030	A-257
Streetcar Line	Railway	AN010	A-216
Structural Pile	Structural Pile	BD100	A-321
Stupa	General Building	AL015	A-124
Substation, Power	Power Substation	AD030	A-201
Sugar Cane	Cane	EC010	A-44
Surface Bunker	Surface Bunker	AM060	A-322
Survey Point	Survey Point	ZB050	A-323
Swamp	Swamp	ED020	A-325
Swimming Pool	Swimming Pool	AK170	A-326
Synagogue	General Building	AL015	A-124
Tailings, Mine	Extraction Mine	AA010	A-102
Tank, Storage	Storage Tank	AM070	A-318
Taxiway	Taxiway	GB075	A-318
Telephone Line	Communication Line	AT060	A-527 A-55
Temple	General Building	AL015	A-33 A-124
·	-	AK060	
Tent Dwellings Test Site	Camp Site		A-38
Test Site	Test Site	FA100	A-328
Thicket	Thicket	EB020	A-329

DFDD Feature Name / Alternate Name	DFDD Feature Name	Feature Code	Page
Tidal Water	Tidal Water	BA040	A-329
Tower	Tower	AL241	A-330
Tower, Control	Tower	AL241	A-330
Tower, Cooling	Tower	AL241	A-330
Tower, Water	Tower	AL241	A-330
Tower, Water Intake	Water Intake Tower	BI050	A-350
Track, Cart	Cart Track	AP010	A-44
Traffic Circle	Road	AP030	A-257
Trail	Trail	AP050	A-333
Training Wall	Training Wall	BB140	A-333
Tramway	Railway	AN010	A-216
Transformer Station	Power Substation	AD030	A-201
Transportation Route Protection Structure	Protection Shed	AL210	A-205
Transportation Station	Transportation Station	AQ125	A-334
Tree	Wood	EC030	A-357
Trees	Wood	EC030	A-357
Trees, Row of	Wood	EC030	A-357
Trench	Engineered Earthwork	AH025	A-100
Tundra	Tundra	BJ110	A-337
Tunnel	Tunnel	AQ130	A-338
Tunnel Mouth	Entrance and/or Exit	AQ090	A-101
Turbine, Wind	Wind Turbine	AJ051	A-356
Turntable, Railway	Railway Turntable	AN075	A-244
Underpass	Bridge	AQ040	A-27
Vanishing Point	Vanishing Point	BH145	A-341
Vehicle Lot	Vehicle Lot	AQ140	A-342
Vertical Obstruction	Vertical Obstruction	No Code	A-342
Viaduct	Bridge	AQ040	A-27
Vineyard	Vineyard	EA050	A-344
Void Collection Area	Void Collection Area	ZD020	A-345
Volcano	Volcano	DB180	A-345
Wadi	River	BH140	A-254
Wall	Wall	AL260	A-347
Water Aerodrome	Water Aerodrome	GB065	A-347
Water Gate	Water Gate	BI041	A-349
Water Intake Tower	Water Intake Tower	BI050	A-350
Water Race	Flume	вн060	A-120
Water Tower	Tower	AL241	A-330
Water Treatment Bed	Water Treatment Bed	BH040	A-350
Water Well	Well	AA050	A-352
Water, Open (Inland)	Lake	BH080	A-168

Sorted By DFDD Feature Name/Alternate Name

29 May 2015

DFDD Feature Name / Alternate Name	DFDD Feature Name	Feature Code	Page
Water, Open (Inland)	Reservoir	BH130	A-251
Water, Open (Tidal)	Tidal Water	BA040	A-329
Waterfall	Waterfall	BH180	A-351
Weir	Dam	BI020	A-67
Well	Well	AA050	A-352
Wharf	Berthing Structure	BB190	A-22
Wind Turbine	Wind Turbine	AJ051	A-356
Windmill	Windmill	AJ050	A-357
Wood	Wood	EC030	A-357
Woodland	Wood	EC030	A-357
Wreck	Wreck	BD180	A-361
Yard, Railway	Railway Yard	AN060	A-245
Zoo	Zoo	AK180	A-362

Feature Code	DFDD Feature Name	Page
AA010	Extraction Mine	A-102
AA012	Quarry	A-210
AA040	Rig	A-254
AA050	Well	A-352
AA052	Hydrocarbons Field	A-165
AB000	Disposal Site	A-72
AB010	Recycling Site	A-248
AC000	Processing Facility	A-202
AC020	Catalytic Cracker	A-45
AC030	Settling Pond	A-298
AD010	Electric Power Station	A-77
AD020	Solar Panel	A-309
AD030	Power Substation	A-201
AD050	Heating Facility	A-158
AF010	Smokestack	A-305
AF020	Conveyor	A-59
AF040	Crane	A-61
AF070	Flare Pipe	A-120
AH025	Engineered Earthwork	A-100
AH050	Fortification	A-122
AH070	Checkpoint	A-53
AI030	Camp	A-37
AJ010	Circular Irrigation System	A-54
AJ030	Holding Pen	A-163
AJ050	Windmill	A-357
AJ051	Wind Turbine	A-356
AJ110	Greenhouse	A-153
AK030	Amusement Park	A-11
AK040	Sports Ground	A-311
AK060	Camp Site	A-38
AK090	Fairground	A-114
AK100	Golf Course	A-148
AK120	Park	A-190
AK130	Racetrack	A-214
AK150	Ski Jump	A-301
AK160	Stadium	A-313
AK170	Swimming Pool	A-326
AK180	Zoo	A-362
AK190	Recreational Pier	A-247
AL010	Facility	A-110
AL012	Archeological Site	A-19

Sorted by reature code		
Feature Code	DFDD Feature Name	Page
AL015	General Building	A-124
AL019	Shed	A-300
AL020	Built Up Area	A-32
AL025	Cairn	A-36
AL030	Cemetery	A-47
AL060	Dragon's Teeth	A-75
AL070	Fence	A-115
AL099	Hut	A-164
AL105	Settlement	A-296
AL130	Memorial Monument	A-181
AL140	Particle Accelerator	A-192
AL170	Public Square	A-206
AL200	Ruins	A-286
AL208	Shanty Town	A-299
AL210	Protection Shed	A-205
AL241	Tower	A-330
AL260	Wall	A-347
AM010	Storage Depot	A-316
AM020	Grain Storage Structure	A-150
AM030	Grain Elevator	A-148
AM040	Mineral Pile	A-183
AM060	Surface Bunker	A-322
AM070	Storage Tank	A-318
AN010	Railway	A-216
AN050	Railway Sidetrack	A-237
AN060	Railway Yard	A-245
AN075	Railway Turntable	A-244
AN076	Roundhouse	A-285
AP010	Cart Track	A-44
AP030	Road	A-257
AP050	Trail	A-333
AQ040	Bridge	A-27
AQ063	Causeway Structure	A-46
AQ065	Culvert	A-65
AQ070	Ferry Crossing	A-115
AQ075	Ice Route	A-166
AQ090	Entrance and/or Exit	A-101
AQ110	Mooring Mast	A-185
AQ113	Pipeline	A-195
AQ116	Pumping Station	A-207
AQ125	Transportation Station	A-334
NACCO Destructed Chandrad Anna et 1 (v.2 0.1)		1 44

Feature Code	DFDD Feature Name	Page
AQ130	Tunnel	A-338
AQ135	Roadside Rest Area	A-281
AQ140	Vehicle Lot	A-342
AT010	Dish Aerial	A-72
AT030	Power Line	A-200
AT041	Cableway	A-35
AT042	Pylon	A-209
AT045	Radar Station	A-215
AT050	Communication Station	A-57
AT060	Communication Line	A-55
BA010	Land Water Boundary	A-171
BA030	Island	A-167
BA040	Tidal Water	A-329
BA050	Beach	A-20
BB005	Harbour	A-157
BB041	Breakwater	A-25
BB043	Groin	A-154
BB090	Dry Dock	A-77
BB140	Training Wall	A-333
BB155	Maritime Signal Station	A-178
BB190	Berthing Structure	A-22
BB230	Seawall	A-295
BB240	Slipway	A-303
BD100	Structural Pile	A-321
BD110	Offshore Platform	A-189
BD120	Reef	A-249
BD130	Hazardous Rock	A-158
BD180	Wreck	A-361
BH010	Aqueduct	A-14
BH015	Bog	A-24
BH020	Canal	A-39
BH030	Ditch	A-73
BH040	Water Treatment Bed	A-350
BH050	Mariculture Site	A-177
BH051	Fish Farm Facility	A-118
ВН060	Flume	A-120
BH070	Ford	A-121
BH080	Lake	A-168
вн090	Land Subject To Inundation	A-170
BH110	Penstock	A-193
BH120	Rapids	A-245

Sorted by reature code		
Feature Code	DFDD Feature Name	Page
BH130	Reservoir	A-251
BH135	Rice Field	A-253
BH140	River	A-254
BH145	Vanishing Point	A-341
BH150	Salt Flat	A-291
BH155	Salt Evaporator	A-290
BH160	Sabkha	A-289
BH165	Spillway	A-310
BH170	Natural Pool	A-187
BH180	Waterfall	A-351
BI010	Cistern	A-54
BI020	Dam	A-67
BI030	Lock	A-174
BI040	Sluice Gate	A-304
BI041	Water Gate	A-349
BI050	Water Intake Tower	A-350
BJ020	Moraine	A-185
BJ030	Glacier	A-147
BJ031	Crevasse	A-61
BJ040	Ice Cliff	A-165
BJ060	Ice Peak	A-166
BJ100	Snow Ice Field	A-306
BJ110	Tundra	A-337
CA010	Elevation Contour	A-79
CA030	Spot Elevation	A-312
DA010	Soil Surface Region	A-306
DB010	Steep Terrain Face	A-315
DB029	Cave Mouth	A-47
DB061	Crevice	A-63
DB071	Cut Line	A-66
DB090	Embankment	A-98
DB100	Esker	A-101
DB110	Geologic Fault	A-143
DB115	Geothermal Outlet	A-146
DB150	Mountain Pass	A-186
DB160	Rock Formation	A-283
DB170	Sand Dunes	A-292
DB180	Volcano	A-345
DB200	Gully	A-156
EA010	Crop Land	A-64
EA020	Hedgerow	A-160
MACCO Destructed Chandrad Assess L (c.2.0.1)		1 40

Feature Code	DFDD Feature Name	Page
EA040	Orchard	A-190
EA050	Vineyard	A-344
EA055	Hop Field	A-164
EB010	Grassland	A-152
EB020	Thicket	A-329
EC010	Cane	A-44
EC020	Oasis	A-188
EC030	Wood	A-357
EC040	Cleared Way	A-55
EC060	Forest Clearing	A-122
ED010	Marsh	A-180
ED020	Swamp	A-325
ED030	Mangrove Swamp	A-176
FA000	Administrative Boundary	A-1
FA002	Geopolitical Entity	A-144
FA003	Administrative Division	A-3
FA015	Firing Range	A-116
FA090	Geophysical Prospecting Grid	A-144
FA100	Test Site	A-328
GA034	Aeronautical Radio Navigation Service	A-7
GB005	Land Aerodrome	A-169
GB015	Apron	A-14
GB030	Helipad	A-161
GB035	Heliport	A-162
GB040	Launch Pad	A-172
GB045	Stopway	A-316
GB050	Aircraft Revetment	A-10
GB055	Runway	A-287
GB065	Water Aerodrome	A-347
GB075	Taxiway	A-327
GB220	Aeronautical Obstacle	A-6
GB230	Aircraft Hangar	A-8
GB485	Approach Lighting System	A-13
No Code	Leader Line	A-173
No Code	Point of Change	A-199
No Code	River Flow Arrow	A-257
No Code	Road Route Marker	A-279
No Code	Vertical Obstruction	A-342
SU001	Military Installation	A-181
ZB050	Survey Point	A-323
ZD020	Void Collection Area	A-345

Feature Code	DFDD Feature Name	Page
ZD040	Named Location	A-186