



The
**Digital Geographic Information
Exchange Standard
(DIGEST)**

**Part 2 - Annex B
ISO 8824 ENCAPSULATION SPECIFICATION**

Edition 2.1
September 2000

Produced and issued by the Digital Geographic Information Working Group (DGIWG)

Annex B

ISO 8824 Encapsulation Specification

Annex B - Contents	page
B.1 INTRODUCTION	B-3
B.2 THE DIGEST TELECOMMUNICATIONS ENCAPSULATION	B-3
B.2.1 ASN.1 Meta Notation	B-4
B.2.2 ASN.1 Encoding Rules	B-9
B.2.3 Normalized Coordinates	B-11
B.3 OVERALL STRUCTURE	B-15
B.3.1 Exchange Set Structure	B-17
B.3.2 Geo Dataset Structure	B-17
B.4 TRANSMITTAL HEADER FILE.....	B-17
B.4.1 Transmittal-Description-Record	B-18
B.4.2 Security-and-Update-Record.....	B-18
B.5 GENERAL-INFORMATION-FILE	B-19
B.5.1 General-Information-Record.....	B-20
B.5.2 Dataset-Description-Record.....	B-26
B.6 GEO-REFERENCE-FILE	B-26
B.6.1 Geo-Reference-Record.....	B-26
B.6.2 Grid-Description-Record	B-28
B.7 SOURCE-FILE.....	B-31
B.7.1 Source-Record.....	B-32
B.7.2 Legend Record	B-35
B.7.3 Metric-Support-Data-Record	B-36
B.7.3.1 Arc-System-Metric-Support-Record.....	B-36
B.7.3.2 UTM / UPS-System-Metric-Support-Record	B-37
B.7.4 Supplementary-Text-Record	B-38
B.7.5 Auxiliary-Parameters-Record	B-38
B.8 QUALITY-FILE	B-42
B.8.1 Quality-Record	B-42
B.8.2 Accuracy-Record.....	B-45
B.8.3 Component-Accuracies-Record	B-46
B.8.3.1 Horizontal-Accuracies-Record	B-46
B.8.3.2 Vertical-Accuracies-Record.....	B-46
B.9 VECTOR-GEO-DATA-FILE.....	B-48
B.9.1 Edge-Record.....	B-49
B.9.2 Node-Record	B-51
B.9.3 Face-Record	B-52
B.9.4 Feature-Record	B-52
B.9.5 Text-Placement-Record	B-54
B.9.6 Feature / Attribute-Entry-Record	B-54
B.9.7 Feature / Attribute-Association-Record	B-55
B.10 RASTER-GEO-DATA-FILE	B-57

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

B.10.1	Image-Record.....	B-57
B.11	MATRIX-GEO-DATA-FILE.....	B-58
B.11.1	Matrix-Record.....	B-58

Annex B - Figures **page**

B-1	ASN.1 Tag Length Structure.....	B-9
B-2	Syntactic Tree.....	B-9
B-3	Serialized Syntactic Tree.....	B-10
B-4	Universal and Implicit Tags	B-10
B-5	Tag Bit Pattern	B-11
B-6	Normalized Coordinate Space.....	B-12
B-7	Normalized Area for the Whole World.....	B-13
B-8	Binary Fraction.....	B-14
B-9	X,Y Interleaved Binary Fractions.....	B-15
B-10	X,Y,Z Interleaved Binary Fractions	B-15

B.1 INTRODUCTION

This annex presents an encoding of DIGEST for the purpose of efficient telecommunications. This annex contains exactly the same information content as DIGEST Annex A, except that the hierarchical style of presentation inherent with the Abstract Syntax Notation (ASN) is used, and that some fields included in Annex A for backward compatibility with earlier Annex A based products are not included.

In order to efficiently communicate geographic data over telecommunications media, the ISO 8824 Abstract Syntax Notation and the ISO 8825 Encoding Rules are used for the encapsulation of DIGEST data. This permits the handling of optional data fields and of geographic coordinates in a compact and efficient manner. Telecommunications applications are particularly sensitive to the volume of data that must be handled in any particular communication data transfer.

ISO 8825 (ASN.1 encoding rules) makes use of a tag length encoding scheme for the identification of data elements as components of a communication stream. Each piece of information is identified by a preceding tag and a number defining the length of the element. Such tag length combinations may be nested to any level. The sending and receiving communications entities follow identical syntactic trees in composing and parsing the data stream. The syntactic tree is a property of the standard and is not communicated. The tag codes permit the communicating entities to skip through the syntactic description. Therefore only actual data elements need be transferred. There is no overhead involved in the self-description of the syntactic tree or the identification of optional but missing elements. This makes the ISO 8824/5 encoding of DIGEST particularly useful in the communications of map segments or updates to previously communicated maps.

B.2 THE DIGEST TELECOMMUNICATIONS ENCAPSULATION

The basic information elements of the interchange format are information fields composed of specific data elements. The fields used in this ISO 8824 description of DIGEST are equivalent to the data fields used in the ISO 8211 description. Where possible the same field names and tags have been used to make it easy to compare the Annex B encapsulation to Annex A.

The following example shows the "Security-and-Release" data field expressed in ISO 8824 (ASN.1) form followed by the same data field in ISO 8211 (as used in DIGEST Annex A). This illustrates the similarity of the two descriptions at the syntactic level.

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

ISO 8824

```
Security-and-Release-Field      --QSR
    ::= SEQUENCE {
qss        Security-Level,      --Highest security classification
qod        Basic-Text-String (Y|N), --Downgrading instructions
cdv10      Date,              --Date of downgrading value
qle        Basic-Text-String     --Releasability
    }

Security-Level                  --QSS
    ::= Basic-Text-String
                                (top-secret("T") |
                                secret("S") |
                                confidential("C") |
                                restricted("R") |
                                unclassified("U"))
```

In the description above "QSR" is a field tag, and "qss", "qod", "cdv10", and "qle" are subfield labels. In ISO 8824, field tags and subfield labels are optional and are included here to provide a reference back to the fields described in ISO 8211 DIGEST described in Annex A. The text following the double hyphen "--" are comments. Note also that in this particular example "Security Level" is defined as a separate element in order to show the use and definition of syntactic sub-elements. Allowable values for an element are given in brackets e.g. (Y|N). The equivalent ISO 8211 encapsulation for the above example is:

ISO 8211

3[C,M]	0	QSR	001	& SECURITY_AND_RELEASE
4[C,M]	1	QSS	A 1	Security classification { T S C R U }
4[C,M]	2	QOD	A 1	Downgrading instructions { Y N }
4[C,O]	3	CDV10	A 8	Downgrading date value
4[C,M]	4	QLE	A	Releasability Statement

999

The USE (i.e. Vector, Matrix, or Raster) classifications in the ISO 8211 notation have been handled by separating out these subfields in the Header Data Subset. Within the Geo Dataset, the Topological Vector Subset may contain only vector data and similarly, the Raster and Matrix Geo Data Subsets may contain only their corresponding data.

B.2.1 ASN.1 Meta Notation

The ISO Abstract Syntax Notation (ASN.1) is a meta language used to provide a data interchange format in a context-independent manner. ASN.1 itself is similar to the compiler description languages used in computer science to define programming languages. In fact the structure is similar to a programming language and a particular data file is analogous to a particular program written in the language. Like a language, the definition of a data file in DIGEST Annex B makes use of only those words in the language that apply in a given situation.

Words, or statements composed of sequences of words, may be used as often as needed, in accordance with the syntactic rules of Annex B. These rules are effectively the grammar of the DIGEST Annex B "language".

A number of basic data types make up the "vocabulary" of the "language". These data types are coded according to the rules of supporting data syntaxes (see DIGEST Part 3 Clause 5). For example, a string of basic text is a primitive data type. The syntax of DIGEST is defined in a rigorous and formal way in the ASN meta language.

A complete description of the Abstract Syntax Notation would take some space to present. However in the specification of DIGEST only a subset of the ASN commands need be used. This subset is identified below:

- Assignment
- CHOICE
- SEQUENCE
- SEQUENCE OF
- SET
- SET OF
- MACRO

Quite complex data types are required to support DIGEST data interchange. This is accomplished by defining a small number of simple data types. The complete range of values of these simple data types may be defined, and then the manner of combining these simple data types into the more complex data types is specified. A data type defined in this manner may be assigned a tag so that it may be identified in the communication or otherwise distinguished. Encoding rules described separately from the syntax of the data format define the manner in which the data types are encoded and delimited in terms of octets of data that are communicated.

The Abstract Syntax Notation defines a communications format in terms of a syntactic tree. At the highest level the entire dataset that is interchanged is described as a sequence of sub-sections. These sub-sections are then broken down into their component elements and so on, until each of the primitive data elements is identified. Each data element has a particular data type such as a basic text string, an integer etc. When data is communicated, it is parsed by the receiving device in the order specified by the syntactic tree. Many branches of the syntactic tree may be optional. In communicating information, it is not necessary to pad the communications with null fields to accommodate information fields that are not used. The tag numbers associated with data elements allow the parser to skip over sections of the syntactic tree, so that only the relevant information needs to be communicated. This approach also allows for recursive definitions, so that there is no limit to the number or length of parameter data.

Branches of the syntactic tree are defined in terms of expressions in the Abstract Syntax Notation. The Assignment operator ::= equates a reference name to a series of more basic commands or primitive data elements. An entire syntax is described in terms of successive

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

refinement. A data file consists of a number of named sections, each of which consists of a number of sub-sections etc. down to the level of the primitive data elements.

The basic operator in an assignment statement is the **SEQUENCE** command. The **SEQUENCE** operator specifies that a branch of the syntactic tree consists of a defined number of elements in a fixed order, that is a list of mandatory or optional elements. The **SEQUENCE OF** operator specifies that number of elements is variable but that the order is fixed, that is it indicates a repeated element or list of elements. The **SET** operator specifies that a branch of the syntactic tree consists of a defined number of elements in any order. It is equivalent to a sequence but the order is not fixed. The **SET OF** operator specifies that number of elements is variable and that the order is variable. The **CHOICE** operator specifies that an instance of the syntactic tree permits the inclusion of one data element (or sub-branch) out of a fixed set of choices.

Elements in a **SEQUENCE** or **SET** may be optional. This is indicated by the keyword **OPTIONAL** immediately following the element name in the sequence or set. If a default value is defined for an optional element, then the keyword **DEFAULT** replaces the term **OPTIONAL** and the value of the default is specified following the **DEFAULT** keyword.

A **MACRO** definition allows a primitive data type to be constructed out of other primitive data types. It also allows a default value notation to be defined for the constructed primitive so that the **DEFAULT** specification may be used with this new element.

Tag numbers are used to identify branches of the syntactic tree. A tag number is expressed in square brackets [] preceding an element name. Tag numbers are not necessary in a fixed **SEQUENCE** with no **OPTIONAL** elements since the order is known; however, in other cases, tag numbers must be supplied for each element. There are four classes of identifier tag codes: Universal, Context Specific, Application, and Private. **Universal tags** are used to identify operators such as **CHOICE** or **SEQUENCE** or basic data elements such as a **GRAPHIC STRING**. **Context Specific tags** are assigned in each branch of the syntactic tree to number the elements of the tree in that branch. The same tag numbers are used over and over in different levels of the syntactic tree, and it is the responsibility of the syntax parser interpreting data encoded in terms of the ASN defined syntax to keep track of the levels of the tree and the local meaning of each tag. **Application wide tags** are used to define unique identifiers to specific elements. The parser does not need to keep track of the level of the syntax to identify the particular data element. Since Application-wide tags are unique to a particular data element, long tag numbers would result if they were used extensively throughout a particular syntax. Therefore their use is restricted to a few strategic places within the DIGEST syntax. **Private tags** are used to build proprietary extensions to an existing standard, and they are not used in DIGEST.

In certain situations, redundant tags are generated. For example, a Universal tag may immediately follow a Context Specific tag. The keyword **IMPLICIT** is used to suppress the generation of a universal tag in those situations where the tag is unnecessary. An **IMPLICIT SEQUENCE** of two tagged elements would be encoded using only the context specific tags identifying each of the elements. The tag identifying the overall sequence would not be included.

The following is a summary of the notations used in the grammar, which is used to formally describe DIGEST in Annex B.

::= - is the production symbol of the grammar and can be read "is produced by" or "is composed of". A production allows the definition of a syntactic entity by the assignment of a name to a collection of data types or other entities. Entities placed on the right of the production symbol are taken together to define the composite entity. By the use of production statements, the elements of the grammar may be defined by successive refinement.

CHOICE { } - is the alternative indicator in a production definition. It can be read as "or". Alternate data entities are separated by commas within the brackets of the CHOICE indicator. Each of these entities must be identified by a TAG, so that the particular entity communicated may be distinguished. For example, the data entity Type consists of a choice of data element Type-1, Type-2, or Type-3. The TAG numbers are enclosed in square brackets.

```
Type    ::=  CHOICE  {      [1]      Type-1,  
                           [2]      Type-2,  
                           [3]      Type-3  
                     }
```

SEQUENCE { } - is the cumulative indicator in a production definition. It can be read as "and". Data entries in a sequence are separated by commas within the brackets of the SEQUENCE indicator. For example, data entity Process consists of the ordered sequence of entities Step-1, Step-2, Step-3. Explicit TAGs are not required since the order of the sequence is fixed.

```
Process  ::=  SEQUENCE  {      Step-1,  
                               Step-2,  
                               Step-3  
                     }
```

SET { } - is also a cumulative indicator in a production definition, which can also be read as "and". It is similar to the SEQUENCE indicator except that the order of the elements is not fixed. Therefore TAG codes must be used to distinguish the elements. For example, data entity Flock consists of the unordered sequence of entities Bird-1, Bird-2, Bird-3.

```
Flock    ::=  SET  {      [1]      Bird-1,  
                           [2]      Bird-2,  
                           [3]      Bird-3  
                     }
```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

SEQUENCE OF - is a series indicator in a production definition. It can be read as iteration or repetition. It permits zero or more data entities of the same type to be part of a production. The end of the sequence is determined when there are no more data elements of the same type. For example, a data element List is composed of a series of Entries (Entry-1, Entry-2, Entry-3,...).

```
List      ::= SEQUENCE OF Entries
```

Data entities in a SEQUENCE or a SET may be optional. Optional data elements are indicated by the keyword OPTIONAL after the data element name. A default value may also be defined for an optional data element. This is indicated by the keyword DEFAULT after the data element name followed by the value of the default state. The keyword DEFAULT implies the keyword OPTIONAL. For example, data entity Group consists of the ordered sequence of entities Element-1, Element-2, Element-3, Element-4, where Element-2 is optional and Element-3 is optional and takes on the default value 1. Explicit TAGs are required in order to distinguish which elements are included.

```
Group ::= SEQUENCE { [1] Element-1,
                     [2] Element-2 OPTIONAL,
                     [3] Element-3 DEFAULT (1),
                     [4] Element-4 }
```

-- signifies the beginning of comments that are not part of the grammar, but are included to clarify the semantic meaning and context.

Keywords - such as **SEQUENCE**, **SET**, **CHOICE** etc. are expressed in capital letters.

identifier name - the name of an identifier consists of a string of letters, digits and hyphens beginning with a lower case letter. Identifier names may be used to identify particular elements of an entity or to assign a value to a particular element of an entity.

Entity Name - the name of an entity consists of a string of letters, digits and hyphens beginning with an upper case letter.

The primitive level of the Abstract Syntax Notation consists of a number of built-in data types. These can be classified into several categories as shown below:

Numerical Data Types	-	BOOLEAN	- True or False
		INTEGER	- Integer number (a signed integer number of arbitrary length)
Bit Oriented Data Types	-	BIT STRING	- String of bits
		OCTET STRING	- String of 8-bit bytes

General Data Types	- NULL ANY	- Null string - Any data string
Time / Date Data Type	- GENERALIZED TIME	- Date / Time (universal time expressed as year, month, day, hour, minutes, seconds, fractions of seconds and a time zone differential from Greenwich)
Character Data Types	- GRAPHIC STRING	- A string of characters (see Part 3 clause 5)

This description of the Meta Notation only identifies the principal functions used in DIGEST Annex B. A more comprehensive description is given in the ISO standard ISO 8824.

B.2.2 ASN.1 Encoding Rules

The Abstract Syntax Notation defines the syntactic structure of the interchange format. However, the structure itself is not communicated. What is communicated are values of the data elements along with delimiting codes and identifier (TAG) numbers that indicate where the data elements are in terms of the syntactic tree. A separate parallel standard to ASN defines the encoding rules for identifying and delimiting data elements for communication in a particular eight-bit transparent communications environment. This is sufficient for communicating DIGEST over a data transparent data communications channel.

The ASN.1 encoding rules make use of an identifier (TAG) and a length code for each data element. The length codes define a nesting structure that corresponds to the relationship of the data elements in the interchange format.




Figure B-1 ASN.1 Tag Length Structure

In the illustration above, **i** is the identifier TAG code and **l** is the length. The range of the length is indicated by a bar above the data elements, starting at the length indicator and proceeding to the end of its range.

A particular string of data, structured in accordance with a tree-oriented syntax, might be illustrated as shown below:




Figure B-2 Syntactic Tree

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

In each case the identifier specifies the type of the data value or how to relate it to the syntactic tree, and the length defines how to find the end of the string or sub-string. This structure can be expressed in a serial manner as:



Figure B-3 Serialized Syntactic Tree

The syntactic tree expressed in ASN corresponding to this expression would be:

```
SEQUENCE { SEQUENCE {b,c}, SEQUENCE {d,e}, IMPLICIT SEQUENCE OF {a} }
```

Universal codes are defined within ASN and indicate the particular tree-node type or the type of the built-in data elements, such as INTEGER or GENERALIZED TIME. The Universal identifier codes of interest in DIGEST are:

Universal Identifier Type Code	Syntactic Tree Node Type
16	SEQUENCE and SEQUENCE OF
17	SET and SET OF
5	NULL
4	OCTET STRING
2	INTEGER
25	GRAPHIC STRING
27	GENERAL STRING
24	GENERALIZED TIME

The DIGEST Annex B specification uses Context Specific identifier codes and a small number of Application identifier codes. No Private identifier codes are used.

Universal tags identify data elements by type. At times this is sufficient to match the data element to the syntactic tree. However in some situations, such as the case of OPTIONAL elements of the same type, it is necessary to make use of Context specific tags in the syntax. An IMPLICIT command may be used to eliminate the redundant universal tag. For example:




Figure B-4 Universal and Implicit Tags

The coding of the identifier **i** takes on the form illustrated below:




Figure B-5 Tag Bit Pattern

The length code contains a count of the number of octets (8-bit bytes) in the particular construct (branch) or primitive (element). For a length of 1 to 127, one octet may be used. For longer lengths, bit 8 in the first octet is 1 and the low order bits contain the length of the string of length octets. Subsequent octets in the length field taken together give the range of the construct or primitive. Note that the special value 255 in the first octet is reserved and the value 128 indicates an indefinite length range. Such a range is terminated by a special identifier of Universal class 0.

Note that a length code of zero for a data item is permitted and that for numeric data items such usage indicates that the value is zero.

B.2.3 Normalized Coordinates

An important aspect of the communication efficiency built into the ISO 8824 / 5 encapsulation of DIGEST is the use of normalized coordinates for the handling of coordinate data and other numbers of fixed range. In some encoding schemes, which are not tuned for a high level of communications efficiency, numbers such as coordinates are handled as real numbers. If only a small range of numbers is valid, this is a potential waste of "code space" and therefore efficiency. For example, if a number could validly range from 0 to 5 then values such as 25 or 2.94×10^{43} would be illegal. However, the real number coding system would assign potential bit combinations to handle these potential values. Since these values would never be encountered in an actual communication, the encoding of the real numbers would be larger than required to handle the actual data.

If a number has a fixed range, such as the 0 to 5 in our example, then it can always be normalized to a corresponding 0 to 1 range. All values in the range would be fractions of 0 to 1. This can be efficiently encoded as a binary fraction. A number in the range 0 (inclusive) to 1 (exclusive) is equivalent to the mantissa part of a real number, and can be termed a fraction number. In an actual implementation there is always a fixed number of bits of precision assigned. A fraction number can therefore easily be implemented by scaling the number up by the number of bits of precision assigned. That is, the decimal

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

point (or more correctly binary point) can be shifted by multiplying by 2^n where n is the number of bits of precision available in the number field. The number therefore can be represented as an integer number in a fixed-length binary field.

Since integer numbers are normally encoded using fewer bits, for equivalent precision, this provides a significant improvement in efficiency. Also, since the number range is a better fit to the value range of the data, it is sometimes possible to use short integers rather than long integers and therefore achieve a four-fold increase in the efficiency of encoding a particular real number.

Coordinate data is normally handled as a Cartesian pair (or triple) of real numbers. Latitude and Longitude are normally represented as degrees, however in other projections, northings and eastings in terms of meters from the equator are at times communicated. Great efficiencies can be achieved by normalizing the coordinate data to the possible number range and carrying that as a pair of normalized binary fractions. For example, if we were interested in a map area with a minimum bounding rectangle of 63° to 62° longitude and 44° to 45° latitude, then we could represent that as a unit square from 0 to 1 and from 0 to 1. Note that both positive and negative normalized number ranges are permitted.




Figure B-6 Normalized Coordinate Space

Normalized unit areas are always square to maintain the aspect ratio of the projected data. Therefore if the map area of interest is not square, it is circumscribed within the minimum bounding square area.

In the DIGEST ISO 8824/5 encapsulation normalized coordinates are used to handle most of the spatial information in the body of the data exchange. This covers the vast majority of the spatial data elements in a dataset. Certain data elements in the header are excluded to make the dataset easier to interpret. In addition, the specification of the Minimum Bounding Rectangle (see Map-Boundary-Coordinates-Subfield in General-Information-Record) for the whole map in the header is specified using real numbers for the coordinate values, because these numbers may be used to calculate the dimensions of the Normalized Unit Area corresponding to the whole map. In effect, all the coordinate information in this

encapsulation is defined as fractions of the minimum bounding rectangle. For most coordinate oriented data, such as "Node" positions, the dimensions of the Minimum Bounding Rectangles (MBRs) around "Features", etc., fraction numbers in a normalized coordinate space are adequate. However the "Edge" topological primitive is a special case.

An edge carries a string of vertices as a spatial attribute defining the shape of the edge. Due to the nature of geographical data each vertex tends to be "near" its neighbor in a mathematical sense. Therefore, an additional efficiency can be achieved for strings of vertices. Three special types of coordinate encoding are defined for edges. These are **absolute**, **relative** and **differential** coordinate strings.

Absolute-coordinate-string(s) are sets of X,Y or X,Y,Z coordinates represented as pairs or triplets of numbers in normalized coordinate space. The number of bits of precision used to specify an absolute coordinate is defined in the tag length structure of the OCTETSTRING used to encode the coordinate. Absolute coordinates are fractions of the normalized whole world map represented as Lat / Long coordinates. See Figure B-2. Note that 64 bits of precision (8 bytes), including both X and Y interleaved, are required to represent a position to 1 millimetre resolution (at the equator).




Figure B-7 Normalized Area for the Whole World

Relative-Coordinate-String(s) are a set of X,Y coordinates specified as relative to a local coordinate system. The origin of the local coordinate system is defined for a Layer/Coverage as part of the metadata of the Layer/Coverage [see part 2 sub-clause 10.2]. Since the possible range of values in a local coordinate system is less than the full absolute coordinate system it requires fewer bits to encode coordinates. A relative coordinate string begins with a sub-string length indicator, which specifies the number of bits of each coordinate element. This is followed by an OCTETSTRING containing the bit packed coordinate information. All of these values are in terms of the normalized coordinate space. For example, an edge might consist of 299 X,Y vertices. This edge might be restricted to a local region that can be represented in 14 bits (7 bits for X and 7 bits for Y). The reference position and scale factor of the coordinate system would be set as part of the metadata for the Layer/Coverage. The relative coordinate string would consist of an integer number indicating that the following relative coordinate sub-strings are each 14 bits long, followed by a string of 4186 bits, packed into an OCTETSTRING of 524 bytes,

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

representing the 299 vertices. Note that there are 6 remaining leftover bits in the octet string that are padded with 0 and ignored.

Note that the origin and scale factor defining the local coordinate system are defined using an Application Tag [A 20] in DIGEST B. This means that before using a relative coordinate string, the local coordinate system should be set up using the element identified by Application Tag [A 20].

Differential-Coordinate-String(s) provide an even higher level of compaction for that class of edge in which there is both a maximum and minimum vectorial displacement between vertices. If the edge is "well behaved" and varies only locally, then it can be represented very efficiently in terms of short vectors that are defined as relative to the preceding vector in a chain of such vectors. Actually, due to the manner in which geographic data is often gathered, this is a very common situation. A differential coordinate defines a differential factor that indicates the increment step size. For example, if each relative coordinate displacement is a minimum of 3-bit increments, for the numerical precision used in the Normalized Unit Coordinate system as defined by the Scale factor for the local coordinate system, then the differential factor of 3 can be divided out of each of the coordinate positions. Also if the maximum increment size is 3 bits, this would mean in the example used above, that each coordinate could be represented as 6 bits (3 bits for X and 3 bits for Y). Therefore the string would consist of an initial coordinate (Coord) position, followed by an integer number specifying a differential factor of 3, followed by an integer number indicating that the following differential coordinate sub-strings are each 6 bits long. This is followed by a string of 1794 bits, packed into an OCTETSTRING of 225 bytes, representing the 299 vertices. Note that there are 6 remaining leftover bits in the octet string that are padded with 0 and ignored.

Coordinates are stored as interleaved normalized binary fractions. That is, a number ranging from 0 (inclusive) to 1 (exclusive) may be stored as a binary fraction encoded in an integer field with the implied binary point at the most significant position. This is illustrated below.






Figure B-8 Binary Fraction



X,Y COORDINATE AS AN INTERLEAVED NORMALIZED BINARY FRACTION

Figure B-9 X,Y Interleaved Binary Fractions



X,Y,Z COORDINATE AS AN INTERLEAVED NORMALIZED BINARY FRACTION

Figure B-10 X,Y,Z Interleaved Binary Fractions

The details of the encoding of coordinate information are given in DIGEST Part 3 clause 5.

B.3 OVERALL STRUCTURE

The DIGEST geographical data interchange standard allows the definition of entire maps or charts, or parts of maps or charts, to be exchanged. The interchange unit corresponding to an entire map or chart is called an "Exchange Set." Such an entity can be broken down into several components for the purpose of defining the various elements that compose a map or chart specified according to the DIGEST format.

If an entire map or chart is being communicated, then it is expected that the full exchange set is being transmitted. This is making use of DIGEST B in the same manner as one would use DIGEST A (ISO 8211) or DIGEST C (VRF) to exchange a dataset. However, it

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

is more likely that DIGEST B would be used to exchange only a part of a dataset. This may occur in the situation where an update is being applied to an already communicated map, or where a portion of a map is extracted from a database or data warehouse. In an update situation, it can be assumed that the entire map already exists at the destination end of the communications, and that only the new information needs to be communicated. In a situation where data is being extracted from a database, the information is in the context of the extraction.

The following is a description of the entire DIGEST specification described in terms of ISO 8824. To communicate an entire map, begin at the exchange set level. To communicate a component of a map, select the appropriate elements as identified by the Application Tags.

The Exchange set is represented schematically below in a form similar to that used in Part 2 Annex A clause 1.1.

The following is a general description of the Exchange set:

```
Exchange set: DIGEST
  - File: TRANSMITTAL HEADER
  - R Geo Dataset
    - File: GENERAL INFORMATION
    - File: GEO REFERENCE
    - R File: SOURCE
    - File: QUALITY
    - R Layer
      |
      *-R File: VECTOR GEO DATA
      |
      *-R File: RASTER GEO DATA
      |
      *-R File: MATRIX GEO DATA
```

This is encapsulated in ISO 8824 in the following sections and subsections.

Note: The term "File" in this exchange encapsulation is a logical grouping of data, not a physical file on an exchange media. The term is retained to make the correspondence between encapsulations clearer.

B.3.1 Exchange Set Structure

```
Exchange-set
  ::= [A 0] SEQUENCE {
    Transmittal-Header-File,
    SEQUENCE OF
      Geo-Dataset-File
  }
```

Note: [A n] represents the application-wide tag [APPLICATION n], where n is an integer. These tag numbers are unique and may be used to identify independent segments of ISO 8825 encoded data.

B.3.2 Geo Dataset Structure

```
Geo-Dataset-File
  ::= SEQUENCE {
    General-Information-File,
    Geo-Reference-File,
    SEQUENCE OF
      Source-File,
      Quality-File,
    SEQUENCE OF
      Layer-Section
  }

Layer-Section
  ::= CHOICE {
    [0] Vector-Geo-Data-File,
    [1] Raster-Geo-Data-File,
    [2] Matrix-Geo-Data-File
  }
```

B.4 TRANSMITTAL HEADER FILE

The Transmittal-Header describes general information encompassing the entire transmittal dataset.

```
Transmittal-Header-File
|
|- Transmittal-Description-Record
  |
  |- Transmittal-Header-Field
  |-R Dataset-Description-Field
|
|- Security-and-Update-Record
  |
  |- Security-and-Release-Field
  |-R Up-to-Dateness-Field
```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

```
Transmittal-Header-File
  ::= SEQUENCE {
    thf      Transmittal-Description-Record,
    lcf      Security-and-Update-Record
  }
```

B.4.1 Transmittal-Description-Record

```
Transmittal-Description-Record      --THF
  ::= SEQUENCE {
    vdr      Transmittal-Header-Field,
    fdr      SEQUENCE OF
              Dataset-Description-Field
  }
Transmittal-Header-Field          --VDR
  ::= SEQUENCE {
    Originator-Subfield      OPTIONAL,
                                --Originator - addressee
    nof      Integer-Number,           --Number of datasets
    urf      Basic-Text-String,        --Transmittal Identifier
    edn      Integer-Number,           --Edition number
    cdv07    Date                   --Creation date value
  }

Originator-Subfield
  ::= SEQUENCE {
    voo      Basic-Text-String,       --Originator
    adr      Basic-Text-String      OPTIONAL,
                                --Addressee
  }

Dataset-Description-Field        --FDR
  ::= SEQUENCE {
    nam      Basic-Text-String,       --Dataset ID
    str      Integer-Number,          --Structure code
    ( Matrix-values(1),
      Matrix-coded(2),
      Raster-RGB(3),
      Raster-color-coded(4),
      Cartographic-Spaghetti(5),   --Vector: Level 0 Topology
      Non-Planar-Graph(6),         --Vector: Level 1 Topology
      Chain-node(7),               --Vector: Level 2 Topology
      Full-Topology(8)             --Vector: Level 3 Topology
    )
    prt      Basic-Text-String,       --Dataset type
    enc      Basic-Text-String,      (B|X) --Encapsulation B only or Mixed
                                            --see Dependency condition 1.1
    swo      Fraction-Number,        --Westernmost longitude
    swa      Fraction-Number,        --Southernmost latitude
    neo      Fraction-Number,        --Easternmost longitude
    nea      Fraction-Number        --Northernmost latitude
  }
```

B.4.2 Security-and-Update-Record

```
Security-and-Update-Record        --LCF
  ::= SEQUENCE {
    qsr      Security-and-Release-Field,
    SEQUENCE OF
    quv      Up-to-Dateness-Field
  }
```

```

Security-and-Release-Field          --QSR
 ::= SEQUENCE {
qss      Security-Level,           --Security classification
qod      Basic-Text-String,   (Y|N) --Downgrading instructions
cdv10     Date                   OPTIONAL,
          --Date of Downgrading
qle      Basic-Text-String       --Releasability
}

Up-to-Dateness-Field            --QUV
 ::= SEQUENCE {
  [0]  DIGEST_specification_Up_to_Dateness,
  [1]  Product_specification_Up_to_Dateness  OPTIONAL
}
DIGEST_specification_Up_to_Dateness
 ::= SEQUENCE {
src1      Basic-Text-String,        --DIGEST Edition ID
cdv12     Date,                  --DIGEST Edition Date
spal      Basic-Text-String       --DIGEST Amendment Number
}
Product_specification_Up_to_Dateness
 ::= SEQUENCE {
src2      Basic-Text-String,        --Specification Edition ID;
cdv22     Date,                  --Specification edition
spa2      Basic-Text-String       --Specification Amendment
}

Security-Level                  --QSS
 ::= Basic-Text-String
          (top-secret("T"),
           secret("S"),
           confidential("C"),
           restricted("R"),
           unclassified("U"))

```

Dependency conditions (list 1):

1-1 Encapsulation:

Must be present when the encapsulation is not homogeneous within the transmittal.

B.5 GENERAL- INFORMATION-FILE

```

General-Information-File
|
|-R General-Information-Record
  |
  |- Dataset-ID-Field
  |
  |- Vector-General
  |
  |- Raster-General
  |
  |- Matrix-General
  |
|- Dataset-Description-Record
  |
  |- Dataset-Description-Field

```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

Note: The USE (i.e., Vector, Matrix, or Raster) classifications in the ISO 8211 notation in the general information record have been handled by breaking out the Vector, Raster and Matrix components into separate elements.

```
General-Information-File
  ::= [A 1] SEQUENCE {
    [0] SEQUENCE OF
      gin           General-Information-Record,
      dss           [1] Dataset-Description-Record   OPTIONAL
  }
```

B.5.1 General-Information-Record

```
General-Information-Record      --GIN
  ::= SEQUENCE {
    dsi           Dataset-ID-Field,        --Dataset name
    gen           CHOICE {
      [0] Vector-General,             --General-Information-Field
      [1] Raster-General,
      [2] Matrix-General
    }
  }

Dataset-ID-Field              --DSI
  ::= SEQUENCE {
    prt-d         Basic-Text-String,     --Dataset type
    nam-d         Basic-Text-String     --Dataset ID
  }

Vector-General                --GEN-V
  ::= SEQUENCE {
    str-v         [0] IMPLICIT-INTEGER,   --General-Information-Field for
                                            --Vector type data
                                            {Cartographic-Spaghetti(5),
                                             Non-Planar-Graph(6),
                                             Chain-node(7),
                                             Full-Topology(8)
                                             --Structure of data within layer
                                             OPTIONAL, {A|B|C|D}
                                             --Encapsulation of the layer
                                             --see Dependency condition 2-1
                                             OPTIONAL,
                                             --Units of GRP and MBR,
                                             OPTIONAL,
                                             --Data cover MBR in percent
                                             OPTIONAL,
                                             --Feature count total in dataset
                                             OPTIONAL,
                                             --Point feature count
                                             OPTIONAL,
                                             --Linear feature count
                                             OPTIONAL,
                                             --Area feature count
                                             OPTIONAL,
                                             --Segment / Edge Record Count
                                             OPTIONAL,
                                             --Node record count
                                             OPTIONAL,
                                             --Face record count
                                             OPTIONAL,
                                             --Simple feature count
                                             }
  }
```

```

sca-v          [12] Map-Boundary-Coordinates-Subfield, -- in WGS84
                [13] Integer-Number   OPTIONAL,
                      --Source graphic scale reciprocal
lcs-v          [14] Local-Coordinate-System-Definition,
                OPTIONAL,
                      --Local Coordinate System for
                      --Layer or Coverage
txt-v          [15] Basic-Text-String
                OPTIONAL,
                      --Free text
spr-v          [16] Vector-Dataset-Parameters --Dataset Parameters
}

Local-Coordinate-System-Definition
 ::= [A 20] SEQUENCE {
lso-v          Fraction-Number      --Longitude / Eastings of Origin
psv-v          Fraction-Number      --Latitude / Northings of Origin
csf-v          Integer-Number       --Coordinates scale factor
}

--Note: Latitude and Longitude are coded as a fraction of 360
--degrees with the usual directional conventions.

Raster-General           --GEN-R
 ::= SEQUENCE {
    Raster-General-Information-Field
        --General-Information-Field
        --for Raster type data
    spr-r          Dataset-Parameters-Field
    bdf-r          Band-ID-Subfield
    tim-r          Tile-Index-Map-Subfield
                  OPTIONAL,
                  --Tile Index Map
                  --see dependency condition 2-6
    cid-r          Compression-ID-Subfield
                  OPTIONAL,
                  --Compression ID
                  --see dependency condition 2-7
    ltd-r          Compression-Lookup-Table-Description OPTIONAL,
                  --Compression Lookup
                  --Table Description
                  --see dependency condition 2-8
    ltv-r          Compression-Lookup-Table-Values  OPTIONAL,
                  --Compression Lookup
                  --Table Description
                  --see dependency condition 2-8
    cpm-r          Compression-Parameters
                  OPTIONAL,
                  --Compression Parameters
                  --see dependency condition 2-9
}

Raster-General-Information-Field
 ::= SEQUENCE {
str-r          [0] IMPLICIT-INTEGER,      {raster-RGB(3),raster-color-coded(4)}
                --Structure of data within layer
enc-r          [1] Integer-Number
                OPTIONAL, {A|B|C|D}
                --Encapsulation of the layer
                --see Dependency condition 2-1
                [2] Data-Density-Subfield
                OPTIONAL,
                --see Dependency condition 2-2
                [3] Map-Boundary-Coordinates-Subfield,
sca-r          [4] Integer-Number,
                --Source graphic scale reciprocal
psp-r          [5] Real-Number,
                --Sample Pixel Spacing in microns
                --at capture stage
}

```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

```

imr-r      [ 6] Basic-Text-String           OPTIONAL,
            { rectified("Y"),
              unrectified("N") }
--Image Rectified during Scanning

[ 7] Pixel-Ground-Spacing-Subfield
      OPTIONAL,
      --see Dependency condition 2-4
      --Longitude / Eastings of Origin
      --Latitude / Northings of Origin
      OPTIONAL,
      --Free text
}

--Note: Latitude and Longitude are coded as a fraction of 360
--degrees with the usual directional conventions.

Matrix-General          --GEN-M
 ::= SEQUENCE  {
   Matrix-General-Information-Field
     --General-Information-Field
     --for Matrix type data
   spr-a    Dataset-Parameters-Field
   bdf-a    Band-ID-Subfield
   tim-a    Tile-Index-Map-Subfield
     OPTIONAL,
     --Tile Index Map
     --see dependency condition 2-6
   cid-a    Compression-ID-Subfield
     OPTIONAL,
     --Compression ID
     --see dependency condition 2-7
   ltd-a    Compression-Lookup-Table-Description
     OPTIONAL,
     --Compression Lookup
     --Table Description
     --see dependency condition 2-8
   ltv-a    Compression-Lookup-Table-Values
     OPTIONAL,
     --Compression Lookup
     --Table Description
     --see dependency condition 2-8
   cpm-a    Compression-Parameters
     OPTIONAL,
     --Compression Parameters
     --see dependency condition 2-9
 }

Matrix-General-Information-Field
 ::= SEQUENCE  {
   str-a    [ 0] IMPLICIT-INTEGER,    {matrix-values(1),matrix-coded(2)}
             --Structure of data within layer
   enc-a    [ 1] Integer-Number
             OPTIONAL, {A|B|C|D}
             --Encapsulation of the layer
             --see Dependency condition 2-1

             [ 2] Data-Density-Subfield
   unimat-a [ 3] Integer-Number,
             --see Dependency condition 2-2
             --Unit of measure for Matrix data
             --null if not relevant
             --see Dependency condition 2-3
   cov-a    [ 4] Integer-Number
             OPTIONAL,
             --Data cover MBR in percent
   zna-a    [ 5] Integer-Number
             OPTIONAL,
             --Zone number; see Dependency
             --condition 2-4
   sca-a    [ 6] Map-Boundary-Coordinates-Subfield,
             [ 7] Integer-Number
             OPTIONAL,
             --Source graphic scale reciprocal
   [ 8] Pixel-Ground-Spacing-Subfield
             OPTIONAL,
             --see Dependency condition 2-4

```

```

lso-a      [9] Fraction-Number ,          --Longitude / Eastings of Origin
psa-a      [10] Fraction-Number,         --Latitude / Northings of Origin
txt-a      [11] Basic-Text-String       OPTIONAL,
}
--Note: Latitude and Longitude are coded as a fraction of 360
--degrees with the usual directional conventions

Data-Density-Subfield
 ::= SEQUENCE {
lod      [0] Real-Number,           --Data interval in E / W direction
lad      [1] Real-Number,           --Data interval in N / S direction
uniloa   [2] Basic-Text-String     --Unit of measure for LOD and LAD
}

Pixel-Ground-Spacing-Subfield
 ::= SEQUENCE {
arv      Integer-Number,          --Longitude density: Number of
brv      Integer-Number           --pixels in 360 degrees (E-W)
}
--Latitude density: Number of
--pixels in 360 degrees (N-S)

Map-Boundary-Coordinates-Subfield
 ::= SEQUENCE {
swo-mb   Fraction-Number,         --Westernmost Longitude
swa-mb   Fraction-Number,         --Southernmost Latitude
neo-mb   Fraction-Number,         --Easternmost Longitude
nea-mb   Fraction-Number         --Northernmost Latitude
}
}

Vector-DataSet-Parameters          --SPR-V
 ::= SEQUENCE {
bad-v    Basic-Text-String,        --Layer file name
}

DataSet-Parameters-Field          --SPR
 ::= SEQUENCE {
[0] Corners-Subfield      OPTIONAL,
nfl      [1] Integer-Number,        --Number of Sub-blocks vertically
nfc      [2] Integer-Number,        --Number of Sub-blocks horizontally
pnc      [3] Integer-Number,        --Number of Pixels / Sub-block line (Q)
 pnl     [4] Integer-Number,        --Number of Scan lines / Sub-block
cod      [5] Integer-Number,        --Column sequence
rod      [6] Integer-Number,        --Row sequence
por      [7] Integer-Number,        --Pixel order
pcb      [8] Integer-Number,        --Size of Pixel / Element count in bits
pvb      [9] Integer-Number,        --Size of Pixel / Element value in bits
bad-d    [10] Basic-Text-String,    --Layer file name for use in the
                                   --General Information File
                                   --(ZZZZZZDD.xxx) or
                                   --Image File name for use
in the
}
tif      [11] Basic-Text-String {Y|N} --Source File (ZZZZZZDD.Lxx)
--Tile index map image

Corners-Subfield
 ::= SEQUENCE {
nul     Integer-Number,           --Row #, Upper Right Corner of MBR
nus     Integer-Number,           --Column #, Upper Right Corner of MBR
nll     Integer-Number,           --Row #, Lower left Corner of MBR
nls     Integer-Number           --Column #, Lower left Corner of MBR
}
}

```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

```
Band-ID-Subfield          --BDF
                               --Raster and Matrix Applications
      ::= SEQUENCE OF
          SEQUENCE {
            bid    [0] Basic-Text-String      OPTIONAL,
                    --Band identification
            [1] SEQUENCE   {
                --Band Description; see Dependency
                -- condition 2-5
              ws1     Integer-Number,        --ON color code value or
                                --Lower limit wavelength in
                                --nanometers
              ws2     Integer-Number        --OFF color code value or
                                --Upper limit wavelength in
                                --nanometers
            }
          }
          OPTIONAL
}

Tile-Index-Map-Subfield      --TIM
                               --Raster and Matrix Applications
      ::= SEQUENCE OF
        tsi     Integer-Number       --Tile Index Map Value

Compression-ID-Subfield      --CID
                               --Raster and Matrix Applications
      ::= SEQUENCE {
        com     [0] Integer-Number      --Compression Algorithm ID
        cpr     [1] Basic-Text-String,  OPTIONAL
                                --Compression Ratio
      }

Compression-Lookup-Table-Description --LTD
                               --Raster and Matrix Applications
      ::= SEQUENCE {
        lti     [0] Integer-Number,    --Compression Lookup ID
        nlr     [1] Integer-Number,    --Number of Compression Lookup
                                      --Table Rows
        nva     [2] Integer-Number,    --Number of Values per Compression
                                      --Lookup Table Row
        vlb     [3] Integer-Number,    OPTIONAL
                                      --Number of Bits per Values
      }

Compression-Lookup-Table-Values  --LTV
                               --Raster and Matrix Applications
      ::= SEQUENCE OF
        clv     Integer-Number       --Compression Lookup Table Value
```

```
Compression-Parameters          --CPM
                                --Raster and Matrix Applications
      ::= SEQUENCE OF
          SEQUENCE {
              cqi           Integer-Number,      --Compression Parameters ID
              cpv           Integer-Number      --Compression Parameter Value
          }
      }
```

Dependency conditions (list 2):

2-1 Encapsulation:

Must be present when the encapsulation is not homogeneous within the transmittal.

2-2 Data-Density-Subfield: see Pixel Ground Spacing

Raster and matrix data consist of arrays of information pertaining to pixels or points at regularly identified intervals. The dimension of these pixels or intervals must be transmitted. If the dimension of these intervals is based on cartographic coordinates or Cartesian coordinates (USR), the LOD, LAD and UNIloa subfields must be used. There is no default value for UNIloa.

2-3 Unit of measurement for Matrix Data:

Must be present when matrix values are actual values.

2-4 Pixel-Ground-Spacing-Field: see data density

Raster and matrix data consist of arrays of information pertaining to pixels or points at regularly identified intervals. The dimension of these pixels or intervals must be transmitted. If the dimension of these intervals is based on geographic coordinates (ASRP), the ARV and BRV subfields must be used.

2-5 Band-Description-Field:

The Band identification must be present for any raster or matrix data: counting the number of BID subfields is the only way to know the number of raster or matrix bands. WS1 and WS2 are mandatory in case of multi-banded raster data.

2-6 Tile-Index-Map-Field:

Mandatory if TIF = "Y".

2-7 Compression ID:

Mandatory if Geo data layer is compressed.

2-8 Compression Look Up Table:

Mandatory if the compression algorithm requires it.

2-9 Compression parameters:

Mandatory if the compression algorithm requires it.

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

B.5.2 Dataset-Description-Record

```
Dataset-Description-Record      --DSS
      ::= Dataset-Description

Dataset-Description           --DRF
      ::= SEQUENCE {
nsh          Integer-Number,      --number of horizontal accuracy
nsv          Integer-Number,      --sub-regions
nsp          Integer-Number,      --number of vertical accuracy sub-
                                --regions
noz          Integer-Number,      --number of position accuracy sub-
nos          Integer-Number,      --regions
                                --number of layers
}                                --number of source graphics
```

B.6 GEO-REFERENCE-FILE

```
Geo-Reference-File
|
|- R Geo-Reference-Record
  |
  |- Geo-Parameters-Field
  |- Projection-Field
  |- Registration-Points-Field
  |- Diagnostic-Points-Field
  |
|- R Grid Description
  |
  |-Grid Information
  |-General Information
  |-Dataset Parameters
  |-Band Identification
```

```
Geo-Reference-File
      ::= [A 2] SEQUENCE {
          [0] SEQUENCE OF
              Geo-Reference-Record,
          [1] SEQUENCE OF
              Dataset-Description-Record    OPTIONAL
                                          --Raster and Matrix data only
      }
```

B.6.1 Geo-Reference-Record

```
Geo-Reference-Record          --GEO
      ::= SEQUENCE {
gep          [0] Geo-Parameters-Field   --geographic reference info;
prr          [1] Projection-Field      OPTIONAL,
                                --projection information; see
                                --Dependency condition 3-3
rpr          [2] Registration-Points-Field
                                OPTIONAL,
dpr          [3] Diagnostic-Points-Field
                                OPTIONAL
  }
```

```

Geo-Parameters-Field                                --GEP
  ::= SEQUENCE  {
typ      [0] Basic-Text-String,          --Data Type
uni      [1] Basic-Text-String,          --Unit of measure for coordinates
        [2] Geodetic-Ellipsoid-Subfield,
        [3] Vertical-Datum-Subfield  OPTIONAL,
                                         --see Dependency condition 3-1
        [4] Sounding-Datum-Subfield OPTIONAL,
                                         --see Dependency condition 3-2
        [5] Geodetic-Datum-Subfield
        [6] Grid-System-Subfield
    }

Geodetic-Ellipsoid-Subfield
  ::= SEQUENCE  {
ell      Basic-Text-String,           --Ellipsoid name
elc      Basic-Text-String           --Ellipsoid code
    }

Vertical-Datum-Subfield
  ::= SEQUENCE  {
dvr      Basic-Text-String,           --Vertical Datum Reference
vdcdvrv Integer-Number             --Vertical Datum Code
    }

Sounding-Datum-Subfield
  ::= SEQUENCE  {
sda      Basic-Text-String,           --Sounding Datum Name
vdcsda  Integer-Number              --Sounding Datum Code
    }

Geodetic-Datum-Subfield
  ::= SEQUENCE  {
dag      Basic-Text-String,           --Geodetic Datum Name
dcd      Basic-Text-String           --Geodetic Datum Code
    }

Grid-System-Subfield
  ::= SEQUENCE  {
grd-c   Basic-Text-String,           --Geodetic Datum Name
grn-c   Basic-Text-String,           --Geodetic Datum Code
zna     Integer-Number              --Grid Zone number
    }

Projection-Field                                --PRR
  ::= SEQUENCE  {
prn      [0] Basic-Text-String,
pco      [1] Basic-Text-String,
paa      [2] Real-Number,
pab      [3] Real-Number,
        [4] Real-Number,
pae      [5] Real-Number,
        [6] Projection-False-Origin-Subfield OPTIONAL,
                                         --see Dependency condition 3-7
zor      [7] Real-Number             OPTIONAL,
                                         --Z-values false Origin
                                         --see Dependency condition 3-8
    }

```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

```
Projection-False-Origin-Subfield
    ::= SEQUENCE {
        xor          Real-Number,
        yor          Real-Number
    }
    --Easting false Origin
    --Northing false Origin

Registration-Points-Field
    ::= SEQUENCE OF
        SEQUENCE {
            pid-rp      [0] Basic-Text-String,
            lon-rp      [1] Fraction-Number ,
            lat-rp      [2] Fraction-Number ,
            zvl-rp      [3] Real-Number
            --Registration Point ID
            --Longitude / Easting of
            --Registration Point
            --Latitude / Northing of
            --Registration Point
            dix-rp      [4] Real-Number,
            diy-rp      [5] Real-Number,
            diz-rp      [6] Real-Number,
            --Optional,
            --Elevation of Registration Point;
            --see Dependency condition 3-9
            --Local X Coordinate of
            --Registration Point
            --Local Y Coordinate of
            --Registration Point
            OPTIONAL
            --Local Z Coordinate of
            --Registration Point;
            --see Dependency condition 3-9
            OPTIONAL
            --Located File Name
            --see Dependency condition 3-10
        }
    --RPR

Diagnostic-Points-Field
    ::= SEQUENCE OF
        SEQUENCE {
            dpd-dp      [0] Basic-Text-String,
            lon-dp      [1] Fraction-Number,
            lat-dp      [2] Fraction-Number,
            zvl-dp      [3] Real-Number
            --Diagnostic Point ID
            --Longitude / Easting of
            --Diagnostic
            --Point
            --Latitude / Northing of
            --Diagnostic
            --Point
            OPTIONAL,
            --Elevation of Diagnostic Point
            --see Dependency condition 3-11
            dix-dp      [4] Real-Number,
            diy-dp      [5] Real-Number,
            diz-dp      [6] Real-Number
            --Local X Coordinate of
            --Diagnostic Point
            --Local Y Coordinate of
            --Diagnostic Point
            OPTIONAL
            --Local Z Coordinate of
            --Diagnostic Point;
            --see Dependency condition 3-11
            bad-dp      [7] Basic-Text-String
            --Optional
            --Controlled File Name
            --see Dependency condition 3-12
        }
    --DPR

Grid-Description-Record
    ::= SEQUENCE {
        gri          Grid-Information-Field,
    }
    --GRD
    --Grid information;
```

B.6.2 Grid-Description-Record

```
Grid-Description-Record
    ::= SEQUENCE {
        gri          Grid-Information-Field,
    }
    --GRD
    --Grid information;
```

```

gen-g      Grid-General-Information-Field,
           --General grid information;
spr       Grid-Dataset-Parameters-Field,
           --Grid parameter information;
bdf       Band-ID-Field
           --Band identification
           --information;
}

Grid-Information-Field
 ::= SEQUENCE {
zvl          [0] Integer-Number,
bad-g        [1] Basic-Text-String
}

Grid-General-Information-Field
 ::= SEQUENCE {
lod-g        Real-Number,
lad-g        Real-Number,
lso          Real-Number,
pso          Real-Number,
}
           --GRI
           OPTIONAL,
           --Grid elevation
           --Located image filename
           --GEN-G
           --Data density in columns;
           --Data density in rows;
           --Origin in columns;
           --Origin in rows;

Grid-Dataset-Parameters-Field
 ::= SEQUENCE {
Location-Grid-Corners,
nfl-g        Integer-Number,
nfc-g        Integer-Number,
pcn-g        Integer-Number,
pn1-g        Integer-Number,
cod-g        Integer-Number,      {0|1}
rod-g        Integer-Number,     {0|1}
por-g        Integer-Number,     {0|1|4|5} --pixel order
pcb-g        Integer-Number,
pvb-g        Integer-Number,
pvt-g        Basic-Text-String {INT|SI|R},
bad-l        Basic-Text-String
}
           --SPR
           --used to compute the number of
           --rows and columns of the
           --location grid.
           --number of subblocks vertically
           --number of subblocks
           --horizontally
           --number of elements per profile
           --total number of grid elements
           --left to right
           --number of profiles per subblock
           --total number of grid elements
           --top to bottom
           --column sequence
           --row sequence
           --size of pixel count in bits
           --size of pixel value in bits
           --Type of Pixel / Element Value
           --Location Grid File Name
           -- (zzzzzzdd.Gcc)

Location-Grid-Corners
 ::= SEQUENCE {
nul-g        Integer-Number,
nus-g        Integer-Number,
nll-g        Integer-Number,
nls-g        Integer-Number,
}
           --Row number of the upper right
           --hand corner of Location Grid.
           --Column number of the upper
           --right hand corner of Location
           --Grid.
           --Row number of the lower left
           --hand corner of Location Grid.
           --Column number of the lower
           --left hand corner of Location
           --Grid.
}

```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

```
Band-ID-Field          --BDF
  ::= SEQUENCE OF
bid-g      Basic-Text-String {GGX|GGX|CGY|CGY}
                                         --Band Identification
```

Dependency conditions (list 3):**3-1 Vertical-Datum:**

Mandatory if elevation information is present in the dataset (z values).

3-2 Sounding-Datum-Subfield:

Mandatory if sounding information is present in the dataset (depth values).

3-3 Projection-Field:

The Projection-Field is mandatory when the coordinates type is MAP (cartographic coordinates) and forbidden otherwise.

3-4 Parameter 2:

see Part 3, Clause 6.

3-5 Parameter 3:

see Part 3, Clause 6.

3-6 Parameter 4:

see Part 3, Clause 6.

3-7 Projection False Origin:

only when relevant (usually the case).

3-8 Z Values False Origin:

only when relevant.

3-9 Elevation Registration Point:

Mandatory if z coordinates must be registered. In this case the Local coordinates will have a Z value.

3-10 Located File Name:

Mandatory if the Registration Point does not apply to the whole dataset.

3-11 Elevation Diagnostic Point:

Mandatory if z coordinates must be controlled. In this case the Local coordinates will have a Z value.

3-12 Controlled File Name:

Mandatory if the Diagnostic Point does not apply to the whole dataset.

B.7 SOURCE-FILE

```
Source-File
|
|- Source-Record
  |
  |- Source-Summary
  |- Source-Field
  |- Magnetic-Rate-Field
  |-R Bounding-Polygon-Coordinates-Field
  |- Projection-Field
  |- Security-and-Release-Field
  |- Inset-Field
  |- Copyright-Field
  |
  |-R Legend-Record
  |
  |- Legend-Field
  |- Legend-Parameters-Field
  |- Tile-Index-Map-Field
  |
  |-R Metric-Support-Record
  |
  |- Normalization-Constants-Field
  |- Source-Datum-Coefficients-Data-Field
  |- Map-Projections-Coefficients-Data-Field
  |- Datum-Change-Constants-Field
  |- Source-Datum-Coefficients-Counter-Field
  |- Source-Datum-Long.-Coefficients-Field
  |- Source-Datum-Lat.-Coefficients-Field
  |- Grid-Rotation-Coefficients-Field
  |
  |- Supplementary-Text-Record
  |
  |- Supplementary-Text-Field
  |
  |- Auxiliary-Parameters-Record
    |- Source-Summary
    |- R Bounding-Polygon-Coordinates
    |- Original-Scene-Band-ID
      |- Resolution-and-Ground-Sample-Distance
    |- Basic-Auxiliary-Parameters
    |- Additional-Auxiliary-Parameters
```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

```
Source-File
  ::= SEQUENCE {
sou      [A 3] Source-Record           OPTIONAL,
              --Source Graphic Description Only
leg      [A 4] SEQUENCE OF
          Legend-Record           OPTIONAL,
              --Source Graphic Description Only
msd      [A 5] Metric-Support-Record   OPTIONAL,
              --Source Graphic Description Only
spt      [A 6] Supplementary-Text-Record
          OPTIONAL
              --Source Graphic Description Only
aup      [A 7] Auxiliary-Parameters-Record
          OPTIONAL
              --Sensor Parameters Description
              --Only
    }
```

B.7.1 Source-Record

```
Source-Record  --SOU
  ::= SEQUENCE {
sgf      [0] Source-Summary-Field     OPTIONAL,
sor      [1] Source-Field,
mag      [2] Magnetic-Rate-Field      OPTIONAL,
rci      [3] SEQUENCE OF
          Bounding-Polygon-Coordinates-Field
          OPTIONAL,
              --Coordinates of the Source
              --Bounding Polygon;
              --see dependency condition 4-6
prr-s    [4] Projection-Field        OPTIONAL,
              --strongly recommended for Raster
qsr-s    [5] Security-and-Release-Field
          OPTIONAL,
              --strongly recommended
ins      [6] Inset-Field             OPTIONAL,
              --see dependency condition 4-11
cpy      [7] Copyright-Field         OPTIONAL
Source-Summary-Field  --SGF
  ::= SEQUENCE {
bad-s    [0] Basic-Text-String       OPTIONAL,
              --Name of derived layer; see
              --Dependency condition 4-1
nmi      [1] Integer-Number         OPTIONAL,
              --Number of magnetic information
              --Raster applications only
nst      [2] Integer-Number         OPTIONAL,
              --Number of supplementary text
              --records
nli      [3] Integer-Number         OPTIONAL,
              --Number of legend images; Raster
              --applications only
nin      [4] Integer-Number         OPTIONAL
              --Number of insets; Raster
              --applications only
  }
```

```

Source-Field      --SOR
      ::= SEQUENCE  {
prt-s          [0] Basic-Text-String
                OPTIONAL,
                --Series Designator for the
                --Series; strongly recommended
urf-s          [1] Basic-Text-String
edn-s          [2] Basic-Text-String
nam-s          [3] Basic-Text-String
                --Unique Source ID;
                --Source Edition Number;
                OPTIONAL
cdp-s          [4] Integer-Number
cdv-s          [5] Date
cdv27-s        [6] Date
                --Full name of source document;
                --strongly recommended
                --Type of significant date;
                --Significant date value;
                OPTIONAL
                --Perishable information date
                --value; strongly recommended

sca-s          [7] Integer-Number
                OPTIONAL,
                --Cartographic Scale; (grid system)
                --strongly recommended
[9] Carto-Grid-Subfield
                OPTIONAL,
                --Cartographic Grid Code
[10] Area-Coverage-Subfield
                OPTIONAL,
[11] Contour-Interval-Subfield
                OPTIONAL,
wpc            [12] Integer-Number
                OPTIONAL,
                --Percentage covered by water
nst-s          [13] Integer-Number
                OPTIONAL,
                --Navigational System Type
[14] Geodetic-Ellipsoid-Subfield
                OPTIONAL,
                --see Dependency condition 4-2
[15] Vertical-Datum-Subfield
                OPTIONAL,
                --see Dependency condition 4-3
[16] Sounding-Datum-Subfield
                OPTIONAL,
                --see Dependency condition 4-4
[17] Geodetic-Datum-Subfield
                OPTIONAL,
                --see Dependency condition 4-5
srn-s          [18] Basic-Text-String
                OPTIONAL,
                --Library / Source Reference Number
[19] Highest-Elevation-Subfield
                OPTIONAL
                --Raster applications only
}
Carto-Grid-Subfield
  ::= SEQUENCE  {
grd-s          Basic-Text-String,
grn-s          Basic-Text-String,
zna-s          Integer-Number
}
Area-Coverage-Subfield
  ::= SEQUENCE  {
squ            Integer-Number,
unisqu        Basic-Text-String
}
Contour-Interval-Subfield

```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

```

 ::= SEQUENCE {
 pci      Integer-Number,
 unipci   Basic-Text-String
}

--Geodetic-Ellipsoid-Subfield
--Vertical-Datum-Subfield
--Sounding-Datum-Subfield
--Geodetic-Datum-Subfield

Highest-Elevation-Subfield
 ::= SEQUENCE {
 hke      [0] Integer-Number,
 unihke   [1] Basic-Text-String,
 [2] Highest-Elevation-Point
}

Highest-Elevation-Point
 ::= SEQUENCE {
 lon-h    Fraction-Number,
 lat-h    Fraction-Number
}

```

Magnetic-Rate-Field

```

 ::= SEQUENCE OF
   SEQUENCE {
     cdp      [0] Integer-Number,
     cdv      [1] Date,
     rat      [2] Real-Number,
     unirat   [3] Basic-Text-String,
     gma      [4] Real-Number,
     unigma   [5] Basic-Text-String,
     [6] Magnetic-Rate-Reference-Point-Subfield
   OPTIONAL,
   --strongly recommended
   [7] Grid-Convergence-Subfield
   OPTIONAL
}

```

Magnetic-Rate-Reference-Point-Subfield

```

 ::= SEQUENCE {
 lon-m    Fraction-Number,
 lat-m    Fraction-Number
}

```

Grid-Convergence-Subfield

```

 ::= SEQUENCE {
 gca      Real-Number,
 unigca   Basic-Text-String
}

```

pci Integer-Number,
unipci Basic-Text-String
}
--Predominant Contour Interval
--Unit of Measure for Contour
--Interval
--Geodetic-Ellipsoid-Subfield
--Vertical-Datum-Subfield
--Sounding-Datum-Subfield
--Geodetic-Datum-Subfield
see Geo-Reference-Record
see Geo-Reference-Record
see Geo-Reference-Record
see Geo-Reference-Record
Highest known elevation of
--source
--Units of elevation value
OPTIONAL
--strongly recommended
}
--Longitude / Easting of HKE
--Latitude / Northing of HKE
--MAG
--Type of magnetic date rate
--Magnetic rate Date value
--Annual magnetic rate of change
--Units of annual rate of change
--Grid north-magnetic north
--Units of grid magnetic angle
OPTIONAL,
--strongly recommended
[7] Grid-Convergence-Subfield
OPTIONAL
}
--Longitude / Easting of the G-M
--angle reference point
--Latitude / Northing of the G-M
--angle reference point
--Grid convergence angle
--Units of grid convergence angle

```

Bounding-Polygon-Coordinates-Field      --RCI
  ::= SEQUENCE OF
    SEQUENCE {
      lon      Fraction-Number,
      lat      Fraction-Number
    }
--Projection-Field
--Security-and-Release-Field
Inset-Field
  ::= SEQUENCE OF
    SEQUENCE {
      int      Basic-Text-String,
      sca      Integer-Number,
      nam-i   Basic-Text-String,
      ntl      Fraction-Number,
      ttl      Fraction-Number,
      nvl      Fraction-Number,
      tvl      Fraction-Number,
      ntr      Fraction-Number,
      ttr      Fraction-Number,
      nvr      Fraction-Number,
      tvr      Fraction-Number,
      nrl      Fraction-Number,
      trl      Fraction-Number,
      nsl      Fraction-Number,
      tsl      Fraction-Number,
      nrr      Fraction-Number,
      trr      Fraction-Number,
      nsr-i   Fraction-Number,
      tsr      Fraction-Number
    }
--Copyright-Field
  cpz      ::= General-Text-String

```

--Unique ID of an Inset
 --Cartographic Scale of Inset
 --Name of Inset
 --Abs. lon. lower left corner
 --Abs. lat. lower left corner
 --Abs. lon. upper left corner
 --Abs. lat. upper left corner
 --Abs. lon. upper right corner
 --Abs. lat. upper right corner
 --Abs. lon. lower right corner
 --Abs. lat. lower right corner
 --Rel. lon. lower left corner
 --Rel. lat. lower left corner
 --Rel. lon. upper left corner
 --Rel. lat. upper left corner
 --Rel. lon. upper right corner
 --Rel. lat. upper right corner
 --Rel. lon. lower right corner
 --Rel. lat. lower right corner

--CPY
 --Copyright statement

B.7.2 Legend-Record

```

Legend-Record
  ::= SEQUENCE {
    lgi      [0] Legend-Field,
    spr-l   [1] Legend-Parameters-Field,
    tim-l   [2] Tile-Index-Map-Subfield
  }
--LEG
--Source Graphic Description Only
--Legend info captured for easier
--interpretation of source to
--which it relates
--Parameters to interpret Legend
--Image Data
--Info regarding empty subblocks;
--see Dependency condition 4-12

Legend-Field
  ::= SEQUENCE {
    nam-l   [0] Basic-Text-String
    str-l   [1] Integer-Number
  }
--LGI
--OPTIONAL,
--Legend name
--Structure class code

Legend-Parameters-Field
  spr-p   ::= Dataset-Parameters-Subfield
--SPR-L
--see General-Information-Record

--Dataset-Parameters-Field
--SPR

```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

```
--see General-Information-Record  
--Tile-Index-Map-Subfield  
--TIM  
--see General-Information-Record
```

B.7.3 Metric-Support-Data-Record

```
Metric-Support-Record          --MSD  
 ::= CHOICE {  
   [0] Arc-System-Metric-Support-Record,  
   [1] UTM / UPS-System-Metric-Support-Record  
 }
```

B.7.3.1 Arc-System-Metric-Support-Record

```
Arc-System-Metric-Support-Record  
 ::= SEQUENCE {  
 ncd      Normalization-Constants-Field,  
 sdc      Source-Datum-Coefficients-Data-Field,  
 mpc      Map-Projection-Coefficients-Field  
 }  
  
Normalization-Constants-Field      --NCD  
 ::= SEQUENCE {  
 tsf      [0] Real-Number,           --Latitude Scale Factor  
 gsf      [1] Real-Number,           --Longitude Scale Factor  
 ttt      [2] Real-Number,           --Latitude Translation Term  
 gtt      [3] Real-Number,           --Longitude Translation Term  
 nsf      [4] Real-Number,           --Northing Scale Factor  
 esf      [5] Real-Number,           --Easting Scale Factor  
 ntt      [6] Real-Number,           --Northing Translation Term  
 ett      [7] Real-Number,           --Easting Translation Term  
 }  
  
Source-Datum-Coefficients-Field    --SDC  
 ::= SEQUENCE {  
 ax1      [0] Real-Number,           --Latitude coefficient 1  
 ax2      [1] Real-Number,           --Latitude coefficient 2  
 ax3      [2] Real-Number,           --Latitude coefficient 3  
 ax4      [3] Real-Number,           --Latitude coefficient 4  
 ax5      [4] Real-Number,           --Latitude coefficient 5  
 ax6      [5] Real-Number,           --Latitude coefficient 6  
 ax7      [6] Real-Number,           --Latitude coefficient 7  
 bx1      [7] Real-Number,           --Longitude coefficient 1  
 bx2      [8] Real-Number,           --Longitude coefficient 2  
 bx3      [9] Real-Number,           --Longitude coefficient 3  
 bx4      [10] Real-Number,          --Longitude coefficient 4  
 bx5     [11] Real-Number,          --Longitude coefficient 5  
 bx6     [12] Real-Number,          --Longitude coefficient 6  
 bx7     [13] Real-Number,          --Longitude coefficient 7  
 }  
Map-Projection-Coefficients-Field  --MPC  
 ::= SEQUENCE {  
 cx1      [0] Real-Number,           --Northing coefficient 1  
 cx2      [1] Real-Number,           --Northing coefficient 2  
 cx3      [2] Real-Number,           --Northing coefficient 3  
 cx4      [3] Real-Number,           --Northing coefficient 4  
 cx5      [4] Real-Number,           --Northing coefficient 5  
 cx6      [5] Real-Number,           --Northing coefficient 6  
 cx7      [6] Real-Number,           --Northing coefficient 7  
 cx8      [7] Real-Number,           --Northing coefficient 8  
 cx9      [8] Real-Number,           --Northing coefficient 9  
 cxA     [9] Real-Number,           --Northing coefficient 10  
 dx1     [10] Real-Number,          --Easting coefficient 1  
 dx2     [11] Real-Number,          --Easting coefficient 2
```

```

dx3      [12] Real-Number,          --Easting coefficient 3
dx4      [13] Real-Number,          --Easting coefficient 4
dx5      [14] Real-Number,          --Easting coefficient 5
dx6      [15] Real-Number,          --Easting coefficient 6
dx7      [16] Real-Number,          --Easting coefficient 7
dx8      [17] Real-Number,          --Easting coefficient 8
dx9      [18] Real-Number,          --Easting coefficient 9
dxA      [19] Real-Number          --Easting coefficient 10
}

```

B.7.3.2 UTM / UPS-System-Metric-Support-Record

```

UTM / UPS-System-Metric-Support-Record
 ::= SEQUENCE {
  dcc      [0] Datum-Change-Constants-Field,
  scc      [1] Source-Datum-Coefficients-Counter-Field,
  slg      [2] Source-Datum-Longitude-Coefficients-Field,
 slt      [3] Source-Datum-Latitude-Coefficients-Field,
  grc      [4] Grid-Rotation-Coefficients-Field   OPTIONAL
}

Datum-Change-Constants-Field           --DCC
                                         --(Note: Units for all datum change
                                         --constants are in degrees and
                                         --decimal part of a degree.)
 ::= SEQUENCE {
  tof      Real-Number,          --Latitude normalizing offset
  gof      Real-Number,          --Longitude normalizing offset
  nzt      Real-Number,          --Normalizing factor
  elv      Real-Number,          --Eastern limit of validity to use
                                --multiple regression equations
  wlv      Real-Number,          --Western limit of validity to use
                                --multiple regression equations
  nlv      Real-Number,          --Northern limit of validity to use
                                --multiple regression equations
  slv      Real-Number          --Southern limit of validity to use
                                --multiple regression equations
}

Source-Datum-Coefficients-Counter-Field    --SCC
 ::= SEQUENCE {
  bct      Integer-Number,       --Number of longitude coefficients
  act      Integer-Number        --Number of latitude coefficients
}

Source-Datum-Longitude-Coefficients-Field    --SLG
 ::= SEQUENCE OF
   SEQUENCE {
  cbi      Integer-Number,       --i index of the coefficient of MRE b[i,j]
  cbj      Integer-Number,       --j index of the coefficient of MRE b[i,j]
  lgc      Real-Number          --Coefficient of MRE b[i,j] ( b[i,j]
                                --coefficients are ordered with respect
                                --to increasing i then j )
}

Source-Datum-Latitude-Coefficients-Field    --SLT
 ::= SEQUENCE OF
   SEQUENCE {
  cai      Integer-Number,       --i index of the coefficient of MRE a[i,j]
  caj      Integer-Number,       --j index of the coefficient of MRE a[i,j]
}

```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

```
ltc          Real-Number      --Coefficient of MRE a[i,j] ( a[i,j]
                                --coefficients are ordered with respect
                                --to increasing i then j )
}

Grid-Rotation-Coefficients-Field      --GRC
 ::= SEQUENCE {  
    nes        Real-Number,      --Normalized Eastings Shift
    nns        Real-Number,      --Normalized Northings Shift
    aor        Real-Number      --Angle of orientation from source
                                positive if clockwise
                                --datum grid to WGS84 UTM grid
}
```

B.7.4 Supplementary-Text-Record

```
Supplementary-Text-Record           --Source Graphic Description Only
sup        ::= Supplementary-Text-Field      --SPT

Supplementary-Text-Field            --SUP
 ::= SEQUENCE OF
    SEQUENCE {
        try      [0] Basic-Text-String,      --Supplementary text record type
        tri      [1] Basic-Text-String      --OPTIONAL,
                                --Supplementary text field
                                --reference identifier
        txt      [2] General-Text-String     --Supplementary text
    }
```

B.7.5 Auxiliary-Parameters-Record

```
Auxiliary-Parameters-Record          --Sensor Parameters Description Only
 ::= SEQUENCE {  
    sgf      [0] Source-Summary,      --AUP
    rci-a    [1] Bounding-Polygon-Coordinates OPTIONAL,
                                --see Dependency Condition 4-6
    bdf      [2] Original-Scene-Band-ID,
    rsd      [3] Resolution-and-Ground-Sample-Distance,
    bap      [4] Basic-Auxiliary-Parameters,
    aap      [5] Additional-Auxiliary-Parameters
}

Source-Summary                   --SGF
 ::= SEQUENCE OF
bad-x      Basic-Text-String      --see Dependency Condition 4-1
                                --Name of Derived Layer

Bounding-Polygon-Coordinates-Field  --RCI
                                         --see Source Record
Original-Scene-Band-ID            --BDF
 ::= SEQUENCE OF
    SEQUENCE {
        bid-f    Basic-Text-String,      --Orig-Scene-Band-Identification
        SEQUENCE {
            ws1      Integer-Number,    --Signal Lower Limit
            ws2      Integer-Number,    --Signal Upper Limit,
        }
    }
```

```

Resolution-and-Ground-Sample-Distance --RSD
 ::= SEQUENCE {
rex      Real-Number,          --Resolution at Source E-W Direction
rey      Real-Number,          --Resolution at Source N-S Direction
gsx      Real-Number          --Ground Sample Distance at Source E-W
gsy      Real-Number,          --Ground Sample Distance at Source N-S
gsl      Real-Number,          --Ground Sample Distance Measurement
unires   Real-Number          --Location
}                                         --Unit of Resolution measurement

Basic-Auxiliary-Parameters           --BAP
 ::= SEQUENCE {
vec      [0] Basic-Text-String,    --Vector or Mission name
sns      [1] Basic-Text-String,    --Sensor or Instrument Name
mod      [2] General-Text-String,  --Spectral Mode
prl      [3] Basic-Text-String,    --Processing Level
cdv07   [4] Basic-Text-String,    --Acquisition Date
atm      [5] General-Text-String, --Acquisition Time
[6] Incidence-Angle-Subfield OPTIONAL,
[7] Altitude-Subfield        OPTIONAL,
[8] Scene-Coord              OPTIONAL,
[9] Solar-Angle               --Coordinates of the Original
[10] Attitude-Angle            --Scene Centre
[11] Pixel-Time                --Solar Angles at the Original
[12] Attitude-Speed             --Scene Centre
[13] Attitude-Subfield          --Attitude Angles at the Original
[14] Attitude-Subfield          --Scene Centre in the Local
[15] Attitude-Subfield          --Orbital Reference
[16] Attitude-Subfield          --Start Time of Acquisition
[17] Attitude-Subfield          --Altitude Speed at the Original
[18] Attitude-Subfield          --Scene Centre in the Local
[19] Attitude-Subfield          --Orbital Reference
}

Incidence-Angle-Subfield
 ::= SEQUENCE {
ang      Real-Number,          --Incidence Angle
uniang   Real-Number          --Unit of Incidence Angle
}

Altitude-Subfield
 ::= SEQUENCE {
ant      Real-Number,          --Altitude
unialt   Basic-Text-String,    --Unit of Altitude
}

Scene-Coord
 ::= SEQUENCE {
lon-sc   Real-Number,          --Longitude
lat-sc   Real-Number          --Latitude
}

Solar-Angle
 ::= SEQUENCE {
saz      Real-Number,          --Solar Azimuth
sel      Real-Number,          --Solar Elevation
unisae  Basic-Text-String,    --Unit of Solar Angles
}

```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

```

Attitude-Angle
  ::= SEQUENCE {
rol          Real-Number,           --Roll
pit          Real-Number,           --Pitch
yaw          Real-Number,           --Yaw
unirpy      Basic-Text-String    --Unit of Attitude Angles
}

Pixel-Time
  ::= SEQUENCE {
pxt          Basic-Text-String,   --Pixel Time
unipxt      Basic-Text-String    --Unit of Pixel-Time
}

Attitude-Speed
  ::= SEQUENCE {
ros          Real-Number,           --Roll Speed
pis          Real-Number,           --Pitch Speed
yas          Real-Number,           --Yaw Speed
unispe      Basic-Text-String    --Unit of Attitude-Speed
}

Additional-Auxiliary-Parameters           --AAP
 ::= SEQUENCE OF
  SEQUENCE {
api          [0] Basic-Text-String, --Auxiliary Parameter ID
uniapx      [1] Basic-Text-String --OPTIONAL,
                         --Unit of Auxiliary Parameters
                         -- see Dependency Condition

apf          [2] CHOICE {
  apn          [0] Integer-Number --Auxiliary Par Integer Value
  apr          [1] Real-Number,    --Auxiliary Par Real Value
  apa          [2] Basic-Text-String --Auxiliary Par Character
                                --String Value
                                -- Note: Type of Parameter
                                -- is encoded implicitly in
                                -- ISO 8825 encapsulation
}
}

```

Dependency conditions (list 4):**4-1 Name of derived layer:**

Name of the derived layer will be transmitted whenever the source described in the source record does not apply to all layers in the dataset.

4-2 Ellipsoid:

Mandatory if the Projection-Field is transmitted.

4-3 Vertical Datum:

Strongly recommended if elevation information is present on the source (e.g. contour lines on a raster map). Forbidden if no elevation information is present on the source.

4-4 Sounding Datum:

Mandatory if sounding information is present in the source (depth values or sounding information on a raster map). Forbidden if no sounding information is present on the source.

4-5 Geodetic Datum:

Mandatory if the Projection-Field is transmitted.

4-6 Bounding Polygon:

Mandatory when the source information is not valid for the whole dataset extension.

4-7 Parameter 2: see part 3 clause 6

4-8 Parameter 3: see part 3 clause 6

4-9 Parameter 4: see part 3 clause 6

4-10 Projection False origin:

when relevant only (usually the case).

4-11 Inset:

mandatory when relevant only.

4-12 Tile-Index-Map:

mandatory if TIF = "Y".

4-13 Unit of Auxillary Parameter:

mandatory for Integer or Real parameters.

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

B.8 QUALITY-FILE

```
Quality-File
|
|- Quality-Record
|
|- Security-and-Release-Field
|- Quality-Up-To-Dateness-Field
|- Other-Quality-Information-Field
|
|-R Vector-Quality-Section
    |- Completeness-and-Consistency-Field
    |- Attribute-Accuracy-Field
|
|-R Raster-Quality-Section
    |- Color-Patch-Description-Field
    |- Color-Code-ID-Field
|
|-R Matrix-Quality-Section
    |- Nominal-Code-ID-Field
|
|- Accuracy-Record
    |- Positional-Accuracy-Field
    |-R Bounding-Polygon-Coordinates-Field
|
|- Component-Accuracies
    |- Horizontal-Accuracies-Record
    |- Vertical-Accuracies-Record
```

```
Quality-File
      ::= SEQUENCE {
          SEQUENCE OF
qal           [A 8] Quality-Record,
          SEQUENCE OF
              [A 9] CHOICE {           --see Dependency condition 5-6
qai                  [0] Accuracy-Record
                                OPTIONAL,
car                  [1] Component-Accuracies-Record
                                OPTIONAL
              }
      }
```

B.8.1 Quality-Record

```
Quality-Record          --QAL
      ::= SEQUENCE {
qsr-q        [0] Security-and-Release-Field,
                    --Security classification,
                    --handling, and release info.
                    --see Security-and-Update-Record
quv-q        [1] Quality-Up-To-Dateness-Field
                    OPTIONAL,
                    --describes currency of Geo Data
                    --Subset
qoi         [2] Other-Quality-Information-Field
                    OPTIONAL,
                    --Free text
```

```

[ 3 ] CHOICE      {
    [0] Vector-Quality-Section,
    [1] Raster-Quality-Section,
    [2] Matrix-Quality-Section
}
}

Vector-Quality-Section
 ::= SEQUENCE  {
qcc-v      [0] Completeness-and-Consistency-Field
                OPTIONAL,
qaa-v      [1] Attribute-Accuracy-Field
                OPTIONAL
}

Raster-Quality-Section
 ::= SEQUENCE  {
    [0] Color-Patch-Description-Field
                OPTIONAL,
col        [1] Color-Code-ID-Field      OPTIONAL,
                --see Dependency condition 5-5
}

Matrix-Quality-Section          --NOM-M
 ::= Nominal-Code-ID-Field

Completeness-and-Consistency-Field --QCC
 ::= SEQUENCE OF
    SEQUENCE  {
bad-c      [0] Basic-Text-String
                OPTIONAL,
                --Layer name; see Dependency
                --condition 5-1
qfc       [1] Integer-Number
                OPTIONAL,
                --Feature Completeness percent
qac       [2] Integer-Number
                OPTIONAL,
                --Attribute Completeness percent
qlc       [3] Basic-Text-String
                OPTIONAL
                --Logical Consistency
}

Quality-Up-to-Dateness-Field      --QUQ
 ::= SEQUENCE  {
edn-u      [0] Integer-Number,
cdv07-u    [1] Date,
cdv24      [2] Date,
rec-u      [3] Integer-Number
                OPTIONAL,
                --Recompilation count
rev-u      [4] Integer-Number
                OPTIONAL,
                --Revision count
src-u      [5] Basic-Text-String,
cdv22-u    [6] Date
                OPTIONAL,
                --Specification date value; see
                --Dependency condition 5-2
spa-u      [7] Basic-Text-String
                OPTIONAL,
                --Specification amendment; see
cdv20      [8] Date
                OPTIONAL,
                --Earliest source date value
cdv21      [9] Date
                OPTIONAL
                --Latest source date value
}
}

```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

```
Attribute-Accuracy-Field          --QAA
    ::= SEQUENCE OF
        SEQUENCE {
            bad-a   [0] Basic-Text-String
                OPTIONAL,
                --Layer name; see Dependency
                --condition 5-3
            qut      [1] Integer-Number
                OPTIONAL,
                --Standard Deviation of
                --Quantitative Attributes
            qul      [2] Integer-Number
                OPTIONAL,
                --Percent Reliability of
                --Qualitative Attributes
            ccr      [3] Basic-Text-String
                OPTIONAL,
                --Collection Criteria
        }

Color-Patch-Description-Field
    ::= SEQUENCE {
        cpt      [0] Color-Patch-Type-Subfield,
        cpi      [1] Color-Patch-ID-Subfield  OPTIONAL,
        spr-c    [2] Dataset-Parameters-Subfield
                OPTIONAL
                    --see Dependency condition 5-4
                    --see General-Information-Record
    }

Color-Patch-Type-Subfield
scr      ::= Basic-Text-String          --CPT
                --Standard color patch reference

Color-Patch-ID-Subfield
    ::= SEQUENCE OF
        SEQUENCE {
            pnm      Basic-Text-String,
            pir      Integer-Number,
            pig      Integer-Number,
            pib      Integer-Number
        }Color-Code-ID-Field
            ::= SEQUENCE OF
                SEQUENCE {
                    cbd      [0] Basic-Text-String,
                        --Name and / or Description of
                        --Color
                        --Code
                        --Color Code Assigned in Dataset
                        --(0-255)
                    ccd      [1] Integer-Number,
                        [2] CIE-Color-Description-Subfield
                            OPTIONAL,
                        [3] RGB-Color-Description-Subfield
                            OPTIONAL,
                }
                --COL

CIE-Color-Description-Subfield
    ::= SEQUENCE {
        [0] SEQUENCE {
            cr1      Integer-Number,    --CIEx
            cr2      Integer-Number,    --CIEy
            cr3      Integer-Number    --CIE Reflectivity (y)
        }
        frm      [1] Basic-Text-String
                OPTIONAL,
                --mathematical relation to other
                --colour codes (free text)
                --see part 2 sec. 10.4
    }
```

```

RGB-Color-Description-Subfield
 ::= SEQUENCE {
   [0] SEQUENCE {
     nsr      Integer-Number,          --Color Intensity - Red
                                         -- actual (0-255)
     nsg      Integer-Number,          --Color Intensity - Green
                                         -- actual (0-255)
     nsb      Integer-Number          --Color Intensity - Blue
                                         -- actual (0-255)
   }
   bad-rg   [1] Basic-Text-String    OPTIONAL,
                                         --Layer name
 }

Nominal-Code-ID-Field           --NOM
 ::= SEQUENCE OF
   SEQUENCE {
     nci      Basic-Text-String,       --Code Identifier
     nbd      Basic-Text-String,       --Description / meaning of code
     ncd-n   Integer-Number,          --Nominal code assigned in dataset
     bad-rg   Basic-Text-String      OPTIONAL,
                                         --Layer name
   }
 }

Other-Quality-Information-Field --QOI
 oqi      ::= General-Text-String --Free Text

```

B.8.2 Accuracy-Record

```

Accuracy-Record                  --QAI
 ::= SEQUENCE OF
   SEQUENCE {
     qap      [0] Positional-Accuracy-Field, --Positional accuracy of the
                                         --dataset file
                                         [1] SEQUENCE OF
     rci-a   Bounding-Polygon-Coordinates-Field
                                         OPTIONAL
                                         --Coordinates of the polygon
                                         --delineating the accuracy
                                         --region; see Dependency
                                         --condition 5-8
   }
 }

Positional-Accuracy-Field        --QAP
 ::= SEQUENCE {
   aah-p    [0] Integer-Number,          --Accuracy Absolute Horizontal
   uniaah  [1] Integer-Number,          --Unit of measure
   aav      [2] Integer-Number,          --Accuracy Absolute Vertical
   uniaav  [3] Integer-Number,          --Unit of measure
   aph     [4] Integer-Number,          --Accuracy Point to Point Horizontal
   uniaph  [5] Integer-Number,          --Unit of measure
   apv     [6] Integer-Number,          --Accuracy Point to Point Vertical
   uniapv  [7] Integer-Number,          --Unit of measure
   bad-p   [8] Basic-Text-String      OPTIONAL
                                         --Layer name; see Dependency
                                         --condition 5-7
 }
```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

```
--Bounding-Polygon-Coordinates-Field      RCI
                                         --see Source-Record
```

B.8.3 Component-Accuracies-Record

```
Component-Accuracies-Record          --CAR
  ::= SEQUENCE {
    Horizontal-Accuracies-Record OPTIONAL,
      --see Dependency Condition 5-6
    Vertical-Accuracies-Record   OPTIONAL
      --see Dependency Condition 5-6
  }
```

B.8.3.1 Horizontal-Accuracies-Record

```
Horizontal-Accuracies-Record        --HOR
  := SEQUENCE OF
    SEQUENCE {
      ash      [0] Horizontal-Accuracies-Field,
      rci-h    [1] SEQUENCE OF
                Bounding-Polygon-Coordinates-Field
                  OPTIONAL
                  --see Dependency condition 5-8
    }
```

```
Horizontal-Accuracies-Field        --ASH
  ::= SEQUENCE {
    aah-h    [0] Integer-Number,           --Absolute Horizontal Accuracy
    uniaah-h [1] Integer-Number,          --Unit of measure
    aph-h    [2] Integer-Number,           --Relative Horizontal Accuracy
    uniaph-h [3] Integer-Number,          --Unit of measure
    bad-h    [4] Basic-Text-String        OPTIONAL
                                              --Layer name; see Dependency
                                              --condition 5-7
  }
```

```
--Bounding-Polygon-Coordinates-Field      RCI
                                         --see Source-Record
```

B.8.3.2 Vertical-Accuracies-Record

```
Vertical-Accuracies-Record         --VER
  := SEQUENCE OF
    SEQUENCE {
      asv      [0] Aertical-Accuracies-Field,
      rci-h    [1] SEQUENCE OF
                Bounding-Polygon-Coordinates-Field
                  OPTIONAL
                  --see Dependency condition 5-8
    }
```

```
Vertical-Accuracies-Field         --ASV
  ::= SEQUENCE {
    aav-v    [0] Integer-Number,           --Absolute Vertical Accuracy
    uniaav-v [1] Integer-Number,          --Unit of measure
    apv-v    [2] Integer-Number,           --Relative Vertical Accuracy
    uniapv-v [3] Integer-Number,          --Unit of measure
    bad-v    [4] Basic-Text-String        OPTIONAL
                                              --Layer name; see Dependency
                                              --condition 5-7
  }
```

--Bounding-Polygon-Coordinates-Field RCI
 --see Source-Record

Dependency conditions (list 5):

5-1 Name of layer:

The name of the layer will be transmitted whenever the completeness and consistency information does not apply to all layers in the dataset.

5-2 Revision date:

If relevant only.

5-3 Name of layer:

The name of the layer will be transmitted whenever the completeness and consistency information does not apply to all layers in the dataset.

5-4 Color patch dataset parameters:

The color patch dataset parameters will be transmitted if the color patch image file exists.

5-5 Color coded:

Must be defined when raster color-coded data is transmitted (STR = 2). Forbidden otherwise.

5-6 Accuracy record:

Must be used when both horizontal and vertical accuracy are known and homogeneous on the same area. If it is absent then both horizontal and vertical accuracy records must be present.

5-7 Name of layer:

The name of the layer will be transmitted whenever the completeness and consistency information does not apply to all layers in the dataset.

5-8 Bounding polygon:

Mandatory when the source information is not valid for the whole dataset extent.

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

B.9 VECTOR-GEO-DATA-FILE

```
Vector-Geo-Data-File
|
|-R Edge-Record
    |- Edge-Implicit-Relation-Pointers-Field
    |- Implicit-Relations-Pointer-Field
    |- Implicit-Attributes-Field
    |- Explicit-Attribute-Labels-and-Values-Field
    |- Coordinates-Field
|
|-R Node-Record
    |- Node-Implicit-Relation-Pointer-Field
    |- Implicit-Relations-Pointer-Field
    |- Explicit-Attribute-Labels-and-Values-Field
    |- Coordinates-Field
|
|-R Face-Record
    |- Implicit-Relations-Pointer-Field
    |- Implicit-Attributes-Field
    |- Explicit-Attribute-Labels-and-Values-Field
|
|-R Spatial-Data-Record
    |- Implicit-Relations-Pointer-Field
    |- Implicit-Attributes-Field
    |- Explicit-Attribute-Labels-and-Values-Field
    |- Coordinates / elevation-Field
|
|-R Feature-Record
    |- Implicit-Relation-Pointer-Field
    |- Feature-Implicit-Attributes-Field
    |- Feature-Explicit-Attribute-Labels-and-Values-Field
        |-R - Explicit-Relation-Pointer-Field
        |-R - Explicit-Relation-Value-Field
|
|-R Text-Placement-Record
    |- Implicit-Relations-Pointers-Field
    |- Explicit-Attribute-Labels-and-Values-Field
    |- Text-Field
    |- Coordinates-Field
|
|-R Feature / Attribute-Entry-Record
    |- Feature-Attribute-Entry-Field
|
|-R Feature / Attribute-Association-Record
    |- Feature-Association-Field
    |- Attribute-Association-Field
|
|-R Attribute / Value-Association-Record
    |- Attribute-Format-Description-Field
    |- Attribute-Value-Description-Field
```

```

Vector-Geo-Data-File
  := SEQUENCE {
    [0] SEQUENCE OF
      ed           Edge-Record
                                OPTIONAL,
                                --see Dependency condition 6-1
    [1] SEQUENCE OF
      no           Node-Record
                                OPTIONAL,
                                --see Dependency condition 6-4
    [2] SEQUENCE OF
      fe           Face-Record
                                OPTIONAL,
                                --for Level 3 topology only;
                                --Levels 0-2: not included
    [3] SEQUENCE OF
      sp           Spatial-Data-Record
                                OPTIONAL,
                                --Optional for Level 0 topology;
                                --see Dependency condition 6-3;
                                --Levels 1-3: not included
    [4] SEQUENCE OF
      tp           Feature-Record,
    [5] SEQUENCE OF
      dd           Text-Placement-Record
                                OPTIONAL,
    [6] SEQUENCE OF
      df           Feature / Attribute-Entry-Record
                                OPTIONAL,
                                --see Dependency condition 6-10
    [7] SEQUENCE OF
      da           Feature / Attribute-Association-Record
                                OPTIONAL,
    [8] SEQUENCE OF
      da           Attribute / Value-Association-Record
                                OPTIONAL
                                --see Dependency condition 6-11
  }
}

```

B.9.1 Edge-Record

```

Edge-Record                                     --ED
  ::= [A 10] SEQUENCE {
    [0] Record-ID-Number,
    ire-e   [1] Edge-Implicit-Relation-Pointers-Field
                                OPTIONAL,
                                --Mandatory for Level 3 topology,
                                --Levels 1 and 2: Optional Level
                                --0: not included
    irs-e   [2] Implicit-Relations-Pointer-Field
                                OPTIONAL,
                                --Optional for all levels of
                                --topology
    iat-e   [3] Implicit-Attributes-Field
                                OPTIONAL,
                                --Optional for all levels of
                                --topology
    att-e   [4] Explicit-Attribute-Labels-and-Values-Field
                                OPTIONAL,
                                --Optional for all levels of
                                --topology
    cor-e   [5] Edge-Coordinates-Field
                                OPTIONAL
                                --Mandatory for all levels of
                                --topology
  }
}

```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

```

Record-ID-Number
 ::= Integer-Number                                --Unique ID number of the record

Edge-Implicit-Relation-Pointers-Field    --IRE
 ::= SEQUENCE {
   [0] Face-Topology-Subfield      OPTIONAL,
                                             --Level 3 topology : Mandatory;
                                             --Levels 0-2: not included
   [1] Edge-Node-Topology-Subfield  OPTIONAL,
                                             --Level 3 topology: Mandatory ;
                                             --Levels 1 and 2: Optional;
                                             --Level 0: Not included
   [2] Winged-Edge-Topology-Subfield OPTIONAL
                                             --Levels 1, 2, and 3 topology:
                                             --Optional,
                                             --Level 0: Not included
 }

Face-Topology-Subfield
 ::= SEQUENCE {
   fal      Integer-Number,                      --Left-Face-Pointer
   far      Integer-Number,                      --Right-Face-Pointer
 }

Edge-Node-Topology-Subfield
 ::= SEQUENCE {
   nos-e    Integer-Number,                      -- Start-Node-Pointer,
   noe-e    Integer-Number,                      -- End-Node-Pointer
 }

Winged-Edge-Topology-Subfield
 ::= SEQUENCE {
   ner      Integer-Number,                      --Pointer-to-Next-Right-Edge,
   nel      Integer-Number,                      --Pointer-to-Previous-Left-Edge
 }

-- Note: In DIGEST B pointer information is considered to be
-- Unclassified. Only DIGEST A provides the capability of defining
-- Security at the pointer field level.

Implicit-Relations-Pointer-Field    --IRS
 ::= SEQUENCE OF
   rid-COS    Integer-Number,                  --Optional reverse pointer back to
                                             --Line feature or Area feature
                                             --(Level 2, 1 or 0) for Edges, and
                                             --back to Point feature for Nodes
                                             --Record ID; Mandatory for all
                                             --levels of topology

Implicit-Attributes-Field          --IAT
 ::= SEQUENCE {
   mie      [0] Fraction-Number,                --Minimum Easting / Longitude
                                             --Value
                                             --of the MBR; mandatory for all
                                             --levels of topology
   min      [1] Fraction-Number,                --Minimum Northing / Latitude
                                             --Value
                                             --of the MBR; mandatory for all
                                             --levels of topology
 }

```

```

zwi      [ 2 ] Fraction-Number
                    OPTIONAL,
                    --Minimum Elevation Value of the
                    --MBR; see Dependency condition
                    -- 6-2, 6-6, 6-7
mae      [ 3 ] Fraction-Number,
                    --Maximum Easting / Longitude
                    --Value
                    --of the MBR; mandatory for all
                    --levels of topology
man      [ 4 ] Fraction-Number,
                    --Maximum Northing / Latitude
                    --Value
                    --of the MBR;
                    --mandatory for all levels of
                    --topology
OPTIONAL
                    --Maximum Elevation Value of the
                    --MBR; see Dependency condition
                    -- 6-2, 6-6, 6-7
zv2      [ 5 ] Fraction-Number
}

Explicit-Attribute-Labels-and-Values-Field
--ATT
 ::= SEQUENCE OF
      SEQUENCE {
        atc      Basic-Text-String,           --Attribute label; Mandatory for
                                            --all levels of topology
        val      CHOICE {                  --Attribute Value; consistent with
                                            --value of for subfield;
                                            --Mandatory for all levels of
                                            --topology. The value format can
                                            --be determined from the choice.
          [ 0 ] Basic-Text-String,
          [ 1 ] Integer-Number,
          [ 2 ] Real-Number
        }
      }

```

```

Edge-Coordinates-Field           --COR-E
 ::= CHOICE {
    [ 0 ] Abs-Coordinate-String,
    [ 1 ] Rel-Coordinate-String,
    [ 2 ] Dif-Coordinate-String
}                                     --see Dependency condition 6-6.

```

B.9.2 Node-Record

```

Node-Record                   --NO
 ::= [A 11] SEQUENCE {
   [ 0 ] Record-ID-Number,
   irn      [ 1 ] Node-Implicit-Relation-Pointer-Field
             OPTIONAL,
             --Level 3 topology: Mandatory ;
             --Levels 0-2: Not included
   irs-n     [ 2 ] Implicit-Relations-Pointer-Field
             OPTIONAL,
             --Optional for all levels of
             --topology
   att-n     [ 3 ] Explicit-Attribute-Labels-and-Values-Field
             OPTIONAL,
             --Optional for all levels of
             --topology
   cor-n     [ 4 ] Coordinate-Field       --Mandatory for all levels of
                                         --topology
}

```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

```
--Record-ID-Number           --see Edge-Record
Node-Implicit-Relation-Pointer-Field   --IRN
  ::= Integer-Number
    OPTIONAL,
      --Containment pointer, only for
      --isolated nodes. see Dependency
      --condition 6-5
}

--Implicit-Relations-Pointer-Field     --IRS
--Optional reverse pointer back
--to point feature; --see
--Edge-Record

--Explicit-Attribute-Labels-and-Values-Field --ATT
--see Edge-Record

Coordinate-Field                      --COR
  ::= SEQUENCE OF
    SEQUENCE {
      lon-f      [0] Fraction-Number,      --Longitude / Easting
      lat-f      [1] Fraction-Number,      --Latitude / Northing
      ele-f      [2] Real-Number         OPTIONAL
                                         --Elevation
    }
}
```

B.9.3 Face-Record

```
Face-Record                         --FE
                                      --for Level 3 topology only
  ::= [A 12] SEQUENCE {
    [0] Record-ID-Number,
    irs-r      [1] Implicit-Relations-Pointer-Field
                OPTIONAL,
    iat-r      [2] Implicit-Attributes-Field
                OPTIONAL,
    att-r      [3] Explicit-Attribute-Labels-and-Values-Field
                OPTIONAL
  }
--Record-ID-Number                   --see Edge-Record

--Implicit-Relations-Pointer-Field   IRS
                                      --see Edge-Record

--Explicit-Attributes-Labels-and-Values-Field
  ATT
  --see Edge-Record
--Implicit-Attributes-Field          IAT
  --see Edge-Record
```

B.9.4 Feature-Record

```
Feature-Record
  --FL for line feature, FP for
  --point feature, FA for area
  --feature, FC for complex feature;
  --for all levels of topology
```

```

 ::= [A 13] SEQUENCE {
   [0] Record-ID-Number,
   irs-f   [1] Feature-Implicit-Relations-Pointer-Field,
   iat-f   [2] Feature-Implicit-Attributes-Field,
   att-fe  [3] Feature-Explicit-Attribute-Labels-and-Values-Field
             OPTIONAL,
   [4] SEQUENCE OF
   r1l      Explicit-Relation-Pointers-Field
             OPTIONAL
 }

--Record-ID-Number                      --see Edge-Record

Feature-Implicit-Relations-Pointer-Field  --IAT-F
 ::= Basic-Text-String      {FL|FP|FA|FC}
                                         --Feature Type: Line, Point,
                                         --Area, Complex

Feature-Implicit-Attributes-Field          --IAT-F
 ::= SEQUENCE {
   fac      [0] Basic-Text-String,        --FACC identifier code
   iat-i    [1] Implicit-Attributes-Field
             OPTIONAL,
   [2] Control-Point-Subfield
             OPTIONAL
 }

--Implicit-Attributes-Field            --IAT
                                         --see Edge-Record

Control-Point-Subfield
 ::= SEQUENCE {
   glo      Real-Number,                --Longitude / Easting of
                                         --geographic reference point
   gla      Real-Number                --Latitude / Northing of
                                         --geographic reference point
 }

Feature-Explicit-Attribute-Labels-and-Values-Field
                                         --ATT-F
 ::= SEQUENCE OF
   SEQUENCE {
     [0] Ordered-Rooted-Tree-Links
             OPTIONAL,
             --see Dependency condition 6-9
     att-f    [1] Explicit-Attribute-Labels-and-Values-Field
   }

Ordered-Rooted-Tree-Links
 ::= SEQUENCE OF
   SEQUENCE {
     llk      Integer-Number,           --Left link
     rlk      Integer-Number           --Right link
   }

Note: These two subfields are maintained for backward compatibility.

--Explicit-Attribute-Labels-and-Values-Field      ATT
                                         --see Edge-Record

Explicit-Relation-Pointers-Field          --R1L
 ::= SEQUENCE {
   ert      Basic-Text-String         --Relation type
                                         --see Dependency condition 6-8
   r1v      Explicit-Relation-Value-Field
 }

```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

```
Explicit-Relation-Value-Field      --RIV
    ::= SEQUENCE OF
    rid-e          Integer-Number,      --Record ID Number
```

B.9.5 Text-Placement-Record

```
Text-Placement-Record           --TP
                                --for all levels of topology
    ::= [A 14] SEQUENCE {
        [0] Record-ID-Number,
        irs-t   [1] Implicit-Relations-Pointer-Field
                                OPTIONAL,
        att-t   [2] Explicit-Attribute-Labels-and-Values-Field
                                OPTIONAL,
        txt-t   [3] Text-Field,           --Text
        cor-t   [4] Coordinate-Field
    }

--Record-ID-Number            --see Edge-Record

--Implicit-Relation-Pointer-Field  --IRS
                                --see Edge-Record

--Explicit-Attribute-Labels-and-Values-Field
                                --ATT
                                --see Edge-Record

Text-Field                   --TXT
ftx      ::= General-Text-String      --Text

--Coordinate-Field            COR
                                --see Node-Record
```

B.9.6 Feature / Attribute-Entry-Record

```
Feature / Attribute-Entry-Record  --DD
                                --see Dependency condition 6-10
    ::= [A 15] SEQUENCE {
        Record-ID-Number,
        dfa      Feature / Attribute-Entry-Field
    }
```

```
--Record-ID-Number                                see Edge-Record

Feature / Attribute-Entry-Field      --DFA
 ::= SEQUENCE {                               --Feature or attribute ( 1 =
 faq       [0] Integer-Number,                --Feature; 2 = Attribute )
 lab       [1] Basic-Text-String,             --Feature code / name or Attribute
 sog       [2] Basic-Text-String,             --label
 des       [3] Basic-Text-String,             OPTIONAL,
 fan       [4] Basic-Text-String,             --Source for the feature or
 def       [5] General-Text-String          OPTIONAL,
           }                                --attribute
                                         --Description of originator and /
                                         --or source
                                         OPTIONAL,
                                         --Short name for the feature or
                                         --attribute
                                         --Attribute or feature definition
```

B.9.7 Feature / Attribute-Association-Record

```
Feature / Attribute-Association-Record    --DF
 ::= [A 16] SEQUENCE {                      --see Edge-Record
   Record-ID-Number,
   Feature-Association-Field,
   Attribute-Association-Field
 }

--Record-ID-Number                                --see Edge-Record

Feature-Association-Field                  --DAA
 lab-f     ::= Basic-Text-String            --Feature label

Attribute-Association-Field                  --AAD
 ::= SEQUENCE OF
 alb-f     Basic-Text-String              --Attribute label
 B.9.8     Attribute / Value-Association-Record

Attribute / Value-Association-Record    --DA
 ::= [A 17] SEQUENCE {                      --see Dependency condition 6-11
   [0] Record-ID-Number,
   [1] Attribute-Format-Description-Field,
   vad       [2] Attribute-Value-Description-Field
             OPTIONAL
             --see Dependency condition 6-12
 }

--Record-ID-Number                                --see Edge-Record
```

DIGEST Part 2

Edition 2.1, September 2000

Annex B - ISO 8824 Encapsulation

```
Attribute-Format-Description-Field      --DAV
  ::= SEQUENCE {
    lab-a      [0] Basic-Text-String,
    avt       [1] Basic-Text-String,
    avf       [2] Basic-Text-String
    avu       [3] Basic-Text-String
  }
Attribute-Value-Description-Field        --VAD
  ::= SEQUENCE OF
    SEQUENCE {
      alb-v     Integer-Number,
      avd-v     General-Text-String
    }
  }
```

Dependency conditions (list 6):

6-1 Edge-Record:

Vector geodata files containing only nodes and no edges or faces may exist. Edge record is mandatory if Vector geodata file contains Line or Area feature records.

6-2 Elevation MBR subfield (edge record):

Minimum and maximum elevation must be transmitted if the transmitted coordinates (COR) contain elevation value(s).

6-3 Elevation Coordinates subfield:

Elevation must be absent or present for all transmitted coordinates; that is, either elevation is present for all transmitted coordinates, or for none, but not for some.

6-4 Node-Record:

Vector geodata files without any node record may exist. Node record is mandatory if Vector geodata file contains Point feature records or if Edge record contains edge-node topology description.

6-5 Connected node IRN:

Containment pointers are allowed only for isolated nodes at level three topology.

6-6 Elevation MBR subfield (face record):

Minimum and maximum elevation must be transmitted if the bordering edges are transmitted with elevation value(s) in their coordinates field (COR).

6-7 Elevation MBR subfield (feature record):

If any of the topological entities, composing or bordering the simple feature or any of the simple feature composing the complex feature, contains elevation values in its coordinates field, maximum and minimum elevation values will be transmitted.

6-8 Relationship Type Restriction:

Complex Feature (FC) type is not appropriate for stacked on / stacked under (STK / STU) relationship type.

6-9 Left / Right Link:

Left and right link subfield will exist for all attributes, if there is at least one multi-level attribute.

6-10 Feature / Attribute-Entry-Record:

Will be present if any Feature (or attribute) transmitted in the Vector Geodata file is not described in FACC (DIGEST Part 4).

6-11 Attribute / Value-Association-Record:

Will be present for each attribute transmitted in the Vector Geodata file that is not present in FACC.

6-12 Attribute value format / Attribute measurement unit:

Depends on type of attribute.

B.10 RASTER-GEO-DATA-FILE

```
Raster-Geo-Data-Field
|
|-R Image-Record
  |- Record-ID-Number
  |- Pixel-Field
```

Raster-Geo-Data-File

```
 ::= [A 18] SEQUENCE OF
img      Image-Record
```

B.10.1 Image-Record

```
Image-Record          --IMG
  ::= SEQUENCE {
    Record-ID-Number,
    scn       Pixel-Field
  }
--Record-ID-Number      --see Edge-Record

Pixel-Field           --SCN
  ::= OCTETSTRING      --Pixel values
```

B.11 MATRIX-GEO-DATA-FILE

```
Matrix-Geo-Data-File  
|  
|-R Matrix-Record  
  |- Record-ID-Number  
  |- Element-Field
```

Matrix-Geo-Data-File
 $::=$ [A 19] SEQUENCE OF
var Matrix-Record

B.11.1 Matrix-Record

```

Matrix-Record          --VAR
    ::= SEQUENCE      :
                  Record-ID-Number,
scn-m       Element-Field
            }

--Record-ID-Number           --see Edge-Record

Element-Field           --SCN-M
    ::= OCTETSTRING           --Element values

```